SAFETY DATA SHEET



Date of issue	29 June 2021
---------------	--------------

Version 4

Section 1. Product and company identification

Product name	: MEGASEAL SL Heavy Duty Catalyst Comp B
Product code	: 00333447
Other means of identification	: Not available.
Product type	: Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Coating. Paints. Painting-related materials.

Uses advised against	Reason
Not applicable.	

Supplier's details:	
Supplier	 PPG Industrial do Brasil – Tintas e Vernizes Ltda Via Anhanguera KM 106, Bairro Sao Judas Tadeu Sumare / SP, Brasil 55 19 2103-6000 (Recepção e Portaria)
Email address:	: HazComLatam@ppg.com
Emergency telephone number	: 0800 707 1767 / 0800 707 7022 – Empresa Suatrans Cotec 0800 14 8110 – CEATOX - Centro de Assistência Toxicológica

Section 2. Hazards identification

Classification of the	: ACUTE TOXICITY (oral) - Category 4
substance or mixture	ACUTE TOXICITY (dermal) - Category 5
	ACUTE TOXICITY (inhalation) - Category 4
	SKIN CORROSION - Category 1
	SERIOUS EYE DAMAGE - Category 1
	SKIN SENSITIZATION - Category 1
	TOXIC TO REPRODUCTION - Category 2
	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
	AQUATIC HAZARD (ACUTE) - Category 1
	AQUATIC HAZARD (LONG-TERM) - Category 1
Target organs	: 🗭 ontains material which causes damage to the following organs: blood, liver, heart,
	brain, upper respiratory tract.
	Contains material which may cause damage to the following organs: kidneys,
	bladder, gastrointestinal tract, immune system, central nervous system (CNS).

Code00333447Product nameMEGASEAL	Date of issue SL Heavy Duty Catalyst Comp B	29 June 2021	Version	4
Section 2. Hazard	s identification			
	Percentage of the mixture consi 19.4%	isting of ingredient(s) of u	nknown acute o	ral toxicity:
	Percentage of the mixture consi toxicity: 21.5%	isting of ingredient(s) of u	nknown acute de	ermal
	Percentage of the mixture consi toxicity: 24.8%	isting of ingredient(s) of u	nknown acute in	halation
	Percentage of the mixture consi aquatic environment: 58.4%	isting of ingredient(s) of u	nknown hazards	to the
GHS label elements				
Hazard pictograms				
Signal word	: Danger	•		
Hazard statements	 Farmful if swallowed or if inhale May be harmful in contact with s Causes severe skin burns and e May cause an allergic skin reac Suspected of damaging fertility May cause damage to organs th tract) Very toxic to aquatic life with lor 	skin. eye damage. tion. or the unborn child. nrough prolonged or repea	ated exposure. (respiratory
Precautionary statements				
Prevention	: Øbtain special instructions before and eye or face protection. Ave Do not eat, drink or smoke when	id release to the environm	nent. Do not bre	eathe vapor.
Response	: Collect spillage. IF exposed or INHALED: Immediately call a PO Immediately call a POISON CEI vomiting. IF ON SKIN (or hair): Rinse skin with water. Immedia contaminated clothing before re doctor if you feel unwell. Wash Get medical advice or attention. minutes. Remove contact lense Immediately call a POISON CEI	concerned: Get medical a DISON CENTER or docto NTER or doctor. Rinse m Take off immediately all o tely call a POISON CENT use. IF ON SKIN: Call a with plenty of water. If sk IF IN EYES: Rinse cauti s, if present and easy to c	advice or attentic or. IF SWALLOV outh. Do NOT in contaminated clo TER or doctor. V POISON CENTR cin irritation or ra ously with water	on. IF VED: nduce othing. Vash ER or sh occurs: for several
Storage	: Not applicable.			
Disposal	: Dispose of contents and contair and international regulations.	ner in accordance with all	local, regional, r	national
Other hazards which do not result in classification	: None known.			

Section 3. Composition/information on ingredients

Substance/mixture Other means of identification

CAS number

: Mixture

: Not available.

CAS number/other identifiers

: Not applicable.

Ingredient name	%	CAS number
penzyl alcohol	30 - <60	100-51-6
3-aminomethyl-3,5,5-trimethylcyclohexylamine	30 - <60	2855-13-2
2-piperazin-1-ylethylamine	3 - <5	140-31-8
nonylphenol	3 - <5	25154-52-3
Amines, coco alkyl	1 - <2	61788-46-3
trimethylhexane-1,6-diamine	1 - <2	25620-58-0

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
Indication of immediate me	cal attention and special treatment needed, if necessary
Notes to physician Specific treatments	 In case of inhalation of decomposition products in a fire, symptoms may be delayed The exposed person may need to be kept under medical surveillance for 48 hours. No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
Potential acute health effec	
Eye contact	: Causes serious eye damage.
Inhalation	: Harmful if inhaled.
Skin contact	: Causes severe burns. May be harmful in contact with skin. May cause an allergic skin reaction.
Ingestion	: Harmful if swallowed.

Section 4. First aid measures

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	In a fire or if heated, a pressure increase will occur and the container may burst. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides
Special protective actions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
Methods and materials for co	ntainment and cleaning up
Small spill	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Code	00333447	Date of issue	29 June 2021	Version	4
Product nam	ie	MEGASEAL SL Heavy Duty Catalyst Comp B			

Section 6. Accidental release measures Large spill : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling	:	Fut on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Conditions for safe storage, including any incompatibilities	:	Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Occupational exposure limits	
None.	
Recommended monitoring procedures	: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Section 8. Exposure controls/personal protection

Individual protection measures

Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye protection Skin protection	1	Chemical splash goggles and face shield.
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	:	butyl rubber
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

Physical state	: Liquid.
Color	: Not available.
Odor	: Characteristic.
рН	: Not applicable.
Melting point	: Not available.
Boiling point	: >37.78°C (>100°F)
Flash point	: Closed cup: 115.56°C (240°F)
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Not available.
Vapor pressure	: Not available.
Vapor density	: Not available.
Relative density	: 1

Section 9. Physical and chemical properties

Solubility	1	Insoluble in the following materials: cold water.
Water Solubility at room temperature	:	0.1 g/l
Partition coefficient: n- octanol/water	:	Not applicable.
Auto-ignition temperature	1	Not available.
Decomposition temperature	1	Not available.
Viscosity	:	Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)

Section 10. Stability and reactivity

Reactivity	No specific test data related to reactivity available for this product or its inc	gredients.
Chemical stability	The product is stable.	
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not	occur.
Conditions to avoid	When exposed to high temperatures may produce hazardous decomposit products.	ion
Incompatible materials	Keep away from the following materials to prevent strong exothermic reac oxidizing agents, strong alkalis, strong acids.	tions:
Hazardous decomposition products	Depending on conditions, decomposition products may include the following carbon oxides nitrogen oxides	ng materials

Section 11. Toxicological information

Information on toxicological effects

Product/ingredient name	Result	Species	Dose	Exposure
penzyl alcohol	LC50 Inhalation Dusts and mists	Rat	>4178 mg/m ³	4 hours
5	LD50 Dermal	Rabbit	2000 mg/kg	-
	LD50 Oral	Rat	1.23 g/kg	-
3-aminomethyl-	LC50 Inhalation Dusts and mists	Rat	>5.01 mg/l	4 hours
3,5,5-trimethylcyclohexylamine			Ū	
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	1030 mg/kg	-
2-piperazin-1-ylethylamine	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours
	LD50 Dermal	Rabbit	866 mg/kg	-
	LD50 Oral	Rat	2140 mg/kg	-
nonylphenol	LD50 Dermal	Rabbit	2.14 g/kg	-
	LD50 Oral	Rat	580 mg/kg	-

Irritation/Corrosion

Not available.

Conclusion/Summary Skin

: There are no data available on the mixture itself.

4

- : There are no data available on the mixture itself.

Sensitization

Respiratory

Product/ingredient name	Route of exposure	Species	Result
3 -aminomethyl- 3,5,5-trimethylcyclohexylamine	skin	Guinea pig	Sensitizing
2-piperazin-1-ylethylamine	skin	Guinea pig	Sensitizing

Conclusion/Summary	
Skin Respiratory <u>Mutagenicity</u> Not available.	There are no data available on the mixture itself.There are no data available on the mixture itself.
Conclusion/Summary Carcinogenicity Not available.	: There are no data available on the mixture itself.
Conclusion/Summary <u>Reproductive toxicity</u> Not available.	: There are no data available on the mixture itself.
Conclusion/Summary <u>Teratogenicity</u>	: There are no data available on the mixture itself.

Not available.

Conclusion/Summary There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Name		Route of exposure	Target organs
Kinnes, coco alkyl	Category 3		Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Ź piperazin-1-ylethylamine Amines, coco alkyl	Category 1 Category 2	inhalation -	respiratory tract gastrointestinal tract, immune system, liver

Target organs

: Contains material which causes damage to the following organs: blood, liver, heart, brain, upper respiratory tract.

Contains material which may cause damage to the following organs: kidneys, bladder, gastrointestinal tract, immune system, central nervous system (CNS).

Aspiration hazard

Code	00333447	Date of issue	29 June 2021	Version	4
Product nam	е	MEGASEAL SL Heavy Duty Catalyst Comp B			

Section 11. Toxicological information

Name	Result
	ASPIRATION HAZARD - Category 2 ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure	Ē	Not available.
Potential acute health effects		
Eye contact	÷	Causes serious eye damage.
Inhalation	1	Harmful if inhaled.
Skin contact	:	Zauses severe burns. May be harmful in contact with skin. May cause an allergic skin reaction.
Ingestion	:	Harmful if swallowed.
		al, chemical and toxicological characteristics
Eye contact	:	Adverse symptoms may include the following: pain watering redness
Inhalation	:	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	:	Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	:	Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Conclusion/Summary	: There are no data available on the mixture itself. Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. There is some evidence that repeated exposure to organic solvent vapors in combination with constant loud noise can cause greater hearing loss than expected from exposure to noise alone. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from exposure to form exposure to may cause and immediate effects and also chronic effects of components from exposure to form exposure to may cause and immediate effects and also chronic effects of components from exposure to may cause and the effects and also chronic effects of components from exposure and long terms exposure form exposure form exposure to form exposure form
	short-term and long-term exposure by oral, inhalation and dermal routes of

29 June 2021

4

Section 11. Toxicological information

	exposure and eye contact.
<u>Short term exposure</u>	
Potential immediate effects	: There are no data available on the mixture itself.
Potential delayed effects	: There are no data available on the mixture itself.
<u>Long term exposure</u>	
Potential immediate effects	: There are no data available on the mixture itself.
Potential delayed effects	: There are no data available on the mixture itself.
Potential chronic health eff	<u>ects</u>
Not available.	
General	: May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
MEGASEAL SL Heavy Duty Catalyst Comp B	1093.4	2039	N/A	N/A	2.9
benzyl alcohol	1230	2000	N/A	N/A	1.5
3-aminomethyl-3,5,5-trimethylcyclohexylamine	1030	2500	N/A	N/A	N/A
2-piperazin-1-ylethylamine	2140	866	N/A	N/A	N/A
nonylphenol	580	2140	N/A	N/A	N/A
Amines, coco alkyl	500	N/A	N/A	N/A	N/A
trimethylhexane-1,6-diamine	500	N/A	N/A	N/A	N/A

Other information

: Not available.

Section 12. Ecological information

Ecotoxicity

Product/ingredient name	Result	Species	Exposure
2-piperazin-1-ylethylamine	Acute EC50 58 mg/l	Daphnia	48 hours
nonylphenol	Acute EC50 0.056 mg/l Fresh water	Algae - Desmodesmus subspicatus	72 hours
	Chronic EC10 0.003 mg/l Fresh water	Algae - Desmodesmus subspicatus	72 hours
	Chronic NOEC 1 µg/l Fresh water	Daphnia - Daphnia magna	21 days

Persistence/degradability

English (US)	South America
--------------	---------------

Code	00333447	Date of issue	29 June 2021	Version	4	
Product nam	le	MEGASEAL SL Heavy Duty Catalyst Comp B				

Section 12. Ecological information

Product/ingredient name	Test	Result		Dose		Inoculum
2-piperazin-1-ylethylamine	OECD 301F	0 % - Not r	eadily - 28 days	-		-
Product/ingredient name	Aquatic half-lif	e	Photolysis		Biodeg	gradability
penzyl alcohol 2-piperazin-1-ylethylamine			-		Readily Not rea	/

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
benzyl alcohol	0.87	-	low
3-aminomethyl- 3,5,5-trimethylcyclohexylamine	0.99	-	low
2-piperazin-1-ylethylamine nonylphenol	-1.48 3.28	- 154.88	low low

Mobility in soil

Soil/water partition coefficient (Koc)

Other adverse effects

: Not available.

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	Brazil (ANTT)	IMDG	ΙΑΤΑ
UN number	UN3066	UN3066	UN3066	UN3066
UN proper shipping name	PAINT	PAINT	PAINT	PAINT
Transport hazard class(es)	8	8	8	8
Packing group	II			II
			English (US) South Americ	a 11/1:

Code	00333447	Date of issue	29 June 2021	Version	4
Product nam	ne	MEGASEAL SL Heavy Duty Catalyst Comp B			

Section 14. Transport information

Environmental	Yes. The	Yes. The	Yes.	Yes. The
hazards	environmentally	environmentally		environmentally
	hazardous substance	hazardous substance		hazardous substance
	mark is not required.	mark is not required.		mark is not required.
Marine pollutant	Not applicable.	Not applicable.	(nonylphenol, Amines,	Not applicable.
substances			coco alkyl)	

Additional information

UN	: None identified.
Brazil	: None identified.
Risk number	: 80
IMDG	: The marine pollutant mark is not required when transported in sizes of \leq 5 L or \leq 5 kg.
ΙΑΤΑ	: The environmentally hazardous substance mark may appear if required by other transportation regulations.
Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.	

Transport in bulk according : Not applicable.

to IMO instruments

Section 15. Regulatory information

Safety, health and environmental regulations specific for the product : No known specific national and/or regional regulations applicable to this product (including its ingredients).

Section 16. Other information

<u>History</u>	
Date of previous issue	: 8/12/2019
Version	: 4
	EHS
Key to abbreviations	: ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
	ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
	ATE = Acute Toxicity Estimate
	BCF = Bioconcentration Factor
	GHS = Globally Harmonized System of Classification and Labelling of Chemicals
	IATA = International Air Transport Association
	IMDG = International Maritime Dangerous Goods
	LogPow = logarithm of the octanol/water partition coefficient
	MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
	RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
	UN = United Nations

Section 16. Other information

References

: ABNT NBR 14725-4: 2014 ANTT - National Land Transportation Agency

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.