# SAFETY DATA SHEET



Date of issue
---------------

1 July 2021

Version 5

# Section 1. Product and company identification

Product name	: PIT
Product code	: 97-
Other means of identification	: Not
Product type	: Liqu

### T-CHAR XP HARDENER BLACK 195

available.

uid.

### Relevant identified uses of the substance or mixture and uses advised against

### **Identified uses**

Coating. Paints. Painting-related materials.

Uses advised against	Reason
Not applicable.	

Supplier's details:	
Supplier	<ul> <li>PPG Industrial do Brasil – Tintas e Vernizes Ltda</li> <li>Via Anhanguera KM 106, Bairro Sao Judas Tadeu</li> <li>Sumare / SP, Brasil</li> <li>55 19 2103-6000 (Recepção e Portaria)</li> </ul>
Email address:	: HazComLatam@ppg.com
Emergency telephone number	: 0800 707 1767 / 0800 707 7022 – Empresa Suatrans Cotec 0800 14 8110 – CEATOX - Centro de Assistência Toxicológica

# Section 2. Hazards identification

Classification of the substance or mixture	: ACUTE TOXICITY (oral) - Category 5 ACUTE TOXICITY (dermal) - Category 4 SKIN CORROSION - Category 1C SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 1A AQUATIC HAZARD (ACUTE) - Category 2 AQUATIC HAZARD (LONG-TERM) - Category 2
Target organs	<ul> <li>Contains material which may cause damage to the following organs: kidneys, liver, brain, upper respiratory tract, skin, eyes.</li> <li>Percentage of the mixture consisting of ingredient(s) of unknown acute oral toxicity: 69.9%</li> <li>Percentage of the mixture consisting of ingredient(s) of unknown acute dermal toxicity: 90%</li> </ul>

Code 97-195 Product name	PITT-CHAR XP	Date of issue HARDENER BLACK	1 July 2021	Version	5
Section 2. H	azards i	dentification			
		Percentage of the mixture consist aquatic environment: 9.2%	ing of ingredient(s) of	unknown hazards	to the
GHS label elements	5				
Hazard pictograms					
Signal word	:	Danger	•		
Hazard statements	s :	May be harmful if swallowed. Harmful in contact with skin. Causes severe skin burns and eye May cause an allergic skin reactio May cause cancer. Toxic to aquatic life with long lasti	n.		
Precautionary stat	tements		0		
Prevention	:	Øbtain special instructions before and eye or face protection. Avoid vapor.			
Response	:	Collect spillage. IF exposed or co INHALED: Immediately call a POI Immediately call a POISON CENT vomiting. IF ON SKIN (or hair): Ta Rinse skin with water. Immediate contaminated clothing before reus doctor if you feel unwell. Wash w Get medical advice or attention. I minutes. Remove contact lenses, Immediately call a POISON CENT	SON CENTER or doct TER or doctor. Rinse r ake off immediately all ly call a POISON CEN se. IF ON SKIN: Call a ith plenty of water. If s F IN EYES: Rinse cau if present and easy to	tor. IF SWALLOW mouth. Do NOT ir contaminated clo ITER or doctor. V POISON CENTE skin irritation or ra tiously with water	VED: nduce othing. Vash ER or sh occurs for sever
Storage	:	Not applicable.			
Disposal	:	Dispose of contents and contained and international regulations.	r in accordance with al	ll local, regional, r	national

Other hazards which do not : Rauses digestive tract burns. result in classification

# Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of identification	: Not available.

CAS number/other identified	<u>ers</u>
CAS number	: Not applicable.

# Section 3. Composition/information on ingredients

Ingredient name	%	CAS number	
Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines	30 - <60	68410-23-1	
melamine	20 - <30	108-78-1	
4,4'-Isopropylidenediphenol, ethoxylated	7 - <10	32492-61-8 (EO> 4.5 moles)	
2,4,6-tris(dimethylaminomethyl)phenol	5 - <7	90-72-2	
3,6-diazaoctanethylenediamin	1 - <2	112-24-3	
glass, oxide, chemicals	1 - <2	65997-17-3	
crystalline silica, respirable powder (>10 microns)	0.5 - <1	14808-60-7	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

# Section 4. First aid measures

Description of necessary fir	rst a	id measures
Eye contact	:	Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Inhalation	:	Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	:	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	:	If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
Indication of immediate me	dica	attention and special treatment needed, if necessary
Notes to physician Specific treatments		In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. No specific treatment.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
Potential acute health effec	<u>ts</u>	
Eye contact	:	Causes serious eye damage.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	Causes severe burns. Harmful in contact with skin. May cause an allergic skin reaction.
Ingestion	:	May be harmful if swallowed. Corrosive to the digestive tract. Causes burns.

### See toxicological information (Section 11)

Code	97-195	
Product n	ame	PI

Date of issue PITT-CHAR XP HARDENER BLACK 1 July 2021

5

# Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides
Special protective actions for fire-fighters	<ul> <li>Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.</li> </ul>
Special protective equipment for fire-fighters	<ul> <li>Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.</li> </ul>

# Section 6. Accidental release measures

Personal precautions, prot	ecti <sup>*</sup>	ve equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	s :	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
		Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
Methods and materials for	con	tainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

1 July 2021

5

# Section 6. Accidental release measures

# Section 7. Handling and storage

Precautions for safe handling	: Fut on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Conditions for safe storage, including any incompatibilities	: Storage temperature: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

### **Control parameters**

### **Occupational exposure limits**

Ingredient name	Exposure limits
glass, oxide, chemicals	ACGIH TLV (United States). TWA: 1 f/cc Form: Continuous filament glass fibers TWA: 5 mg/m³, (Inhalable) Form: Continuous filament glass fibers TWA: 3 mg/m³ Form: Respirable TWA: 10 mg/m³ Form: Total dust ACGIH TLV (United States, 3/2020). TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction TWA: 1 f/cc 8 hours. Form: Respirable fibers: length greater than 5 uM; aspect ratio equal to or greater than 3:1 as determined by the membrane filter method at 400-450X magnification (4-mm objective) phase contrast illumination.
crystalline silica, respirable powder (>10 microns)	ACGIH TLV (United States, 3/2020). TWA: 0.025 mg/m <sup>3</sup> 8 hours. Form: Respirable fraction

English (US)	Brazil	
English (US)	Drazii	

5

# Section 8. Exposure controls/personal protection

Recommended monitoring procedures	:	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls		If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measur	res	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye protection Skin protection	4	Chemical splash goggles and face shield.
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves		nitrile neoprene
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

1 July 2021

5

# Section 9. Physical and chemical properties

<u>Appearance</u>		
Physical state	:	Liquid.
Color	1	Black.
Odor	1	Amine-like.
рН	:	Not applicable.
Melting point	:	Not available.
Boiling point	:	>37.78°C (>100°F)
Flash point	:	Closed cup: Not applicable.
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive (flammable) limits	:	Not available.
Vapor pressure	:	Not available.
Vapor density	:	Not available.
Relative density	:	1.14
Bulk density (g/cm³)	:	1.13
Solubility	:	Insoluble in the following materials: cold water.
Partition coefficient: n- octanol/water	:	Not applicable.
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
Viscosity	:	Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)
		• • • •

# Section 10. Stability and reactivity

Reactivity	o specific test data related to reactivity available for this product or its ing	redients.
Chemical stability	he product is stable.	
Possibility of hazardous reactions	nder normal conditions of storage and use, hazardous reactions will not	occur.
Conditions to avoid	/hen exposed to high temperatures may produce hazardous decomposit roducts.	ion
Incompatible materials	eep away from the following materials to prevent strong exothermic reac xidizing agents, strong alkalis, strong acids.	tions:
Hazardous decomposition products	epending on conditions, decomposition products may include the followin arbon oxides nitrogen oxides	ng materials:

7/13

# Section 11. Toxicological information

### Information on toxicological effects

Acute toxicity					
Product/ingredient name	Result	Species	Dose	Exposure	
melamine	LC50 Inhalation Dusts and mists	Rat	>5190 mg/m <sup>3</sup>	4 hours	
	LD50 Oral	Rat	3161 mg/kg	-	
2,4,6-tris	LD50 Dermal	Rabbit	1.28 g/kg	-	
(dimethylaminomethyl)					
phenol					
	LD50 Dermal	Rat	1280 mg/kg	-	
	LD50 Oral	Rat	1200 mg/kg	-	
3,6-diazaoctanethylenediamin	LD50 Dermal	Rabbit	1465 mg/kg	-	
·	LD50 Oral	Rat	1716 mg/kg	-	
Conclusion/Summary	: There are no data available on	the mixture i	tself.		

### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
<b>2</b> ,4,6-tris (dimethylaminomethyl) phenol	Skin - Visible necrosis	Rabbit	-	4 hours	7 days

# Conclusion/SummarySkin: There are no data available on the mixture itself.Eyes: There are no data available on the mixture itself.

**Respiratory** : There are no data available on the mixture itself.

### Sensitization

Product/ingredient name	Route of exposure	Species	Result
Atty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines	skin	Mouse	Sensitizing
2,4,6-tris (dimethylaminomethyl) phenol	skin	Guinea pig	Sensitizing
3,6-diazaoctanethylenediamin	skin	Guinea pig	Sensitizing

# Conclusion/Summary Skin : There are no data available on the mixture itself. Respiratory : There are no data available on the mixture itself. Mutagenicity : There are no data available on the mixture itself. Not available. : There are no data available on the mixture itself. Conclusion/Summary : There are no data available on the mixture itself. Not available. : There are no data available on the mixture itself. Conclusion/Summary : There are no data available on the mixture itself. Conclusion/Summary : There are no data available on the mixture itself.

# Section 11. Toxicological information

	- J		
Product/ingredient name	OSHA	IARC	NTP
Melamine glass, oxide, chemicals crystalline silica, respirable powder (>10 microns)	- - -	2B 3 1	- - Known to be a human carcinogen.

Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4 NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen OSHA: + Not listed/not regulated: -

### **Reproductive toxicity**

Not available.

**Conclusion/Summary** : There are no data available on the mixture itself.

### Teratogenicity

Not available.

**Conclusion/Summary** : There are no data available on the mixture itself.

### Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

Not available.

Target organs

: Contains material which may cause damage to the following organs: kidneys, liver, brain, upper respiratory tract, skin, eyes.

### Aspiration hazard

Not available.

Information on the likely routes of exposure	: Not available.
Potential acute health effec	<u>5</u>
Eye contact	: Causes serious eye damage.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes severe burns. Harmful in contact with skin. May cause an allergic skin reaction.
Ingestion	: May be harmful if swallowed. Corrosive to the digestive tract. Causes burns.
Symptoms related to the ph	/sical, chemical and toxicological characteristics
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: No specific data.

Brazil

1 July 2021

5

# Section 11. Toxicological information

Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion	: Adverse symptoms may include the following: stomach pains

### Delayed and immediate effects and also chronic effects from short and long term exposure

Conclusion/Summary	: There are no data available on the mixture itself. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. There is some evidence that repeated exposure to organic solvent vapors in combination with constant loud noise can cause greater hearing loss than expected from exposure to noise alone. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.
<u>Short term exposure</u>	
Potential immediate effects	: There are no data available on the mixture itself.
Potential delayed effects	: There are no data available on the mixture itself.
Long term exposure	-
Potential immediate effects	: There are no data available on the mixture itself.
Potential delayed effects	: There are no data available on the mixture itself.
Potential chronic health eff	i <u>cts</u>
Not available.	
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: May cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.
· · · · · · · · · · · · · · · · · · ·	

### Numerical measures of toxicity

Acute toxicity estimates

Brazil

Code	97-195	Date of issue	1 July 2021	Version	5	
Product nam	e	PITT-CHAR XP HARDENER BLACK				

# Section 11. Toxicological information

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
<ul> <li>TTT-CHAR XP HARDENER BLACK melamine</li> <li>2,4,6-tris(dimethylaminomethyl)phenol</li> <li>3,6-diazaoctanethylenediamin</li> </ul>	2593.8 3161 1200 1716	1951.9 N/A 1280 1465	N/A N/A N/A N/A	N/A N/A N/A N/A	N/A N/A N/A N/A

**Other information** 

: Not available.

# Section 12. Ecological information

### **Ecotoxicity**

Product/ingredient name	Result	Species	Exposure
Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines	EC50 4.11 mg/l Fresh water	Algae	72 hours
melamine 2,4,6-tris (dimethylaminomethyl)phenol	Acute EC50 200 mg/l Acute LC50 175 mg/l	Daphnia Fish	48 hours 96 hours

### Persistence/degradability

Product/ingredient name	Test	Result	Result			Inoculum
Tatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines	-	15 % - 28 c	lays	-		-
Product/ingredient name	Aquatic half-life		Photolysis		Biodeg	radability
Atty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines	-		-		Not rea	adily

### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
melamine	-1.22	3.8	low
2,4,6-tris	0.219	-	low
(dimethylaminomethyl)phenol			
3,6-diazaoctanethylenediamin	-1.66 to -1.4	-	low

### Mobility in soil

Soil/water partition : Not available. coefficient (K<sub>oc</sub>)

### Other adverse effects

: No known significant effects or critical hazards.

Brazil

Date of issue

5

# Section 13. Disposal considerations

### Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# Section 14. Transport information

	Brazil (ANTT)	IMDG	IATA
UN number	UN3066	UN3066	UN3066
UN proper shipping name	PAINT	PAINT	PAINT
Transport hazard class(es)	8	8	8
Packing group	III	III	III
Environmental hazards	Yes. The environmentally hazardous substance mark is not required.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	(Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines)	Not applicable.

### Additional information

Brazil	: None identified.
<b>Risk number</b>	: 80
IMDG	: The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.
ΙΑΤΑ	: The environmentally hazardous substance mark may appear if required by other transportation regulations.

**Special precautions for user : Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Code	97-195		Date of issue	1 July 2021	Version	5
Product na	ime	PITT-CHAR XP HARDENER BLAC	К			

## Section 15. Regulatory information

Safety, health and environmental regulations specific for the product : No known specific national and/or regional regulations applicable to this product (including its ingredients).

# Section 16. Other information

### **History**

Date of previous issue Version Prepared by	: 7/28/2018 : 5 : EHS
Key to abbreviations	<ul> <li>ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail UN = United Nations</li> </ul>
References	: ABNT NBR 14725-4: 2014 ANTT - National Land Transportation Agency

Indicates information that has changed from previously issued version.

### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.