# **SAFETY DATA SHEET**

Date of issue/Date of revision 2 August 2021

Version1.02

### Section 1. Identification

Product code	: 00445011
Product name	: SIGMAGUARD CSF 650 BASE
CAS number	: Not applicable.
EC number	: Mixture.
Product type	: Liquid.
Relevant identified uses	of the substance or mixture and uses advised against
Product use	Coating. Professional applications, Used by spraying.
Uses advised against	: Product is not intended, labelled or packaged for consumer use.
Supplier's details	: PPG Yung Chi Coatings Co. Ltd Lot 219, Amata Street, Long Binh IZ Bien Hoa City, Dong Nai Province Vietnam Tel : +84 61 3936121/22
Emergency telephone number (with hours of operation)	: CHEMTREC +(84)-444581938 (CCN 17704)

## Section 2. Hazards identification



### Section 2. Hazards identification

Get medical advice or attention.
Not applicable.
Dispose of contents and container in accordance with all local, regional, national and international regulations.
Not available.
None known.
N

### Section 3. Composition/information on ingredients

#### **CAS number/other identifiers**

CAS number	: Not applicable.
EC number	: Mixture.

Ingredient name	CAS number	Chemical formula	%
bis-[4-(2,3-epoxipropoxi)phenyl]propane 1,6-bis(2,3-epoxypropoxy)hexane benzyl alcohol Talc, not containing asbestiform fibers	16096-31-4 100-51-6	C12H22O4 C7-H8-O	≥25 - ≤50 ≤10 ≤10 ≤5

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

SUB codes represent substances without registered CAS Numbers.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### **Description of necessary first aid measures**

Eye contact	<ul> <li>Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.</li> </ul>
Inhalation	<ul> <li>Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.</li> </ul>
Skin contact	<ul> <li>Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.</li> </ul>
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed		
Potential acute health effects		
Eye contact	: Causes serious eye irritation.	
Inhalation	: No known significant effects or critical hazards.	
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.	
Ingestion	: No known significant effects or critical hazards.	

### Section 4. First aid measures

Over-exposure signs/symptoms		
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness	
Inhalation	: No specific data.	
Skin contact	: Adverse symptoms may include the following: irritation redness	
Ingestion	: No specific data.	
Indication of immediate me	lical attention and special treatment needed, if necessary	
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>	
Specific treatments	: No specific treatment.	
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.	

See toxicological information (Section 11)

### Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	<ul> <li>Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.</li> </ul>

Product name SIGMAGUARD CSF 650 BASE

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures For non-emergency : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from personnel entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". **Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways. drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage. Methods and materials for containment and cleaning up Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. Large spill : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### Section 7. Handling and storage

Precautions for safe handling	
Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Product name SIGMAGUARD CSF 650 BASE

### Section 7. Handling and storage

Conditions for safe storage,	:	Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct
including any		
incompatibilities		sunlight in a dry, cool and well-ventilated area, away from incompatible materials
		(see Section 10) and food and drink. Keep container tightly closed and sealed until
		ready for use. Containers that have been opened must be carefully resealed and
		kept upright to prevent leakage. Do not store in unlabeled containers. Use
		appropriate containment to avoid environmental contamination. See Section 10 for
		incompatible materials before handling or use.

### Section 8. Exposure controls/personal protection

#### **Control parameters**

#### **Occupational exposure limits**

Ingredient name			Exposure limits	
Talc, not containing asbestif	orm	fibers	Ministry of Health (Viet Nam, 6/2019). TWA: 3 mg/m <sup>3</sup> 8 hours. Form: inhalable dust TWA: 1 mg/m <sup>3</sup> 8 hours. Form: respirable dust TWA: 2 mg/m <sup>3</sup> 8 hours. Form: total dust concentration	
Recommended monitoring procedures	:	atmosphere or biological monitoring r of the ventilation or other control mea protective equipment. Reference sho	th exposure limits, personal, workplace may be required to determine the effectivene sures and/or the necessity to use respirator buld be made to appropriate monitoring dance documents for methods for the es will also be required.	
Appropriate engineering controls	:	Good general ventilation should be su contaminants.	ufficient to control worker exposure to airbor	ne
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.		
ndividual protection measu	<u>res</u>			
Hygiene measures	:	eating, smoking and using the lavator Appropriate techniques should be use Contaminated work clothing should n	oughly after handling chemical products, bef y and at the end of the working period. ed to remove potentially contaminated clothi ot be allowed out of the workplace. Wash . Ensure that eyewash stations and safety location.	
Eye/face protection	:	Chemical splash goggles.		
Skin protection				
Hand protection	:	be worn at all times when handling ch this is necessary. Considering the pa check during use that the gloves are should be noted that the time to break	s complying with an approved standard shown nemical products if a risk assessment indical arameters specified by the glove manufactur still retaining their protective properties. It kthrough for any glove material may be arers. In the case of mixtures, consisting of the of the gloves cannot be accurately	tes
			Viet Nam Page:	5/11

Version 1.02

Product name SIGMAGUARD CSF 650 BASE

### Section 8. Exposure controls/personal protection

Gloves	: butyl rubber
Body protection	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

### Section 9. Physical and chemical properties

<u>Appearance</u>			
Physical state	: Liquid.		
Color	: Off-white.		
Odor	Aromatic.		
Odor threshold	: Not available.		
рН	: Not applicable.		
Melting point	: Not available.		
Boiling point	: >37.78°C (>100°F)		
Flash point	: Closed cup: 266°C (510.8°F)		
Evaporation rate	: Not available.		
Flammability (solid, gas)	: Not available.		
Lower and upper explosive (flammable) limits	: Greatest known range: Lower: 1.3% Upper: 13% (benzyl alcohol)		
Vapor pressure	: Not available.		
Vapor density	: Not available.		
Relative density	: 1.41		
Solubility	: Insoluble in the following materials: cold water.		
Partition coefficient: n- octanol/water	: Not applicable.		
Auto-ignition temperature	: Not available.		
Decomposition temperature	: Not available.		
Viscosity	: Kinematic (40°C): >21 mm²/s		

### Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	The product is stable.
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.

Incompatible materials	:	Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	:	Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides

### Section 11. Toxicological information

#### Information on toxicological effects

•	1		1		1		1
Product/ingredient name	Result		Species	5	Dose	•	Exposure
bis-[4-(2,3-epoxipropoxi) phenyl]propane	LD50 Dermal					0 mg/kg	-
	LD50 Oral	LD50 Oral		Rat 15		)0 mg/kg	-
benzyl alcohol	LC50 Inhalation Dusts and mists		Rat	>4178		′8 mg/m³	4 hours
	LD50 Dermal		Rabbit		2000	) mg/kg	-
	LD50 Oral		Rat		1.23 g/kg		-
Conclusion/Summary <u>rritation/Corrosion</u>	: There are no data avail	able on	the mixt	ure itse	lf.		
Product/ingredient name	Result	Spec	cies	Score	e	Exposure	Observation
bis-[4-(2,3-epoxipropoxi) phenyl]propane	Eyes - Redness of the conjunctivae	Rabb	oit	0.4		24 hours	-
	conjunctivae	Rabb Rabb		0.4		24 hours 24 hours	-
	conjunctivae Eyes - Mild irritant		bit	-			
	conjunctivae	Rabb	pit pit	0.4 - 0.8 0.5		24 hours	-

**Conclusion/Summary** 

- : There are no data available on the mixture itself. Eyes
  - Respiratory : There are no data available on the mixture itself.

#### **Sensitization**

Skin

Product/ingredient name	Route of exposure	Species	Result			
bis-[4-(2,3-epoxipropoxi) phenyl]propane	skin	Mouse	Sensitiz	ing		
Skin		data available on the				
Respiratory	: There are no	o data available on the	mixture itself.			
<u>Mutagenicity</u>						
<b>Conclusion/Summary</b>	: There are no	: There are no data available on the mixture itself.				
Carcinogenicity						
<b>Conclusion/Summary</b>	: There are no	o data available on the	mixture itself.			
Reproductive toxicity						
<b>Conclusion/Summary</b>	: There are no	o data available on the	mixture itself.			
<b>Teratogenicity</b>						
Conclusion/Summary	: There are no	o data available on the	mixture itself.			
				Viet Nam	Page: 7/11	

### Section 11. Toxicological information

### Specific target organ toxicity (single exposure)

Name	• •	Route of exposure	Target organs
Talc, not containing asbestiform fibers	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Information on the likely : Not available.

Not available.

#### Aspiration hazard

Name	Result
benzyl alcohol	ASPIRATION HAZARD - Category 2

routes of exposure			
Potential acute health effect	<u>&gt;</u>		
Eye contact	: Causes serious eye irritation.		
Inhalation	No known significant effects or critical hazards.		
Skin contact	Causes skin irritation. May cause an allergic skin reaction.		
Ingestion	: No known significant effects or critical hazards.		
Symptoms related to the phy	vsical, chemical and toxicological characteristics		
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness		
Inhalation	: No specific data.		
Skin contact	: Adverse symptoms may include the following: irritation redness		
Ingestion	: No specific data.		
Delayed and immediate effect	ts and also chronic effects from short and long term exposure		
<u>Short term exposure</u>			
Potential immediate effects	: There are no data available on the mixture itself.		
Potential delayed effects	: There are no data available on the mixture itself.		
<u>Long term exposure</u>			
Potential immediate effects	: There are no data available on the mixture itself.		
Potential delayed effects	: There are no data available on the mixture itself.		
Potential chronic health eff	<u>ects</u>		
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.		
Carcinogenicity	: No known significant effects or critical hazards.		
Mutagenicity	: No known significant effects or critical hazards.		
Reproductive toxicity	: No known significant effects or critical hazards.		

### Section 11. Toxicological information

#### Numerical measures of toxicity

#### Acute toxicity estimates

Route	ATE value
Oral	11556.53 mg/kg
Dermal	17541.63 mg/kg
Inhalation (dusts and mists)	5.7 mg/l

#### Other information

Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death.

### Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
bis-[4-(2,3-epoxipropoxi) phenyl]propane	Acute LC50 1.8 mg/l Fresh water	Daphnia - daphnia magna	48 hours
	Chronic NOEC 0.3 mg/l	Daphnia	21 days

#### Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
bis-[4-(2,3-epoxipropoxi) phenyl]propane	-	-	Not readily
benzyl alcohol	-	-	Readily

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
1,6-bis(2,3-epoxypropoxy) hexane	0.822	-	low
benzyl alcohol	0.87	-	low

#### Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

Other adverse effects : No known significant effects or critical hazards.

### Section 13. Disposal considerations

Disposal methods: The generation of waste should be avoided or minimized wherever possible.<br/>Disposal of this product, solutions and any by-products should at all times comply<br/>with the requirements of environmental protection and waste disposal legislation<br/>and any regional local authority requirements. Dispose of surplus and non-<br/>recyclable products via a licensed waste disposal contractor. Waste should not be<br/>disposed of untreated to the sewer unless fully compliant with the requirements of<br/>all authorities with jurisdiction. Waste packaging should be recycled. Incineration or

Viet Nam Page: 9/11

#### Product code 00445011 Product name SIGMAGUARD CSF 650 BASE

### Section 13. Disposal considerations

landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### Section 14. Transport information

	UN	IMDG	ΙΑΤΑ
UN number	UN3082	UN3082	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)
Transport hazard class(es)	9	9	9
Packing group	III	III	
Environmental hazards	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)	Not applicable.

#### **Additional information**

UN	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
IMDG	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
ΙΑΤΑ	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

### Section 15. Regulatory information

#### Safety, health and environmental regulations specific for the product

2 No known specific national and/or regional regulations applicable to this product (including its ingredients).

#### Circular no. 05/1999/TT-BYT

Ingredient name	Category	Notes
1-chloro-2,3-epoxypropane chromium antimony arsenic	Category 2 Category 2 Category 2 Category 1	

### Section 15. Regulatory information

Toxic classification (TCVN : 4

3164-79)

International regulations

#### **Montreal Protocol**

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

### Section 16. Other information

#### <u>History</u>

motory	
Date of issue/Date of revision	: 2 August 2021
Date of previous issue	: 7/19/2021
Version	: 1.02
Prepared by	: EHS
Key to abbreviations	<ul> <li>ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations</li> </ul>
References	: Not available.

✓ Indicates information that has changed from previously issued version.

#### Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.