# **SAFETY DATA SHEET**



Date of issue 11/8/2021 (month/day/year)

**Version 5** 

# Section 1. Chemical product and company identification

A. Product name : PSX 700 HARDENER

Product code : 00393283

B. Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Professional applications, Used by spraying.

Use of the substance/

mixture

: Coating.

**Uses advised against**: Product is not intended, labelled or packaged for consumer use.

C. Supplier's or Importer's

information

**Email Address** 

: PPG SSC (680-090)

19, Yeocheon-ro 217beon-gil, Nam-gu,

Ulsan, Korea

Tel: +82-52-210-8222 Korea.MSDS@PPG.COM

**Emergency telephone** 

number:

: +82-52-210-8222

# Section 2. Hazards identification

A. Hazard classification : CORROSIVE TO METALS - Category 1

ACUTE TOXICITY (oral) - Category 4
SKIN CORROSION - Category 1B
SERIOUS EYE DAMAGE - Category 1
SKIN SENSITIZATION - Category 1

GERM CELL MUTAGENICITY - Category 2

**CARCINOGENICITY - Category 2** 

TOXIC TO REPRODUCTION - Category 1B

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2

AQUATIC HAZARD (LONG-TERM) - Category 2

This product is classified in accordance with the Industrial Safety and Health Act and the Chemical Control Act.

B. GHS label elements, including precautionary statements

Symbol









Signal word : Danger

Korea (GHS) Page: 1/13

Date of issue 11/8/2021 (month/day/year) **Version 5** 

**Product name PSX 700 HARDENER** 

Product code 00393283

### Section 2. Hazards identification

: F290 - May be corrosive to metals. **Hazard statements** 

H302 - Harmful if swallowed.

H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction. H341 - Suspected of causing genetic defects.

H351 - Suspected of causing cancer.

H360 - May damage fertility or the unborn child.

H371 - May cause damage to organs.

H373 - May cause damage to organs through prolonged or repeated exposure.

(immune system)

H411 - Toxic to aquatic life with long lasting effects.

#### **Precautionary statements**

Prevention

: P202 - Do not handle until all safety precautions have been read and understood.

P280 - Wear protective gloves, protective clothing and eye or face protection.

P234 - Keep only in original packaging. P273 - Avoid release to the environment.

P260 - Do not breathe vapor.

P270 - Do not eat, drink or smoke when using this product.

P264 - Wash thoroughly after handling.

Response

: P391 - Collect spillage.

P390 - Absorb spillage to prevent material damage.

P308 + P311 - IF exposed or concerned: Call a POISON CENTER or doctor. P304 + P310 - IF INHALED: Immediately call a POISON CENTER or doctor. P301 + P310, P330, P331 - IF SWALLOWED: Immediately call a POISON

CENTER or doctor. Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353, P310 - IF ON SKIN (or hair): Take off immediately all

contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER

or doctor.

P363 - Wash contaminated clothing before reuse. P302 + P352 - IF ON SKIN: Wash with plenty of water.

P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor.

: Not applicable. **Storage Disposal** : Not applicable.

C. Other hazards which do not result in classification

: Causes digestive tract burns. Prolonged or repeated contact may dry skin and cause irritation.

### Section 3. Composition/information on ingredients

#### **CAS** number/other identifiers

**CAS** number : Not applicable.

Chemical name	Common name	Identifiers	%
3-aminopropyltriethoxysilane	3-aminopropyltriethoxysilane	CAS: 919-30-2	90 - 100
dibutylbis(pentane-2,4-dionato-O,O')tin	DIBUTYLBIS(PENTANE-2.4-DIONATO-	CAS: 22673-19-4	5 - <10
	O.O`)TIN		
ethanol	ETHYL ALCOHOL	CAS: 64-17-5	1 - <5

Korea (GHS) Page: 2/13 Date of issue 11/8/2021 (month/day/year) **Version 5** 

Product code 00393283

**Product name PSX 700 HARDENER** 

### Section 3. Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

A. Eye contact

: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.

**B.** Skin contact

: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

C. Inhalation

: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

**D.** Ingestion

: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

E. Notes to physician

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments Protection of first-aiders**  : No specific treatment.

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

### Section 5. Fire-fighting measures

A. Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable** extinguishing media : None known.

B. Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous thermal** decomposition products : Decomposition products may include the following materials: carbon oxides

nitrogen oxides metal oxide/oxides Formaldehyde.

> Korea (GHS) Page: 3/13

**Product name PSX 700 HARDENER** 

### Section 5. Fire-fighting measures

C. Special equipment for fire-fighting

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

**Fire-fighting procedures** 

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

### Section 6. Accidental release measures

- A. Personal precautions, protective equipment and emergency procedures
- : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- B. Environmental precautions
- : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
- C. Methods and materials for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Absorb spillage to prevent material damage. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Absorb spillage to prevent material damage. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

- A. Precautions for safe handling
- : Fut on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Absorb spillage to prevent material damage.

Korea (GHS) Page: 4/13

**Product name PSX 700 HARDENER** 

### Section 7. Handling and storage

- B. Conditions for safe storage, including any incompatibilities
- Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a corrosion resistant container with a resistant inner liner. Store locked up. Keep away from metals. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

#### A. Occupational exposure limits

Ingredient name	Exposure limits
arbutylbis(pentane-2,4-dionato-O,O')tin	Ministry of Employment and Labor (Republic of Korea, 1/2020). Absorbed through skin.
ethanol	TWA: 0.1 mg/m³, (as Sn) 8 hours.  Ministry of Employment and Labor (Republic of Korea, 1/2020).  TWA: 1000 ppm 8 hours.

#### Recommended monitoring procedures

- : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
- controls
- B. Appropriate engineering: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**Environmental** exposure controls

- Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
- C. Personal protective equipment

**Respiratory protection** 

: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

**Eye protection Hand protection** 

- : Chemical splash goggles and face shield.
- Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Korea (GHS) Page: 5/13

**Product name PSX 700 HARDENER** 

### Section 8. Exposure controls/personal protection

**Gloves** 

: nitrile neoprene

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

### Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

A. Appearance

Physical state : Liquid.
Color : Clear

B. Odor : Characteristic.
C. Odor threshold : Not available.
D. pH : Not applicable.
E. Melting/freezing point : Not available.
F. Boiling point/boiling : >37.78°C (>100°F)

range

G. Flash point : Closed cup: Not applicable.

H. Evaporation rate : Not available.I. Flammability (solid, gas) : Not available.

J. Lower and upper explosive (flammable)

limits

K.

: Createst known range: Lower: 3.3% Upper: 19% (ethanol)

. Vapor pressure :		Vapor Pressure at 20°C			Vapo	r pressu	re at 50°C
	Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method

42.95

L. Solubility : Insoluble in the following materials: cold water.

ethanol

Solubility in water : Not available.

M. Vapor density : Not available.

N. Relative density : 0.96

O. Partition coefficient: noctanol/water : Not applicable.

P. Auto-ignition temperature

Ingredient name	°C	°F	Method
butylbis(pentane-2,4-dionato-O,O') tin	400	752	EU A.15

Q. Decomposition temperature

: Not available.

ŧ

R. Viscosity

: Kinematic (40°C (104°F)): >21 mm<sup>2</sup>/s (>21 cSt)

Korea (GHS) Page: 6/13

**Product name PSX 700 HARDENER** 

### Section 9. Physical and chemical properties

Flow time (ISO 2431) : Not available.

S. Molecular weight : Not applicable.

### Section 10. Stability and reactivity

A. Chemical stability : The product is stable.

Possibility of hazardous : Under normal conditions of storage and use, hazardous reactions will not occur.

reactions

B. Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition

products.

**C.** Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents, strong alkalis, strong acids.

D. Hazardous : Depending on conditions, decomposition products may include the following

materials: carbon oxides nitrogen oxides Formaldehyde. metal oxide/oxides

# **Section 11. Toxicological information**

A. Information on the likely : Not available. routes of exposure

Potential acute health effects

decomposition products

**Inhalation** : No known significant effects or critical hazards.

Ingestion : Marmful if swallowed. Corrosive to the digestive tract. Causes burns. May cause

damage to organs following a single exposure if swallowed.

**Skin contact**: Zauses severe burns. May cause damage to organs following a single exposure in

contact with skin. Defatting to the skin. May cause an allergic skin reaction.

**Eye contact** : Causes serious eye damage.

Over-exposure signs/symptoms

**Inhalation** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

**Ingestion** : Adverse symptoms may include the following:

stomach pains reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

pain or irritation

redness dryness cracking

blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations

Korea (GHS) Page: 7/13

**Product name PSX 700 HARDENER** 

### **Section 11. Toxicological information**

**Eye contact**: Adverse symptoms may include the following:

pain watering redness

#### B. Health hazards

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
<b>3</b> -aminopropyltriethoxysilane	LC50 Inhalation Dusts and mists	Rat	>7.35 mg/l	4 hours
	LD50 Dermal	Rabbit	4 g/kg	-
	LD50 Oral	Rat	1.57 g/kg	-
dibutylbis(pentane-2,4-dionato-O,O')tin	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	1864 mg/kg	-
ethanol	LC50 Inhalation Vapor	Rat	124700 mg/m <sup>3</sup>	4 hours
	LD50 Dermal	Rat	17100 mg/kg	-
	LD50 Oral	Rat	7 g/kg	-

**Conclusion/Summary**: There are no data available on the mixture itself.

#### **Irritation/Corrosion**

**Conclusion/Summary** 

Skin: There are no data available on the mixture itself.Eyes: There are no data available on the mixture itself.Respiratory: There are no data available on the mixture itself.

#### **Sensitization**

Product/ingredient name	Route of exposure	Species	Result
3-aminopropyltriethoxysilane	skin	Guinea pig	Sensitizing

**Conclusion/Summary** 

Skin : There are no data available on the mixture itself.Respiratory : There are no data available on the mixture itself.

**Mutagenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Carcinogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Reproductive toxicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Teratogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Korea (GHS) Page: 8/13

Product code 00393283	Date of issue 11/8/2021 (month/day/year)	Version 5
Product name PSX 700 HARDENER		

# **Section 11. Toxicological information**

Name	Classification	Route of exposure	Target organs
butylbis(pentane-2,4-dionato-O,O')tin	Category 1	-	-

#### Specific target organ toxicity (repeated exposure)

Name	Classification	Route of exposure	Target organs
dibutylbis(pentane-2,4-dionato-O,O')tin	Category 1	-	immune system

#### **Aspiration hazard**

Not available.

#### Potential chronic health effects

General: May cause damage to organs through prolonged or repeated exposure. Prolonged or

repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to

very low levels.

**Carcinogenicity**: Suspected of causing cancer. Risk of cancer depends on duration and level of

exposure.

Mutagenicity : Suspected of causing genetic defects.Reproductive toxicity : May damage fertility or the unborn child.

#### **Additional information**

Causes digestive tract burns. Prolonged or repeated contact may dry skin and cause irritation. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Contains a substance that may emit formaldehyde if stored beyond its shelf life and/or during cure at curing temperatures greater than 60C (140F). Avoid contact with skin and clothing.

Chemical name	Identifiers	GHS Classification
3-aminopropyltriethoxysilane	CAS: 919-30-2	FLAMMABLE LIQUIDS - Category 4 CORROSIVE TO METALS - Category 1 ACUTE TOXICITY (oral) - Category 4 SKIN CORROSION - Category 1B SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1B
dibutylbis(pentane-2,4-dionato-O,O')tin	CAS: 22673-19-4	CORROSIVE TO METALS - Category 1 ACUTE TOXICITY (oral) - Category 4 SKIN CORROSION - Category 1C SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1B GERM CELL MUTAGENICITY - Category 2 TOXIC TO REPRODUCTION - Category 1B SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1 AQUATIC HAZARD (ACUTE) - Category 1

Korea (GHS) Page: 9/13

Product code 00393283	Date of is	sue 11/8/2021 (month/day/year)	Version 5
Product name PSX 700 HARDENER			
Section 11. Toxicologic	al information		
ethanol	CAS: 64-17-5	AQUATIC HAZARD (LONG-TER FLAMMABLE LIQUIDS - Categor EYE IRRITATION - Category 2A CARCINOGENICITY - Category 2	y 2

### **Section 12. Ecological information**

#### A. **Ecotoxicity**

Product/ingredient name	Result	Species	Exposure
3-aminopropyltriethoxysilane	Acute LC50 >934 mg/l	Fish	96 hours
ethanol	Acute EC50 7640 mg/l Fresh water	Daphnia - Daphnia magna	48 hours

#### B. Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
<b>e</b> thanol	-	-	Readily

### C. Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
3-aminopropyltriethoxysilane	1.7	3.4	low
ethanol	-0.35	-	low

#### D. Mobility in soil

Soil/water partition coefficient (K<sub>oc</sub>)

: Not available.

#### E. Other adverse effects

: No known significant effects or critical hazards.

### Section 13. Disposal considerations

#### A. Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

#### **B.** Disposal precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Korea (GHS) Page: 10/13

**Product name PSX 700 HARDENER** 

# **Section 14. Transport information**

	UN	IMDG	IATA
A. UN number	UN3066	UN3066	UN3066
B. UN proper shipping name	PAINT	PAINT	PAINT
C. Transport hazard class(es)	8	8	8
D. Packing group	II	II	II
Environmental hazards	Yes. The environmentally hazardous substance mark is not required.	Yes.	Yes. The environmentally hazardous substance mark is not required.
E. Marine pollutant substances	Not applicable.	(dibutylbis(pentane- 2,4-dionato-O,O')tin)	Not applicable.

#### **Additional information**

UN : None identified.

**IMDG**: The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.

**IATA** : The environmentally hazardous substance mark may appear if required by other transportation

regulations.

# F. Special precaution which a user to be aware of or needs to comply with in connection with transport or transportation

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

### **Section 15. Regulatory information**

#### A. Regulation according to ISHA

ISHA article 117 (Harmful substances prohibited from manufacture) : None of the components are listed.

ISHA article 118 (Harmful substances requiring permission) : None of the components are listed.

Article 2 of Youth Protection Act on Substances Hazardous to Youth : It is not allowed to sell to persons under the age of 19.

#### **Exposure Limits of Chemical Substances and Physical Factors**

The following components have an OEL: pributylbis(pentane-2,4-dionato-O,O')tin ethanol

Korea (GHS) Page: 11/13

**Product name PSX 700 HARDENER** 

### Section 15. Regulatory information

ISHA Enforcement Regs : None of the components are listed.

**Annex 19 (Exposure** standards established for harmful factors)

**ISHA Enforcement Regs** 

Annex 21 (Harmful factors subject to Work

**Environment Measurement)**  The following components are listed: tin and its compounds (excluding

hydrogenated tin)

ISHA Enforcement Regs

**Annex 22 (Harmful Factors Subject to Special Health Check-** : The following components are listed: Tin and its compounds

up)

Standard of Industrial **Safety and Health Annex 12 (Hazardous** substances subject to control)

: The following components are listed: tin and its compounds

B. Regulation according to Chemicals Control Act

**CCA Article 11 (TRI)** : The following components are listed: Tin and its compounds

Article 18 Prohibited (K-

Reach Article 27)

**Article 19 Subject to** authorization (K-Reach

Article 25)

: None of the components are listed.

: None of the components are listed.

**Article 20 Restricted (K-**

Reach Article 27)

**Article 20 Toxic Chemicals (K-Reach** 

**Korea inventory** 

Article 20)

: None of the components are listed.

: Not applicable

**CCA Article 39** (Accident Precaution

**Chemicals**)

C. Dangerous Materials Safety Management Act : All components are listed or exempted.

: None of the components are listed.

: Not applicable.

D. Wastes regulation

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

E. Regulation according to other foreign laws

Safety, health and environmental regulations specific for the product

: No known specific national and/or regional regulations applicable to this product (including its ingredients).

Korea (GHS) Page: 12/13

**Product name PSX 700 HARDENER** 

### Section 16. Other information

A. References : Korean Ministry of Environment; Chemical Control Act

Korean Ministry of Labor; Industrial Safety and Health Act

**NIER Notice** 

Registry of Toxic Effects of Chemical Substances (RTECS)

U.S. Environmental Protection Agency, AQUIRE (Aquatic toxicity Information

Retrieval) ECOTOX Database System.

B. Date of issue/Date of

revision

: 11/8/2021

C. Version : 5
Prepared by : EHS

D. Other

**▼** Indicates information that has changed from previously issued version.

#### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

Korea (GHS) Page: 13/13