SAFETY DATA SHEET

Date of issue : 8 November 2021

: 2 Version



Section 1. Identification

: 10090-FILLR/29K **Product code**

: AMERCOAT D9 FILLER **Product name**

: Powder. **Product type** Recommended use and restrictions Use of the substance/ : Coating.

mixture

Uses advised against

: Not applicable.

Supplier's details

: PPG INDUSTRIES NEW ZEALAND LTD 5 MONAHAN ROAD, MT WELLINGTON,

AUCKLAND www.ppgnz.co.nz

Telephone Numbers: 09 573 1620, 0800 659378 021 940 920 (24 Hours)

Emergency telephone number (with hours of

For international shipping emergencies: 1-412-391-1618

operation)

e-mail address of person responsible for this SDS

: ehsnz@ppg.com

Section 2. Hazards identification

: SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 **HSNO Classification**

LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1

: New Zealand 0800 000 096 (24 hours) / Australia 1800 883 254 (24 hours)

Symbol

GHS label elements

: Warning Signal word

Hazard statements : Very toxic to aquatic life with long lasting effects.

May form combustible dust concentrations in air.

Precautionary statements

Prevention : Avoid release to the environment.

Response : Collect spillage. : Not applicable. **Storage**

Disposal : Dispose of contents and container in accordance with all local, regional, national

and international regulations.

result in classification

Other hazards which do not : May form explosible dust-air mixture if dispersed. Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes,

skin, nose and throat.

New Zealand Page: 1/10 Product code 10090-FILLR/29K Date of issue 8 November 2021 Version 2

Product name AMERCOAT D9 FILLER

Section 2. Hazards identification

This material is classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Notice 2017 and has been classified according to the Hazardous Substances (Classifications) Notice 2017.

This material is classified as DANGEROUS GOODS according to criteria in New Zealand Land Transport Rule: Dangerous Goods 2005.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

CAS number/other identifiers

Product code : 10090-FILLR/29K

Hazardous ingredients	%	CAS number
Zinc powder - zinc dust (stabilized) zinc oxide		7440-66-6 1314-13-2

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment or have an OEL and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact: Remove contact lenses, irrigate copiously with clean, fresh water, holding the

eyelids apart for at least 10 minutes and seek immediate medical advice.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognised skin cleanser. Do NOT use solvents or thinners.

Ingestion: If swallowed, seek medical advice immediately and show the container or label.

Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Exposure to airborne concentrations above statutory or recommended exposure

limits may cause irritation of the eyes.

Inhalation : Exposure to airborne concentrations above statutory or recommended exposure

limits may cause irritation of the nose, throat and lungs.

Skin contactIngestionNo known significant effects or critical hazards.No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eyes: Adverse symptoms may include the following:

irritation redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin: No specific data.Ingestion: No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

New Zealand Page: 2/10

Product code 10090-FILLR/29K

Date of issue 8 November 2021 Version 2

Product name AMERCOAT D9 FILLER

Section 4. First aid measures

Specific treatments

: Not available.

Notes to physician

: Freat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

Suitable

: Use dry chemical powder.

Not suitable

: Kvoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.

Specific hazards arising from the chemical

: May form explosible dust-air mixture if dispersed. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products : Decomposition products may include the following materials: metal oxide/oxides

oxides of lead

Special precautions for firefighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk.

Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

: Fspecialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

Methods and material for containment and cleaning up

Small spill

: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor.

Large spill

: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labelled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

> **New Zealand** Page: 3/10

Product name AMERCOAT D9 FILLER

Section 7. Handling and storage

Precautions for safe handling

: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing dust. Avoid release to the environment. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Conditions for safe storage, including any incompatibilities

Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Ingredient name	Exposure limits
z nc oxide	NZ HSWA 2015 (New Zealand, 11/2020). WES-TWA: 0.1 mg/m³ 8 hours. Form: The value for respirable dust. WES-STEL: 0.5 mg/m³ 15 minutes. Form: The value for respirable dust. WES-STEL: 5 mg/m³ 15 minutes. WES-TWA: 2 mg/m³ 8 hours.

procedures

Recommended monitoring: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

New Zealand Page: 4/10

Date of issue 8 November 2021 Version 2

Product code 10090-FILLR/29K

Product name AMERCOAT D9 FILLER

Section 8. Exposure controls/personal protection

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Respiratory protection

: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Eye protection

: Safety glasses with side shields.

Skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Section 9. Physical and chemical properties

Appearance

Physical state : Solid.

Powder.

Colour : Not available. **Odour** : Not available. : Not available. **Odour threshold** Hq : Not applicable. **Melting point** : 999°C (1830.2°F) **Boiling point** : 908°C (1666.4°F)

Flash point : Closed cup: Not applicable.

Flammability (solid, gas) : Not available. Lower and upper explosive : Not applicable.

(flammable) limits

: Not available. Vapour pressure

Relative density 7.1 Bulk Density (g/cm³) 7.1

Solubility : Insoluble in the following materials: cold water.

Partition coefficient: n-

octanol/water

: Not applicable.

Auto-ignition temperature : Not applicable. **Decomposition temperature** Not available.

Viscosity : Kinematic (40°C (104°F)): Not applicable.

> **New Zealand** Page: 5/10

Date of issue 8 November 2021 Version 2

Product name AMERCOAT D9 FILLER

Product code 10090-FILLR/29K

Section 10. Stability and reactivity

Stability

: The product may not be stable under certain conditions of storage or use.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid

: Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. 807i:rkep:8hy

Prevent dust accumulation.

Incompatible materials

: Reactive or incompatible with the following materials:

oxidising materials strong acids strong alkalis

Hazardous decomposition

products

: Evolves hydrogen on contact with water. Depending on conditions, decomposition

products may include the following materials: metal oxide/oxides

: Under normal conditions of storage and use, hazardous polymerisation will not **Hazardous polymerisation**

occur.

Section 11. Toxicological information

Information on likely routes of exposure

Inhalation : Exposure to airborne concentrations above statutory or recommended exposure

limits may cause irritation of the nose, throat and lungs.

Ingestion No known significant effects or critical hazards. : No known significant effects or critical hazards. Skin contact

Eye contact : Exposure to airborne concentrations above statutory or recommended exposure

limits may cause irritation of the eyes.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation

: Adverse symptoms may include the following:

respiratory tract irritation

coughing

Ingestion : No specific data. Skin contact : No specific data.

Eye contact : Adverse symptoms may include the following:

irritation redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Zinc powder - zinc dust (stabilized)	LC50 Inhalation Dusts and mists	Rat	>5.4 mg/l	4 hours
	LD50 Oral	Rat	>2000 mg/kg	-
zinc oxide	LC50 Inhalation Dusts and mists LD50 Dermal LD50 Oral	Rat	>5700 mg/m³ >2000 mg/kg >5000 mg/kg	4 hours - -

Conclusion/Summary

Irritation/Corrosion

: There are no data available on the mixture itself.

Conclusion/Summary

Skin : There are no data available on the mixture itself.

> **New Zealand** Page: 6/10

Product code 10090-FILLR/29K Date of issue 8 November 2021 Version 2

Product name AMERCOAT D9 FILLER

Section 11. Toxicological information

Eyes : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Sensitisation

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Potential chronic health effects

General : Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.

Inhalation: Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.
 Fertility effects : No known significant effects or critical hazards.

Chronic toxicity

Not available.

Carcinogenicity

Conclusion/Summary: There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary: There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary: There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary: There are no data available on the mixture itself.

Not available.

Aspiration hazard

Not available.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Other information :

Sanding and grinding dusts may be harmful if inhaled.

Section 12. Ecological information

Ecotoxicity : This material is very toxic to aquatic life with long lasting effects.

Aquatic and terrestrial toxicity

New Zealand Page: 7/10

Date of issue 8 November 2021 Version 2

Product code 10090-FILLR/29K

Product name AMERCOAT D9 FILLER

Section 12. Ecological information

Product/ingredient name	Result	Species	Exposure
Zinc powder - zinc dust (stabilized)	Acute EC50 0.106 mg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
, ,	Chronic NOEC 0.0727 mg/l Fresh water	Daphnia - Daphnia Magna	21 days
zinc oxide	Acute EC50 0.17 mg/l	Algae	72 hours
	Acute EC50 0.481 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Chronic NOEC 0.017 mg/l Fresh water	Algae	72 hours

Persistence/degradability

Not available.

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Do not allow to enter drains or watercourses.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Not suitable:

: Do not allow to enter drains or watercourses.

The classification of the product may meet the criteria for a hazardous waste. Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL

PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

14. Transport information

	NZ	IMDG	IATA
UN number	UN3077	UN3077	UN3077
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
	(Zinc powder - zinc dust (stabilized), zinc oxide)	(Zinc powder - zinc dust (stabilized), zinc oxide)	(Zinc powder - zinc dust (stabilized), zinc oxide)

New Zealand Page: 8/10

Date of issue 8 November 2021 Version 2 Product code 10090-FILLR/29K

14. Transport information

Product name AMERCOAT D9 FILLER

Transport hazard class(es)	9	9	9
	MARIAL ARGUN		
Packing group	III	III	III
Environmental hazards	Yes.	Yes.	Yes.
Marine pollutant substances	(Zinc powder - zinc dust (stabilized), zinc oxide)	(Zinc powder - zinc dust (stabilized), zinc oxide)	Not applicable.

Additional information

NZ : None identified. Hazchem code: Not applicable.

IMDG : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

The segregation group has been manually assigned based upon product analysis.

IATA : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg,

provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according: Not applicable.

to IMO instruments

Section 15. Regulatory information

New Zealand Inventory of

Chemicals (NZIoC)

: All components are listed or exempted.

HSNO Approval Number

: None assigned.

Emergency Management

Regulations

: Level 1: Not applicable.

Level 2: MSDS required when any amount is present in a workplace.

Level 3: Not applicable.

Approved Handler

International regulations

: Not applicable.

Chemical Weapon Convention List Schedules I. II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

New Zealand Page: 9/10 Product code 10090-FILLR/29K

Date of issue 8 November 2021 Version 2

Product name AMERCOAT D9 FILLER

Section 15. Regulatory information

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Section 16. Other information

Date of issue : 8 November 2021

▼ Indicates information that has changed from previously issued version.

Key to abbreviations : STEL = Short Term Exposure Limit

TWA = Time-Weighted Average WES = Work Exposure Standard

References : Not available.

Organisation that prepared : EHS

the SDS

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

New Zealand Page: 10/10