Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830

SAFETY DATA SHEET

Date of issue/Date of revision

: 22 February 2022 Version



: 2

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: PPG AQUACOVER 45 BASE WHITE.
Product code	: 000001103707
Product type	: Liquid.
Other means of identification	
00146103	
1.2 Relevant identified uses of	the substance or mixture and uses advised against
Product use	Professional applications, Used by spraying.
Use of the substance/ mixture	: Coating.
Uses advised against	Product is not intended, labelled or packaged for consumer use.
1.3 Details of the supplier of th	e safety data sheet
Sigma Paint Saudi Arabia Ltd.	
PO Box 7509 Dammam 31472	
Saudi Arabia	
Tel: 00966 138 47 31 00 Fax: 00966 138 47 17 34	
Fax. 00900 138 47 17 34	
	ndpic@sfda.gov.sa
responsible for this SDS	
1.4 Emergency telephone	00966 138473100 extn 1001
number	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture <u>Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]</u> Skin Irrit. 2, H315

Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements Hazard pictograms



Signal word

: Warning

Conforms to Regulation (EC)	lo. 1907/2006 (REACH), Annex II	
Code : 000001103707	Date of issue/Date of revision : 22 February 20	:022
PPG AQUACOVER 45 BASE	HITE.	
SECTION 2: Hazards	dentification	
Hazard statements	 Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects. 	
Precautionary statements		
Prevention	: Wear protective gloves. Wear eye or face protection. Avoid release to the environm Avoid breathing vapour. Wash thoroughly after handling.	nent.
Response	: 🖸 ollect spillage. Take off contaminated clothing and wash it before reuse.	
Storage	: Not applicable.	
Disposal	: Not applicable.	
Hazardous ingredients	 tetraamminezinc(2+) carbonate 4,5-dichloro-2-octyl-2H-isothiazol-3-one 1,2-benzisothiazol-3(2H)-one 2-methylisothiazol-3(2H)-one octhilinone (ISO) 	
Supplemental label elements	: Warning! Hazardous respirable droplets may be formed when sprayed. Do not brea spray or mist.	athe
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.	
Special packaging requirem	<u>nts</u>	
Containers to be fitted with child-resistant fastenings	: Not applicable.	
Tactile warning of danger	: Not applicable.	
2.3 Other hazards		
Product meets the criteria for PBT or vPvB	: This mixture contains substances that are assessed to be a PBT or a vPvB, refer to Section 3.2.)
Other hazards which do	: Prolonged or repeated contact may dry skin and cause irritation.	

not result in classification

SECTION 3: Composition/information on ingredients

3.2 Mixtures : I	Mixture			
Product/ingredient name	Identifiers	% by weight	<u>Classification</u> Regulation (EC) No. 1272/2008 [CLP]	Туре
2 methoxymethylethoxy)propanol	REACH #: 01-2119450011-60 EC: 252-104-2 CAS: 34590-94-8	≥1.0 - ≤5.0	Not classified.	[2]
propane-1,2-diol	REACH #: 01-2119456809-23 EC: 200-338-0 CAS: 57-55-6	≥1.0 - ≤5.0	Not classified.	[2]
tetraamminezinc(2+) carbonate	REACH #: 01-2120760626-49 EC: 254-099-2 CAS: 38714-47-5	≤0.26	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
	English (GB)	United Arab	Emirates	2/15

Conforms to Regulation (EC) No. Code : 000001103707		issue/Date of re	vision : 22 Februa	rv 2022
PPG AQUACOVER 45 BASE WHI				19 2022
SECTION 3: Composition	on/information on ingre	edients		
propylidynetrimethanol	REACH #: 01-2119486799-10	≤0.30	Repr. 2, H361	[1]
	EC: 201-074-9 CAS: 77-99-6			
ammonia	REACH #: 01-2119982985-14 EC: 215-647-6 CAS: 1336-21-6 Index: 007-001-01-2	≤0.20	Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400 (M=1)	[1]
4,5-dichloro-2-octyl-2H-isothiazol- 3-one	EC: 264-843-8 CAS: 64359-81-5 Index: 613-335-00-8	<0.10	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 2, H330 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 STOT SE 3, H335 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100) EUH071	[1]
1,2-benzisothiazol-3(2H)-one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.10	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411	[1]
3-iodo-2-propynyl butylcarbamate	EC: 259-627-5 CAS: 55406-53-6 Index: 616-212-00-7	≤0.067	Acute Tox. 4, H302 Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (larynx) Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1)	[1]
octamethylcyclotetrasiloxane	REACH #: 01-2119529238-36 EC: 209-136-7 CAS: 556-67-2 Index: 014-018-00-1	≤0.036	Repr. 2, H361f Aquatic Chronic 1, H410 (M=10)	[1] [2] [3] [4]
pyrithione zinc	REACH #: 01-2119511196-46 EC: 236-671-3 CAS: 13463-41-7 Index: 613-333-00-7	<0.010	Acute Tox. 3, H301 Acute Tox. 2, H330 Eye Dam. 1, H318 Repr. 1B, H360D STOT RE 1, H372 Aquatic Acute 1, H400 (M=1000) Aquatic Chronic 1, H410 (M=10)	[1]
2-methylisothiazol-3(2H)-one	REACH #: 01-2120764690-50 EC: 220-239-6 CAS: 2682-20-4 Index: 613-326-00-9	<0.010	Acute Tox. 3, H301 Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1)	[1]
	English (GB)	United Ara	b Emirates	3/15

Conforms to Regulation (EC) No. 1907/	/2006 (REACH), Annex II		
Code : 000001103707	Date of issue/Date of revision : 22 Februa	ary 2022	
PPG AQUACOVER 45 BASE WHITE.			
SECTION 3: Composition/in	nformation on ingredients		
	EUH071		
See Section 16 for the full text of the H	l statements declared above.		
e .	ent which, within the current knowledge of the supplier and in the concent o health or the environment, are PBTs, vPvBs or Substances of equivalen		

concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

[6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	:	Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	:	Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	:	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	:	If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effec	ts	
Eye contact	: 🖉auses serious eye irritation.	
Inhalation	: No known significant effects or critical hazards.	
Skin contact	: 🖉 auses skin irritation. Defatting to the skin. May cause an allergic skin reaction.	
Ingestion	: No known significant effects or critical hazards.	
Over-exposure signs/symp	<u>ioms</u>	
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness	
Inhalation	: No specific data.	
Skin contact	: Adverse symptoms may include the following: irritation redness dryness cracking	
Ingestion	: No specific data.	
4.3 Indication of any immedia	ate medical attention and special treatment needed	
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. 	
	English (CB) United Arch Emirates 4/4	

English (GB) United Arab Emirates

Conforms to Regulation (EC)	No. 1907/2006 (REACH), Annex II	
Code : 00000110370	Date of issue/Date of revision : 22 February 20	22
PPG AQUACOVER 45 BASE	VHITE.	
SECTION 4: First aid	measures	
Specific treatments	: No specific treatment.	
SECTION 5: Firefigh	ing measures	
5.1 Extinguishing media Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.	
Unsuitable extinguishing media	: None known.	
5.2 Special hazards arising f	om the substance or mixture	
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterwas sewer or drain.	า
Hazardous combustion products	: Decomposition products may include the following materials: carbon oxides metal oxide/oxides	
5.3 Advice for firefighters		
Special precautions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breath apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothin for fire-fighters (including helmets, protective boots and gloves) conforming to Europ standard EN 469 will provide a basic level of protection for chemical incidents.	ng

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	otective equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non emergency personnel".
6.2 Environmental precautions	: Kooid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
6.3 Methods and material for	containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Conforms to Regulation (C) No. 1907/2006 (REACH), Annex II		
Code : 000001103	707 Date of issue	e/Date of revision	: 22 February 2022
PPG AQUACOVER 45 BAS	E WHITE.		
SECTION 6: Accid	ental release measures		
Large spill	: Stop leak if without risk. Move container upwind. Prevent entry into sewers, wate spillages into an effluent treatment plant spillage with non-combustible, absorben diatomaceous earth and place in contain Dispose of via a licensed waste disposa may pose the same hazard as the spilt p	er courses, basements t or proceed as follows. nt material e.g. sand, ea ner for disposal accordi Il contractor. Contamin	or confined areas. Wash Contain and collect Irth, vermiculite or ng to local regulations.
6.4 Reference to other sections	: See Section 1 for emergency contact inf See Section 8 for information on approp See Section 13 for additional waste treat	oriate personal protectiv	e equipment.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
7.2 Conditions for safe storage, including any incompatibilities	: Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

Recommendations	: Not available.
Industrial sector specific	: Not available.
solutions	

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Code : 000001103707 PPG AQUACOVER 45 BASE WHITE. Date of issue/Date of revision

SECTION 8: Exposure controls/personal protection

Product/ingredier	nt name	Exposure limit values
Z-methoxymethylethoxy)prop	banol	EU OEL (Europe, 10/2019). Absorbed through skin. TWA: 308 mg/m ³ 8 hours. TWA: 50 ppm 8 hours.
propane-1,2-diol		IPEL (-). TWA: 10 mg/m ³
octamethylcyclotetrasiloxane		IPEL (-, 10/2017). TWA: 10 ppm
Recommended monitoring procedures	atmosphere or b the ventilation or protective equipr following: Europ assessment of e values and meas atmospheres - G exposure to cher atmospheres - G measurement of	ntains ingredients with exposure limits, personal, workplace iological monitoring may be required to determine the effectiveness of other control measures and/or the necessity to use respiratory nent. Reference should be made to monitoring standards, such as the ean Standard EN 689 (Workplace atmospheres - Guidance for the xposure by inhalation to chemical agents for comparison with limit surement strategy) European Standard EN 14042 (Workplace buide for the application and use of procedures for the assessment of mical and biological agents) European Standard EN 482 (Workplace teneral requirements for the performance of procedures for the chemical agents) Reference to national guidance documents for determination of hazardous substances will also be required.
3.2 Exposure controls		
Appropriate engineering controls	: Good general ve contaminants.	ntilation should be sufficient to control worker exposure to airborne
Individual protection measur	<u>'es</u>	
Hygiene measures	eating, smoking Appropriate tech Contaminated w contaminated clo	earms and face thoroughly after handling chemical products, before and using the lavatory and at the end of the working period. niques should be used to remove potentially contaminated clothing. ork clothing should not be allowed out of the workplace. Wash othing before reusing. Ensure that eyewash stations and safety se to the workstation location.
Eye/face protection Skin protection	: Safety glasses w	ith side shields.
Hand protection	worn at all times necessary. Cons during use that th noted that the tin glove manufactu protection time o frequently repeat (breakthrough tin When only brief o (breakthrough tin The user must cl product is the mo	nt, impervious gloves complying with an approved standard should be when handling chemical products if a risk assessment indicates this is sidering the parameters specified by the glove manufacturer, check he gloves are still retaining their protective properties. It should be he to breakthrough for any glove material may be different for different rers. In the case of mixtures, consisting of several substances, the f the gloves cannot be accurately estimated. When prolonged or red contact may occur, a glove with a protection class of 6 ne greater than 480 minutes according to EN 374) is recommended. contact is expected, a glove with a protection class of 2 or higher ne greater than 30 minutes according to EN 374) is recommended. heck that the final choice of type of glove selected for handling this best appropriate and takes into account the particular conditions of use, e user's risk assessment.
Gloves		repeated handling, use the following type of gloves: butyl rubber, Viton®, nitrile rubber
Body protection		ive equipment for the body should be selected based on the task being ne risks involved and should be approved by a specialist before duct.

Conforms to Regulation	on (EC) No. 1907/2006 (REAC	H), Annex II			
Code : 000001	103707	Date of issue/Date of revision	: 22 February 2022		
PPG AQUACOVER 45 BASE WHITE.					
SECTION 8: Exp	oosure controls/pers	onal protection			
Other skin protecti	based on the task	ar and any additional skin protection measu being performed and the risks involved and andling this product.			
Respiratory protecti	hazards of the proc are exposed to cor certified respirators	n must be based on known or anticipated e duct and the safe working limits of the selec ncentrations above the exposure limit, they s. Use a properly fitted, air-purifying or air-fo tandard if a risk assessment indicates this i	ted respirator. If workers must use appropriate, ed respirator complying		
Environmental expo controls	they comply with th cases, fume scrub	ntilation or work process equipment should ne requirements of environmental protection bers, filters or engineering modifications to preduce emissions to acceptable levels.	legislation. In some		

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance								
Physical state	÷	Liquid.						
Colour		, White.						
Odour	÷	Amine-like.						
Odour threshold	÷	Not available.						
pH		8						
Melting point/freezing point		May start to solidify a for the following ingre						ised on data
Initial boiling point and boiling range	:	>37.78°C						
Flash point	:	Closed cup: 120°C						
Evaporation rate	:	Highest known value 0.02compared with b			/methylethoxy)propanc	l) Weigł	nted average
Flammability (solid, gas)	:	liquid						
Upper/lower flammability or explosive limits	:	Greatest known rang propanol)	e: Lower:	1.1% U	pper: 14% ((2	-methox	ymethyle	thoxy)
Vapour pressure	:	:	Vapour Pressure at 20°C		Vapour pressure at 50°C			
		Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
		water	23.8	3.2				
Vapour density	:	Highest known value 2,2,4-trimethylpentar						
Relative density	:	2,2,4-trimethylpentar	ie-1,3-dio	I). Weigl	hted average:	5.35 (Ai		
Relative density Solubility(ies) Partition coefficient: n-octanol/	:	2,2,4-trimethylpentar 1.25	ie-1,3-dio	I). Weigl	hted average:	5.35 (Ai		
Relative density Solubility(ies) Partition coefficient: n-octanol/ water	: : :	2,2,4-trimethylpentar 1.25 Partially soluble in the	ie-1,3-dio	I). Weigl	hted average:	5.35 (Ai		
Relative density Solubility(ies) Partition coefficient: n-octanol/ water Auto-ignition temperature		2,2,4-trimethylpentar 1.25 Partially soluble in the Not applicable.	e-1,3-dio	l). Weigl g materia	hted average: als: cold water	5.35 (Ai	r = 1)	tion 7).
Relative density Solubility(ies) Partition coefficient: n-octanol/ water Auto-ignition temperature Decomposition temperature		2,2,4-trimethylpentar 1.25 Partially soluble in the Not applicable. 207°C (404.6°F)	e followin nended s	l). Weigl g materia	hted average: als: cold water	5.35 (Ai	r = 1)	tion 7).
Relative density Solubility(ies) Partition coefficient: n-octanol/ water Auto-ignition temperature Decomposition temperature Viscosity		2,2,4-trimethylpentar 1.25 Partially soluble in the Not applicable. 207°C (404.6°F) Stable under recomm	ne-1,3-dio e followin nended si 1 mm²/s	l). Weigl g materia	hted average: als: cold water	5.35 (Ai	r = 1)	tion 7).
Vapour density Relative density Solubility(ies) Partition coefficient: n-octanol/ water Auto-ignition temperature Decomposition temperature Viscosity Viscosity Explosive properties		2,2,4-trimethylpentar 1.25 Partially soluble in the Not applicable. 207°C (404.6°F) Stable under recomm	ne-1,3-dio e followin nended si 1 mm²/s)	l). Weigl g materia torage ar	hted average: als: cold water nd handling co	5.35 (Ai	r = 1)	tion 7).

: 000001103707

PPG AQUACOVER 45 BASE WHITE.

Date of issue/Date of revision

SECTION 9: Physical and chemical properties

9.2 Other information

Code

No additional information.

SECTION 10: Stability and reactivity					
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.				
10.2 Chemical stability	: The product is stable.				
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.				
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.				
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.				
10.6 Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides				

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

	Result	Species	Dose	Exposure
Z-methoxymethylethoxy)propanol	LC50 Inhalation Vapour	Rat	500 ppm	4 hours
	LD50 Dermal	Rabbit	9.5 g/kg	-
	LD50 Oral	Rat	5.23 g/kg	-
propane-1,2-diol	LD50 Dermal	Rabbit	20800 mg/kg	-
•	LD50 Oral	Rat	20 g/kg	-
propylidynetrimethanol	LD50 Dermal	Rabbit	10 g/kg	-
	LD50 Oral	Rat	14000 mg/kg	-
ammonia	LD50 Oral	Rat	350 mg/kg	-
4,5-dichloro-2-octyl-2H-isothiazol-3-one	LC50 Inhalation Dusts and	Rat	0.16 mg/l	4 hours
•	mists		, C	
	LD50 Dermal	Rabbit	3.9 g/kg	-
	LD50 Oral	Rat	567 mg/kg	-
1,2-benzisothiazol-3(2H)-one	LC50 Inhalation Dusts and	Rat	0.4 mg/l	4 hours
	mists		Ŭ	
	LD50 Oral	Rat	1020 mg/kg	-
3-iodo-2-propynyl butylcarbamate	LC50 Inhalation Dusts and	Rat	0.67 mg/l	4 hours
	mists		Ŭ	
	LD50 Dermal	Rabbit	>2 g/kg	-
	LD50 Oral	Rat	1470 mg/kg	-
octamethylcyclotetrasiloxane	LC50 Inhalation Vapour	Rat	36 g/m³	4 hours
, ,	LD50 Oral	Rat	>4800 mg/kg	-
pyrithione zinc	LC50 Inhalation Dusts and	Rat	0.14 mg/l	4 hours
	mists		- 5	
	LD50 Dermal	Rabbit	>2 g/kg	-
	LD50 Oral	Rat	177 mg/kg	-
3(2H)-Isothiazolone, 2-methyl-	LC50 Inhalation Dusts and	Rat	0.19 mg/l	4 hours
	mists		J	
	LD50 Dermal	Rat	242 mg/kg	-
	LD50 Oral	Rat - Male	235 mg/kg	-

English (GB)

United Arab Emirates

Date of issue/Date of revision

SECTION 11: Toxicological information

Conclusion/Summary

PPG AQUACOVER 45 BASE WHITE.

: There are no data available on the mixture itself.

Acute toxicity estimates

Not available.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Fiodo-2-propynyl butylcarbamate pyrithione zinc	Eyes - Severe irritant Eyes - Cornea opacity	Rabbit Rabbit	- 4	- 24 hours	- 24 hours
Conclusion/Summary					
Skin : There are no data available on the mixture itself.					
Eyes : There are no data available on the mixture itself.					

: There are no data available on the mixture itself.

: There are no data available on the mixture itself. Respiratory

Sensitisation

Product/ingredient name	Route of exposure	Species	Result
1,2-benzisothiazol-3(2H)-one	skin	Guinea pig	Sensitising

Conclusion/Summary	
Skin	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
Mutagenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Carcinogenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Reproductive toxicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Teratogenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Specific target organ toxi	city (single exposure)

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
ammonia	Category 3	-	Respiratory tract irritation
4,5-dichloro-2-octyl-2H-isothiazol-3-one	Category 3		Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
	Category 1 Category 1	-	larynx -

Aspiration hazard

Not available.

Information on likely : Not :	ot available.
-------------------------------	---------------

routes of exposure

Potential acute health ef		
Inhalation	: No known significant effects or critical hazards.	
Ingestion	: No known significant effects or critical hazards.	
Skin contact	: Causes skin irritation. Defatting to the skin. May cause an allergic sk	in reaction.
Eye contact	: 🖉auses serious eye irritation.	

English (GB) Ur	nited Arab Emirates
-----------------	---------------------

Conforms to Regulation (EC)) No. 1907/2006 (R	EACH), Annex II	
Code : 00000110370	7	Date of issue/Date of revision	: 22 February 2022
PPG AQUACOVER 45 BASE	WHITE.		
SECTION 11: Toxico	logical inform	nation	
Symptoms related to the pl	hysical, chemical a	and toxicological characteristics	
Inhalation	: No specific da	ta.	
Ingestion	: No specific da	ta.	
Skin contact	: Adverse symp irritation redness dryness cracking	toms may include the following:	
Eye contact	: Adverse symp pain or irritatio watering redness	toms may include the following: n	
Delayed and immediate effe	<u>ects as well as ch</u>	ronic effects from short and long-term expos	<u>sure</u>
Short term exposure			
Potential immediate effects	: Not available.		
Potential delayed effects	Not available.		
Long term exposure			
Potential immediate effects	: Not available.		
Potential delayed effects	Not available.		
Potential chronic health eff Not available.	fects		
Conclusion/Summary	: Not available.		
General		epeated contact can defat the skin and lead to i ice sensitized, a severe allergic reaction may oc ry low levels.	
Carcinogenicity	: No known sigr	ificant effects or critical hazards.	
Mutagenicity	: No known sigr	ificant effects or critical hazards.	
Reproductive toxicity	: No known sigr	ificant effects or critical hazards.	
Other information	: Not available.		

Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Contains isothiazolinones. May cause allergic reaction. Avoid contact with skin and clothing.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Z-methoxymethylethoxy)propanol	Acute EC50 1919 mg/l	Daphnia	48 hours
propane-1,2-diol	Acute LC50 40613 mg/l	Fish	96 hours
propylidynetrimethanol	Acute LC50 >1000 mg/l	Fish	96 hours
4,5-dichloro-2-octyl-2H-isothiazol-3-one	Acute EC50 267.368 µg/l	Algae - Nitzschia	96 hours
•	Marine water	pungens	
	Acute LC50 0.318 mg/l	Crustaceans -	48 hours
	Marine water	Artemia sp.	
	Acute LC50 0.0027 mg/l	, Fish	96 hours
	Fresh water		
	Chronic NOEC 19.789 µg/l	Algae - Nitzschia	96 hours
	Marine water	pungens	
	Chronic NOEC 0.00056 mg/l	Fish	97 days
	5		
	English (GB) United Ara	b Emirates	11/15

Conforms to Regulation (EC) No. 1907/2006 (REAC	H), Annex II			
Code : 000001103707	Date of issue/Date of rev	vision : 22 Fe	: 22 February 2022	
PPG AQUACOVER 45 BASE WHITE.				
SECTION 12: Ecological information	ו			
	Fresh water			
1,2-benzisothiazol-3(2H)-one	Acute EC50 0.11 mg/l	Algae	72 hours	
	Chronic NOEC 0.09 mg/l	Fish	28 days	
3-iodo-2-propynyl butylcarbamate	Acute EC50 0.186 mg/l	Daphnia - Daphnia	48 hours	
	Fresh water	magna		
	Acute LC50 0.067 mg/l	Fish	96 hours	
	Chronic NOEC 0.049 mg/l	Fish	96 hours	
pyrithione zinc	Acute EC50 5.513 µg/l Marine	Algae - Nitzschia	96 hours	
	water	pungens		
	Acute LC50 0.0082 mg/l	Daphnia	48 hours	
	Chronic NOEC 1.889 µg/l	Algae - Nitzschia	96 hours	
	Marine water	pungens		
	Chronic NOEC 0.0027 mg/l	Daphnia	21 days	

Conclusion/Summary

: There are no data available on the mixture itself.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
了iodo-2-propynyl butylcarbamate	-	25 % - Inherent - 28 days	-	-
pyrithione zinc	-	39 % - 28 days	-	-

Conclusion/Summary : There are no data available on the mixture itself.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
propane-1,2-diol		-	Readily
1,2-benzisothiazol-3(2H)-one		-	Readily
3-iodo-2-propynyl butylcarbamate		-	Inherent
pyrithione zinc		50%; < 28 day(s)	Not readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-methoxymethylethoxy)propanol	0.004	-	low
propane-1,2-diol	-1.07	-	low
propylidynetrimethanol	-0.47	-	low
1,2-benzisothiazol-3(2H)-one	0.7	-	low
octamethylcyclotetrasiloxane	6.488	-	high
pyrithione zinc	0.9	0.9	low

12.4 Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

		En	glish (GB)	United A	Arab Emirates		12/15
pyrithione zinc	Ňo	N/A	No	Yes	Ňo	N/A	No
	(Candidate)	opeenieu	opeomed	opeemea	(Candidate)	opeemed	opeenied
octamethylcyclotetrasiloxane	SVHC	Specified	Specified	Specified	SVHC	Specified	Specified
carbonate 1,2-benzisothiazol-3(2H)-one	No	N/A	N/A	No	N/A	N/A	N/A
tetraamminezinc(2+)	No	N/A	N/A	No	N/A	N/A	N/A
propanol propane-1,2-diol	No	N/A	N/A	No	N/A	N/A	N/A
Z-methoxymethylethoxy)	No	N/A	N/A	No	N/A	N/A	N/A
Product/ingredient name	PBT	Р	В	Т	vPvB	vP	vB

onforms to Regulation (EC	C) No. 1907/2	006 (REACH	l), Annex II				
Code : 0000011037	07 Date of issue/Date of revision : 22 February 2					ebruary 2022	
PPG AQUACOVER 45 BASE	EWHITE.						
SECTION 12: Ecolo	gical info	rmation					
2-methylisothiazol-3(2H)-or	ne No	N/A	N/A	No	N/A	N/A	N/A
2.6 Other adverse effects	: No kno	wn significan	t effects or ci	itical hazaro	ls.		
SECTION 13: Dispo	sal consi	ideration	S				
The information in this sectio						in Section 1	should be
consulted for any available us	se-specific inf	ormation pro	vided in the l	Exposure So	enario(s).		
3.1 Waste treatment method	ods						
Product							
Methods of disposal	of this p require regiona via a lic	product, solut ments of envi l local author ensed waste	ions and any ironmental pi ity requireme disposal cor	by-products otection and ents. Dispos tractor. Wa	r minimised whe s should at all tin d waste disposal e of surplus and ste should not b irements of all a	nes comply legislation a non-recycla e disposed	with the and any able products of untreated to
Hazardous waste	: Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.					l as hazardous	
European waste catalog	<u>ue (EWC)</u>						
Waste code			١	Vaste desig	Ination		
08 01 12	waste paint and varnish other than those mentioned in 08 01 11						
Packaging							
Methods of disposal	packag		e recycled. Ir		r minimised whe r landfill should		
Type of packaging			Europe	an waste ca	talogue (EWC)		
Container	15 01 06		mixed pa	ckaging			

 Special precautions
 : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number	<mark>₩</mark> N3082	₩ N3082	V N3082
14.2 UN proper shipping name	NVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Tetraamminezinc(2+) carbonate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
14.3 Transport hazard class(es)	9	9 ′	9
14.4 Packing group	I	W	W
14.5 Environmental hazards	₩es.	Y es.	Yes.
Marine pollutant substances	Not applicable.	(retraamminezinc(2+) carbonate)	Not applicable.

Additional information

English (GB) United Arab Emirates

Conforms to Reg	gulation (EC) N	o. 1907/2006 (REACH), A	Annex II	
Code : (00001103707		Date of issue/Date of revision	: 22 February 2022
PPG AQUACOV	ER 45 BASE WI	HITE.		
SECTION 1	4: Transpo	rt information		
ADR/RID Tunnel code	provided the		ngerous good when transported in size meral provisions of 4.1.1.1, 4.1.1.2 and	
IMDG			ngerous good when transported in size neral provisions of 4.1.1.1, 4.1.1.2 and	
ΙΑΤΑ			ngerous good when transported in size neral provisions of 5.0.2.4.1, 5.0.2.6.1.	
14.6 Special pre user	ecautions for :		's premises: always transport in closed sure that persons transporting the produ spillage.	
14.7 Transport i according to IM instruments		Not applicable.		

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

Intrinsic property	Ingredient name	Status	 Date of revision
	octamethylcyclotetrasiloxane; D4 octamethylcyclotetrasiloxane; D4	•	 6/27/2018 6/27/2018

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Other national and international regulations.

Ozone depleting substances (1005/2009/EU)

Not listed.

- **15.2 Chemical safety**
- : No Chemical Safety Assessment has been carried out.

assessment

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
Full text of abbreviated H statements	

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II					
Code : 0000011037	07	Date of issue/Date of revision	: 22 February 2022		
PPG AQUACOVER 45 BASE	E WHITE.				
SECTION 16: Other information					
	 #301 Toxic if swallo H302 Harmful if swallo H311 Toxic in conta H312 Harmful in cor H314 Causes severe H315 Causes skin ir H317 May cause an H318 Causes seriou H319 Causes seriou H330 Fatal if inhaled H331 Toxic if inhaled H335 May cause res H360D May damage t H361 Suspected of d H361f Suspected of d H372 Causes dama H400 Very toxic to a H410 Very toxic to a 	Illowed. ct with skin. itact with skin. e skin burns and eye damage. ritation. allergic skin reaction. is eye damage. is eye damage. is eye irritation. d. d. spiratory irritation. he unborn child. damaging fertility or the unborn child. damaging fertility. ge to organs through prolonged or repe quatic life. quatic life with long lasting effects. ic life with long lasting effects.	eated exposure.		
Full text of classifications [CLP/GHS]	: Acute Tox. 2 Acute Tox. 3 Acute Tox. 4 Aquatic Acute 1 Aquatic Chronic 1 Aquatic Chronic 2 Eye Dam. 1 Eye Irrit. 2 Repr. 1B Repr. 2 Skin Corr. 1 Skin Corr. 1B Skin Irrit. 2 Skin Sens. 1 Skin Sens. 1 Stort RE 1	ACUTE TOXICITY - Category 2 ACUTE TOXICITY - Category 3 ACUTE TOXICITY - Category 4 SHORT-TERM (ACUTE) AQUATIC LONG-TERM (CHRONIC) AQUAT SERIOUS EYE DAMAGE/EYE IRF SERIOUS EYE DAMAGE/EYE IRF REPRODUCTIVE TOXICITY - Cate REPRODUCTIVE TOXICITY - Cate SKIN CORROSION/IRRITATION - SKIN CORROSION/IRRITATION - SKIN SENSITISATION - Category SKIN SENSITISATION - Category SPECIFIC TARGET ORGAN TOXI EXPOSURE - Category 1 SPECIFIC TARGET ORGAN TOXI EXPOSURE - Category 3	IC HAZARD - Category 1 IC HAZARD - Category 2 RITATION - Category 1 RITATION - Category 2 egory 1B egory 2 Category 1 Category 1B Category 2 1 1A ICITY - REPEATED		
<u>History</u> Date of issue/ Date of revision	: 22 February 2022				
Date of previous issue	: 26 February 2021				
Prepared by	: EHS				
Version	: 2				
Disclaimer					

<u>Disclaimer</u>

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.