SAFETY DATA SHEET



Date of issue/Date of revision 1 March 2022 Version 5

Section 1. Identification of the substance/mixture and of the company/undertaking

Product code	: 00249340
Product name	: PPG AQUACOVER 45 REDBROWN 6179
Other means of identification	: Not available.
Product type	: Liquid.

Relevant identified uses of the substance or mixture and uses advised against		
Product use	 Coating. Professional applications, Used by spraying. 	
Uses advised against	: Product is not intended, labelled or packaged for consumer use.	
Supplier's details	: PPG Coatings (Thailand) Co., Ltd. 15 Rama 9 Road, Kwaeng Huamark, Khet Bangkapi, Bangkok 10240 Thailand T: 662-319-4190 #224 F: 662-319-4189	
Emergency telephone number (with hours of operation)	: CHEMTREC 001-800-13-203-9987 (CCN 17704)	

Section 2. Hazards identification

Classification of the substance or mixture	: AQUATIC HAZARD (ACUTE) - Category 2 AQUATIC HAZARD (LONG-TERM) - Category 2
	Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 2.7%
GHS label elements	
Hazard pictograms	: 🔽 🔨
Signal word	: No signal word.
Hazard statements	: 🔽 Toxic to aquatic life with long lasting effects.

Date of issue 1 March 2022

Section 2. Hazards identification

Product name PPG AQUACOVER 45 REDBROWN 6179

Precautionary statements		
Prevention	1	Avoid release to the environment.
Response	1	🖉ollect spillage.
Storage	1	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Other hazards which do not result in classification	:	Prolonged or repeated contact may dry skin and cause irritation. Contains isothiazolinones. May cause allergic reaction.

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

CAS number/other identifiers

CAS number : Not applicable.		
Ingredient name	%	CAS number
✓ (2-butoxy-1-methylethoxy)propan-2-ol	1- <3	29911-28-2
tetraamminezinc(2+) carbonate	0.3 - <1	38714-47-5
4,5-dichloro-2-octyl-2H-isothiazol-3-one	<0.1	64359-81-5
3-iodo-2-propynyl butylcarbamate	<0.1	55406-53-6
pyrithione zinc	<0.1	13463-41-7

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Section 4. First aid measures

Description of necess	ary first aid measures
Eye contact	 Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health	<u>effects</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Defatting to the skin. May cause skin dryness and irritation.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/	symptoms

Over-exposure signs/symptoms

Date of issue 1 March 2022

Product name PPG AQUACOVER 45 REDBROWN 6179

Section 4. First aid measures

Eye contact: No specific data.Inhalation: No specific data.Skin contact: Adverse symptoms may include the following: irritation dryness crackingIngestion: No specific data.Indication of immediate medical attention and special treatment needed, if necessary quantities have been ingested or inhaled.Notes to physician: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.Specific treatments: No specific treatment.Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.			
Skin contact : Adverse symptoms may include the following: irritation dryness cracking Ingestion : No specific data. Indication of immediate medical attention and special treatment needed, if necessary Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. Specific treatments : No specific treatment. Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It	Eye contact	: No specific data.	
irritation dryness cracking Ingestion : No specific data. Indication of immediate medical attention and special treatment needed, if necessary Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. Specific treatments : No specific treatment. Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It	Inhalation	: No specific data.	
Indication of immediate medical attention and special treatment needed, if necessaryNotes to physician: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.Specific treatments: No specific treatment.Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training. It	Skin contact	irritation dryness	
Notes to physician: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.Specific treatments: No specific treatment.Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training. It	Ingestion	: No specific data.	
quantities have been ingested or inhaled.Specific treatments: No specific treatment.Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training. It	Indication of immediate me	ical attention and special treatment needed, if necessary	
Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It	Notes to physician		
	Specific treatments	: No specific treatment.	
	Protection of first-aiders		n.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Product name PPG AQUACOVER 45 REDBROWN 6179

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions Methods and materials for co		Woid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
methods and materials for co		annent and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
	Stop look if without rick. Move containers from chill area. Approach release from

Large spill
 Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling	•	Fut on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Conditions for safe storage, including any incompatibilities	:	Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Mo	ne
MO	ie.

Recommended monitoring procedures	:	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	:	Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, befor eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.		
Eye protection	: Safety glasses with side shields.		
Skin protection			
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.		
Gloves	: For prolonged or repeated handling, use the following type of gloves: Recommended: butyl rubber		
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.		
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.		

Product name PPG AQUACOVER 45 REDBROWN 6179

Section 8. Exposure controls/personal protection

Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

Appearance Physical state : Liquid. Color : Brownish-red. Odor : Amine-like. Odor threshold : Not available. pH : Not available. Melting point : May start to solidify at the following temperature: 0°C (32°F) This is based on d for the following ingredient: water. Weighted average: -7.1°C (19.2°F) Boiling point : >37.78°C (>100°F) Flash point : Closed cup: Not applicable. Evaporation rate : 0.02 ((2-methoxymethylethoxy)propanol) compared with butyl acetate Flammability (solid, gas) : liquid Lower and upper explosive (flammable) limits : Greatest known range: Lower: 0.6% Upper: 20.4% (1-(2-butoxy-1-methylethox propan-2-ol) Vapor pressure : Highest known value: 3.2 kPa (23.8 mm Hg) (at 20°C) (water). Weighted average: 2.93 kPa (21.98 mm Hg) (at 20°C) Vapor density : Highest known value: 6.6 (Air = 1) (1-(2-butoxy-1-methylethoxy)propan-2-ol). Weighted average: 5.85 (Air = 1) Relative density : 1.1 Solubility : Partially soluble in the following materials: cold water.	
Color: Brownish-red.Odor: Amine-like.Odor threshold: Not available.pH: Not available.Melting point: May start to solidify at the following temperature: 0°C (32°F) This is based on d for the following ingredient: water. Weighted average: -7.1°C (19.2°F)Boiling point: >37.78°C (>100°F)Flash point: Closed cup: Not applicable.Evaporation rate: 0.02 ((2-methoxymethylethoxy)propanol) compared with butyl acetateFlammability (solid, gas): liquidLower and upper explosive (flammable) limits: Greatest known range: Lower: 0.6% Upper: 20.4% (1-(2-butoxy-1-methylethox propan-2-ol)Vapor density: Highest known value: 3.2 kPa (23.8 mm Hg) (at 20°C) (water). Weighted average 2.93 kPa (21.98 mm Hg) (at 20°C)Vapor density: Highest known value: 6.6 (Air = 1) (1-(2-butoxy-1-methylethoxy)propan-2-ol). Weighted average: 5.85 (Air = 1)	Appearance
Odor: Amine-like.Odor threshold: Not available.pH: Not available.Melting point: May start to solidify at the following temperature: 0°C (32°F) This is based on d for the following ingredient: water. Weighted average: -7.1°C (19.2°F)Boiling point: >37.78°C (>100°F)Flash point: Closed cup: Not applicable.Evaporation rate: 0.02 ((2-methoxymethylethoxy)propanol) compared with butyl acetateFlammability (solid, gas): liquidLower and upper explosive (flammable) limits: Greatest known range: Lower: 0.6% Upper: 20.4% (1-(2-butoxy-1-methylethox propan-2-ol)Vapor density: Highest known value: 3.2 kPa (23.8 mm Hg) (at 20°C) (water). Weighted average 2.93 kPa (21.98 mm Hg) (at 20°C)Vapor density: Highest known value: 6.6 (Air = 1) (1-(2-butoxy-1-methylethoxy)propan-2-ol). Weighted average: 5.85 (Air = 1)Relative density: 1.1	Physical state
Odor threshold: Not available.pH: Not available.Melting point: May start to solidify at the following temperature: 0°C (32°F) This is based on d for the following ingredient: water. Weighted average: -7.1°C (19.2°F)Boiling point: >37.78°C (>100°F)Flash point: Closed cup: Not applicable.Evaporation rate: 0.02 ((2-methoxymethylethoxy)propanol) compared with butyl acetateFlammability (solid, gas): liquidLower and upper explosive (flammable) limits: Greatest known range: Lower: 0.6% Upper: 20.4% (1-(2-butoxy-1-methylethox propan-2-ol)Vapor density: Highest known value: 3.2 kPa (23.8 mm Hg) (at 20°C) (water). Weighted average: 2.93 kPa (21.98 mm Hg) (at 20°C)Vapor density: Highest known value: 6.6 (Air = 1) (1-(2-butoxy-1-methylethoxy)propan-2-ol). Weighted average: 5.85 (Air = 1)Relative density: 1.1	Color
pH: Not available.Melting point: May start to solidify at the following temperature: 0°C (32°F) This is based on d for the following ingredient: water. Weighted average: -7.1°C (19.2°F)Boiling point: >37.78°C (>100°F)Flash point: Closed cup: Not applicable.Evaporation rate: 0.02 ((2-methoxymethylethoxy)propanol) compared with butyl acetateFlammability (solid, gas): liquidLower and upper explosive (flammable) limits: Greatest known range: Lower: 0.6% Upper: 20.4% (1-(2-butoxy-1-methylethox propan-2-ol)Vapor pressure: Highest known value: 3.2 kPa (23.8 mm Hg) (at 20°C) (water). Weighted average: 2.93 kPa (21.98 mm Hg) (at 20°C)Vapor density: Highest known value: 6.6 (Air = 1) (1-(2-butoxy-1-methylethoxy)propan-2-ol). Weighted average: 5.85 (Air = 1)Relative density: 1.1	Odor
Melting point: May start to solidify at the following temperature: 0°C (32°F) This is based on d for the following ingredient: water. Weighted average: -7.1°C (19.2°F)Boiling point: >37.78°C (>100°F)Flash point: Closed cup: Not applicable.Evaporation rate: 0.02 ((2-methoxymethylethoxy)propanol) compared with butyl acetateFlammability (solid, gas): liquidLower and upper explosive (flammable) limits: Greatest known range: Lower: 0.6% Upper: 20.4% (1-(2-butoxy-1-methylethox propan-2-ol)Vapor pressure: Highest known value: 3.2 kPa (23.8 mm Hg) (at 20°C) (water). Weighted average: 2.93 kPa (21.98 mm Hg) (at 20°C)Vapor density: Highest known value: 6.6 (Air = 1) (1-(2-butoxy-1-methylethoxy)propan-2-ol). Weighted average: 5.85 (Air = 1)Relative density: 1.1	Odor threshold
for the following ingredient: water. Weighted average: -7.1°C (19.2°F)Boiling point: >37.78°C (>100°F)Flash point: Closed cup: Not applicable.Evaporation rate: 0.02 ((2-methoxymethylethoxy)propanol) compared with butyl acetateFlammability (solid, gas): liquidLower and upper explosive (flammable) limits: Greatest known range: Lower: 0.6% Upper: 20.4% (1-(2-butoxy-1-methylethox propan-2-ol)Vapor pressure: Highest known value: 3.2 kPa (23.8 mm Hg) (at 20°C) (water). Weighted average: 2.93 kPa (21.98 mm Hg) (at 20°C)Vapor density: Highest known value: 6.6 (Air = 1) (1-(2-butoxy-1-methylethoxy)propan-2-ol). Weighted average: 5.85 (Air = 1)Relative density: 1.1	рН
Flash point: Closed cup: Not applicable.Evaporation rate: 0.02 ((2-methoxymethylethoxy)propanol) compared with butyl acetateFlammability (solid, gas): liquidLower and upper explosive (flammable) limits: Greatest known range: Lower: 0.6% Upper: 20.4% (1-(2-butoxy-1-methylethox propan-2-ol)Vapor pressure: Highest known value: 3.2 kPa (23.8 mm Hg) (at 20°C) (water). Weighted avera 2.93 kPa (21.98 mm Hg) (at 20°C)Vapor density: Highest known value: 6.6 (Air = 1) (1-(2-butoxy-1-methylethoxy)propan-2-ol). Weighted average: 5.85 (Air = 1)Relative density: 1.1	Melting point
Evaporation rate: 0.02 ((2-methoxymethylethoxy)propanol) compared with butyl acetateFlammability (solid, gas): liquidLower and upper explosive (flammable) limits: Greatest known range: Lower: 0.6% Upper: 20.4% (1-(2-butoxy-1-methylethox propan-2-ol)Vapor pressure: Highest known value: 3.2 kPa (23.8 mm Hg) (at 20°C) (water). Weighted avera 2.93 kPa (21.98 mm Hg) (at 20°C)Vapor density: Highest known value: 6.6 (Air = 1) (1-(2-butoxy-1-methylethoxy)propan-2-ol). Weighted average: 5.85 (Air = 1)Relative density: 1.1	Boiling point
Flammability (solid, gas): liquidLower and upper explosive (flammable) limits: Greatest known range: Lower: 0.6% Upper: 20.4% (1-(2-butoxy-1-methylethox propan-2-ol)Vapor pressure: Highest known value: 3.2 kPa (23.8 mm Hg) (at 20°C) (water). Weighted average: 2.93 kPa (21.98 mm Hg) (at 20°C)Vapor density: Highest known value: 6.6 (Air = 1) (1-(2-butoxy-1-methylethoxy)propan-2-ol). Weighted average: 5.85 (Air = 1)Relative density: 1.1	Flash point
Lower and upper explosive (flammable) limits: Greatest known range: Lower: 0.6% Upper: 20.4% (1-(2-butoxy-1-methylethox propan-2-ol)Vapor pressure: Highest known value: 3.2 kPa (23.8 mm Hg) (at 20°C) (water). Weighted avera 2.93 kPa (21.98 mm Hg) (at 20°C)Vapor density: Highest known value: 6.6 (Air = 1) (1-(2-butoxy-1-methylethoxy)propan-2-ol). Weighted average: 5.85 (Air = 1)Relative density: 1.1	Evaporation rate
(flammable) limitspropan-2-ol)Vapor pressure: Highest known value: 3.2 kPa (23.8 mm Hg) (at 20°C) (water). Weighted average: 2.93 kPa (21.98 mm Hg) (at 20°C)Vapor density: Highest known value: 6.6 (Air = 1) (1-(2-butoxy-1-methylethoxy)propan-2-ol). Weighted average: 5.85 (Air = 1)Relative density: 1.1	Flammability (solid, gas)
Vapor density2.93 kPa (21.98 mm Hg) (at 20°C)Vapor density: Highest known value: 6.6 (Air = 1) (1-(2-butoxy-1-methylethoxy)propan-2-ol). Weighted average: 5.85 (Air = 1)Relative density: 1.1	
Weighted average: 5.85 (Air = 1)Relative density: 1.1	Vapor pressure
	Vapor density
Solubility	Relative density
	Solubility
Partition coefficient: n- : Not applicable. octanol/water	
Auto-ignition temperature : Lowest known value: 194°C (381.2°F) (1-(2-butoxy-1-methylethoxy)propan-2-c	Auto-ignition temperature
Decomposition temperature : Stable under recommended storage and handling conditions (see Section 7).	Decomposition temperature
Viscosity : Kinematic (40°C): >21 mm²/s	Viscosity

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.

Product code 00249340

Product name PPG AQUACOVER 45 REDBROWN 6179

Section 10. Stability and reactivity

Conditions to avoid	:	When exposed to high temperatures may produce hazardous decomposition products.
Incompatible materials	:	Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	:	Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
(2-butoxy-1-methylethoxy)propan- 2-ol	LC50 Inhalation Dusts and mists	Rat	5.4 mg/l	4 hours
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	4.05 g/kg	-
4,5-dichloro-2-octyl-2H-isothiazol- 3-one	LC50 Inhalation Dusts and mists	Rat	0.16 mg/l	4 hours
	LD50 Dermal	Rabbit	3.9 g/kg	-
	LD50 Oral	Rat	567 mg/kg	-
3-iodo-2-propynyl butylcarbamate	LC50 Inhalation Dusts and mists	Rat	0.67 mg/l	4 hours
	LD50 Dermal	Rabbit	>2 g/kg	-
	LD50 Oral	Rat	1470 mg/kg	-
pyrithione zinc	LC50 Inhalation Dusts and mists	Rat	0.14 mg/l	4 hours
	LD50 Dermal	Rabbit	>2 g/kg	-
	LD50 Oral	Rat	177 mg/kg	-

Conclusion/Summary : There are no data available on the mixture itself.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation	
iodo-2-propynyl butylcarbamate	Eyes - Severe irritant	Rabbit	-	-	-	
pyrithione zinc	Eyes - Cornea opacity	Rabbit	4	24 hours	24 hours	
Conclusion/Summary						
Skin	: There are no data avai	lable on the mixtu	re itself.			
Eyes	There are no data available on the mixture itself.					
Respiratory	: There are no data avai	There are no data available on the mixture itself.				
Sensitization						
Conclusion/Summary						
Skin	: There are no data avai	lable on the mixtu	re itself.			
Respiratory	: There are no data avai	lable on the mixtu	re itself.			
Mutagenicity						
Conclusion/Summary	: There are no data avai	lable on the mixtu	re itself.			
Carcinogenicity						

Product name PPG AQUACOVER 45 REDBROWN 6179

Section 11. Toxicological information

Conclusion/Summary	: There are no data available on the mixture itself.			
Reproductive toxicity				
Conclusion/Summary	: There are no data available on the mixture itself.			
<u>Teratogenicity</u>				
Conclusion/Summary	: There are no data available on the mixture itself.			
Specific target organ toxicity (single exposure)				

Name	•••	Route of exposure	Target organs
	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
	Category 1 Category 1	-	trachea -

Aspiration hazard

Not available.

Information on the likely : Not available. routes of exposure

Potential acute health effects

Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Defatting to the skin. May cause skin dryness and irritation.
Ingestion	: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact Inhalation	No specific data.No specific data.
Skin contact	: Adverse symptoms may include the following: irritation dryness cracking
Ingestion	: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure	
Potential immediate effects	: Not available.

Version 5

irritation, cracking and/

Product name PPG AQUACOVER 45 REDBROWN 6179

Section 11. Toxicological information

Potential delayed effects	: Not available.
<u>Long term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	<u>ects</u>
General	: Prolonged or repeated contact can defat the skin and lead to or dermatitis.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	162612.59 mg/kg
Dermal	89292.29 mg/kg

Other information

Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Contains isothiazolinones. May cause allergic reaction. Avoid contact with skin and clothing.

Section 12. Ecological information

2

<u>Toxicity</u>

Product/ingredient name	Result	Species	Exposure
✓-(2-butoxy-1-methylethoxy) propan-2-ol	Acute LC50 841 mg/l	Fish	96 hours
4,5-dichloro-2-octyl-2H- isothiazol-3-one	Acute EC50 267.368 µg/l Marine water	Algae - Nitzschia pungens	96 hours
	Acute LC50 0.318 mg/l Marine water	Crustaceans - Artemia sp.	48 hours
	Acute LC50 0.0027 mg/l Fresh water	Fish	96 hours
	Chronic NOEC 19.789 µg/l Marine water	Algae - Nitzschia pungens	96 hours
	Chronic NOEC 0.00056 mg/l Fresh water	Fish	97 days
3-iodo-2-propynyl butylcarbamate	Acute EC50 0.186 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
-	Acute LC50 0.067 mg/l	Fish	96 hours
	Chronic NOEC 0.049 mg/l	Fish	96 hours
pyrithione zinc	Acute EC50 5.513 µg/l Marine water	Algae - Nitzschia pungens	96 hours
		Thailand	Page: 9/1

Product code 00249340

Version 5

Product name PPG AQUACOVER 45 REDBROWN 6179

Section 12. Ecological information

	Acute LC50 0.0082 mg/l	Daphnia	48 hours
	Chronic NOEC 1.889 µg/l Marine water	Algae - Nitzschia pungens	96 hours
	Chronic NOEC 0.0027 mg/l	Daphnia	21 days
Conclusion/Summary	: There are no data available on the m	ixture itself.	

.

Persistence/degradability

Product/ingredient name	Test	Result		Dose	Inoculum
√-(2-butoxy-1-methylethoxy) propan-2-ol	OECD 302B	96 % - Readily - 28	days ·	-	-
3-iodo-2-propynyl butylcarbamate	-	25 % - Inherent - 28	days ·	-	-
pyrithione zinc	-	39 % - 28 days		-	-
Conclusion/Summary : There are no data available on the mixture itself.					
Product/ingredient name	Aquatic half-life		Photolysis		Biodegradability

•	•	• •
-	-	Readily
-	-	Inherent
-	50%; < 28 day(s)	Not readily
-		-

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
(2-butoxy-1-methylethoxy)propan-2-ol	1.523		low
pyrithione zinc	0.9		low

<u>Mobility in soil</u>	
Soil/water partition coefficient (Koc)	: Not available.
Other adverse effects	: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
------------------	--

Section 14. Transport information

	UN	IMDG	ΙΑΤΑ
UN number	VN3082	VN3082	VN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
	(tetraamminezinc(2+) carbonate)	(tetraamminezinc(2+) carbonate)	(tetraamminezinc(2+) carbonate)
Transport hazard class(es)	9	9	9
Packing group			
Environmental hazards	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	(tetraamminezinc(2+) carbonate)	Not applicable.

Additional information

UN	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
IMDG	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
ΙΑΤΑ	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Section 15. Regulatory information

: Listed

Safety, health and environmental regulations specific for the product

Harmful Chemicals List

: No known specific national and/or regional regulations applicable to this product (including its ingredients).

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants Not listed.

Section 16. Other information

<u>History</u>	
Date of issue/Date of revision	: 1 March 2022
Date of previous issue	: 12/23/2020
Version	: 5
Prepared by	: EHS
Key to abbreviations	 ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail UN = United Nations

Indicates information that has changed from previously issued version.

Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.