# SAFETY DATA SHEET



Date of issue/Date of revision 2 March 2022 Version3

### **Section 1. Identification**

Product code : 00384108

Product name : PPG HI-TEMP 808 GREY

Other means of

identification

: Not available.

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Coating.

Professional applications, Used by spraying.

**Uses advised against**: Product is not intended, labelled or packaged for consumer use.

Supplier's details : PT PPG Coatings Indonesia

Jl. Rawagelam III No.1

13930 Jakarta Indonesia

Tel +62 21 4605710 PMC.Safety@PPG.com

**Emergency telephone** 

number

: CHEMTREC 001-803-017-9114 (CCN 17704)

## Section 2. Hazards identification

Classification of the substance or mixture

: SKIN SENSITIZATION - Category 1

TOXIC TO REPRODUCTION - Category 1B AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 2

Percentage of the mixture consisting of ingredient(s) of unknown hazards to the

aquatic environment: 39.4%

GHS label elements, including precautionary statements

Hazard pictograms :







Signal word : Danger

**Hazard statements** : May cause an allergic skin reaction.

May damage fertility or the unborn child.

Very toxic to aquatic life.

Toxic to aquatic life with long lasting effects.

**Precautionary statements** 

Indonesia Page: 1/12

**Product name PPG HI-TEMP 808 GREY** 

### Section 2. Hazards identification

: Obtain special instructions before use. Do not handle until all safety precautions **Prevention** have been read and understood. Wear protective gloves, protective clothing and

eye or face protection. Avoid release to the environment. Avoid breathing vapor.

Contaminated work clothing should not be allowed out of the workplace.

Response Collect spillage. IF exposed or concerned: Get medical advice or attention. Take

off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention.

**Storage** : Store locked up.

: Dispose of contents and container in accordance with all local, regional, national **Disposal** 

and international regulations.

Other hazards which do not : None known. result in classification

# Section 3. Composition/information on ingredients

Substance/mixture Mixture

#### CAS number/other identifiers

**CAS** number : Not applicable. **EC** number Mixture.

Ingredient name	%	CAS number
pyrithione zinc 1,2-benzisothiazol-3(2H)-one	0.3- <1 0.1- <0.3	13463-41-7 2634-33-5
3-iodo-2-propynyl butylcarbamate		55406-53-6

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

SUB codes represent substances without registered CAS Numbers.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

### **Description of necessary first aid measures**

Eye contact : Remove contact lenses, irrigate copiously with clean, fresh water, holding the

eyelids apart for at least 10 minutes and seek immediate medical advice.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognized skin cleanser. Do NOT use solvents or thinners.

: If swallowed, seek medical advice immediately and show this container or label. Ingestion

Keep person warm and at rest. Do NOT induce vomiting.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact** : No known significant effects or critical hazards. Inhalation : No known significant effects or critical hazards.

: May cause an allergic skin reaction. Skin contact

Indonesia Page: 2/12

**Product name PPG HI-TEMP 808 GREY** 

### Section 4. First aid measures

**Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : No specific data.

**Inhalation** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

**Ingestion**: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments**: No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it

is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing

thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

### **Extinguishing media**

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing** 

media

: None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is very toxic to aquatic life. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

 Decomposition products may include the following materials: carbon oxides

carbon oxides metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without

suitable training.

Indonesia Page: 3/12

**Product name PPG HI-TEMP 808 GREY** 

## Section 5. Fire-fighting measures

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

#### Methods and materials for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

#### **Precautions for safe handling**

**Protective measures** 

Eut on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Indonesia Page: 4/12

**Product name PPG HI-TEMP 808 GREY** 

# Section 7. Handling and storage

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

including any incompatibilities

Conditions for safe storage, : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

**Control parameters** 

Occupational exposure limits

None.

**Recommended monitoring** procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

: Fuser operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection Skin protection Hand protection** 

: Safety glasses with side shields.

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

> Indonesia Page: 5/12

**Product name PPG HI-TEMP 808 GREY** 

# Section 8. Exposure controls/personal protection

Gloves : butyl rubber

**Body protection**: Personal protective equipment for the body should be selected based on the task

being performed and the risks involved and should be approved by a specialist

before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the

hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is

necessary.

# Section 9. Physical and chemical properties

**Appearance** 

Physical state : Liquid.
Color : White.

Odor : Characteristic.
Odor threshold : Not available.

pH : Not available.

Melting point : Not available.

Boiling point : >37.78°C (>100°F)

Flash point : Closed cup: Not applicable.

**Evaporation rate** : Not available. **Flammability/Combustible** : Not available.

properties (solid, gas)
Lower and upper explosive

(flammable) limits

: Not available.

Vapor pressure: Not available.Vapor density: Not available.

Relative density : 0.6

**Solubility** : Soluble in the following materials: cold water.

Partition coefficient: n-

octanol/water

: Not applicable.

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Viscosity : Kinematic (40°C): >21 mm<sup>2</sup>/s

## Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability**: The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Indonesia Page: 6/12

**Product name PPG HI-TEMP 808 GREY** 

# Section 10. Stability and reactivity

**Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition

products.

**Incompatible materials**: Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents, strong alkalis, strong acids.

**Hazardous decomposition** 

products

: Depending on conditions, decomposition products may include the following

materials: carbon oxides metal oxide/oxides

# **Section 11. Toxicological information**

#### Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
yrithione zinc	LC50 Inhalation Dusts and mists	Rat	0.14 mg/l	4 hours
	LD50 Dermal	Rabbit	>2 g/kg	-
	LD50 Oral	Rat	177 mg/kg	-
1,2-benzisothiazol-3(2H)-one	LC50 Inhalation Dusts and mists	Rat	0.4 mg/l	4 hours
	LD50 Oral	Rat	1020 mg/kg	-
3-iodo-2-propynyl butylcarbamate	LC50 Inhalation Dusts and mists	Rat	0.67 mg/l	4 hours
	LD50 Dermal	Rabbit	>2 g/kg	-
	LD50 Oral	Rat	1470 mg/kg	-

Conclusion/Summary

: There are no data available on the mixture itself.

# Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
pyrithione zinc 3-iodo-2-propynyl butylcarbamate	Eyes - Cornea opacity Eyes - Severe irritant	Rabbit Rabbit	4	24 hours -	24 hours

#### **Conclusion/Summary**

Skin: There are no data available on the mixture itself.Eyes: There are no data available on the mixture itself.Respiratory: There are no data available on the mixture itself.

### **Sensitization**

3	Route of exposure	Species	Result
1,2-benzisothiazol-3(2H)-one	skin	Guinea pig	Sensitizing

### **Conclusion/Summary**

Skin : There are no data available on the mixture itself.Respiratory : There are no data available on the mixture itself.

**Mutagenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

Carcinogenicity

**Conclusion/Summary**: There are no data available on the mixture itself.

Reproductive toxicity

**Conclusion/Summary**: There are no data available on the mixture itself.

Indonesia <sup>:</sup> Page: 7/12

**Product name PPG HI-TEMP 808 GREY** 

# **Section 11. Toxicological information**

**Teratogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Name	3 3 3	Route of exposure	Target organs
yrithione zinc	Category 1	-	-
3-iodo-2-propynyl butylcarbamate	Category 1		trachea

### **Aspiration hazard**

Not available.

Information on the likely

routes of exposure

: Not available.

Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

**Skin contact** : May cause an allergic skin reaction.

**Ingestion** : No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

**Inhalation** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact**: Kaverse symptoms may include the following:

irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

**Ingestion** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

### Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

**Potential immediate** 

: There are no data available on the mixture itself.

Potential delayed effects

: There are no data available on the mixture itself.

Long term exposure

**Potential immediate** 

: There are no data available on the mixture itself.

effects

effects

Potential delayed effects : There are no data available on the mixture itself.

Indonesia <sup>:</sup> Page: 8/12

**Product name PPG HI-TEMP 808 GREY** 

# **Section 11. Toxicological information**

#### Potential chronic health effects

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

Carcinogenicity : No known significant effects or critical hazards.Mutagenicity : No known significant effects or critical hazards.

**Reproductive toxicity**: May damage fertility or the unborn child.

#### **Numerical measures of toxicity**

#### **Acute toxicity estimates**

Not available.

#### Other information

Sanding and grinding dusts may be harmful if inhaled.

# **Section 12. Ecological information**

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
pyrithione zinc	Acute EC50 5.513 µg/l Marine water	Algae - Nitzschia pungens	96 hours
	Acute LC50 0.0082 mg/l	Daphnia	48 hours
	Chronic NOEC 1.889 µg/l Marine water	Algae - Nitzschia pungens	96 hours
	Chronic NOEC 0.0027 mg/l	Daphnia	21 days
1,2-benzisothiazol-3(2H)-one	Acute EC50 0.11 mg/l	Algae	72 hours
,	Chronic NOEC 0.09 mg/l	Fish	28 days
3-iodo-2-propynyl butylcarbamate	Acute EC50 0.186 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
·	Acute LC50 0.067 mg/l	Fish	96 hours
	Chronic NOEC 0.049 mg/l	Fish	96 hours

### Persistence/degradability

Not available.

Product/ingredient name	Test	Result		Dose	Inoculum
pyrithione zinc 3-iodo-2-propynyl butylcarbamate	-	39 % - 28 d 25 % - Inhe	ays rent - 28 days	-	-
Product/ingredient name	Aquatic hal	f-life	Photoly	/sis	Biodegradability
nyrithione zinc	_		50%: < '	28 day(s)	Not readily

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
pyrithione zinc	-	50%; < 28 day(s)	Not readily
1,2-benzisothiazol-3(2H)-one	-	-	Readily
3-iodo-2-propynyl	-	-	Inherent
butylcarbamate			

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
pyrithione zinc	0.9	0.9	low
1,2-benzisothiazol-3(2H)-one	0.7		low

Indonesia <sup>:</sup> Page: 9/12

Product code 00384108 Version 3 Date of issue 2 March 2022

**Product name PPG HI-TEMP 808 GREY** 

# Section 12. Ecological information

**Mobility in soil** 

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

### Section 13. Disposal considerations

**Disposal methods** 

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# **Section 14. Transport information**

	UN	IMDG	IATA
UN number	UN3082	UN3082	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
	(pyrithione zinc)	(pyrithione zinc)	(pyrithione zinc)
Transport hazard class(es)	9	9	9
Packing group	III	III	III
Environmental hazards	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	(pyrithione zinc)	Not applicable.

#### **Additional information**

UN

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

**IMDG** 

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

IATA

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Indonesia Page: 10/12

**Product name PPG HI-TEMP 808 GREY** 

### Section 14. Transport information

Transport in bulk according : Not applicable.

to IMO instruments

## Section 15. Regulatory information

Safety, health and environmental regulations specific for the product : No known specific national and/or regional regulations applicable to this product (including its ingredients).

Law No. 74/2001 - Banned

None of the components are listed.

#### Law No. 74/2001 - Restricted

None of the components are listed.

Law No. 74/2001 - : Not determined

Chemicals that may be used

**International regulations** 

**Montreal Protocol** 

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

### Section 16. Other information

**History** 

Date of issue/Date of : 2 March 2022

revision

Date of previous issue : 6/28/2021

Version : 3
Prepared by : EHS

**Key to abbreviations** : ADN = European Provisions concerning the International Carriage of Dangerous

Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of

Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

RID = The Regulations concerning the International Carriage of Dangerous Goods

by Rail

UN = United Nations

Indicates information that has changed from previously issued version.

**Notice to reader** 

Indonesia Page: 11/12

**Product name PPG HI-TEMP 808 GREY** 

### Section 16. Other information

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

Indonesia Page: 12/12