# SAFETY DATA SHEET

**AQUAPON WB Epoxy Gloss Comp B** 



Date of issue 4 March 2022

Version 7

# 1. Product and company identification

Product name	: AQUAPON WB Epoxy Gloss Comp B
Product code	: 00338337
Product type	: Liquid.

Relevant identified uses of the substance or mixture and uses advised against		
Product use	: Industrial applications.	
Use of the substance/ mixture	: Raw Material(s) for Paint; Coating.	
Uses advised against	: Not applicable.	
Supplier's details	: PPG PMC Japan Co., Ltd. 8F, Shintetsu Bldg., 1-1, Daikaidori 1-chome, Kobe 652-0803 Tel : +81 78 574 2777 Fax : +81 78 576 0035	
Emergency telephone number	: 078 574 2777	

# 2. Hazards identification

GHS Classification	: ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 TOXIC TO REPRODUCTION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 HAZARDOUS TO THE AQUATIC ENVIRONMENT - ACUTE HAZARD - Category 1 HAZARDOUS TO THE AQUATIC ENVIRONMENT - CHRONIC HAZARD - Category 1
<u>GHS label elements</u> Hazard pictograms	
Signal word	: Warning
Hazard statements	<ul> <li>Causes skin irritation.</li> <li>May cause an allergic skin reaction.</li> <li>Causes serious eye irritation.</li> <li>Harmful if inhaled.</li> <li>Suspected of damaging fertility or the unborn child.</li> <li>May cause damage to organs. (blood, haematopoietic system, kidneys, liver, respiratory system)</li> <li>May cause damage to organs through prolonged or repeated exposure.</li> </ul>

# 2. Hazards identification

		(haematopoietic system)
		Very toxic to aquatic life with long lasting effects.
Precautionary statements		
Prevention	:	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.
Response	:	Collect spillage. IF exposed or concerned: Call a POISON CENTER or doctor. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Storage	:	Store locked up.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Other hazards which do not result in classification	:	Prolonged or repeated contact may dry skin and cause irritation.

# 3. Composition/information on ingredients

Substance/mixture

: Mixture

#### CAS number/other identifiers

**CAS number** : Not applicable.

CSCL number

: Not available.

Ingredient name	%	CAS number	CSCL
✓olycondensate of 4,4'-isopropylidenediphenol and 1-chloro-2,3-epoxypropane (liquid only)	25 - <50	25068-38-6	7-1283
2-Propoxyethanol	5 - <7	2807-30-9	2-2424; 7-97
Ethylene glycol mono-n-butyl ether	3 - <5	111-76-2	2-2424; 2-407; 7-97
Petroleum Derivatives crystalline silica, respirable powder (>10 microns)	1 - <2 0.1 - <0.2	SUB100271 14808-60-7	Not available. 1-548

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

# 4. First aid measures

#### Description of necessary first aid measures

Eye contact	1	Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	:	Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

Product code 00338337	Date of issue 4 March 2022 Version 7
Product name AQUAPON V	
4. First aid measu	ires
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
Most important symptoms/	effects, acute and delayed
Potential acute health effe	<u>cts</u>
Eye contact	: Causes serious eye irritation.
Inhalation	: Harmful if inhaled.
Skin contact	: May cause damage to organs following a single exposure in contact with skin. Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
Ingestion	: May cause damage to organs following a single exposure if swallowed.
<u>Over-exposure signs/sym</u>	<u>ptoms</u>
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: irritation redness dryness cracking reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Indication of immediate me	dical attention and special treatment needed, if necessary
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

# 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides halogenated compounds
Special protective actions for fire-fighters	<ul> <li>Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.</li> </ul>
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# 6. Accidental release measures

Personal precautions, protect	tive equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
Methods and materials for co	ntainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# 7. Handling and storage

Precautions for safe handling	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Conditions for safe storage	Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10

for incompatible materials before handling or use.

# 8. Exposure controls/personal protection

### **Control parameters**

#### **Occupational exposure limits**

Ingredient name	Exposure limits	
Ethylene glycol mono-n-butyl ether	ISHL (Japan, 6/2020). TWA: 25 ppm 8 hours. Japan Society for Occupational Health (Japan, 5/2020). Absorbed through skin. OEL-C: 97 mg/m <sup>3</sup> OEL-C: 20 ppm	
crystalline silica, respirable powder (>10 microns)	Japan Society for Occupational Health (Japan, 5/2020). OEL-C: 0.03 mg/m <sup>3</sup> Form: Respirable dust	

Recommended monitoring	. In this product contains ingredients with exposure limits, personal, workplace
procedures	atmosphere or biological monitoring may be required to determine the effectiveness
-	of the ventilation or other control measures and/or the necessity to use respiratory
	protective equipment. Reference should be made to appropriate monitoring
	standards. Reference to national guidance documents for methods for the
	determination of hazardous substances will also be required.

Appropriate engineering	: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation
controls	or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure	: Emissions from ventilation or work process equipment should be checked to ensure
controls	they comply with the requirements of environmental protection legislation. In some
	cases, fume scrubbers, filters or engineering modifications to the process equipment
	will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

# 8. Exposure controls/personal protection Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Eye protection : Chemical splash goggles. Skin protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates the in protection to products if a risk assessment indicates the in protection

	this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	: butyl rubber
Body protection	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

# 9. Physical and chemical properties

Appearance	
Physical state	: Liquid.
Odor	: Characteristic.
Boiling point	: >37.78°C (>100°F)
Flash point	: Closed cup: 93.33°C (200°F)
Relative density	: 1.07
Solubility	: Partially soluble in the following materials: cold water.
Viscosity	: Not Applicable

10. Stability and reactivity				
Reactivity	: No specific test data related to reactivity available for this product or its ingredients.			
Chemical stability	: The product is stable.			
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.			
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.			
	Japan Page: 6/14			

Hazardous decomposition	: Depending on conditions, decomposition products may include the following
products	materials: carbon oxides halogenated compounds

oxidizing agents, strong alkalis, strong acids.

# **11. Toxicological information**

# Information on toxicological effects

Acute toxicity					
Product/ingredient name	Result	Species	Dose	Exposure	
Polycondensate of 4,4'- isopropylidenediphenol and 1-chloro-2,3-epoxypropane (liquid only)	LD50 Dermal	Rabbit	>2 g/kg	-	
	LD50 Oral	Rat	>2 g/kg	-	
2-Propoxyethanol	LD50 Dermal	Rabbit	1.337 g/kg	-	
	LD50 Oral	Rat	3089 mg/kg	-	
Ethylene glycol mono-n- butyl ether	LD50 Dermal	Rat	>2000 mg/kg	-	
•	LD50 Oral	Rat	1200 mg/kg	-	

## Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Polycondensate of 4,4'- isopropylidenediphenol and 1-chloro-2,3-epoxypropane (liquid only)	Skin - Moderate irritant	Rabbit	-	-	-
	Eyes - Moderate irritant	Rabbit	-	-	-
	Eyes - Mild irritant	Rabbit	-	100 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 UI	-
	Skin - Severe irritant	Rabbit	-	24 hours 2 mg	-
Ethylene glycol mono-n- butyl ether	Skin - Moderate irritant	Rabbit	-	4 hours	28 days
	Eyes - Irritant	Rabbit	-	24 hours	21 days

#### **Sensitization**

Product/ingredient name	Route of exposure	Species	Result
♥olycondensate of 4,4'- isopropylidenediphenol and 1-chloro-2,3-epoxypropane (liquid only)	skin	Mouse	Sensitizing

### **Mutagenicity**

Not available.

# **Carcinogenicity**

Not available.

# **Reproductive toxicity**

Not available.

# 11. Toxicological information

Product name AQUAPON WB Epoxy Gloss Comp B

# **Teratogenicity**

Not available.

# Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
2-Propoxyethanol	Category 1	-	blood
Ethylene glycol mono-n-butyl ether	Category 1	-	haematopoietic system, kidneys, liver, respiratory system
	Category 3		Narcotic effects
Petroleum Derivatives	Category 3	-	Respiratory tract irritation

# Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
2-Propoxyethanol Ethylene glycol mono-n-butyl ether	Category 2 Category 1	-	blood haematopoietic system

# Aspiration hazard

Not available.

Information on the likely routes of exposure	ot available.	
Potential acute health effect		
Eye contact	auses serious eye irritation.	
Inhalation	armful if inhaled.	
Skin contact	ay cause damage to organs following a single exposure in cor auses skin irritation. Defatting to the skin. May cause an aller	
Ingestion	lay cause damage to organs following a single exposure if swa	allowed.
Symptoms related to the phy	II. chemical and toxicological characteristics	
Eye contact	dverse symptoms may include the following: ain or irritation atering edness	
Inhalation	dverse symptoms may include the following: educed fetal weight crease in fetal deaths keletal malformations	
Skin contact	dverse symptoms may include the following: ritation edness ryness racking educed fetal weight crease in fetal deaths keletal malformations	

# 11. Toxicological information

	-
Ingestion	: Adverse symptoms may include the following:
	reduced fetal weight
	increase in fetal deaths
	skeletal malformations

Delayed and immediate effec	ts	and also chronic effects from short and long term exposure
<u>Short term exposure</u>		
Potential immediate effects	:	Not available.
Potential delayed effects	1	Not available.
Long term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	1	Not available.
Potential chronic health effe	ect	<u>S</u>
General	:	May cause damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	:	No known significant effects or critical hazards.
Mutagenicity	:	No known significant effects or critical hazards.
Reproductive toxicity	:	Suspected of damaging fertility or the unborn child.

## Numerical measures of toxicity

#### Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
QUAPON WB Epoxy Gloss Comp B Polycondensate of 4,4'-isopropylidenediphenol and 1-chloro-2,3-epoxypropane (liquid only)	31557.9 2500	2032 2500	N/A N/A	10.2 N/A	N/A N/A
2-Propoxyethanol Ethylene glycol mono-n-butyl ether	3089 1200	300 300	N/A N/A	3 0.5	N/A N/A

#### Other information

Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

# **12. Ecological information**

ŝ

**Toxicity** 

Version 7

# Product name AQUAPON WB Epoxy Gloss Comp B

# 12. Ecological information

0			
Product/ingredient name	Result	Species	Exposure
Polycondensate of 4,4'- isopropylidenediphenol and 1-chloro-2,3-epoxypropane (liquid only)	Chronic NOEC 0.3 mg/l	Daphnia	21 days
Ethylene glycol mono-n-butyl ether	Acute LC50 1474 mg/l	Fish	96 hours
	Chronic NOEC >100 mg/l	Fish	21 days

# Persistence/degradability

Product/ingredient name	Test	Result		Dose		Inoculum
Polycondensate of 4,4'- isopropylidenediphenol and 1-chloro-2,3-epoxypropane (liquid only)	OECD 301F	5 % - 28 da	ays	-		-
Product/ingredient name	Aquatic half-life		Photolysis		Biodeg	radability
Polycondensate of 4,4'- isopropylidenediphenol and 1-chloro-2,3-epoxypropane (liquid only) Ethylene glycol mono-n-butyl ether	-		-		Not rea	

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Polycondensate of 4,4'- isopropylidenediphenol and 1-chloro-2,3-epoxypropane (liquid only)	2.64 to 3.78	31	low
2-Propoxyethanol Ethylene glycol mono-n-butyl ether	0.673 0.81	-	low low

<u>Mobility in soil</u>	
Soil/water partition coefficient (K <sub>oc</sub> )	: Not available.
Mobility	: Not available.

Other adverse effects

: No known significant effects or critical hazards.

# 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty

Japan Page: 10/14

# 13. Disposal considerations

containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# 14. Transport information

	UN	IMDG	ΙΑΤΑ
UN number	UN3082	UN3082	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
	(reaction product: bisphenol-A- (epichlorhydrin); epoxy resin)	(reaction product: bisphenol-A- (epichlorhydrin); epoxy resin)	(reaction product: bisphenol- A-(epichlorhydrin); epoxy resin)
Transport hazard class(es)	9	9	9
Packing group	III	II	III
Environmental hazards	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	(reaction product: bisphenol-A- (epichlorhydrin); epoxy resin)	Not applicable.

## **Additional information**

UN	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
IMDG	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
ΙΑΤΑ	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.
Special prec	cautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according	:	Not applicable.
to IMO instruments		

# 15. Regulatory information

#### Fire Service Law

Category	Substance name/Type	Danger category	Signal word	Designated quantity
Specified flammables	Combustible liquid	Not applicable	Not applicable	2 m³

#### Pollutant Release and Transfer Registers (PRTR)

None of the components are listed.

# <u>ISHL</u>

# Ordinance on the prevention of the hazard due to specified chemical substances

# Product name AQUAPON WB Epoxy Gloss Comp B

# 15. Regulatory information

None of the components are listed.

### Substances requiring labelling

Ingredient name	%		Reference number
Ethylene glycol mono-n-butyl ether; Butylcellosolve; 2-Butoxyethanol	≤10	Listed	79
Crystalline silica	≤10	Listed	165-2

#### **Chemicals requiring notification**

Ingredient name	%		Reference number
Ethylene glycol mono-n-butyl ether; 2-Butoxyethanol; Butylcellosolve	≤10	Listed	79
Crystalline silica	≤10	Listed	165-2

#### **Carcinogen**

None of the components are listed.

#### <u>Mutagen</u>

Ingredient name		%	Status	Reference
sphenol A type epoxy resin intermediate		≥30 - ≤40	Listed	number 110
Corrosive liquid	: Not listed			
Occupational Safety and Health Law	: Not applicable.			
Regulations on the Prevention of Tetraalkyl Lead Poisoning	: Not listed			
Harmful Substances Subject to Obtaining Permission for Manufacturing	: Not listed			
Harmful Substances, Prohibited for Manufacturing	: Not listed			
Lead regulation	: Not listed			
Organic solvents poisoning prevention	: Not applicable.			

Poisonous and Deleterious Substances None of the components are listed.

**Chemical Substances Control Law (CSCL)** 

# Product name AQUAPON WB Epoxy Gloss Comp B

# 15. Regulatory information

Ingredient name	%	Status	Reference number
Polycondensate of 4,4'-isopropylidenediphenol and 1-chloro-2,3-epoxypropane (liquid only); bisphenol A type epoxy resin	36.318	Priority assessment	87
2-Butoxyethanol	3.8026	Priority assessment	109
Ethylene glycol	0.0034254	Priority assessment	105
1,1'-Oxydi(propan-2-ol)	0.000288	Priority assessment	240
Methanol	0.0002583	Priority assessment	90
Formaldehyde	0.00024975	Priority assessment	25
1,4-Dioxane	0.00001215	Priority assessment	80

High Pressure Gas Control : Not available.

#### **Explosives Control Law**

None of the components are listed.

Law concerning prevention : Not available. of pollution of the ocean

#### Maritime Safety Law

#### Notification Regulating Transportation of Dangerous Materials by Sea

None of the components are listed.

#### **Container class**

None of the components are listed.

JSOH Carcinogen	: Group 1
List of Specially Controlled Industrial Waste	: Not listed
Japan inventory	: All components are listed or exempted.
Road law	: Not available.

# 16. Other information

<u>History</u>	
Date of issue/Date of revision	: 4 March 2022
Date of previous issue	: 5/29/2021
Version	: 7
Prepared by	: EHS
Key to abbreviations	: ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

# **16.** Other information

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail UN = United Nations

✓ Indicates information that has changed from previously issued version.

#### Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.