

SAFETY DATA SHEET



Conforms to Official Mexican Standard NOM-018-STPS-2015

Date of revision 12 March 2022
Version 9

Date of issue 12 March 2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product name : HI-TEMP 1027 LIGHT GREY
Product code : 00338473
Other means of identification : Not applicable.
Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.
Use of the substance/mixture : Coating.
Uses advised against : Not applicable.

Manufacturer : PPG Industries, Inc.
One PPG Place
Pittsburgh, PA 15272

Emergency telephone number : (412) 434-4515 (U.S.)
(514) 645-1320 (Canada)
SETIQ Interior de la República: 800-00-214-00 (México)
SETIQ Ciudad de México: (55) 5559-1588 (México)

Technical Phone Number : 888-977-4762

SECTION 2: Hazards identification

Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 3
ACUTE TOXICITY (dermal) - Category 5
SKIN IRRITATION - Category 3
CARCINOGENICITY - Category 1A
TOXIC TO REPRODUCTION - Category 2
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity:
62.1% (oral), 76.3% (dermal), 63.3% (inhalation)

GHS label elements

Hazard pictograms :



Signal word : Danger

SECTION 2: Hazards identification

- Hazard statements** : H226 - Flammable liquid and vapor.
 H313 - May be harmful in contact with skin.
 H316 - Causes mild skin irritation.
 H350 - May cause cancer.
 H361 - Suspected of damaging fertility or the unborn child.
 H373 - May cause damage to organs through prolonged or repeated exposure. (hearing organs)
- Precautionary statements**
- Prevention** : P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P280 - Wear protective gloves, protective clothing and eye or face protection.
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P260 - Do not breathe vapor.
- Response** : P308 + P313 - IF exposed or concerned: Get medical advice or attention.
 P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
 P302 + P312 - IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell.
 P332 + P313 - If skin irritation occurs: Get medical advice or attention.
- Storage** : P405 - Store locked up.
- Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

- Other hazards which do not result in classification** : Sanding and grinding dusts may be harmful if inhaled. Prolonged or repeated contact may dry skin and cause irritation. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. Emits toxic fumes when heated.

See toxicological information (Section 11)

SECTION 3: Composition/information on ingredients

- Substance/mixture** : Mixture
Product name : HI-TEMP 1027 LIGHT GREY
Other means of identification : Not applicable.

Ingredient name	%	CAS number
☑ Solvent naphtha (petroleum), heavy arom.	≥10 - ≤17	64742-94-5
Mica-group minerals	≥5.0 - ≤10	12001-26-2
titanium dioxide	≥5.0 - ≤10	13463-67-7
dimethyl carbonate	≥1.0 - ≤5.0	616-38-6
xylene	≥1.0 - ≤4.9	1330-20-7
Wollastonite	≥1.0 - ≤5.0	13983-17-0
zinc oxide	≥1.0 - ≤3.5	1314-13-2
ethylbenzene	≥0.10 - ≤2.4	100-41-4
toluene	≤2.0	108-88-3
naphthalene	≥0.10 - ≤2.4	91-20-3
crystalline silica, respirable powder (<10 microns)	<1.0	14808-60-7

SECTION 3: Composition/information on ingredients

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

Description of necessary first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : May be harmful in contact with skin. Causes mild skin irritation. Defatting to the skin.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

See toxicological information (Section 11)

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

SECTION 5: Firefighting measures

Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

- Specific hazards arising from the chemical** : Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

SECTION 5: Firefighting measures

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon oxides
phosphorus oxides
halogenated compounds
metal oxide/oxides
Formaldehyde.
- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

SECTION 7: Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Special precautions** : Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Vapors are heavier than air and may spread along floors. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

SECTION 8: Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
<input checked="" type="checkbox"/> Solvent naphtha (petroleum), heavy arom. Mica-group minerals	None. NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 3 mg/m ³ 8 hours. Form: Respirable fraction
titanium dioxide	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 10 mg/m ³ 8 hours.
dimethyl carbonate	None.
xylene	NOM-010-STPS-2014 (Mexico, 4/2016). STEL: 150 ppm 15 minutes. TWA: 100 ppm 8 hours.
Wollastonite	ACGIH TLV (United States, 1/2021). TWA: 1 mg/m ³ 8 hours. Form: Inhalable fraction
zinc oxide	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 2 mg/m ³ 8 hours. Form: Respirable

SECTION 8: Exposure controls/personal protection

ethylbenzene	fraction STEL: 10 mg/m ³ 15 minutes. Form: Respirable fraction
toluene	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 20 ppm 8 hours.
naphthalene	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 20 ppm 8 hours. NOM-010-STPS-2014 (Mexico, 4/2016). Absorbed through skin. STEL: 15 ppm 15 minutes. TWA: 10 ppm 8 hours.
crystalline silica, respirable powder (<10 microns)	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 0.025 mg/m ³ 8 hours. Form: Respirable

Key to abbreviations

C = Ceiling Limit

IPEL = Internal Permissible Exposure Limit

STEL = Short term exposure limit

TLV = Threshold Limit Value

TWA = Time Weighted Average

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety glasses with side shields.

Skin protection**Hand protection**

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

SECTION 8: Exposure controls/personal protection

- Gloves** : For prolonged or repeated handling, use the following type of gloves:
- May be used: nitrile rubber
Recommended: Chloroprene, polyvinyl alcohol (PVA), Viton®
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

SECTION 9: Physical and chemical properties

Appearance

- Physical state** : Liquid.
- Color** : Grayish-white.
- Odor** : Hydrocarbon.
- Odor threshold** : Not available.
- Molecular weight** : Not applicable.
- pH** : Not applicable.
- Melting point** : Not available.
- Boiling point** : >37.78°C (>100°F)
- Flash point** : Closed cup: 24°C (75.2°F)
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : Not available.
- Flammability (solid, gas)** : Not available.
- Lower and upper explosive (flammable) limits** : Not available.
- Evaporation rate** : Not available.
- Vapor pressure** : Not available.
- Vapor density** : Not available.
- Relative density** : 1.88
- Density (lbs / gal)** : 15.69
- Bulk Density (g/cm³)** : 1.902
- Solubility** : Insoluble in the following materials: cold water.
- Solubility in water** : Not available.
- Partition coefficient: n-octanol/water** : Not applicable.
- Viscosity** : Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)
- Volatility** : 48% (v/v), 23.227% (w/w)
- % Solid. (w/w)** : 76.773

SECTION 10: Stability and reactivity

- Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- Chemical stability** : The product is stable.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.
Refer to protective measures listed in sections 7 and 8.
- Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
- Hazardous decomposition products** : Depending on conditions, decomposition products may include the following materials: carbon oxides phosphorus oxides halogenated compounds Formaldehyde. metal oxide/oxides

SECTION 11: Toxicological information**Information on toxicological effects****Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Solvent naphtha (petroleum), heavy arom.	LC50 Inhalation Dusts and mists	Rat	>5.2 mg/l	4 hours
titanium dioxide	LD50 Oral	Rat	>5 g/kg	-
	LC50 Inhalation Dusts and mists	Rat	>6.82 mg/l	4 hours
dimethyl carbonate	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
	LC50 Inhalation Vapor	Rat	140000 mg/m ³	4 hours
xylene	LD50 Dermal	Rabbit	2.5 g/kg	-
	LD50 Oral	Rat	12.9 g/kg	-
	LD50 Dermal	Rabbit	1.7 g/kg	-
zinc oxide	LD50 Oral	Rat	4.3 g/kg	-
	LC50 Inhalation Dusts and mists	Rat	>5700 mg/m ³	4 hours
	LD50 Dermal	Rat	>2000 mg/kg	-
ethylbenzene	LD50 Oral	Rat	>5000 mg/kg	-
	LC50 Inhalation Vapor	Rat	17.8 mg/l	4 hours
	LD50 Dermal	Rabbit	17.8 g/kg	-
toluene	LD50 Oral	Rat	3.5 g/kg	-
	LC50 Inhalation Vapor	Rat	49 g/m ³	4 hours
	LD50 Dermal	Rabbit	8.39 g/kg	-
naphthalene	LD50 Oral	Rat	5580 mg/kg	-
	LD50 Dermal	Rabbit	>20 g/kg	-
	LD50 Oral	Rat	490 mg/kg	-

Conclusion/Summary : There are no data available on the mixture itself.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Xylene	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-

Conclusion/Summary

SECTION 11: Toxicological information

Skin : There are no data available on the mixture itself.

Eyes : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Sensitization**Conclusion/Summary**

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Classification

Product/ingredient name	OSHA	IARC	NTP
Titanium dioxide	-	2B	-
xylene	-	3	-
Wollastonite	-	3	-
ethylbenzene	-	2B	-
toluene	-	3	-
naphthalene	-	2B	Reasonably anticipated to be a human carcinogen.
crystalline silica, respirable powder (<10 microns)	-	1	Known to be a human carcinogen.

Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4

NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen

OSHA: +

Not listed/not regulated: -

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Solvent naphtha (petroleum), heavy arom.	Category 3	-	Narcotic effects
dimethyl carbonate	Category 3	-	Respiratory tract irritation
xylene	Category 3	-	Respiratory tract irritation
toluene	Category 3	-	Narcotic effects

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
ethylbenzene	Category 2	-	hearing organs
toluene	Category 2	-	-
naphthalene	Category 2	-	-
crystalline silica, respirable powder (<10 microns)	Category 1	inhalation	-

SECTION 11: Toxicological information

Target organs : Contains material which causes damage to the following organs: brain.
Contains material which may cause damage to the following organs: blood, kidneys, lungs, the nervous system, the reproductive system, liver, heart, upper respiratory tract, skin, central nervous system (CNS), ears, eye, lens or cornea.

Aspiration hazard

Name	Result
Solvent naphtha (petroleum), heavy arom. xylene ethylbenzene toluene	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure**Potential acute health effects**

Eye contact : No known significant effects or critical hazards.
Inhalation : No known significant effects or critical hazards.
Skin contact : May be harmful in contact with skin. Causes mild skin irritation. Defatting to the skin.
Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:
pain or irritation
watering
redness

Inhalation : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations

Skin contact : Adverse symptoms may include the following:
irritation
redness
dryness
cracking
reduced fetal weight
increase in fetal deaths
skeletal malformations

Ingestion : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Conclusion/Summary : There are no data available on the mixture itself. This product either contains formaldehyde or is capable of releasing formaldehyde above 0.5 ppm under certain conditions. Formaldehyde is a known cancer hazard, a skin sensitizer and a respiratory sensitizer. This product contains crystalline silica which can cause lung cancer or silicosis. The risk of cancer depends on the duration and level of exposure to dust from sanding surfaces or mist from spray applications. For many PPG products, TiO₂ is utilized as a raw material in a liquid coating formulation. In this case, the TiO₂ particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of TiO₂ when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/or engineering controls (see Section

SECTION 11: Toxicological information

8). Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. There is some evidence that repeated exposure to organic solvent vapors in combination with constant loud noise can cause greater hearing loss than expected from exposure to noise alone. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Short term exposure

Potential immediate effects : There are no data available on the mixture itself.

Potential delayed effects : There are no data available on the mixture itself.

Long term exposure

Potential immediate effects : There are no data available on the mixture itself.

Potential delayed effects : There are no data available on the mixture itself.

Potential chronic health effects

General : May cause damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Carcinogenicity : May cause cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

Numerical measures of toxicity**Acute toxicity estimates**

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
HI-TEMP 1027 LIGHT GREY	10059.3	4958	N/A	81.3	10.1
dimethyl carbonate	12900	2500	N/A	140	N/A
xylene	4300	1700	N/A	11	1.5
zinc oxide	N/A	2500	N/A	N/A	N/A
ethylbenzene	3500	17800	N/A	17.8	1.5
toluene	5580	8390	N/A	49	N/A
naphthalene	490	N/A	N/A	N/A	N/A

SECTION 12: Ecological information**Toxicity**

SECTION 12: Ecological information

Product/ingredient name	Result	Species	Exposure
Solvent naphtha (petroleum), heavy arom. titanium dioxide dimethyl carbonate zinc oxide ethylbenzene	NOEL 0.48 mg/l Fresh water	Daphnia	21 days
	Acute LC50 >100 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 >100 mg/l	Fish	96 hours
	Acute EC50 0.17 mg/l	Algae	72 hours
	Acute EC50 0.481 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Chronic NOEC 0.017 mg/l Fresh water	Algae	72 hours
	Acute EC50 1.8 mg/l Fresh water	Daphnia	48 hours
	Chronic NOEC 1 mg/l Fresh water	Daphnia - Ceriodaphnia dubia	-

Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
ethylbenzene	-	79 % - Readily - 10 days	-	-

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
xylene	-	-	Readily
ethylbenzene	-	-	Readily
toluene	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Solvent naphtha (petroleum), heavy arom.	2.8 to 6.5	-	high
dimethyl carbonate	0.354	-	low
xylene	3.12	7.4 to 18.5	low
ethylbenzene	3.6	79.43	low
toluene	2.73	8.32	low
naphthalene	3.4	85.11	low

Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the

SECTION 13: Disposal considerations

container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

SECTION 14: Transport information

	Mexico Classification	IMDG	IATA
UN number	UN1263	UN1263	UN1263
UN proper shipping name	PAINT	PAINT	PAINT
Transport hazard class(es)	3	3	3
Packing group	III	III	III
Environmental hazards	Yes. The environmentally hazardous substance mark is not required.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	(Solvent naphtha (petroleum), heavy aromatic, trizinc bis (orthophosphate))	Not applicable.
Product RQ (lbs)	Not applicable.	Not applicable.	Not applicable.
RQ substances	Not applicable.	Not applicable.	Not applicable.

Additional information

Mexico : None identified.

IMDG : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.

IATA : The environmentally hazardous substance mark may appear if required by other transportation regulations.

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not applicable.

SECTION 15: Regulatory information**Mexico****Classification**

Flammability : 3 **Health** : 2 **Reactivity** : 0

International regulations**Montreal Protocol**

SECTION 15: Regulatory information

Not listed.

[Stockholm Convention on Persistent Organic Pollutants](#)

Not listed.

[Rotterdam Convention on Prior Informed Consent \(PIC\)](#)

Not listed.

SECTION 16: Other information

[Hazardous Material Information System \(U.S.A.\)](#)

Health : 2 * Flammability : 3 Physical hazards : 0

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Date of previous issue : 5/22/2021

Organization that prepared the SDS : EHS

Key to abbreviations : ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
N/A = Not available
SGG = Segregation Group
UN = United Nations

✔ Indicates information that has changed from previously issued version.

[Notice to reader](#)

The information, which is based on the current knowledge of the chemical substance or mixture and applies to appropriate safety precautions for the product, is deemed correct but is not exhaustive and will be used only as a guide.

[Disclaimer](#)

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.