SAFETY DATA SHEET



Date of issue/Date of revision 28 March 2022 Version 2.01

Section 1. Identification		
Product code	: 000001100017	
Product name	: SIGMASHIELD 1200 HARDENER CLEAR	
Other means of identification 00317450	on	
Product type	: Liquid.	
Relevant identified uses of	the substance or mixture and uses advised against	
Product use	Coating. Professional applications, Used by spraying.	
Supplier's details	: PPG Industries (Singapore) Pte. Ltd., No. 1 Tuas Basin Close, Singapore 638803. Tel +65 68653737	
Emergency telephone number (with hours of operation)	: CHEMTREC +(65)-31581349 (CCN 17704)	

Section 2. Hazards identification

Classification of the substance or mixture	: ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (dermal) - Category 3 ACUTE TOXICITY (inhalation) - Category 3 SKIN CORROSION/IRRITATION - Category 1A SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 SKIN SENSITISATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2

 GHS label elements, including precautionary statements

 Hazard pictograms
 :

 Signal word
 : Danger

Singapore	English	(GB)
-----------	---------	------

Section 2. Hazards identification

Hazard statements	:	Harmful if swallowed. Toxic in contact with skin or if inhaled. Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause damage to organs through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.
Precautionary statements		
Prevention	-	Wear protective gloves, protective clothing and eye or face protection. Avoid release to the environment. Do not breathe vapour. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.
Response	:	Collect spillage. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor. Wash contaminated clothing before reuse. IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Storage	:	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.

Other hazards which do not	1	None known.
result in classification		

Section 3. Composition/information on ingredients

Substance/mixture	1.1	Mixture
-------------------	-----	---------

CAS number/other identifiers

	CAS number EC number		Not applicable. Mixture.
	ngredient name		
2.4,6-tris(dimethylaminomethyl) 2,4,6-tris(dimethylaminomethyl) 2,4,6-tris(dimethylaminomethyl) 2,4,6-tris(dimethylaminomethyl)		enediamine	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

%

50 - 100

10 - <20

1 - <3

1 - <3

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

CAS number

6864-37-5

1760-24-3

100-51-6

90-72-2

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	 Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Inhalation	 Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	 If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/e	s, acute and delayed	
Potential acute health effe		
Eye contact	Causes serious eye damage.	
Inhalation	Toxic if inhaled.	
Skin contact	Causes severe burns. Toxic in contact with skin. May cause an allerg reaction.	ic skin
Ingestion	Harmful if swallowed.	
<u>Over-exposure signs/sym</u>	<u>5</u>	
Eye contact	Adverse symptoms may include the following: pain watering redness	
Inhalation	No specific data.	
Skin contact	Adverse symptoms may include the following: pain or irritation redness blistering may occur	
Ingestion	Adverse symptoms may include the following: stomach pains	
Indication of immediate me	attention and special treatment needed, if necessary	
Notes to physician	In case of inhalation of decomposition products in a fire, symptoms ma The exposed person may need to be kept under medical surveillance f	
Specific treatments	No specific treatment.	
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable is suspected that fumes are still present, the rescuer should wear an a mask or self-contained breathing apparatus. It may be dangerous to th providing aid to give mouth-to-mouth resuscitation. Wash contaminate thoroughly with water before removing it, or wear gloves.	ppropriate ne person

See toxicological information (Section 11)

Singapore	English (GB)	Page: 3/12
-----------	--------------	------------

Section 5. Firefighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides Formaldehyde.
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
Methods and material for cont	ainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a

licensed waste disposal contractor.

Product name SIGMASHIELD 1200 HARDENER CLEAR

Section 6. Accidental release measures

Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limit	ts
None.	
Recommended monitoring procedures	: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Singapore	English (GB)	Page: 5/12
-----------	--------------	------------

Version 2.01

Product name SIGMASHIELD 1200 HARDENER CLEAR

Section 8. Exposure controls/personal protection

Appropriate engineering controls	:	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measur	<u>'es</u>	
Hygiene measures	res : Wash hands, forearms and face thoroughly after handling chemical peating, smoking and using the lavatory and at the end of the working Appropriate techniques should be used to remove potentially contam Contaminated work clothing should not be allowed out of the workplacentaminated clothing before reusing. Ensure that eyewash stations showers are close to the workstation location.	
Eye/face protection	1	Chemical splash goggles and face shield.
Skin protection		
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard be worn at all times when handling chemical products if a risk assessment in this is necessary. Considering the parameters specified by the glove manufacheck during use that the gloves are still retaining their protective properties. should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting several substances, the protection time of the gloves cannot be accurately estimated.	
Gloves	:	nitrile neoprene
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

₋iquid.
Colourless.
haracteristic.
nsoluble in water.
>37.78°C (>100°F)
r

Singapore	English (GB)	Page: 6/12
-----------	--------------	------------

Section 9. Physical and chemical properties

Flash point	: 🕅osed cup: 104°C (219.2°F)
Evaporation rate	: 0.007 (benzyl alcohol) compared with butyl acetate
Flammability (solid, gas)	: liquid
Vapour pressure	 Fighest known value: 0.04 kPa (0.3 mm Hg) (at 20°C) (N-(3-(trimethoxysilyl)propyl) ethylenediamine). Weighted average: 0.002 kPa (0.02 mm Hg) (at 20°C)
Vapour density	: Highest known value: 3.7 (Air = 1) (benzyl alcohol).
Relative density	: 0.97
Solubility	: Insoluble in the following materials: cold water.
Auto-ignition temperature	 Lowest known value: 275°C (527°F) (2,2'-dimethyl-4,4'-methylenebis (cyclohexylamine)).
Viscosity	: Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients	3 .
Chemical stability	: The product is stable.	
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.	
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.	
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.	
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides Formaldehyde. metal oxide/oxides	

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2,2'-dimethyl-4,4'- methylenebis (cyclohexylamine)	LC50 Inhalation Dusts and mists	Rat	420 mg/m ³	4 hours
(-)	LD50 Dermal	Rabbit	>0.2 g/kg	-
	LD50 Oral	Rat	>0.32 g/kg	-
benzyl alcohol	LC50 Inhalation Dusts and mists	Rat	>4178 mg/m ³	4 hours
,	LD50 Dermal	Rabbit	2000 mg/kg	-
	LD50 Oral	Rat	1.23 g/kg	-
N-(3-(trimethoxysilyl)propyl) ethylenediamine	LD50 Oral	Rat	2413 mg/kg	-
2,4,6-tris (dimethylaminomethyl)	LD50 Dermal	Rabbit	1.28 g/kg	-

Singapore	English (GB)	Page: 7/12
-----------	--------------	------------

Version 2.01

Section 11. Toxicological information

phenol							
	LD50 Dermal	Rat	1280 mg/kg	-			
	LD50 Oral	Rat	1200 mg/kg	-			

Conclusion/Summary : The

: There are no data available on the mixture itself.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
₽,4,6-tris (dimethylaminomethyl) phenol	Skin - Visible necrosis	Rabbit	-	4 hours	7 days

Conclusion/Summary

Skin	: There are no data available on the mixture itself.

: There are no data available on the mixture itself.

```
Eyes
Respiratory
```

: There are no data available on the mixture itself.

Sensitisation

Product/ingredient name	e Route of exposure	Species	Result
2 ,4,6-tris (dimethylaminomethyl) phenol	skin	Guinea pig	Sensitising
Conclusion/Summary	·	·	
Skin	: There are no da	ata available on the mixture i	tself.
Respiratory	: There are no da	ata available on the mixture i	tself.
<u>Mutagenicity</u>			
Conclusion/Summany	Thoro aro no d	ata available on the mixture	itcolf

Conclusion/Summary : There are no data available on the mixture itself.

Conclusion/Summary	: There are no data available on the mixture itself.
--------------------	--

Conclusion/Summary : There are no data available on the mixture itself.

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

Teratogenicity

Carcinogenicity

Reproductive toxicity

Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
2,2'-dimethyl-4,4'-methylenebis(cyclohexylamine)	Category 2	-	-

Aspiration hazard

Not available.

Singapore	English (GB)	Page: 8/12
-----------	--------------	------------

Section 11. Toxicological information

	5	
Information on likely routes of exposure	Not available.	
Potential acute health effect		
Eye contact	Causes serious eye damage.	
Inhalation	Toxic if inhaled.	
Skin contact	Causes severe burns. Toxic in contact with skin. May cause an allergic skin reaction.	
Ingestion	Harmful if swallowed.	
Symptoms related to the ph	cal, chemical and toxicological characteristics	
Eye contact	Adverse symptoms may include the following: pain watering redness	
Inhalation	No specific data.	
Skin contact	Adverse symptoms may include the following: pain or irritation redness blistering may occur	
Ingestion	Adverse symptoms may include the following: stomach pains	
Delayed and immediate effe	as well as chronic effects from short and long-term exposure	
<u>Short term exposure</u>		
Potential immediate effects	Not available.	
Potential delayed effects	Not available.	
Long term exposure		
Potential immediate effects	Not available.	
Potential delayed effects	Not available.	
Potential chronic health eff	2	
General	May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to low levels.	very
Carcinogenicity	No known significant effects or critical hazards.	
Mutagenicity	No known significant effects or critical hazards.	
Reproductive toxicity	No known significant effects or critical hazards.	

Numerical measures of toxicity Acute toxicity estimates

Si	ingapore	English (GB)	Pa
----	----------	--------------	----

Section 11. Toxicological information

ż

Route	ATE value
Øral	574.62 mg/kg
Dermal	360.01 mg/kg
Inhalation (vapours)	380.89 mg/l
Inhalation (dusts and mists)	0.58 mg/l

Other information

Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Trimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness. Contains a substance that may emit formaldehyde if stored beyond its shelf life and/or during cure at curing temperatures greater than 60C/140F.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
₽,4,6-tris (dimethylaminomethyl)phenol	Acute LC50 175 mg/l	Fish	96 hours
Conclusion/Summary	: There are no data available on the mixture itself.		

Persistence/degradability

Conclusion/Summary	: There are no data available on the mixture itself.
--------------------	--

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
benzyl alcohol	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
₽,2'-dimethyl-4,4'- methylenebis (cyclohexylamine)	1.8	-	low
benzyl alcohol 2,4,6-tris (dimethylaminomethyl)phenol	0.87 0.219	-	low low

Mobility in soil Soil/water partition coefficient (Koc)	: Not available.
Other adverse effects	: No known significant effects or critical hazards.

Singapore	English (GB)	Page: 10/12
-----------	--------------	-------------

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	IMDG	ΙΑΤΑ
UN number	UN2922	UN2922	UN2922
UN proper shipping name			Corrosive liquid, toxic, n.o.s.
	(2,2'-dimethyl-4,4'- methylenebis (cyclohexylamine), 2,4,6-tris (dimethylaminomethyl)phenol)	(2,2'-dimethyl-4,4'- methylenebis (cyclohexylamine), 2,4,6-tris (dimethylaminomethyl)phenol)	(2,2'-dimethyl-4,4'- methylenebis (cyclohexylamine), 2,4,6-tris (dimethylaminomethyl)phenol)
Transport hazard class(es)	8 (6.1)	8 (6.1)	8 (6.1)
Packing group	I	II	II
Environmental hazards	Yes. The environmentally hazardous substance mark is not required.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	(2,2'-dimethyl-4,4'- methylenebis (cyclohexylamine))	Not applicable.

Additional information

UN	: None identified.
IMDG	: The marine pollutant mark is not required when transported in sizes of \leq 5 L or \leq 5 kg.
ΙΑΤΑ	: The environmentally hazardous substance mark may appear if required by other transportation regulations.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according	1	Not applicable.
to IMO instruments		

Singapore	English (GB)	Page: 11/12
-----------	--------------	-------------

Section 15. Regulatory information

Singapore - hazardous chemicals under government control

None.

International regulations Montreal Protocol Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Section 16. Other information

<u>History</u>	
Date of issue/Date of revision	: 28 March 2022
Date of previous issue	: 11/7/2021
Version	: 2.01
Prepared by	: EHS
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations

Indicates information that has changed from previously issued version.

Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.