SAFETY DATA SHEET



Conforms to Official Mexican Standard NOM-018-STPS-2015

Date of revision 24 May 2022

Version 2

Date of issue 24 May 2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product name	: PITT-TECH PLUS EP DTM ACRYLIC SATIN NEUTRAL BASE
Product code	: 00445828
Other means of identification	: Not applicable.
Product type	: Liquid.
Relevant identified uses o	f the substance or mixture and uses advised against
Product use	: Professional applications, Used by spraying.
Use of the substance/ mixture	: Coating.
Uses advised against	Not applicable.
Manufacturer	: PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272
Emergency telephone number	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)
Technical Phone Number	: 888-977-4762

SECTION 2: Hazards identification

Classification of the substance or mixture	: CARCINOGENICITY - Category 2
	Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 27.6% (oral), 27.6% (dermal), 31% (inhalation)
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	: 🗹 351 - Suspected of causing cancer.
Precautionary statements	

SECTION 2: Hazards identification

Prevention	:	 P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P280 - Wear protective gloves, protective clothing and eye or face protection.
Response	:	P308 + P313 - IF exposed or concerned: Get medical advice or attention.
Storage	:	P405 - Store locked up.
Disposal	:	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Other hazards which do not result in classification	:	Contains isothiazolinones. May cause allergic reaction. Sanding and grinding dusts may be harmful if inhaled. Emits toxic fumes when heated.
Supplemental label elements (First aid measures):		Photosensitive agents : In case of accidental eye contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation or blistering occurs after contact. In case of accidental skin contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation, rash or blistering occurs after contact.
See toxicological information	n (S	Section 11)

ee toxicological information (Section 11)

SECTION 3: Composition/information on ingredients

Substance/mixture Product name	• • • •	/lixture PITT-TECH PLUS EP DTM ACRYLIC SATIN NEUTRAL BASE
Other means of identification	: N	lot applicable.

Ingredient name	%	CAS number
barium sulfate	≥1.0 - ≤5.0	7727-43-7
2-(2-butoxyethoxy)ethanol	≥1.0 - ≤5.0	112-34-5
benzophenone	<1.0	119-61-9

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

Description of necessary first aid measures

Eye contact	: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. In case of accidental eye contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation or blistering occurs after contact.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

Product name PITT-TECH PLUS EP DTM ACRYLIC SATIN NEUTRAL BASE

SECTION 4: First aid measures

	In case of accidental skin contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation, rash or blistering occurs after contact.	
Ingestion	 If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting. 	
Most important symptoms/effects, acute and delayed Potential acute health effects		
Fotential acute heart		
Eye contact	: No known significant effects or critical hazards.	
Inhalation	: No known significant effects or critical hazards.	

Skin contact : No known significant effects or critical hazards.

Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

See toxicological information (Section 11)

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	 No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

SECTION 5: Firefighting measures

Extinguishing media	
Suitable extinguishing media	: Vise an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides sulfur oxides metal oxide/oxides
Special protective actions for fire-fighters	Fromptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Version 2

Product name PITT-TECH PLUS EP DTM ACRYLIC SATIN NEUTRAL BASE

SECTION 6: Accidental release measures

Personal precautions, protect	ve equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for con	tainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

SECTION 7: Handling and storage

Precautions for safe handlin	đ
Protective measures	: Fut on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Special precautions	: If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

SECTION 7: Handling and storage

Conditions for safe storage,	: Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in
including any	accordance with local regulations. Store in original container protected from direct
incompatibilities	sunlight in a dry, cool and well-ventilated area, away from incompatible materials
	(see Section 10) and food and drink. Store locked up. Keep container tightly closed
	and sealed until ready for use. Containers that have been opened must be carefully
	resealed and kept upright to prevent leakage. Do not store in unlabeled containers.
	Use appropriate containment to avoid environmental contamination.

SECTION 8: Exposure controls/personal protection

Control parameters

Occupational exposure limits		
Ingredient name		Exposure limits
barium sulfate		NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 10 mg/m ³ 8 hours.
2-(2-butoxyethoxy)ethanol		ACGIH TLV (United States, 1/2021). TWA: 10 ppm 8 hours. Form: Inhalable fraction and vapor
benzophenone		None.
	Key to abbreviations	
C = Ceiling Limit IPEL = Internal Permissible Exposur	re Limit TL TV	V = Threshold Limit Value
Consult local authorities for a	cceptable exposure limits.	
procedures	of the ventilation or other control n protective equipment. Reference standards. Reference to national determination of hazardous substa	
Appropriate engineering : controls		Imes, gas, vapor or mist, use process enclosures ngineering controls to keep worker exposure to ecommended or statutory limits.
Environmental exposure : controls	they comply with the requirements cases, fume scrubbers, filters or e	process equipment should be checked to ensure of environmental protection legislation. In some ngineering modifications to the process uce emissions to acceptable levels.
Individual protection measures Hygiene measures :	Wash hands, forearms and face the eating, smoking and using the lave Appropriate techniques should be	oroughly after handling chemical products, before tory and at the end of the working period. used to remove potentially contaminated clothing. e reusing. Ensure that eyewash stations and

safety showers are close to the workstation location.

: Safety glasses with side shields.

Eye/face protection

Skin protection

Product name PITT-TECH PLUS EP DTM ACRYLIC SATIN NEUTRAL BASE

SECTION 8: Exposure controls/personal protection

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	: polyethylene
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

SECTION 9: Physical and chemical properties

			 D
% Solid. (w/w)	:	43.59	
Volatility	4	63% (v/v), 56.41% (w/w)	
Viscosity	:	Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)	
Partition coefficient: n- octanol/water	1	Not applicable.	
Solubility in water			
Solubility Solubility in water		Partially soluble in the following materials: cold water. Not available.	
Density (lbs / gal)		9.26	
Relative density	- 1	1.11	
		Not available.	
Vapor density			
Vapor pressure		Not available.	
(flammable) limits Evaporation rate		Not available.	
Lower and upper explosive	:	Not available.	
Flammability (solid, gas)		Not available.	
Decomposition temperature		Not available.	
Auto-ignition temperature		Not available.	
Flash point		Ølosed cup: 95°C (203°F)	
Boiling point	:	>37.78°C (>100°F)	
Melting point		Not available.	
pH	-	Not available.	
Odor threshold Molecular weight	1	Not available. Not applicable.	
Odor Odor three hold	÷	Characteristic.	
	÷		
Physical state Color		Liquid. Colorless.	
		Liquid	
Appearance			

SECTION 10: Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials carbon oxides sulfur oxides metal oxide/oxides

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result			Species	Dose	Exposure	
barium sulfate	LD50 Derr	nal		Rat	>2000 mg/kg	-	
	LD50 Oral			Rat	>5000 mg/kg	-	
2-(2-butoxyethoxy)ethanol	LD50 Derr			Rabbit	2700 mg/kg	-	
	LD50 Oral			Rat	4500 mg/kg	-	
benzophenone	LD50 Derr			Rabbit	3.535 g/kg	-	
	LD50 Oral			Rat	>10 g/kg	-	
Conclusion/Summary	: There a	re no data	a available on t	the mixture i	tself.		
rritation/Corrosion							
Conclusion/Summary							
Skin	: There a	: There are no data available on the mixture itself.					
Eyes	: There a	: There are no data available on the mixture itself.					
Respiratory	: There a	: There are no data available on the mixture itself.					
Sensitization							
Conclusion/Summary							
Skin	: There are no data available on the mixture itself.						
Respiratory	: There a	: There are no data available on the mixture itself.					
Mutagenicity							
Conclusion/Summary	: There are no data available on the mixture itself.						
Carcinogenicity							
Conclusion/Summary	Conclusion/Summary : There are no data available on the mixture itself.						
Classification							
Product/ingredient name	OSHA	IARC	NTP				

Carcinogen Classification code:

Mexico Page: 7/11

SECTION 11: Toxicological information

IARC: 1, 2A, 2B, 3, 4	
NTP: Known to be a hun	nan carcinogen; Reasonably anticipated to be a human carcinogen
OSHA: +	
Not listed/not regulated:	-

Reproductive toxicity

Conclusion/Summary : There are n	no data available on the mixture itself.
----------------------------------	--

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
benzophenone	Category 2	oral	kidneys, liver

Target organs

: Contains material which may cause damage to the following organs: blood, lungs, liver, upper respiratory tract, skin, eyes, central nervous system (CNS).

Aspiration hazard

Not available.

Information on the likely routes of exposure

Potential acute health effects

:	No known significant effects or critical hazards.
:	No known significant effects or critical hazards.
:	No known significant effects or critical hazards.
:	No known significant effects or critical hazards.
m	<u>5</u>
:	No specific data.
:	No specific data.
:	No specific data.
1	No specific data.
s	and also chronic effects from short and long term exposure
:	There are no data available on the mixture itself. Acrylate components of the mixture have irritating properties. Prolonged or repeated contact with skin or mucous membrane may result in irritation symptoms, such as redness, blistering, dermatitis etc. May cause allergic skin reactions with repeated exposure. The inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract. Ingestion may cause nausea, weakness and central nervous system effects. If splashed in the eyes, the liquid may cause irritation and reversible damage. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.
:	There are no data available on the mixture itself.
;	There are no data available on the mixture itself.
	: : : : : : : : : : : : : : : : : : :

SECTION 11: Toxicological information

Potential immediate effects	:	There are no data available on the mixture itself.
Potential delayed effects	1	There are no data available on the mixture itself.
Potential chronic health effe	cts	
General	:	No known significant effects or critical hazards.
Carcinogenicity	1	Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	1	No known significant effects or critical hazards.
Reproductive toxicity	:	No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
PITT-TECH PLUS EP DTM ACRYLIC SATIN NEUTRAL BASE	219926.3	54162.1	N/A	N/A	N/A
barium sulfate	N/A	2500	N/A	N/A	N/A
2-(2-butoxyethoxy)ethanol	4500	2700	N/A	N/A	N/A
benzophenone	N/A	3535	N/A	N/A	N/A

SECTION 12: Ecological information

Toxicity

Not available.

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-(2-butoxyethoxy)ethanol	1	-	low
benzophenone	3.18	12.02	low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Product name PITT-TECH PLUS EP DTM ACRYLIC SATIN NEUTRAL BASE

SECTION 13: Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

SECTION 14: Transport information

	Mexico Classification	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

Additional information

- Mexico : None identified.
- IMDG : None identified.
- IATA : None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Version 2

Product name PITT-TECH PLUS EP DTM ACRYLIC SATIN NEUTRAL BASE

SECTION 15: Regulatory information

Mexico

Classification

Flammability : 7 Health : 2 Reactivity : 0

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

SECTION 16: Other information

Hazardous Material Information System (U.S.A.)

Health : 2 * Flammability : **7** Physical hazards : 0

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Date of previous issue	: 3/7/2022
Organization that prepared the SDS	: EHS
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations
	have a have see a forward a second a second as second as a

Indicates information that has changed from previously issued version.

Notice to reader

The information, which is based on the current knowledge of the chemical substance or mixture and applies to appropriate safety precautions for the product, is deemed correct but is not exhaustive and will be used only as a guide.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.