SAFETY DATA SHEET



Date of issue 6/12/2022 (month/day/year)

Version 9.09

Section 1. Chemical product and company identification

A. Product name : SIGMAZINC 158 PIGMENT

Product code : 00192684

B. Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.

Use of the substance/

mixture

: Coating.

Uses advised against: Product is not intended, labelled or packaged for consumer use.

C. Supplier's or Importer's

information

Email Address

: PPG SSC (680-090)

19, Yeocheon-ro 217beon-gil, Nam-gu,

Ulsan, Korea

Tel: +82-52-210-8222 Korea.MSDS@PPG.COM

Emergency telephone

number:

: +82-52-210-8222

Section 2. Hazards identification

A. Hazard classification : AQUATIC HAZARD (ACUTE) - Category 1

AQUATIC HAZARD (LONG-TERM) - Category 1

This product is classified in accordance with the Industrial Safety and Health Act and the Chemical Control Act.

B. GHS label elements, including precautionary statements

Symbol :

*

Signal word : Warning

Hazard statements : H410 - Very toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention: P273 - Avoid release to the environment.

Response : P391 - Collect spillage.

Storage : Not applicable.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

Korea (GHS) Page: 1/11

Product code 00192684 Date of issue 6/12/2022 (month/day/year) Version 9.09 **Product name SIGMAZINC 158 PIGMENT**

Section 2. Hazards identification

not result in classification

C. Other hazards which do : May form explosible dust-air mixture if dispersed. Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes, skin, nose and throat.

Section 3. Composition/information on ingredients

CAS number/other identifiers

CAS number : Not applicable.

Chemical name	Common name	Identifiers	%
Zinc powder - zinc dust (stabilized) zinc oxide cadmium	ZINC OXIDE		90 - 100 0.1 - <1 <0.1

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

A. Eye contact : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

B. Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

C. Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

: If swallowed, seek medical advice immediately and show this container or label. D. Ingestion Keep person warm and at rest. Do NOT induce vomiting.

: Treat symptomatically. Contact poison treatment specialist immediately if large E. Notes to physician quantities have been ingested or inhaled.

: No specific treatment. **Specific treatments**

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

A. Extinguishing media

Suitable extinguishing media

: Use dry chemical powder.

Unsuitable

: Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.

extinguishing media

Korea (GHS) Page: 2/11

Product name SIGMAZINC 158 PIGMENT

Section 5. Fire-fighting measures

- from the chemical
- B. Specific hazards arising : May form explosible dust-air mixture if dispersed. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
 - **Hazardous thermal** decomposition products
- Decomposition products may include the following materials: metal oxide/oxides
- C. Special equipment for fire-fighting
- : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Fire-fighting procedures : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Section 6. Accidental release measures

- A. Personal precautions, protective equipment and emergency procedures
- : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Put on appropriate personal protective equipment.
- **B. Environmental** precautions
- : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
- C. Methods and materials for containment and cleaning up

Small spill

: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

Large spill

: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

- A. Precautions for safe handling
- Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing dust. Avoid release to the environment. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Korea (GHS) Page: 3/11 Date of issue 6/12/2022 (month/day/year) Version 9.09

Product name SIGMAZINC 158 PIGMENT

Section 7. Handling and storage

B. Conditions for safe storage, including any incompatibilities

Product code 00192684

: Store between the following temperatures: 5 to 25°C (41 to 77°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

A. Occupational exposure limits

Ingredient name	Exposure limits
z ínc oxide	Ministry of Employment and Labor (Republic of Korea, 1/2020). TWA: 2 mg/m³ 8 hours. Form: Respirable dust STEL: 10 mg/m³ 15 minutes. TWA: 5 mg/m³ 8 hours.
cadmium	Ministry of Employment and Labor (Republic of Korea, 1/2020). [Cadmium and compounds] TWA: 0.01 mg/m³, (as Cd) 8 hours. Form: Respirable dust TWA: 0.002 mg/m³, (as Cd) 8 hours. Form: Respirable fraction

Recommended monitoring procedures

- : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
- B. Appropriate engineering controls
- : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

C. Personal protective equipment

Korea (GHS) Page: 4/11

Product name SIGMAZINC 158 PIGMENT

Section 8. Exposure controls/personal protection

Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the

hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is

necessary.

Eye protection : Safety glasses with side shields.

Hand protection
 Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer.

check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately

estimated.

Body protection: Personal protective equipment for the body should be selected based on the task

being performed and the risks involved and should be approved by a specialist

before handling this product.

Hygiene measures: Wash hands, forearms and face thoroughly after handling chemical products, before

eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and

safety showers are close to the workstation location.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

A. Appearance

Physical state : Solid.

Powder.

Color : Various

B. Odor : Characteristic.

C. Odor threshold : Not available.

D. pH : Not applicable.

E. Melting/freezing point : Not available.F. Boiling point/boiling : Not available.

range

G. Flash point : Closed cup: Not applicable.

H. Evaporation rate : Not available.

I. Flammability (solid, gas) : Not available.J. Lower and upper : Not available.

explosive (flammable)

limits

K. Vapor pressure : Not available.

L. Solubility : Insoluble in the following materials: cold water.

Solubility in water : Not available.

M. Vapor density : Not applicable.

N. Relative density : 7.14

Korea (GHS) Page: 5/11

Product name SIGMAZINC 158 PIGMENT

Section 9. Physical and chemical properties

O. Partition coefficient: n-

octanol/water

: Not applicable.

P. Auto-ignition

: Not applicable.

temperature

Q. Decomposition temperature

: Not available.

R. Viscosity

: Kinematic (40°C (104°F)): Not applicable.

Flow time (ISO 2431) Not available. S. Molecular weight : Not applicable.

Section 10. Stability and reactivity

A. Chemical stability

B. Conditions to avoid

: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

: When exposed to high temperatures may produce hazardous decomposition

products.

C. Incompatible materials

: Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents, strong alkalis, strong acids.

D. Hazardous decomposition products

: Evolves hydrogen on contact with water. Depending on conditions, decomposition

products may include the following materials: metal oxide/oxides

Section 11. Toxicological information

A. Information on the likely routes of exposure

: Not available.

Potential acute health effects

Inhalation

: Exposure to airborne concentrations above statutory or recommended exposure limits

may cause irritation of the nose, throat and lungs.

Ingestion **Skin contact** : No known significant effects or critical hazards. : No known significant effects or critical hazards.

Eye contact

Exposure to airborne concentrations above statutory or recommended exposure limits

may cause irritation of the eyes.

Over-exposure signs/symptoms

Inhalation

: Adverse symptoms may include the following:

respiratory tract irritation

coughing

Ingestion Skin contact : No specific data. No specific data.

Eye contact

: Adverse symptoms may include the following:

irritation redness

B. Health hazards

Korea (GHS) Page: 6/11 Product code 00192684 Date of issue 6/12/2022 (month/day/year) Version 9.09
Product name SIGMAZINC 158 PIGMENT

Section 11. Toxicological information

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
₹inc powder - zinc dust (stabilized)	LC50 Inhalation Dusts and mists	Rat	>5.4 mg/l	4 hours
	LD50 Oral	Rat	>2000 mg/kg	-
zinc oxide	LC50 Inhalation Dusts and mists	Rat	>5700 mg/m ³	4 hours
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
cadmium	LD50 Oral	Rat	0.225 g/kg	-

Conclusion/Summary : There are no data available on the mixture itself.

Irritation/Corrosion

Conclusion/Summary

Skin: There are no data available on the mixture itself.Eyes: There are no data available on the mixture itself.Respiratory: There are no data available on the mixture itself.

Sensitization

Conclusion/Summary

Skin : There are no data available on the mixture itself.Respiratory : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary: There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary: There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary: There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Name	Classification	Route of exposure	Target organs
ø admium	Category 1	-	-

Aspiration hazard

Not available.

Potential chronic health effects

	Korea (GHS)	Page: 7/11
--	-------------	------------

Product name SIGMAZINC 158 PIGMENT

Section 11. Toxicological information

General : Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

Additional information

Sanding and grinding dusts may be harmful if inhaled.

Chemical name	Identifiers	GHS Classification
☑nc powder - zinc dust (stabilized)	CAS: 7440-66-6	SUBSTANCES AND MIXTURES, WHICH IN
		CONTACT WITH WATER, EMIT FLAMMABLE
		GASES - Category 3
		AQUATIC HAZARD (ACUTE) - Category 1
		AQUATIC HAZARD (LONG-TERM) - Category 1
zinc oxide	CAS: 1314-13-2	AQUATIC HAZARD (ACUTE) - Category 1
		AQUATIC HAZARD (LONG-TERM) - Category 1
cadmium	CAS: 7440-43-9	ACUTE TOXICITY (oral) - Category 3
		ACUTE TOXICITY (inhalation) - Category 2
		GERM CELL MUTAGENICITY - Category 2
		CARCINOGENICITY - Category 1
		TOXIC TO REPRODUCTION - Category 2
		SPECIFIC TARGET ORGAN TOXICITY
		(REPEATED EXPOSURE) - Category 1
		AQUATIC HAZARD (ACUTE) - Category 1
		AQUATIC HAZARD (LONG-TERM) - Category 1

Section 12. Ecological information

A. **Ecotoxicity**

Product/ingredient name	Result	Species	Exposure
☑nc powder - zinc dust (stabilized)	Acute EC50 0.106 mg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Chronic NOEC 0.0727 mg/l Fresh water	Daphnia - Daphnia Magna	21 days
zinc oxide	Acute EC50 0.17 mg/l Acute EC50 0.481 mg/l Fresh water	Algae Daphnia - Daphnia magna - Neonate	72 hours 48 hours
cadmium	Chronic NOEC 0.017 mg/l Fresh water Acute LC50 1500 ppb	Algae Fish	72 hours 96 hours

B. Persistence and degradability

Not available.

C. Bioaccumulative potential

Not available.

D. Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Korea (GHS) Page: 8/11

Date of issue 6/12/2022 (month/day/year) Version 9.09

Product name SIGMAZINC 158 PIGMENT

Section 12. Ecological information

E. Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

A. Disposal methods

Product code 00192684

- : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
- **B.** Disposal precautions
- : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	IMDG	IATA
A. UN number	UN3077	UN3077	UN3077
B. UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
	☑inc powder - zinc dust (stabilized))	☑inc powder - zinc dust (stabilized))	√Zinc powder - zinc dust (stabilized))
C. Transport hazard class(es)	9	9	9
D. Packing group	III	III	III
Environmental hazards	Yes.	Yes.	Yes.
E. Marine pollutant substances	Not applicable.	Zinc powder - zinc dust (stabilized))	Not applicable.

Additional information

UN

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

IMDG

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. The segregation group has been manually assigned based upon product analysis.

IATA

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

F. Special precaution which a user to be aware of or needs to comply with in connection with transport or transportation

Korea (GHS) Page: 9/11

Product name SIGMAZINC 158 PIGMENT

Section 14. Transport information

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable.

to IMO instruments

Section 15. Regulatory information

A. Regulation according to ISHA

ISHA article 117 (Harmful substances

prohibited from manufacture)

ISHA article 118 (Harmful substances requiring permission)

Article 2 of Youth Protection Act on Substances Hazardous to Youth

: None of the components are listed.

: None of the components are listed.

: It is not allowed to sell to persons under the age of 19.

Exposure Limits of Chemical Substances and Physical Factors

The following components have an OEL:

zinc oxide cadmium

ISHA Enforcement Regs: None of the components are listed.

Annex 19 (Exposure standards established for harmful factors)

ISHA Enforcement Regs

Annex 21 (Harmful factors subject to Work

Environment Measurement)

Annex 22 (Harmful Factors Subject to Special Health Check-

up)

Standard of Industrial Safety and Health **Annex 12 (Hazardous** substances subject to

control)

: None of the components are listed.

ISHA Enforcement Regs: None of the components are listed.

: The following components are listed: zinc and its compounds

B. Regulation according to Chemicals Control Act

Article 11 (TRI) : The following components are listed: Zinc and its compounds

Article 18 Prohibited (K-

Reach Article 27)

: None of the components are listed.

Article 19 Subject to

authorization (K-Reach

Article 25)

: None of the components are listed.

Korea (GHS) Page: 10/11

Product name SIGMAZINC 158 PIGMENT

Section 15. Regulatory information

Reach Article 27)

Article 20 Restricted (K- : None of the components are listed.

Article 20 Toxic

Chemicals (K-Reach

: Not applicable

Article 20)

Korea inventory : All components are listed or exempted.

Article 39 (Accident Precaution Chemicals) : None of the components are listed.

C. Dangerous Materials **Safety Management Act**

: Not applicable.

D. Wastes regulation

the product

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

E. Regulation according to other foreign laws

Safety, health and environmental regulations specific for : No known specific national and/or regional regulations applicable to this product

(including its ingredients).

Section 16. Other information

A. References Korean Ministry of Environment; Chemical Control Act

Korean Ministry of Labor; Industrial Safety and Health Act

NIER Notice

Registry of Toxic Effects of Chemical Substances (RTECS)

U.S. Environmental Protection Agency, AQUIRE (Aquatic toxicity Information

Retrieval) ECOTOX Database System.

B. Date of issue/Date of

revision

: 6/12/2022

C. Version 9.09 **Prepared by** : EHS

D. Other

▼ Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

> Korea (GHS) Page: 11/11