Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830

SAFETY DATA SHEET

Date of issue/Date of revision

: 11 August 2022

Version : 2.01



SECTION 1: Identification of the substance/mixture and of the company/ undertaking

•	
1.1 Product identifier	
Product name	: PSX 700SG DK GRAY F/S 26008 NRL PIGMENT PKG
Product code	: 00428704
Product type	: Liquid.
Other means of identification	tion
Not available.	
1.2 Relevant identified use	s of the substance or mixture and uses advised against
Product use	: Industrial applications, Used by spraying.
Use of the substance/ mixture	: Coating.
Uses advised against	: Product is not intended, labelled or packaged for consumer use.
1.3 Details of the supplier Sigma Paint Saudi Arabia L PO Box 7509 Dammam 31472 Saudi Arabia Tel: 00966 138 47 31 00 Fax: 00966 138 47 17 34	-

e-mail address of person : ndpic@sfda.gov.sa responsible for this SDS

1.4 Emergency telephone : 00966 138473100 extn 1001 number

SECTION 2: Hazards identification

2.1 Classification of the s	ubstance or mixture
Product definition Classification according	: Mixture to Regulation (EC) No. 1272/2008 [CLP/GHS]
Skin Sens. 1, H317 Aquatic Chronic 3, H412	
The product is classified a	s hazardous according to Regulation (EC) 1272/2008 as amended.
	text of the H statements declared above. letailed information on health effects and symptoms.
2.2 Label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	: May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects.

Conforms to Regulation (EC)	No	o. 1907/2006 (REACH), Annex II
Code : 00428704		Date of issue/Date of revision : 11 August 2022
PSX 700SG DK GRAY F/S 26	300	NRL PIGMENT PKG
SECTION 2: Hazards	ic	lentification
Precautionary statements		
Prevention	:	Wear protective gloves. Avoid release to the environment. Avoid breathing vapour.
Response	:	✓ake off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water.
Storage	:	Not applicable.
Disposal	:	₱ spose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	:	4.4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro- 2,3-epoxypropane Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate
Supplemental label elements	:	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Special packaging requirem	nen	u <u>ts</u>
Containers to be fitted with child-resistant fastenings		Not applicable.
Tactile warning of danger	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification	: Prolonged or repeated contact may dry skin and cause irritation.

SECTION 3: Composition/information on ingredients

3.2 Mixtures	: Mixture				
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
4'- Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro- 2,3-epoxypropane	REACH #: 01-2119959495-22 EC: 500-070-7 CAS: 30583-72-3	≥25 - ≤50	Skin Sens. 1, H317 Aquatic Chronic 3, H412	-	[1]
Reaction mass of bis (1,2,2,6,6-pentamethyl- 4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl- 4-piperidyl sebacate	REACH #: 01-2119491304-40 EC: 915-687-0 CAS: 1065336-91-5	≥0.10 - ≤2.2	Skin Sens. 1A, H317 Repr. 2, H361 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1]
n-butyl acetate	REACH #: 01-2119485493-29 EC: 204-658-1 CAS: 123-86-4	≥1.0 - ≤5.0	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	-	[1] [2]
		English	(GB) United Arab E	mirates	2/13

Code : 00428704			Date of issue/Date of revisi	ion : 11 Aug	ust 2022
PSX 700SG DK GRAY F/S	26008 NRL PIGMENT	PKG			
SECTION 3: Comp	osition/informat	tion or	n ingredients		
	Index: 607-025-00-1				
2,5-Furandione, telomer with ethenylbenzene and (1-methylethyl)benzene, 3- (dimethylamino)propyl imide, imide with polyethylene-polypropylene glycol 2-aminopropyl Me ether, 2-[(C10-16-alkyloxy) methyl]oxirane-quaternized benzoates (salts)		≤0.20	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1]
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid n	neasures
Eye contact	: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health e	<u>ffects</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Defatting to the skin. May cause skin dryness and irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/sy	r <u>mptoms</u>
Eye contact	: No specific data.
Inhalation	: No specific data.

Conforms to Regulation (EC)	No. 1907/2006 (REACH), Annex II
Code : 00428704	Date of issue/Date of revision : 11 August 2022
PSX 700SG DK GRAY F/S 26	008 NRL PIGMENT PKG
SECTION 4: First aid	measures
Skin contact	: Adverse symptoms may include the following: irritation redness dryness cracking
Ingestion	: No specific data.
4.3 Indication of any immedia	ate medical attention and special treatment needed
Notes to physician	 In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.
SECTION 5: Firefight	ting measures
5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising f	rom the substance or mixture
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides sulfur oxides halogenated compounds metal oxide/oxides
5.3 Advice for firefighters	
Special precautions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.
SECTION 6: Acciden	tal release measures

6.1 Personal precautions, prot	ective equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II			
	00428704 GRAY F/S 26008	Date of issue/Date of revision : 11 August 2022 3 NRL PIGMENT PKG :	
SECTION 6	3: Accidenta	I release measures	
6.2 Environmer precautions	ntal :	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.	
6.3 Methods an	d material for co	ontainment and cleaning up	
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.	
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product.	
6.4 Reference t sections	o other :	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.	

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
7.2 Conditions for safe storage, including any incompatibilities	: Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

Recommendations	: Not available.
Industrial sector specific solutions	: Not available.

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II : 00428704 Date of issue/Date of revision Code

PSX 700SG DK GRAY F/S 26008 NRL PIGMENT PKG

: 11 August 2022

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredien	t name	Exposure limit values
n-butyl acetate		EU OEL (Europe, 10/2019). STEL: 150 ppm 15 minutes. STEL: 723 mg/m ³ 15 minutes. TWA: 241 mg/m ³ 8 hours. TWA: 50 ppm 8 hours.
Recommended monitoring procedures	atmosphere or bi the ventilation or protective equipm following: Europe assessment of ex values and meas atmospheres - G exposure to cher atmospheres - G measurement of	ntains ingredients with exposure limits, personal, workplace iological monitoring may be required to determine the effectiveness of other control measures and/or the necessity to use respiratory nent. Reference should be made to monitoring standards, such as the ean Standard EN 689 (Workplace atmospheres - Guidance for the xposure by inhalation to chemical agents for comparison with limit surement strategy) European Standard EN 14042 (Workplace buide for the application and use of procedures for the assessment of mical and biological agents) European Standard EN 482 (Workplace beneral requirements for the performance of procedures for the chemical agents) Reference to national guidance documents for determination of hazardous substances will also be required.
8.2 Exposure controls		
Appropriate engineering controls	: Good general ve contaminants.	ntilation should be sufficient to control worker exposure to airborne
Individual protection measur	<u>es</u>	
Hygiene measures	eating, smoking a Appropriate tech Contaminated wo contaminated clo	earms and face thoroughly after handling chemical products, before and using the lavatory and at the end of the working period. niques should be used to remove potentially contaminated clothing. ork clothing should not be allowed out of the workplace. Wash othing before reusing. Ensure that eyewash stations and safety se to the workstation location.
Eye/face protection <u>Skin protection</u>	: Safety glasses w	ith side shields.
Hand protection	worn at all times necessary. Cons during use that th noted that the tim glove manufactur protection time of frequently repeat (breakthrough tim When only brief of (breakthrough tim The user must ch product is the mo	nt, impervious gloves complying with an approved standard should be when handling chemical products if a risk assessment indicates this is sidering the parameters specified by the glove manufacturer, check he gloves are still retaining their protective properties. It should be he to breakthrough for any glove material may be different for different rers. In the case of mixtures, consisting of several substances, the f the gloves cannot be accurately estimated. When prolonged or ted contact may occur, a glove with a protection class of 6 ne greater than 480 minutes according to EN 374) is recommended. contact is expected, a glove with a protection class of 2 or higher ne greater than 30 minutes according to EN 374) is recommended. heck that the final choice of type of glove selected for handling this bost appropriate and takes into account the particular conditions of use, e user's risk assessment.
Gloves	: butyl rubber	
Body protection		ive equipment for the body should be selected based on the task being ne risks involved and should be approved by a specialist before duct.

	specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment

will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physica	l a	nd chemical properties				
<u>Appearance</u>						
Physical state	4	Liquid.				
Colour	1	Not available.				
Odour	1	Characteristic.				
Odour threshold	:	Not available.				
Melting point/freezing point	:	May start to solidify at the following temperature: -12.9°C (8.8°F) This is based on data for the following ingredient: 4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane. Weighted average: -17.55°C (0.4°F)				
Initial boiling point and boiling range	:	>37.78°C				
Flammability (solid, gas)	1	liquid				
Upper/lower flammability or explosive limits	:	Greatest known range: Lower:	1.4% Upp	oer: 7.6% (n-	butyl acetate)	
Auto-ignition temperature	:	Ingredient name	°C	°F	Method	
		n-butyl acetate	415	779	EU A.15	
Decomposition temperature	:	Stable under recommended sto	orage and	handling cor	nditions (see Section 7).	
рН	:	insoluble in water.				
Viscosity	1	Kinematic (40°C): >21 mm²/s				
Solubility(ies)	1					
Media		Result				
cold water		Not soluble				
Water Solubility at room temperature	:	0.4 g/l			,	
Partition coefficient: n-octanol/ water	:	Not applicable.				
Vapour pressure	1	1.5 kPa (11.2 mm Hg)				
Evaporation rate	:	0.97 (butyl acetate = 1)				
Relative density		1.49				
Vapour density		Highest known value: 4 (Air = 1				
Explosive properties	4	Product does not present an ex	plosion h	azard.		
Oxidising properties	1	Product does not present an ox	idizing ha	zard.		
Particle characteristics						

Conforms to Regulation (EC)	No. 1907/2006 (REACH), Annex II
Code : 00428704	Date of issue/Date of revision : 11 August 2022
PSX 700SG DK GRAY F/S 26	008 NRL PIGMENT PKG
SECTION 9: Physica	I and chemical properties
Median particle size	: Not applicable.
9.2 Other information	
No additional information.	
SECTION 10: Stabilit	y and reactivity
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
10.6 Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides sulfur oxides halogenated compounds metal oxide/ oxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Reaction mass of bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	LD50 Dermal	Rat	>3170 mg/kg	-
	LD50 Oral	Rat - Male, Female	3230 mg/kg	-
n-butyl acetate	LC50 Inhalation Vapour LC50 Inhalation Vapour LD50 Dermal LD50 Oral	Rat Rat Rabbit Rat	>21.1 mg/l 2000 ppm >17600 mg/kg 10.768 g/kg	4 hours 4 hours - -
2,5-Furandione, telomer with ethenylbenzene and (1-methylethyl) benzene, 3-(dimethylamino)propyl imide, imide with polyethylene-polypropylene glycol 2-aminopropyl Me ether, 2-[(C10-16-alkyloxy)methyl]oxirane- quaternized, benzoates (salts)	LD50 Oral	Rat - Female	>2000 mg/kg	-

Conclusion/Summary	: There are no data available on the mixture itself.
Irritation/Corrosion	
Conclusion/Summary	
Skin	: There are no data available on the mixture itself.
Eyes	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
Sensitisation	

Conforms to Regulation (EC)) No. 1907/2006 (REACH), Ann	ex II			
Code : 00428704	[Date of issue/	Date of revision	: 11 August 2022	
PSX 700SG DK GRAY F/S 26008 NRL PIGMENT PKG					
SECTION 11: Toxico	logical information				
Conclusion/Summary					
Skin	: There are no data available				
Respiratory	: There are no data available	on the mixtur	e itself.		
Mutagenicity					
Conclusion/Summary	: There are no data available	on the mixtur	e itself.		
Carcinogenicity		4l i4			
Conclusion/Summary	: There are no data available	on the mixtur	e ilsell.		
Reproductive toxicity	There are no data available	on the mixtur	o itaalf		
Conclusion/Summary	: There are no data available		e ilsell.		
Teratogenicity	There are no data available	on the mixtur	o itaalf		
Conclusion/Summary	: There are no data available		e ilsell.		
Specific target organ toxici		0	Desit 1	Tanat	
Product/ing	redient name	Category	Route of exposure	Target organs	
n-butyl acetate		Category 3	-	Narcotic effects	
Specific target organ toxici	ty (ropostod oxposuro)				
Not available.	<u>ty (repeated exposure)</u>				
Aspiration hazard					
Not available.					
Information on likely routes of exposure	: Not available.				
Potential acute health effect	<u>:ts</u>				
Inhalation	: No known significant effect	s or critical ha	zards.		
Ingestion	: No known significant effect	s or critical ha	zards.		
Skin contact	: Defatting to the skin. May or reaction.	cause skin dry	ness and irritation.	May cause an allergic skin	
Eye contact	: No known significant effect	s or critical ha	zards.		
Symptoms related to the pl	hysical, chemical and toxicolo	gical charact	eristics		
Inhalation	: No specific data.				
Ingestion	: No specific data.				
Skin contact	: Adverse symptoms may inc	lude the follow	wing:		
	irritation redness				
	dryness				
	cracking				
Eye contact	: No specific data.				
Delayed and immediate effe	ects as well as chronic effects	from short a	ind long-term exp	<u>osure</u>	
Short term exposure					
Potential immediate effects	: Not available.				
Potential delayed effects	: Not available.				
Long term exposure					
Potential immediate effects	: Not available.				
Potential delayed effects	: Not available.				
Potential chronic health eff	iects				
Not available.					
	Englis	h (GB)	Inited Arab Emira	tes 9/13	
l				5/10	

SECTION 11: Toxicological information

Conclusion/Summary	: Not available.
General	 Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.
Other information	: Not available.

Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Trimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness. Avoid contact with skin and clothing.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
4-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	LC50 11.5 mg/l	Fish	96 hours
Reaction mass of bis(1,2,2,6,6-pentamethyl- 4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	EC50 1.68 mg/l	Algae	72 hours
n-butyl acetate 2,5-Furandione, telomer with ethenylbenzene and (1-methylethyl)benzene, 3-(dimethylamino)propyl imide, imide with polyethylene-polypropylene glycol 2-aminopropyl Me ether, 2-[(C10-16-alkyloxy)methyl] oxirane-quaternized, benzoates (salts)	LC50 0.9 mg/l Acute LC50 18 mg/l EC50 0.25 mg/l	Fish Fish Algae - Pseudokirchneriella subcapitata	96 hours 96 hours 72 hours

Conclusion/Summary : There are no data available on the mixture itself.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum		
n-butyl acetate	TEPA and OECD 301D	83 % - Readily - 28 days	-	-		
Conclusion/Summary : There are no data available on the mixture itself.						
Product/ingredient name Aquatic half-life Photolysis Biodegradability						
n-butyl acetate		-	-	Readily		

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
n-butyl acetate	2.3	-	low

12.4 Mobility in soil

Code : 00428704 PSX 700SG DK GRAY F/S 26008 NRL PIGMENT PKG Date of issue/Date of revision

: 11 August 2022

SECTION 12: Ecological information

Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.

European waste catalogue (EWC)

Waste code	Waste designation		
08 01 99	wastes not otherwise specified		
ackaging			
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.		
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.		

SECTION 14: Transport information

	ADR/RID	IM	DG	ΙΑΤΑ	
14.1 UN number or ID number	Not regulated.	Not regulated.		Not regulated.	
14.2 UN proper shipping name	-	-		-	
14.3 Transport hazard class(es)	-	-		-	
14.4 Packing group	-	-		-	
		English (GB)	United Arab Em	irates	11/13

Conforms to Regulation	n (EC) No. 1907/2006 (RE	ACH), Annex II	
Code: 00428704Date of issue/Date of revision: 11 August 20			of revision : 11 August 2022
PSX 700SG DK GRAY F	F/S 26008 NRL PIGMENT	PKG	
SECTION 14: Tra	ansport information	on	
14.5 Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.
IMDG : No	ne identified. ne identified. ne identified.		
14.6 Special precaution user	upright and sec		nsport in closed containers that are porting the product know what to do in the
14.7 Transport in bulk according to IMO instruments	: Not applicable.		
SECTION 15: Re	gulatory informat	ion	
15.1 Safety, health and	l environmental regulation	ons/legislation specific for the	e substance or mixture
EU Regulation (EC) N	<u>lo. 1907/2006 (REACH)</u>		
Annex XIV - List of s	ubstances subject to au	thorisation	
<u>Annex XIV</u>			
None of the compone			
Substances of very			
None of the compone			
Annex XVII - Restric on the manufacture, placing on the mark and use of certain dangerous substand mixtures and article	et ces,		
Other national and in	ternational regulations.		
Ozone depleting sub	stances (1005/2009/EU)		
Not listed.			
15.2 Chemical safety assessment	: No Chemical Sa	fety Assessment has been car	ied out.
SECTION 16: Ot	her information		
Indicates information	n that has changed from pi	reviously issued version.	
Abbreviations and acronyms	: ATE = Acute To CLP = Classific		Regulation [Regulation (EC) No.

acronyms

statements

Full text of abbreviated H

1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

Code : 00428704) No. 1907/2006 (REACH), Annex II Date of issue/Date of revision : 11 August 2022
PSX 700SG DK GRAY F/S 26	-
SECTION 16: Other	information
Full text of classifications [CLP/GHS]	 H226 Flammable liquid and vapour. H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness. H361 Suspected of damaging fertility or the unborn child. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. EUH066 Repeated exposure may cause skin dryness or cracking. Aquatic Acute 1 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 Aquatic Chronic 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 Aquatic Chronic 3 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 Flam. Liq. 3 FLAMMABLE LIQUIDS - Category 3 Repr. 2 REPRODUCTIVE TOXICITY - Category 2 Skin Sens. 1 SKIN SENSITISATION - Category 1 Skin Sens. 1A SKIN SENSITISATION - Category 1A STOT SE 3 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3
<u>History</u>	
Date of issue/ Date of revision	: 11 August 2022
Date of previous issue	: 29 November 2021
Prepared by	: EHS
Version	: 2.01
Disclaimer	

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.