SAFETY DATA SHEET



Date of issue 8/22/2022 (month/day/year)

Version 1

Section 1. Chemical product and company identification

A. Product name : PPG AQUACOVER 200 BASE RAL 1015 Product code : 000001100021

Other means of identification 00240676

B. Relevant identified uses of the substance or mixture and uses advised against

Product use	: Professional applications, Used by spraying.
Use of the substance/ mixture	: Coating.
Uses advised against	: Product is not intended, labelled or packaged for consumer use.
C. Supplier's or Importer's information	: PPG SSC (680-090) 19, Yeocheon-ro 217beon-gil, Nam-gu, Ulsan, Korea Tel: +82-52-210-8222
Email Address	Korea.MSDS@PPG.COM
Emergency telephone number:	: +82-52-210-8222

Section 2. Hazards identification

A. Hazard classification	: SERIOUS EYE DAMAGE - Category 1
	SKIN SENSITIZATION - Category 1
	CARCINOGENICITY - Category 1A
	AQUATIC HAZARD (LONG-TERM) - Category 3
This product is classified in a	accordance with the Industrial Safety and Health Act and the Chemical Control

This product is classified in accordance with the Industrial Safety and Health Act and the Chemical Control Act.

B. GHS label elements, including precautionary statements

Symbol



Signal word Hazard statements : Danger

- atements : H317 May cause an allergic skin reaction.
 - H318 Causes serious eye damage.
 - H350 May cause cancer.
 - H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

Korea (GHS) Page: 1/14

Date of issue 8/22/2022 (month/day/year)

Product name PPG AQUACOVER 200 BASE RAL 1015

Section 2. Hazards identification

Prevention	 P202 - Do not handle until all safety precautions have been read and understood. P280 - Wear protective gloves, protective clothing and eye or face protection. P273 - Avoid release to the environment. P261 - Avoid breathing vapor.
Response	 P308 + P313 - IF exposed or concerned: Get medical advice or attention. P362 + P364 - Take off contaminated clothing and wash it before reuse. P302 + P352 - IF ON SKIN: Wash with plenty of water. P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Storage	: Not applicable.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

C. Other hazards which do : None known. not result in classification

Section 3. Composition/information on ingredients

CAS number/other identifiers

CAS number

: Not applicable.

Chemical name	Common name	Identifiers	%
Decanedioic acid, compds. with 1,3-benzenedimethanamine-bisphenol A- bisphenol A diglycidyl ether- diethylenetriamine glycidyl Ph ether reaction product-epichlorohydrin- formaldehyde-propylene oxide- triethylenetetramine polymer	Decanedioic acid, compds. with 1,3-benzenedimethanamine-bisphenol A- bisphenol A diglycidyl ether- diethylenetriamine glycidyl Ph ether reaction product-epichlorohydrin- formaldehyde-propylene oxide- triethylenetetramine polymer	CAS: 260549-92-6	10 -<20
titanium dioxide Kaolin Talc , not containing asbestiform fibres aluminium dihydrogen triphosphate zinc oxide Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil	TITANIUM DIOXIDE ALUMINUM SILICATE Talc, non-asbestos form ALUMINIUM TRIPHOSPHATE ZINC OXIDE POLYAMIDE	CAS: 13463-67-7 CAS: 1332-58-7 CAS: 14807-96-6 CAS: 13939-25-8 CAS: 1314-13-2 CAS: 68082-29-1	10 -<20 10 -<20 5 - <10 1 - <5 1 - <5 0.1 - <1
fatty acids and triethylenetetramine Nitrous acid, salts ammonia 2-butoxyethanol crystalline silica, respirable powder (<10 microns)	SODIUM NITRITE AMMONIUM HYDROXIDE 2-BUTOXY ETHANOL QUARTZ (<10 microns)	CAS: 7632-00-0 CAS: 1336-21-6 CAS: 111-76-2 CAS: 14808-60-7	0.1 - <1 0.1 - <1 0.1 - <1 0.1 - <1 0.1 - <1

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Product name PPG AQUACOVER 200 BASE RAL 1015

Section 4. First aid measures

Α.	Eye contact	:	Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
			In case of accidental eye contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation or blistering occurs after contact.
В.	Skin contact	:	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
C.	Inhalation	:	Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
D.	Ingestion	:	If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
Е.	Notes to physician	:	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
	Specific treatments	1	No specific treatment.
	Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Α.	Extinguishing media		
	Suitable extinguishing media	1	Use an extinguishing agent suitable for the surrounding fire.
	Unsuitable extinguishing media	:	None known.
В.	Specific hazards arising from the chemical	:	In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
	Hazardous thermal decomposition products	:	Decomposition products may include the following materials: carbon oxides sulfur oxides metal oxide/oxides
C.	Special equipment for fire-fighting	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
	Fire-fighting procedures	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
			Korea (GHS) Page: 3/14
1			

Product name PPG AQUACOVER 200 BASE RAL 1015

Section 6. Accidental release measures

A. Personal precautions, protective equipment and emergency procedures	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
B. Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
C. Methods and materials for	со	ntainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Α.	Precautions for safe handling	:	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
В.	Conditions for safe storage, including any incompatibilities	:	Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10

for incompatible materials before handling or use.

Product name PPG AQUACOVER 200 BASE RAL 1015

Section 8. Exposure controls/personal protection

A. Occupational exposure limits

Β.

Ingredient name		Exposure limits					
titanium dioxide		Ministry of Employment and Labor (Republic of Korea, 1/2020). TWA: 10 mg/m ³ 8 hours. Form: total dust					
		with less than 1% of free SiO2					
Kaolin		Ministry of Employment and Labor (Republic of Korea, 1/2020).					
		TWA: 2 mg/m ³ 8 hours. Form: Respirable fraction					
Talc , not containing asbes	stiform fibres	Ministry of Employment and Labor					
		(Republic of Korea, 1/2020).					
		TWA: 2 mg/m ³ 8 hours. Form: fibers					
aluminium dihydrogen triph	nosphate	Ministry of Employment and Labor					
, , , , , , , , , , , , , , , , , , , ,	•	(Republic of Korea, 1/2020). [Aluminum					
		(Soluble salts)]					
		TWA: 2 mg/m³, (as Al) 8 hours. Form:					
		Respirable fraction					
zinc oxide		Ministry of Employment and Labor					
		(Republic of Korea, 1/2020).					
		TWA: 2 mg/m ³ 8 hours. Form: Respirable					
		dust					
		STEL: 10 mg/m ³ 15 minutes.					
		TWA: 5 mg/m ³ 8 hours.					
ammonia		Ministry of Employment and Labor					
		(Republic of Korea, 1/2020). [Ammonia]					
		STEL: 35 ppm 15 minutes.					
		TWA: 25 ppm 8 hours.					
2-butoxyethanol		Ministry of Employment and Labor					
5		(Republic of Korea, 1/2020). Absorbed					
		through skin.					
		TWA: 20 ppm 8 hours.					
crystalline silica, respirable	e powder (<10 microns)	Ministry of Employment and Labor					
y		(Republic of Korea, 1/2020).					
		TWA: 0.05 mg/m ³ 8 hours. Form:					
		Respirable fraction					
Recommended	If this product contains ingradiant	s with exposure limits, personal, workplace					
monitoring procedures		ng may be required to determine the effectiveness					
monitoring procedures		neasures and/or the necessity to use respiratory					
		should be made to appropriate monitoring					
		standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.					
Appropriate engineering	If user operations generate dust	fumes, gas, vapor or mist, use process enclosure					
controls		engineering controls to keep worker exposure to					
001111015	airborne contaminants below any						
Environmentel		-					
Environmental		k process equipment should be checked to ensur					
exposure controls		s of environmental protection legislation. In some					
	cases, rume scrubbers, mers or e	engineering modifications to the process					

equipment will be necessary to reduce emissions to acceptable levels.

Product name PPG AQUACOVER 200 BASE RAL 1015

Section 8. Exposure controls/personal protection

C.	Personal protective equip	me	ent
	Respiratory protection	:	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
	Eye protection	4	Chemical splash goggles and face shield.
	Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
	Gloves	:	polyethylene butyl rubber
	Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
	Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Α.	Appearance		
	Physical state	:	Liquid.
	Color	:	Beige.
В.	Odor	:	Aromatic. [Slight]
С.	Odor threshold	:	Not available.
D.	рН	:	Not available.
Ε.	Melting/freezing point	:	Not available.
F .	Boiling point/boiling	:	>37.78°C (>100°F)
	range		
G.	Flash point	1	Closed cup: Not applicable.
н.	Evaporation rate	:	Not available.
I.	Flammability (solid, gas)	:	Not available.
J.	Lower and upper	:	Not available.
	explosive (flammable) limits		
K.	Vapor pressure	;	

Korea (GHS) Page: 6/14

Product name PPG AQUACOVER 200 BASE RAL 1015

Section 9. Physical and chemical properties

			Vapor Pressure at 20°C			Vapor pressure at 50°C		
		Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
		water	23.8	3.2				
L. Solubility	:	Partially soluble in th	ne following	g materi	ials: cold wate	er.		
Solubility in water	:	Not available.						
M. Vapor density	:	Not available.						
N. Relative density	:	1.42						
O. Partition coefficient: n- octanol/water	:	Not applicable.						
P. Auto-ignition temperature	:	Not available.						
Q. Decomposition temperature	:	Not available.						
R. Viscosity	:	Kinematic (40°C (10	4°F)): >21	mm²/s	(>21 cSt)			
Flow time (ISO 2431)	:	Not available.						
S. Molecular weight	:	Not applicable.						

Section 10. Stability and reactivity

		-	-
Α.	Chemical stability	:	The product is stable.
	Possibility of hazardous reactions	-	Under normal conditions of storage and use, hazardous reactions will not occur.
в.	Conditions to avoid	:	When exposed to high temperatures may produce hazardous decomposition products.
C.	Incompatible materials	:	Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
D.	Hazardous decomposition products	:	Depending on conditions, decomposition products may include the following materials: carbon oxides sulfur oxides metal oxide/oxides

Section 11. Toxicological information

A. Information on the routes of exposure	
Potential acute healt	<u>h effects</u>
Inhalation	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Skin contact	: May cause an allergic skin reaction.
Eye contact	: Causes serious eye damage.
Over-exposure signs	s/symptoms
Inhalation	: No specific data.

Date of issue 8/22/2022 (month/day/year)

Version 1

Product name PPG AQUACOVER 200 BASE RAL 1015

Section 11. Toxicological information

Ingestion	: Adverse symptoms may include the following: stomach pains
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
Eye contact	: Adverse symptoms may include the following: pain watering redness

B. Health hazards

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
titanium dioxide	LC50 Inhalation Dusts and mists	Rat	>6.82 mg/l	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Kaolin	LC50 Inhalation Dusts and mists	Rat	>5.07 mg/l	4 hours
	LD50 Oral	Rat	>5000 mg/kg	-
aluminium dihydrogen triphosphate	LD50 Oral	Rat	>2000 mg/kg	-
zinc oxide	LC50 Inhalation Dusts and mists	Rat	>5700 mg/m ³	4 hours
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	LD50 Dermal	Rat	>2000 mg/kg	-
,	LD50 Oral	Rat	>2000 mg/kg	-
Nitrous acid, salts	LD50 Oral	Rat	180 mg/kg	-
ammonia	LD50 Oral	Rat	350 mg/kg	-
2-butoxyethanol	LD50 Dermal	Rat	>2000 mg/kg	-
-	LD50 Oral	Rat	1200 mg/kg	-

Conclusion/Summary : There are no data available on the mixture itself.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	Eyes - Severe irritant	Rabbit	-	-	-
2-butoxyethanol	Skin - Irritant Eyes - Irritant Skin - Moderate irritant	Human Rabbit Rabbit	- - -	- 24 hours 4 hours	- 21 days 28 days
Conclusion/Summary					
Skin : 7	Skin : There are no data available on the mixture itself.				
Eyes : 7	: There are no data available on the mixture itself.				

Respiratory : There are no data available on the mixture itself.

Sensitization

Date of issue 8/22/2022 (month/day/year)

Version 1

Product name PPG AQUACOVER 200 BASE RAL 1015

Section 11. Toxicological information

Product/ingredient name	Route of exposure	Species	Result
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	skin	Mouse	Sensitizing
Conclusion/Summary			
Skin :	There are no data	a available on the mixture itself.	
Respiratory :	There are no data	a available on the mixture itself.	
<u>Mutagenicity</u> Conclusion/Summary :	There are no dat	ta available on the mixture itself.	
<u>Carcinogenicity</u> Conclusion/Summary :	There are no da	ta available on the mixture itself.	
Reproductive toxicity Conclusion/Summary :	There are no da	ata available on the mixture itself.	
<u>Teratogenicity</u> Conclusion/Summary :	There are no da	ata available on the mixture itself.	

Specific target organ toxicity (single exposure)

Name	Classification	Route of exposure	Target organs
Talc , not containing asbestiform fibres	Category 3	-	Respiratory tract irritation
ammonia	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Potential chronic health effects

General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity Mutagenicity Reproductive toxicity	 May cause cancer. Risk of cancer depends on duration and level of exposure. No known significant effects or critical hazards. No known significant effects or critical hazards.

Additional information

Product name PPG AQUACOVER 200 BASE RAL 1015

Section 11. Toxicological information

Sanding and grinding dusts may be harmful if inhaled. Acrylate components of the mixture have irritating properties. Prolonged or repeated contact with skin or mucous membrane may result in irritation symptoms, such as redness, blistering, dermatitis etc. May cause allergic skin reactions with repeated exposure. The inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract. Ingestion may cause nausea, weakness and central nervous system effects. In case of accidental skin contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation, rash or blistering occurs after contact.

Chemical name	Identifiers	GHS Classification
Decanedioic acid, compds. with 1,3-benzenedimethanamine-bisphenol A- bisphenol A diglycidyl ether- diethylenetriamine glycidyl Ph ether reaction product-epichlorohydrin- formaldehyde-propylene oxide- triethylenetetramine polymer	CAS: 260549-92-6	SERIOUS EYE DAMAGE - Category 1
titanium dioxide	CAS: 13463-67-7	CARCINOGENICITY - Category 2
Kaolin	CAS: 1332-58-7	Not classified.
Talc , not containing asbestiform fibres	CAS: 14807-96-6	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
aluminium dihydrogen triphosphate	CAS: 13939-25-8	EYE IRRITATION - Category 2A
zinc oxide	CAS: 1314-13-2	AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	CAS: 68082-29-1	SKIN IRRITATION - Category 2
Nitrous acid, salts	CAS: 7632-00-0	SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1A AQUATIC HAZARD (LONG-TERM) - Category 2 OXIDIZING SOLIDS - Category 2
		ACUTE TOXICITY (oral) - Category 3 AQUATIC HAZARD (ACUTE) - Category 1
ammonia	CAS: 1336-21-6	SERIOUS EYE DAMAGE - Category 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 AQUATIC HAZARD (ACUTE) - Category 1
2-butoxyethanol	CAS: 111-76-2	FLAMMABLE LIQUIDS - Category 4 ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A CARCINOGENICITY - Category 2
crystalline silica, respirable powder (<10 microns)	CAS: 14808-60-7	CARCINOGENICITY - Category 1A

Date of issue 8/22/2022 (month/day/year)

Product name PPG AQUACOVER 200 BASE RAL 1015

Section 12. Ecological information

A. Ecotoxicity

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute LC50 >100 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
zinc oxide	Acute EC50 0.17 mg/l	Algae	72 hours
	Acute EC50 0.481 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Chronic NOEC 0.017 mg/l Fresh water	Algae	72 hours
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	EC10 1.78 mg/l	Algae	72 hours
Nitrous acid, salts	EC50 0.54 to 26.3 mg/l	Fish	96 hours
2-butoxyethanol	Acute LC50 1474 mg/l	Fish	96 hours
	Chronic NOEC >100 mg/l	Fish	21 days

B. Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	-	-	Not readily
Nitrous acid, salts 2-butoxyethanol	-	-	Readily Readily

C. Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Nitrous acid, salts	-3.7	-	low
2-butoxyethanol	0.81	-	low

D. Mobility in soil

Soil/water partition : Not available. coefficient (Koc)

E. <u>Other adverse effects</u> : No known significant effects or critical hazards.

Section 13. Disposal considerations

з.

A. Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Date of issue 8/22/2022 (month/day/year)

Product name PPG AQUACOVER 200 BASE RAL 1015

Section 13. Disposal considerations

B. Disposal precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	IMDG	ΙΑΤΑ	
A. UN number	Not regulated.	Not regulated.	Not regulated.	
B. UN proper shipping name	-	-	-	
C. Transport hazard class(es)	-	-	-	
D. Packing group	-	-	-	
Environmental hazards	No.	No.	No.	
E. Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	

Additional information

UN	: None identified.
IMDG	: None identified.
ΙΑΤΑ	: None identified.

F. Special precaution which a user to be aware of or needs to comply with in connection with transport or transportation

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Section 15. Regulatory information

Α.	Regulation according to l	<u>SHA</u>
	ISHA article 117 (Harmful substances prohibited from manufacture)	: None of the components are listed.
	ISHA article 118 (Harmful substances requiring permission)	: None of the components are listed.
	Article 2 of Youth Protection Act on Substances Hazardous to Youth	: It is not allowed to sell to persons under the age of 19.

Exposure Limits of Chemical Substances and Physical Factors

Korea (GHS) Page: 12/14

Date of issue 8/22/2022 (month/day/year)

Product name PPG AQUACOVER 200 BASE RAL 1015

Section 15. Regulatory information

	The following components titanium dioxide Kaolin Talc , not containing asbes aluminium dihydrogen tripl zinc oxide ammonia 2-butoxyethanol crystalline silica, respirable	stif ho:	orm fibres sphate
	ISHA Enforcement Regs Annex 19 (Exposure standards established for harmful factors)	:	None of the components are listed.
	ISHA Enforcement Regs Annex 21 (Harmful factors subject to Work Environment Measurement)	:	The following components are listed: titanium dioxide, silicates, talc / soapstone, zinc oxide
	ISHA Enforcement Regs Annex 22 (Harmful Factors Subject to Special Health Check- up)	:	The following components are listed: Aluminum and its compounds, Zinc oxide
	Standard of Industrial Safety and Health Annex 12 (Hazardous substances subject to control)	:	The following components are listed: titanium dioxide, aluminum and its compounds, zinc and its compounds
В.	Regulation according to (Ch	emicals Control Act
	Article 11 (TRI)	:	The following components are listed: Aluminium and its compounds, Zinc and its compounds
	Article 18 Prohibited (K- Reach Article 27)	:	None of the components are listed.
	Article 19 Subject to authorization (K-Reach Article 25)	:	None of the components are listed.
	Article 20 Restricted (K- Reach Article 27)	:	None of the components are listed.
	Article 20 Toxic Chemicals (K-Reach Article 20)	:	Not applicable
	Korea inventory	:	All components are listed or exempted.
	Article 39 (Accident Precaution Chemicals)	;	None of the components are listed.
C.	Dangerous Materials Safety Management Act	:	Not applicable.
D.	Wastes regulation	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.

Korea (GHS) Page: 13/14

Date of issue 8/22/2022 (month/day/year)

Version 1

Product name PPG AQUACOVER 200 BASE RAL 1015

Section 15. Regulatory information

E. <u>Regulation according to other foreign laws</u>

Safety, health and environmental regulations specific for the product : No known specific national and/or regional regulations applicable to this product (including its ingredients).

Section 16. Other information

Α.	References	Korean Ministry of Environment; Chemical Control Act Korean Ministry of Labor; Industrial Safety and Health Act NIER Notice Registry of Toxic Effects of Chemical Substances (RTECS) U.S. Environmental Protection Agency, AQUIRE (Aquatic toxicity Informatio Retrieval) ECOTOX Database System.	'n
В.	Date of issue/Date of revision	8/22/2022	
С.	Version	1	
	Prepared by	EHS	
	Other		

D. Other

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.