SAFETY DATA SHEET

Date of issue/Date of revision

: 8 September 2022 Version



: 1

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: AMERLOCK / SIGMACOVER 400 BASE ALUMINUM
Product code	: 000001194894
Product type	: Liquid.
Other means of identifi	cation
00467492; 00467493	
1.2 Relevant identified u	ses of the substance or mixture and uses advised against
Product use	: Professional applications, Used by spraying.

FIGUUCIUSE	· Professional applications, used by spraying.
Use of the substance/ mixture	: Coating.
Uses advised against	: Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

Sigma Paint Saudi Arabia Ltd. PO Box 7509, Dammam 3147 Saudi Arabia Tel: 00966 138 47 31 00 Fax: 00966 138 47 17 34	
e-mail address of person responsible for this SDS	: PS.ACEMEA@ppg.com
1.4 Emergency telephone number	: 00966 138473100 extn 1001

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Product definition : Mixture <u>Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]</u> Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Muta. 2, H341 Aquatic Chronic 2, H411 The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended. See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.



Conforms to Regulation (EC)	No. 1907/2006 (REACH), A	Annex II	
Code : 000001194894	ļ	Date of issue/Date of revision	: 8 September 2022
AMERLOCK / SIGMACOVER	400 BASE ALUMINUM		
SECTION 2: Hazards	identification		
Hazard statements	: Causes skin irritation. May cause an allergic s Causes serious eye irrit Suspected of causing g Toxic to aquatic life with	ation. enetic defects.	
Precautionary statements			
Prevention		afety precautions have been read and ctive clothing and eye or face protectio eathing vapour.	
Response	: Collect spillage.		
Storage	: Not applicable.		
Disposal	: Dispose of contents and international regulations	d container in accordance with all loca 3.	l, regional, national and
Hazardous ingredients	: bis-[4-(2,3-epoxipropox 2,3-epoxypropyl neoded		
Supplemental label elements	: Contains epoxy constitu	uents. May produce an allergic reaction	٦.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.		
Special packaging requiren	<u>ients</u>		
Containers to be fitted with child-resistant fastenings	: Not applicable.		
Tactile warning of danger	: Not applicable.		
2.3 Other hazards			
Product meets the criteria for PBT or vPvB	: This mixture does not c	ontain any substances that are assess	sed to be a PBT or a vPvB.
Other hazards which do	: Prolonged or repeated	contact may dry skin and cause irritation	on.

not result in classification

SECTION 3: Composition/information on ingredients

3.2 Mixtures	: Mixture				
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
bis-[4-(2,3-epoxipropoxi) phenyl]propane	REACH #: 01-2119456619-26 EC: 216-823-5 CAS: 1675-54-3 Index: 603-073-00-2	≥50 - ≤75	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	Skin Irrit. 2, H315: C ≥ 5% Eye Irrit. 2, H319: C ≥ 5%	[1]
2,3-epoxypropyl neodecanoate	REACH #: 01-2119431597-33 EC: 247-979-2 CAS: 26761-45-5	≥10 - ≤25	Skin Sens. 1, H317 Muta. 2, H341 Aquatic Chronic 2, H411	-	[1]
Solvent naphtha (petroleum), heavy arom.	EC: 265-198-5 CAS: 64742-94-5	≥5.0 - ≤10	STOT SE 3, H336 Asp. Tox. 1, H304	-	[1]
		English	(GB) Saudi	Arabia	2/13

Code : 000001194	894	Date of issue/Date of revision	: 8 September 2022
AMERLOCK / SIGMACOVE	ER 400 BASE ALUMINUM		
SECTION 3: Comp	osition/information	on ingredients	
Nota(s) P	Index: 649-424-00-3	Aquatic Chronic 2, H411 EUH066	
		See Section 16 for the full text of the H statements declared	
There are no incrediente pr		above.	

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

[1] Substance classified with a health or environmental hazard

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II

SECTION 4: First aid measures

4.1 Description of first aid m	neasures
Eye contact	: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

4.2 Most important symp	toms and enects, both acute and delayed
Potential acute health e	ffects
Eye contact	: Causes serious eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/sy	<u>mptoms</u>
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness dryness cracking
Ingestion	: No specific data.
4.3 Indication of any imm	ediate medical attention and special treatment needed
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

Conforms to Regulation (EC)	No. 1907/2006 (REACH), Ar	inex II	
Code : 00000119489	4	Date of issue/Date of revision	: 8 September 2022
AMERLOCK / SIGMACOVER	400 BASE ALUMINUM		
SECTION 5: Firefigh	ting measures		
5.1 Extinguishing media			
Suitable extinguishing media	: Use an extinguishing age	ent suitable for the surrounding fire.	
Unsuitable extinguishing media	: None known.		
5.2 Special hazards arising f	rom the substance or mixtu	re	
Hazards from the substance or mixture	material is toxic to aquati	essure increase will occur and the cor c life with long lasting effects. Fire wa tained and prevented from being disc	ater contaminated with
Hazardous combustion products	: Decomposition products carbon oxides metal oxide/oxides	may include the following materials:	
5.3 Advice for firefighters			
Special precautions for fire-fighters		e by removing all persons from the vi shall be taken involving any personal	
Special protective equipment for fire-fighters	apparatus (SCBA) with a for fire-fighters (including	appropriate protective equipment and full face-piece operated in positive pr helmets, protective boots and gloves vide a basic level of protection for che	essure mode. Clothing) conforming to European

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

o. i Personal precautions, pro	tective equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
6.3 Methods and material for	containment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product.

AMERLOCK / SIGMACOVER 400 BASE ALUMINUM

: 000001194894

SECTION 6: Accidental release measures

6.4 Reference to other	: See Section 1 for emergency contact information.
sections	See Section 8 for information on appropriate personal protective equipment.
	See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Code

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
7.2 Conditions for safe storage, including any incompatibilities	: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.
7.3 Specific end use(s)	
Can Castian 1.0 famildantifier	

See Section 1.2 for Identified uses.

Recommendations	: Not available.
Industrial sector specific solutions	: Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace

English (GB) Saudi Arabia

Code : 000001194894 AMERLOCK / SIGMACOVER 400 BASE ALUMINUM Date of issue/Date of revision

SECTION 8: Exposu	re controls/personal protection
	atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure controls	
Appropriate engineering controls	: If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Individual protection meas	<u>ires</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection Skin protection	: Chemical splash goggles.
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Gloves	: butyl rubber
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance		
Physical state	: Liqui	d.
Colour	: Grey	•

Code : 000001194894		Date of	issue/Da	te of revisi	on	: 8 Se	ptember 202
AMERLOCK / SIGMACOVER 400	BASE ALUMINUM						
SECTION 9: Physical ar		operties					
Odour	: Aromatic. [Strong]	-					
Odour threshold	: Not available.						
Melting point/freezing point	: May start to solidif based on data for Weighted average	the following	ingredier				
Initial boiling point and boiling range	: >37.78°C						
Flammability (solid, gas)	: liquid						
Upper/lower flammability or explosive limits	: Greatest known ra heavy arom.)	inge: Lower:	0.6% Up	per: 7% (So	lvent na	phtha (pe	troleum),
Auto-ignition temperature	: Ingredient name		°C	°F		Method	
	Solvent naphtha (petro arom.	oleum), heavy	220 to 25	0 428 to 4	482 <i>A</i>	ASTM E 659	
Decomposition temperature pH Viscosity Solubility(ies) Not available.	 Stable under recor Not applicable. Kinematic (40°C): 		orage and	l handling co	onditions	s (see Sec	tion 7).
Partition coefficient: n-octanol/ water	: Not applicable.						
Vapour pressure	:	Vapoι	Vapour Pressure at 20°C		Vap	our pres	sure at 50°C
	Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
	Solvent naphtha (petroleum), heavy arc	1.875 om.	0.25				
Evaporation rate	: Not available.						
Relative density	: 1.21						
Vapour density	: Highest known val	•	, ,		oxipropo	xi)phenyl]	propane).
Explosive properties	: Product does not p		•				
Oxidising properties	: Product does not p	present an o	xidizing ha	azard.			
Particle characteristics							
Median particle size	: Not applicable.						
9.2 Other information							
No additional information.							
No additional information. SECTION 10: Stability a	nd reactivity						

SECTION TO: Stabilit	y			
10.1 Reactivity	:	No specific test data related to reactivity available	ble for this product or its ingredier	nts.
10.2 Chemical stability	:	The product is stable.		
10.3 Possibility of hazardous reactions	:	Under normal conditions of storage and use, ha	azardous reactions will not occur.	
10.4 Conditions to avoid	:	When exposed to high temperatures may prod Refer to protective measures listed in sections		oducts.
10.5 Incompatible materials	:	Keep away from the following materials to prev oxidising agents, strong alkalis, strong acids.	ent strong exothermic reactions:	
		English (GB)	Saudi Arabia	7/13

AMERLOCK / SIGMACOVER 400 BASE ALUMINUM

: 000001194894

SECTION 10: Stability and reactivity

10.6 Hazardous decomposition products

Code

: Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
bis-[4-(2,3-epoxipropoxi)phenyl]propane	LD50 Dermal	Rabbit	23000 mg/kg	-
	LD50 Oral	Rat	15000 mg/kg	-
2,3-epoxypropyl neodecanoate	LD50 Dermal	Rat	3800 mg/kg	-
	LD50 Oral	Rat	9.6 g/kg	-
Solvent naphtha (petroleum), heavy arom.	LC50 Inhalation Dusts and mists	Rat	>5.2 mg/l	4 hours
	LD50 Oral	Rat	>5 g/kg	-

Conclusion/Summary : There are no data available on the mixture itself.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Eyes - Mild irritant	Rabbit	-	24 hours	-
	Eyes - Redness of the	Rabbit	0.4	24 hours	-
	conjunctivae				
	Skin - Oedema	Rabbit	0.5	4 hours	-
	Skin - Erythema/Eschar	Rabbit	0.8	4 hours	-
	Skin - Mild irritant	Rabbit	-	4 hours	-

Conclusion/Summary

: There are no data available on the mixture itself.

Skin Eyes

: There are no data available on the mixture itself.

Respiratory

: There are no data available on the mixture itself.

Sensitisation

Product/ingredient name	Route of exposure	Species	Result
bis-[4-(2,3-epoxipropoxi)phenyl]propane	skin	Mouse	Sensitising

Conclusion/Summary

Skin Respiratory	There are no data available on the mixture itself.There are no data available on the mixture itself.
<u>Mutagenicity</u> Conclusion/Summary	: There are no data available on the mixture itself.
Carcinogenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Reproductive toxicity	T I
Conclusion/Summary Teratogenicity	: There are no data available on the mixture itself.
Conclusion/Summary	: There are no data available on the mixture itself.
Specific target organ toxic	ity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Solvent naphtha (petroleum), heavy arom. Nota(s) P	Category 3	-	Narcotic effects

Specific target organ toxicity (repeated exposure)

English (GB)

: 8 September 2022

SECTION 11: Toxicological information

AMERLOCK / SIGMACOVER 400 BASE ALUMINUM

: 000001194894

Not available.

Code

Aspiration hazard

Product/i	ngredient name	Result
Solvent naphtha (petroleum),	, heavy arom. Nota(s) P	ASPIRATION HAZARD - Category 1
Information on likely routes of exposure	: Not available.	
Potential acute health effect	<u>ts</u>	
Inhalation	: No known significant effects or crit	ical hazards.
Ingestion	: No known significant effects or crit	ical hazards.
Skin contact	: Causes skin irritation. Defatting to	the skin. May cause an allergic skin reaction.
Eye contact	: Causes serious eye irritation.	
Symptoms related to the ph	ysical, chemical and toxicological c	haracteristics
Inhalation	: No specific data.	
Ingestion	: No specific data.	
Skin contact	: Adverse symptoms may include the irritation redness dryness cracking	e following:
Eye contact	: Adverse symptoms may include the pain or irritation watering redness	e following:
Delayed and immediate effe	ects as well as chronic effects from s	short and long-term exposure
Short term exposure		
Potential immediate effects	: Not available.	
Potential delayed effects	: Not available.	
Long term exposure		
Potential immediate effects	: Not available.	
Potential delayed effects	: Not available.	
Potential chronic health effe	<u>ects</u>	
Not available.		
Conclusion/Summary	: Not available.	
General		defat the skin and lead to irritation, cracking and/or ere allergic reaction may occur when subsequently
Carcinogenicity	: No known significant effects or crit	ical hazards.
Mutagenicity	: Suspected of causing genetic defe	cts.
Reproductive toxicity	: No known significant effects or crit	ical hazards.
Other information	: Not available.	
Prolonged or repeated contac	t may dry akin and aquaa irritation. Par	peated exposure to high vapor concentrations may

Prolonged or repeated contact may dry skin and cause irritation. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

English (GB)

SECTION 11: Toxicological information

AMERLOCK / SIGMACOVER 400 BASE ALUMINUM

: 000001194894

Not available.

Code

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure	
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Acute LC50 1.8 mg/l Fresh	Daphnia - daphnia	48 hours	
	water	magna		
	Chronic NOEC 0.3 mg/l	Daphnia	21 days	
2,3-epoxypropyl neodecanoate	Acute EC50 3.5 mg/l	Algae	96 hours	
	Acute EC50 4.8 mg/l	Daphnia - Daphnia	48 hours	
		magna		
	Acute LC50 9.6 mg/l	Fish - Oncorhynchus	96 hours	
		mykiss		
Solvent naphtha (petroleum), heavy arom.	NOEL 0.48 mg/l Fresh water	Daphnia	21 days	

Conclusion/Summary : There are no data available on the mixture itself.

12.2 Persistence and degradability

Conclusion/Summary : There are no data available on the mixture itself.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
bis-[4-(2,3-epoxipropoxi)phenyl]propane 2,3-epoxypropyl neodecanoate	-		Not readily Not readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2,3-epoxypropyl neodecanoate Solvent naphtha (petroleum), heavy arom. Nota(s) P	4.4 2.8 to 6.5	-	high high

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

English (GB)

Code : 000001194894

AMERLOCK / SIGMACOVER 400 BASE ALUMINUM

Date of issue/Date of revision

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. **Hazardous waste** te.

: The classification of the product may meet the criteria for a hazard	ous wast
--	----------

European waste catalogue (EWC)

Waste code	Waste designation	
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	
ackaging		
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.	
Type of packaging	European waste catalogue (EWC)	
Container	15 01 06 mixed packaging	
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.	

SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number or ID number	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis-[4-(2,3-epoxipropoxi) phenyl]propane, 2,3-epoxypropyl neodecanoate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
14.3 Transport hazard class(es)	9	9	9
14.4 Packing group	Ш	Ш	III
14.5 Environmental hazards	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	(bis-[4-(2,3-epoxipropoxi) phenyl]propane, 2,3-epoxypropyl neodecanoate)	Not applicable.

Additional information

ADR/RID : This product is not regulated as a dangerous good when transported in sizes of ≤ 5 L or ≤ 5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

rabia 11/13
١

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II			
Code	: 000001194894	Date of issue/Date of revision : 8 September 2022	
AMERLOCK	/ SIGMACOVER 40	BASE ALUMINUM	
SECTION 14: Transport information			
Tunnel code	e : (-)		
IMDG	IMDG : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.		
ΙΑΤΑ	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.		
user upright and secure. En		Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.	
14.7 Transport in bulk : Not applicable. according to IMO instruments		Not applicable.	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable.

on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles

Other national and international regulations.

Ozone depleting substances (1005/2009/EU)

Not listed.

15.2 Chemical safety : No Chemical Safety Assessment has been carried out.

assessment

.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number	
Full text of abbreviated H statements	 H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H341 Suspected of causing genetic defects. H411 Toxic to aquatic life with long lasting effects. EUH066 Repeated exposure may cause skin dryness or cracking. 	

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II			
Code : 000001194894		Date of issue/Date of revision : 8 September 2022	
AMERLOCK / SIGMACOVER	400 BASE ALUMINUM		
SECTION 16: Other	information		
Full text of classifications [CLP/GHS]	: Aquatic Chronic 2 Asp. Tox. 1 Eye Irrit. 2 Muta. 2 Skin Irrit. 2 Skin Sens. 1 STOT SE 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 ASPIRATION HAZARD - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 GERM CELL MUTAGENICITY - Category 2 SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITISATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3	
<u>History</u>			
Date of issue/ Date of revision	: 8 September 2022		
Date of previous issue	: No previous validation		
Prepared by	: EHS		
Version	: 1		

<u>Disclaimer</u>

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.