Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830

## **SAFETY DATA SHEET**

Date of issue/Date of revision

: 12 September 2022 Version : 8.02



## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: NOVAGUARD 615/650 HARDENER
Product code	: 00330614
Product type	: Liquid.
Other means of identification	on
Not available.	
1.2 Relevant identified uses	of the substance or mixture and uses advised against
Product use	: Professional applications, Used by spraying.
Use of the substance/ mixture	: Coating.
Uses advised against	: Product is not intended, labelled or packaged for consumer use.
1.3 Details of the supplier of	the safety data sheet
Sigma Paint Saudi Arabia Ltd	
PO Box 7509 Dammam 31472	
Saudi Arabia	
Tel: 00966 138 47 31 00	
Fax: 00966 138 47 17 34	
e-mail address of person	: ndpic@sfda.gov.sa
responsible for this SDS	
1.4 Emergency telephone	: 00966 138473100 extn 1001

## **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Product definition : Mixture Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 2, H411

number

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

Conforms to Regulation (EC)	No. 1907/2006 (REACH),		
Code : 00330614		Date of issue/Date of revision	: 12 September 2022
NOVAGUARD 615/650 HARD	ENER		
<b>SECTION 2: Hazards</b>	identification		
Hazard pictograms			
Signal word	: Danger		
Hazard statements	May cause an allergic	urns and eye damage.	
Precautionary statements			
Prevention	: Wear protective glove the environment.	s, protective clothing and eye or face pro	otection. Avoid release to
Response		HALED: Immediately call a POISON CE diately call a POISON CENTER or doctor	
Storage	: Not applicable.		
Disposal	: Dispose of contents an international regulation	nd container in accordance with all local ns.	, regional, national and
Hazardous ingredients		ol, propoxylated, reaction products with a rimethylcyclohexylamine nomethyl)phenol	ammonia
Supplemental label elements	: Not applicable.		
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.		
Special packaging requiren	<u>nents</u>		
Containers to be fitted with child-resistant fastenings	: Not applicable.		
Tactile warning of danger	: Not applicable.		
2.3 Other hazards			
Product meets the criteria for PBT or vPvB	: This mixture does not	contain any substances that are assess	ed to be a PBT or a vPvB.
Other hazards which do not result in classification	: None known.		

## **SECTION 3: Composition/information on ingredients**

3.2 Mixtures

: Mixture

Code : 00330614		Da	ate of issue/Date of revisi	on : 12 Septem 2022	ber
NOVAGUARD 615/650 HAR	DENER			2022	
SECTION 3: Compo	sition/informat	tion on ii	ngredients		
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
✓ropylidynetrimethanol, propoxylated, reaction products with ammonia	REACH #: 01-2119556886-20 EC: 500-105-6 CAS: 39423-51-3	≥50 - ≤75	Acute Tox. 4, H302 Acute Tox. 4, H312 Eye Dam. 1, H318 Aquatic Chronic 2, H411	ATE [Oral] = 500 mg/ kg ATE [Dermal] = 1100 mg/kg	[1]
3-aminomethyl- 3,5,5-trimethylcyclohexylamine	REACH #: 01-2119514687-32 EC: 220-666-8 CAS: 2855-13-2 Index: 612-067-00-9	≥10 - ≤25	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317	ATE [Oral] = 1030 mg/ kg Skin Sens. 1, H317: C ≥ 0.001%	[1]
benzyl alcohol	REACH #: 01-2119492630-38 EC: 202-859-9 CAS: 100-51-6 Index: 603-057-00-5	≥10 - ≤25	Acute Tox. 4, H302 Acute Tox. 4, H332 Eye Irrit. 2, H319	ATE [Oral] = 1230 mg/ kg ATE [Inhalation (dusts and mists)] = 1.5 mg/l	[1] [2]
Epoxy Amine Resin	CAS: SUB114180	≥5.0 - ≤10	Eye Irrit. 2, H319 Skin Sens. 1, H317	-	[1]
2,4,6-tris (dimethylaminomethyl) phenol	REACH #: 01-2119560597-27 EC: 202-013-9 CAS: 90-72-2 Index: 603-069-00-0	≥1.0 - ≤5.0	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1C, H314 Eye Dam. 1, H318	ATE [Oral] = 1200 mg/ kg ATE [Dermal] = 1280 mg/kg	[1]
salicylic acid	REACH #: 01-2119486984-17 EC: 200-712-3 CAS: 69-72-7 Index: 607-732-00-5	≥1.0 - <3.0	Acute Tox. 4, H302 Eye Dam. 1, H318 Repr. 2, H361d	ATE [Oral] = 891 mg/ kg	[1]
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

#### SUB codes represent substances without registered CAS Numbers.

## **SECTION 4: First aid measures**

4.1 Description of first	t aid measures
Eye contact	: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
	English (GB) United Arab Emirates 3/14

Code : 00330614	Date of issue/Date of revision : 12 September 2022
NOVAGUARD 615/650 HARD	
<b>SECTION 4: First aid</b>	l measures
Ingestion	: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
4.2 Most important sympton	ns and effects, both acute and delayed
Potential acute health effect	<u>xts</u>
Eye contact	: Causes serious eye damage.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes severe burns. Harmful in contact with skin. May cause an allergic skin reaction
Ingestion	: Harmful if swallowed.
Over-exposure signs/symp	utoms
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion	: Adverse symptoms may include the following: stomach pains
4.3 Indication of any immed	iate medical attention and special treatment needed
Notes to physician	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.
<b>SECTION 5: Firefigh</b>	ting measures
5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.

#### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	<ul> <li>Decomposition products may include the following materials: carbon oxides nitrogen oxides</li> </ul>

#### 5.3 Advice for firefighters

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II			
Code : 00330614		Date of issue/Date of revision	: 12 September 2022
NOVAGUARD 615/650 HARDI	ENER		
SECTION 5: Firefight	ing measures		
Special precautions for fire-fighters		scene by removing all persons from the viction shall be taken involving any personal	
Special protective equipment for fire-fighters	apparatus (SCBA) v for fire-fighters (incl	wear appropriate protective equipment and with a full face-piece operated in positive pr uding helmets, protective boots and gloves Il provide a basic level of protection for che	essure mode. Clothing conforming to European

## SECTION 6: Accidental release measures

6.1 Personal precautions, pro	ote	ctive equipment and emergency procedures	
For non-emergency personnel	:	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.	
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".	
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.	
6.3 Methods and material for	со	ntainment and cleaning up	
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.	
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product.	
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.	

## **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be bazardous. Do not reuse container
	product residue and can be hazardous. Do not reuse container.

Conforms to Regulation (E	C) No. 1907/2006 (REACH), Annex II
Code : 00330614	Date of issue/Date of revision: 12 September 2022
NOVAGUARD 615/650 HAP	DENER
SECTION 7: Handli	ng and storage
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
7.2 Conditions for safe storage, including any incompatibilities	: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.
7.3 Specific end use(s)	
See Section 1.2 for Identifie	uses.

Recommendations	: Not available.
Industrial sector specific solutions	: Not available.

## **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 8.1 Control parameters

#### **Occupational exposure limits**

Product/ingredient name		Exposure limit values
benzyl alcohol		IPEL (-). TWA: 5 ppm STEL: 10 ppm
Recommended monitoring : procedures	atmosphere or bi the ventilation or protective equipm following: Europ assessment of ex values and meas atmospheres - G exposure to cher atmospheres - G measurement of	ntains ingredients with exposure limits, personal, workplace iological monitoring may be required to determine the effectiveness of other control measures and/or the necessity to use respiratory nent. Reference should be made to monitoring standards, such as the ean Standard EN 689 (Workplace atmospheres - Guidance for the xposure by inhalation to chemical agents for comparison with limit surement strategy) European Standard EN 14042 (Workplace buide for the application and use of procedures for the assessment of mical and biological agents) European Standard EN 482 (Workplace eneral requirements for the performance of procedures for the chemical agents) Reference to national guidance documents for determination of hazardous substances will also be required.
8.2 Exposure controls		
Appropriate engineering : controls	local exhaust ver	s generate dust, fumes, gas, vapour or mist, use process enclosures, ntilation or other engineering controls to keep worker exposure to inants below any recommended or statutory limits.
Individual protection measures		

ode : 00330614	Date of issue/Date of revision : 12 September 2022
IOVAGUARD 615/650 HAR	ENER
SECTION 8: Exposi	re controls/personal protection
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection <u>Skin protection</u>	: Chemical splash goggles and face shield.
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Gloves	: butyl rubber
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Colour	: Clear.
Odour	: Amine-like.
Odour threshold	: Not available.
Melting point/freezing point	<ul> <li>May start to solidify at the following temperature: 8°C (46.4°F) This is based on data for the following ingredient: 3-aminomethyl-3,5,5-trimethylcyclohexylamine.</li> <li>Weighted average: -14.18°C (6.5°F)</li> </ul>
Initial boiling point and boiling range	: >37.78°C
Flammability (solid, gas)	: liquid

Code : 00330614			Date of	issue/l	Date of revision	on	: 12 S 2022	eptember 2
OVAGUARD 615/650 HARDEN	ER							
SECTION 9: Physical a	nd	cibernical prop	perties					
Upper/lower flammability or explosive limits	:	Greatest known rang	je: Lower:	1.3%	Upper: 13% (b	enzyl al	cohol)	
Auto-ignition temperature	:	Ingredient name		°C	°F		Method	
		Propylidynetrimethanol, preaction products with an		320	608		EU A.15	
Decomposition temperature pH Viscosity		Stable under recomr insoluble in water. Kinematic (40°C): >2		orage a	and handling co	ondition	s (see Sec	tion 7).
Viscosity	1	30 - <40 s (ISO 6mm	ı)					
Solubility(ies)	:							
Media		Result						
<mark>⊭o</mark> ld water		Not soluble						
Partition coefficient: n-octanol water	/:	Not applicable.						
Vapour pressure	:	:	Vapou	r Pres	sure at 20°C	Vap	our pres	sure at 50°C
		Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
		Propylidynetrimethanol, propoxylated, reaction products with ammonia	5.12	0.68	EU A.4	5		
Evaporation rate Relative density		0.007 (benzyl alcoho 0.98	l) compar	ed with	butyl acetate			
Vapour density Explosive properties	:	Highest known value: 3.7 (Air = 1) (benzyl alcohol). Product does not present an explosion hazard.						
Oxidising properties	:	Product does not pre	esent an o	xidizing	hazard.			
Particle characteristics								
Median particle size	:	Not applicable.						
.2 Other information								
No additional information.								

	English (GB) United Arab Emirates 8/14					
10.6 Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides					
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.					
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.					
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.					
10.2 Chemical stability	: The product is stable.					
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.					

# Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II Code : 00330614 Date of issue/Date of revision : 12 September 2022 NOVAGUARD 615/650 HARDENER Date of issue/Date of revision : 12 September 2022

### **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Propylidynetrimethanol, propoxylated,	LD50 Dermal	Rabbit	0.4 g/kg	-
reaction products with ammonia				
	LD50 Oral	Rat	0.22 g/kg	-
3-aminomethyl-	LC50 Inhalation Dusts and	Rat	>5.01 mg/l	4 hours
3,5,5-trimethylcyclohexylamine	mists			
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	1030 mg/kg	-
benzyl alcohol	LC50 Inhalation Dusts and	Rat	>4178 mg/m <sup>3</sup>	4 hours
	mists		, i i i i i i i i i i i i i i i i i i i	
	LD50 Dermal	Rabbit	2000 mg/kg	-
	LD50 Oral	Rat	1.23 g/kg	-
2,4,6-tris(dimethylaminomethyl)phenol	LD50 Dermal	Rabbit	1.28 g/kg	-
	LD50 Dermal	Rat	1280 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-
salicylic acid	LD50 Oral	Rat	0.891 g/kg	-

**Conclusion/Summary** 

: There are no data available on the mixture itself.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2,4,6-tris(dimethylaminomethyl)phenol	Skin - Visible necrosis	Rabbit	-	4 hours	7 days

#### **Conclusion/Summary**

Skin : There are no data available on the mixture itself.

: There are no data available on the mixture itself.

- Eyes Respiratory
- : There are no data available on the mixture itself.

#### **Sensitisation**

Product/ingredient name	Route of exposure	Species	Result
-aminomethyl-3,5,5-trimethylcyclohexylamine	skin	Guinea pig	Sensitising
Conclusion/Summary	-		•

Conclusion/Summary	
Skin	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
<u>Mutagenicity</u>	
<b>Conclusion/Summary</b>	: There are no data available on the mixture itself.
Carcinogenicity	
<b>Conclusion/Summary</b>	: There are no data available on the mixture itself.
Reproductive toxicity	
<b>Conclusion/Summary</b>	: There are no data available on the mixture itself.
Teratogenicity	
<b>Conclusion/Summary</b>	: There are no data available on the mixture itself.
Specific target organ toxic	<u>city (single exposure)</u>
Not available.	
Specific target argen toxi	sity (repeated experience)

#### Specific target organ toxicity (repeated exposure)

Not available.

#### Aspiration hazard

Not available.

Conforms to Regulation (EC	) No. 1907/2006 (REACH), Annex II
Code : 00330614	Date of issue/Date of revision : 12 September 2022
NOVAGUARD 615/650 HARE	DENER
SECTION 11: Toxico	logical information
Information on likely routes of exposure	: Not available.
Potential acute health effect	<u>cts</u>
Inhalation	: No known significant effects or critical hazards.
Ingestion	: Harmful if swallowed.
Skin contact	: Causes severe burns. Harmful in contact with skin. May cause an allergic skin reaction
Eye contact	: Causes serious eye damage.
Symptoms related to the p	hysical, chemical and toxicological characteristics
Inhalation	: No specific data.
Ingestion	: Adverse symptoms may include the following: stomach pains
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
Eye contact	: Adverse symptoms may include the following: pain watering redness
	ects as well as chronic effects from short and long-term exposure
Short term exposure Potential immediate effects	: Not available.
Potential delayed effects	Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	Not available.
Potential chronic health ef	
Not available.	
Conclusion/Summary	: Not available.
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.
Other information	: Not available.
	apor concentrations may cause irritation of the respiratory system and permanent brain and palation of vapour/aerosol concentrations above the recommended exposure limits causes

nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death.

#### 11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

**11.2.2 Other information** 

Not available.

Date of issue/Date of revision

: 12 September 2022

NOVAGUARD 615/650 HARDENER

**SECTION 12: Ecological information** 

#### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
7,4,6-tris(dimethylaminomethyl)phenol salicylic acid	Acute LC50 175 mg/l Acute EC50 1147.57 mg/l Fresh water Chronic NOEC 5.6 mg/l Fresh water	Fish Daphnia - Daphnia Iongispina - Neonate Daphnia - Daphnia magna - Neonate	96 hours 48 hours 21 days

**Conclusion/Summary** 

There are no data available on the mixture itself.

#### 12.2 Persistence and degradability

**Conclusion/Summary** : There are no data available on the mixture itself.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
benzyl alcohol	-	-	Readily

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Propylidynetrimethanol, propoxylated, reaction products with ammonia	-1.13	-	low
3-aminomethyl-3,5,5-trimethylcyclohexylamine	0.99	-	low
benzyl alcohol	0.87	-	low
2,4,6-tris(dimethylaminomethyl)phenol	0.219	-	low
salicylic acid	2.21 to 2.26	-	low

#### 12.4 Mobility in soil

Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

#### 12.6 Endocrine disrupting properties

Not available.

#### 12.7 Other adverse effects

No known significant effects or critical hazards.

#### **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 13.1 Waste treatment methods

Product

	C) No. 1907/2006 (REACH), Annex II		
ode : 00330614	Date of issue/Date of revision : 12 September 2022		
OVAGUARD 615/650 HAF	RDENER		
ECTION 13: Dispo	osal considerations		
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.		
Hazardous waste	: Yes.		
European waste catalog	<u>jue (EWC)</u>		
Waste code	Waste designation		
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances		
Packaging			
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.		
Type of packaging	European waste catalogue (EWC)		
Container	15 01 06 mixed packaging		
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.		

## **SECTION 14: Transport information**

	ADR/RID	IMDG	ΙΑΤΑ
14.1 UN number or ID number	UN3066	UN3066	UN3066
14.2 UN proper shipping name	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	8	8	8
14.4 Packing group	II	11	II
14.5 Environmental hazards	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	(Polyoxy propylene diamine)	Not applicable.

#### **Additional information**

ADR/RID	The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
Tunnel code	: (E)
IMDG	: The marine pollutant mark is not required when transported in sizes of $\leq$ 5 L or $\leq$ 5 kg.
ΙΑΤΑ	: The environmentally hazardous substance mark may appear if required by other transportation regulations.

14.6 Special precautions for	:	Transport within user's premises: always transport in closed containers that are
user		upright and secure. Ensure that persons transporting the product know what to do in the
		event of an accident or spillage.

English (GB)	United Arab Emirates

Conforms to Regulati	on (EC) No. 1907/2006 (REA	CH), Annex II		
Code : 00330	614	Date of issue/Date of revision	: 12 September 2022	
NOVAGUARD 615/650 HARDENER				
SECTION 14: T	ransport information	1		
14.7 Transport in bul according to IMO instruments	k : Not applicable.			
SECTION 15: R	egulatory informatio	'n		
15.1 Safety, health ar	d environmental regulations	s/legislation specific for the substance or i	mixture	
EU Regulation (EC)	<u>No. 1907/2006 (REACH)</u>			
Annex XIV - List of	substances subject to authority	<u>orisation</u>		
Annex XIV				
None of the compo	nents are listed.			
Substances of ver	<u>y high concern</u>			
None of the compo	nents are listed.			
	ctions : Not applicable.			
on the manufactur	-			
placing on the mar and use of certain	Ket			
dangerous substa	nces.			
mixtures and artic				
Other national and i	nternational regulations.			
Ozone depleting su	<u>lbstances (1005/2009/EU)</u>			
Not listed.				
15.2 Chemical safety assessment	: No Chemical Safet	ty Assessment has been carried out.		
SECTION 16: O	ther information			
Indicates information	on that has changed from prev	<i>i</i> ously issued version.		
Abbreviations and	: ATE = Acute Toxic			
acronyms	1272/2008]	on, Labelling and Packaging Regulation [Reg	ulation (EC) No.	

	1272/2008] DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number		
Full text of abbreviated H statements	H317 May cause an a H318 Causes serious H319 Causes serious H332 Harmful if inhale H361d Suspected of da	act with skin. skin burns and eye damage. Illergic skin reaction. eye damage. eye irritation.	
Full text of classifications [CLP/GHS]	: Acute Tox. 4 Aquatic Chronic 2 Eye Dam. 1 Eye Irrit. 2 Repr. 2 Skin Corr. 1B Skin Corr. 1C Skin Sens. 1 Skin Sens. 1A	ACUTE TOXICITY - Category 4 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 REPRODUCTIVE TOXICITY - Category 2 SKIN CORROSION/IRRITATION - Category 1B SKIN CORROSION/IRRITATION - Category 1C SKIN SENSITISATION - Category 1 SKIN SENSITISATION - Category 1A	
<u>History</u>			

English (GB) United

United Arab Emirates

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II				
Code : 0033061	4	Date of issue/Date of revision	: 12 September 2022	
NOVAGUARD 615/650 H	NOVAGUARD 615/650 HARDENER			
SECTION 16: Other information				
Date of issue/ Date of revision	: 12 September 2022			
Date of previous issue	: 5 May 2022			
Prepared by	: EHS			
Version	: 8.02			

#### <u>Disclaimer</u>

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.