SAFETY DATA SHEET

Date of issue/Date of revision

: 5 October 2022

Version : 1



SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier			
Product name	: NOVAGUARD 840/890 HARDENER CREAM		
Product code	: 000001195279		
Product type	: Liquid.		
Other means of identific	ation		
00463832			
00463832	es of the substance or mixture and uses advised against		
00463832	es of the substance or mixture and uses advised against : Consumer applications, Professional applications, Used by spraying.		

1.3 Details of the supplier of the safety data sheet

Sigma Paints Egypt	
Villa#8, street 279	
New Maadi, Cairo	
Egypt	
Tel: 00202 516 223 797	
Fax: 00202 516 38 04	
e-mail address of person responsible for this SDS	: PS.ACEMEA@ppg.com

1.4 Emergency telephone : +20 2 6840902 number

SECTION 2: Hazards identification

Skin Sens. 1, H317

2.1 Classification of the substance or mixture **Product definition** : Mixture Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] Acute Tox. 4, H302 Acute Tox. 3, H311 Acute Tox. 3, H331 Skin Corr. 1A, H314 Eye Dam. 1, H318

Aquatic Chronic 2, H411 The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.



Conforms to Regulation (EC)	No. 1907/2006 (REACH), Annex II		
Code : 000001195279	Date of issue/Date of revision : 5 October 2022		
NOVAGUARD 840/890 HARDI	ENER CREAM		
SECTION 2: Hazards	identification		
Signal word	: Danger		
Hazard statements	Harmful if swallowed. Toxic in contact with skin or if inhaled. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects.		
Precautionary statements			
General	: Keep out of reach of children. If medical advice is needed, have product container or label at hand.		
Prevention	: Wear protective gloves, protective clothing and eye or face protection. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Avoid breathing vapour. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.		
Response	: Collect spillage. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor. Wash contaminated clothing before reuse. IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.		
Storage	: Store locked up.		
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.		
Hazardous ingredients	: 2,2'-dimethyl-4,4'-methylenebis(cyclohexylamine) N-(3-(trimethoxysilyl)propyl)ethylenediamine		
Supplemental label elements	: Not applicable.		
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.		
Special packaging requirem			
Containers to be fitted with child-resistant fastenings	: Yes, applicable.		
Tactile warning of danger	: Yes, applicable.		
2.3 Other hazards			
Product meets the criteria for PBT or vPvB	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.		
Other hazards which do not result in classification	: None known.		

Date of issue/Date of revision

: 5 October 2022

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture					
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
2,2'-dimethyl-4,4'- methylenebis (cyclohexylamine)	EC: 229-962-1 CAS: 6864-37-5 Index: 612-110-00-1	≥75 - ≤90	Acute Tox. 4, H302 Acute Tox. 3, H311 Acute Tox. 3, H331 Skin Corr. 1A, H314 Eye Dam. 1, H318 Aquatic Chronic 2, H411	ATE [Oral] = 500 mg/ kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (dusts and mists)] = 0.5 mg/l	[1]
benzyl alcohol	REACH #: 01-2119492630-38 EC: 202-859-9 CAS: 100-51-6 Index: 603-057-00-5	≥10 - ≤15	Acute Tox. 4, H302 Acute Tox. 4, H332 Eye Irrit. 2, H319	ATE [Oral] = 1230 mg/ kg ATE [Inhalation (dusts and mists)] = 1.5 mg/l	[1] [2]
N-(3-(trimethoxysilyl)propyl) ethylenediamine	EC: 217-164-6 CAS: 1760-24-3	≥1.0 - ≤5.0	Acute Tox. 4, H332 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412	ATE [Inhalation (vapours)] = 11 mg/l	[1]
2,4,6-tris (dimethylaminomethyl) phenol	REACH #: 01-2119560597-27 EC: 202-013-9 CAS: 90-72-2 Index: 603-069-00-0	≥1.0 - ≤3.7	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1C, H314 Eye Dam. 1, H318	ATE [Oral] = 1200 mg/ kg ATE [Dermal] = 1280 mg/kg	[1]
			See Section 16 for the full text of the H statements declared above.		

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

[1] Substance classified with a health or environmental hazard [2] Substance with a workplace exposure limit

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.		
Inhalation	Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.		
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners. 		
Ingestion	: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.		
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.		

4.2 Most important symptoms and effects, both acute and delayed <u>Potential acute health effects</u>

Code : 00000119527	9 Date of issue/Date of revision : 5 October 2022	
NOVAGUARD 840/890 HARE		
SECTION 4: First aid	d measures	
Eye contact	: Causes serious eye damage.	
Inhalation	: Toxic if inhaled.	
Skin contact	: Causes severe burns. Toxic in contact with skin. May cause an allergic skin reaction	
Ingestion	: Harmful if swallowed.	
Over-exposure signs/symp	<u>ptoms</u>	
Eye contact	: Adverse symptoms may include the following: pain watering redness	
Inhalation	: No specific data.	
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur	
Ingestion	: Adverse symptoms may include the following: stomach pains	
4.3 Indication of any immed	iate medical attention and special treatment needed	
Notes to physician	 In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. 	
Specific treatments	: No specific treatment.	
SECTION 5: Firefigh	ting measures	
5.1 Extinguishing media		
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.	
Unsuitable extinguishing media	: None known.	

Hazards from the substance or mixture Hazards from the substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst. This

substance or mixture	material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.	
Hazardous combustion products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides Formaldehyde.	
5.3 Advice for firefighters		
Special precautions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breath apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothir for fire-fighters (including helmets, protective boots and gloves) conforming to Europ standard EN 469 will provide a basic level of protection for chemical incidents.	

Date of issue/Date of revision

: 5 October 2022

SECTION 6: Accidental release measures 6.1 Personal precautions, protective equipment and emergency procedures For non-emergency : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from personnel entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. For emergency responders ÷ If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel". 6.2 Environmental : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental precautions pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage. 6.3 Methods and material for containment and cleaning up : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up Small spill if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. Stop leak if without risk. Move containers from spill area. Approach the release from Large spill ÷. upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. 6.4 Reference to other See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. sections See Section 13 for additional waste treatment information. SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conforms to Regulation (EC)	No. 1907/2006 (REACH), Annex II
Code : 000001195279	Date of issue/Date of revision : 5 October 2022
NOVAGUARD 840/890 HARDE	ENER CREAM
SECTION 7: Handling	g and storage
7.2 Conditions for safe storage, including any incompatibilities	: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

Recommendations	: Not available.
Industrial sector specific solutions	: Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name		Exposure limit values		
benzyl alcohol		IPEL (-). TWA: 5 ppm STEL: 10 ppm		
procedures atmosphere or b the ventilation or protective equipy following: Europ assessment of e values and meas atmospheres - G exposure to cher atmospheres - G measurement of		ntains ingredients with exposure limits, personal, workplace ological monitoring may be required to determine the effectiveness of other control measures and/or the necessity to use respiratory nent. Reference should be made to monitoring standards, such as the ean Standard EN 689 (Workplace atmospheres - Guidance for the xposure by inhalation to chemical agents for comparison with limit surement strategy) European Standard EN 14042 (Workplace uide for the application and use of procedures for the assessment of nical and biological agents) European Standard EN 482 (Workplace eneral requirements for the performance of procedures for the chemical agents) Reference to national guidance documents for determination of hazardous substances will also be required.		
8.2 Exposure controls				
Appropriate engineering controls		equate ventilation. Use process enclosures, local exhaust ventilation or g controls to keep worker exposure to airborne contaminants below any r statutory limits.		
Individual protection measur	<u>es</u>			
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.			
Eye/face protection <u>Skin protection</u>	: Chemical splash	goggles and face shield.		
Hand protection	:			

Date of issue/Date of revision

SECTION 8: Exposure controls/personal protection

•	
	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Gloves	: nitrile neoprene
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical 4properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

	English (GE	3)	E	gypt	7/13
Viscosity	: Kinematic (40°C): >21 mm ² /s	;			
рН	Not applicable.				
Decomposition temperature	: Stable under recommended	storage and	handling cond	litions (see Secti	on 7).
	2,2'-dimethyl-4,4'-methylenebis (cyclohexylamine)	275	527		
Auto-ignition temperature	: Ingredient name	°C	°F	Method	
Flammability (solid, gas) Upper/lower flammability or explosive limits	: liquid : Greatest known range: Lowe	r: 1.3% Upp	ber: 13% (ben:	zyl alcohol)	
Initial boiling point and boiling range	: >37.78°C				
Melting point/freezing point	: May start to solidify at the foll data for the following ingredie Weighted average: -8.54°C (ent: 2,2'-dim		· · ·	
Odour threshold	: Not available.				
Odour	: Amine-like. [Slight]				
Colour	: Light straw.				
Physical state	: Liquid.				
<u>Appearance</u>					

Code : 000001195279			Date of	issue/l	Date of revision	on	: 5 Oc	tober 2022
NOVAGUARD 840/890 HARD	ENER (CREAM						
SECTION 9: Physical	l and	cbemical4proj	perties					
Viscosity	:	30 - <40 s (ISO 6mn	n)					
Solubility(ies)	:	·						
Media		Result						
cold water		Not soluble						
Partition coefficient: n-octa water	nol/ :	Not applicable.						
Vapour pressure			Vapour Pressure at 20°C		Vapour pressure at 50°C			
vapour pressure			Vapoι	ir Press	sure at 20°C	Vap	our press	sure at 50°C
vapour pressure		Ingredient name	Vapou mm Hg		sure at 20°C Method	Vapo mm Hg	kPa	Method
vapour pressure		Ingredient name N-(3-(trimethoxysilyl) propyl)ethylenediamine	-	kPa		mm	-1	1
	:	N-(3-(trimethoxysilyl)	mm Hg	kPa 0.04	Method	mm	-1	1
Evaporation rate Relative density		N-(3-(trimethoxysilyl) propyl)ethylenediamine	mm Hg	kPa 0.04	Method	mm	-1	1
Evaporation rate Relative density	:	N-(3-(trimethoxysilyl) propyl)ethylenediamine 0.007 (benzyl alcoho	mm Hg 0.3000246 DI) compar	kPa 0.04 ed with	Method butyl acetate	mm Hg	-1	1
Evaporation rate	:	N-(3-(trimethoxysilyl) propyl)ethylenediamine 0.007 (benzyl alcoho 0.97	mm Hg 0.3000246 bl) compar e: 3.7 (Air	kPa 0.04 ed with = 1) (b	Method butyl acetate benzyl alcohol).	mm Hg	-1	1
Evaporation rate Relative density Vapour density	:	N-(3-(trimethoxysilyl) propyl)ethylenediamine 0.007 (benzyl alcoho 0.97 Highest known value	mm Hg 0.3000246 bl) compar e: 3.7 (Air esent an e	kPa 0.04 ed with = 1) (b xplosion	Method butyl acetate penzyl alcohol). n hazard.	mm Hg	-1	1
Evaporation rate Relative density Vapour density Explosive properties	:	N-(3-(trimethoxysilyl) propyl)ethylenediamine 0.007 (benzyl alcoho 0.97 Highest known value Product does not pre	mm Hg 0.3000246 bl) compar e: 3.7 (Air esent an e	kPa 0.04 ed with = 1) (b xplosion	Method butyl acetate penzyl alcohol). n hazard.	mm Hg	-1	1

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
10.6 Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides Formaldehyde. metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects Acute toxicity

Date of issue/Date of revision

: 5 October 2022

SECTION 11: Toxicological information

Product/ingredient name	Result	Species	Dose	Exposure
2,2'-dimethyl-4,4'-methylenebis	LC50 Inhalation Dusts and	Rat	420 mg/m ³	4 hours
(cyclohexylamine)	mists			
	LD50 Dermal	Rabbit	>0.2 g/kg	-
	LD50 Oral	Rat	>0.32 g/kg	-
benzyl alcohol	LC50 Inhalation Dusts and	Rat	>4178 mg/m ³	4 hours
	mists			
	LD50 Dermal	Rabbit	2000 mg/kg	-
	LD50 Oral	Rat	1.23 g/kg	-
N-(3-(trimethoxysilyl)propyl) ethylenediamine	LD50 Oral	Rat	2413 mg/kg	-
2,4,6-tris(dimethylaminomethyl)phenol	LD50 Dermal	Rabbit	1.28 g/kg	-
	LD50 Dermal	Rat	1280 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-

Conclusion/Summary

: There are no data available on the mixture itself.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2,4,6-tris(dimethylaminomethyl)phenol	Skin - Visible necrosis	Rabbit	-	4 hours	7 days

Conclusion/Summary	
Skin	: There are no data available on the mixture itself.
Eyes	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
Sensitisation	
Conclusion/Summary	
Skin	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
Mutagenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Carcinogenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Reproductive toxicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Teratogenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Specific target organ toxic	ity (single exposure)
Not available.	
Specific target organ toxic	ity (repeated exposure)
Not available.	
Aspiration hazard	
Not available.	
Information on likely routes of exposure	: Not available.
Potential acute health effe	<u>ets</u>
Inhalation	: Toxic if inhaled.

Ingestion	1	Harmful if swallowed.
Skin contact	:	Causes severe burns. Toxic in contact with skin. May cause an allergic skin reaction.
Eye contact	:	Causes serious eye damage.

Conforms to Regulation (EC)	No. 1907/2006 (REACH), A	nnex II	
Code : 000001195279		Date of issue/Date of revision	: 5 October 2022
NOVAGUARD 840/890 HARDE	ENER CREAM		
SECTION 11: Toxicol	logical information		
Symptoms related to the ph	ysical, chemical and toxico	blogical characteristics	
Inhalation	: No specific data.		
Ingestion	: Adverse symptoms may stomach pains	include the following:	
Skin contact	: Adverse symptoms may pain or irritation redness blistering may occur	include the following:	
Eye contact	: Adverse symptoms may pain watering redness	include the following:	
Delayed and immediate effe	cts as well as chronic effe	cts from short and long-term exposur	<u>.6</u>
<u>Short term exposure</u>			
Potential immediate effects	: Not available.		
Potential delayed effects	: Not available.		
Long term exposure			
Potential immediate effects	: Not available.		
Potential delayed effects	: Not available.		
Potential chronic health effe	ects		
Not available.			
Conclusion/Summary	: Not available.		
General	: Once sensitized, a sever very low levels.	e allergic reaction may occur when subs	equently exposed to
Carcinogenicity	: No known significant effe	ects or critical hazards.	
Mutagenicity	: No known significant effe	ects or critical hazards.	
Reproductive toxicity	: No known significant effe	ects or critical hazards.	
Other information	: Not available.		

Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Trimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness. Contains a substance that may emit formaldehyde if stored beyond its shelf life and/or during cure at curing temperatures greater than 60C/140F.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
2,4,6-tris(dimethylaminomethyl)phenol	Acute LC50 175 mg/l	Fish	96 hours

Conclusion/Summary : There are no data available on the mixture itself.

12.2 Persistence and degradability

Conforms to	onforms to Regulation (EC) No. 1907/2006 (REACH), Annex II						
Code	: 000001195279	Date of issue/Date of revision	: 5 October 2022				
NOVAGUARI	D 840/890 HARDENER CREAM						

SECTION 12: Ecological information

Conclusion/Summary	: There are no data available on the mixture itself.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
benzyl alcohol	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2,2'-dimethyl-4,4'-methylenebis(cyclohexylamine)	1.8	-	low
benzyl alcohol	0.87	-	low
2,4,6-tris(dimethylaminomethyl)phenol	0.219	-	low

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.

European waste catalogue (EWC)

Waste code	Waste designation		
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances		
Packaging Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.		
Turne of meeting			

Type of packaging	European waste catalogue (EWC)	
Container	15 01 06	mixed packaging

English (GB)	Egypt	11/13

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II

Code : 000001195279 NOVAGUARD 840/890 HARDENER CREAM Date of issue/Date of revision

SECTION 13: Disposal considerations

Special precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number or ID number	UN2922	UN2922	UN2922
14.2 UN proper shipping name	CORROSIVE LIQUID, TOXIC, N.O.S. (2,2'-dimethyl-4,4'- methylenebis (cyclohexylamine), 2,4,6-tris (dimethylaminomethyl)phenol)	CORROSIVE LIQUID, TOXIC, N.O.S.	CORROSIVE LIQUID, TOXIC, N.O.S.
14.3 Transport hazard class(es)	8 (6.1)	8 (6.1)	8 (6.1)
14.4 Packing group	Ш	II	II
14.5 Environmental hazards	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	(2,2'-dimethyl-4,4'- methylenebis (cyclohexylamine))	Not applicable.

Additional information

ADR/RID: The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or
≤5 kg.IMDG: The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.IATA: The environmentally hazardous substance mark may appear if required by other transportation
regulations.

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk	: Not applicable.
according to IMO	
instruments	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Conforms to Regulation (EC) No. 1907/2006 (REACH), A	nnex II	
Code : 00000119527		Date of issue/Date of revision	: 5 October 2022
NOVAGUARD 840/890 HARE	ENER CREAM		
SECTION 15: Regula	atory information		
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.		
Other national and internat	tional regulations.		
Ozone depleting substance	<u>es (1005/2009/EU)</u>		
Not listed.			
15.2 Chemical safety assessment	: No Chemical Safety Asse	essment has been carried out.	
SECTION 16: Other	information		
Indicates information that	has changed from previously	issued version.	
Abbreviations and acronyms	1272/2008] DNEL = Derived No Effe	belling and Packaging Regulation [Reg ect Level specific Hazard statement ffect Concentration	julation (EC) No.
Full text of abbreviated H statements	 H302 Harmful if swa H311 Toxic in contac H312 Harmful in con H314 Causes severa H317 May cause an H318 Causes seriou H319 Causes seriou H331 Toxic if inhaled H332 Harmful if inha H411 Toxic to aquat 	Illowed. ct with skin. ntact with skin. e skin burns and eye damage. allergic skin reaction. is eye damage. is eye irritation. d.	
Full text of classifications [CLP/GHS]	: Acute Tox. 3 Acute Tox. 4 Aquatic Chronic 2 Aquatic Chronic 3 Eye Dam. 1 Eye Irrit. 2 Skin Corr. 1A Skin Corr. 1C Skin Sens. 1	ACUTE TOXICITY - Category 3 ACUTE TOXICITY - Category 4 LONG-TERM (CHRONIC) AQUAT LONG-TERM (CHRONIC) AQUAT SERIOUS EYE DAMAGE/EYE IRR SERIOUS EYE DAMAGE/EYE IRR SKIN CORROSION/IRRITATION - SKIN CORROSION/IRRITATION - SKIN SENSITISATION - Category	IC HAZARD - Category 3 ITATION - Category 1 ITATION - Category 2 Category 1A Category 1C
History			
Date of issue/ Date of revision	: 5 October 2022		
Date of previous issue	: No previous validation		
Prepared by	: EHS		
Version	: 1		
<u>Disclaimer</u>			

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

English (G	B)
------------	----