SAFETY DATA SHEET

Date of issue/Date of revision

: 9 November 2022



: 1

Version

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: MEGASEAL WBPC Waterbased Epoxy Primer Clear Comp A
Product code	: 00333471
Product description	:
Product type	: Liquid.
Other means of identification	: Not available.
1.2 Relevant identified use	s of the substance or mixture and uses advised against
Product use	: Industrial applications, Used by spraying.
Use of the substance/ mixture	: Coating.
Uses advised against	: Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL Tweemontstraat 104 B-2100 Deurne Belgium Telephone +32-33606311 Fax +32-33606435

e-mail address of person : Pro

: Product.Stewardship.EMEA@ppg.com

responsible for this SDS

1.4 Emergency telephone number

<u>Supplier</u>

+31 20 4075210

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture Classification according to UK CLP/GHS

Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements Hazard pictograms



Signal word

: Warning

Code	: 00333471	Date of issue/Date of revision	: 9 November 2022
MEGASEAL	WBPC Waterbased Epoxy Primer Clea	r Comp A	

SECTION 2: Hazards identification

Hazard statements	:	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.
Precautionary statements		
Prevention	:	Wear protective gloves. Wear eye or face protection. Avoid release to the environment. Avoid breathing vapour. Wash thoroughly after handling.
Response	:	Collect spillage.
Storage	:	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations. P280, P273, P261, P264, P391, P501
Supplemental label elements	:	Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Special packaging requirements		
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	None known.
SECTION 3: Compos	iti	on/information on ingredients

3.2 Mixtures

Mixture

ŝ

Product/ingredient name	Identifiers	%	Classification	Туре
Oxirane, 2,2'-[(1-methylethylidene) bis(4,1-phenyleneoxymethylene)] bis-, homopolymer	CAS: 25085-99-8	≥25 - ≤50	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	[1]
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. <u>Type</u>

[1] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Code<th:: 00333471</th>Date of issue/Date of revision: 9 November 2022MEGASEAL WBPC Waterbased Epoxy Primer Clear Comp A

SECTION 4: First aid measures

4.1 Description of first aid measures				
Eye contact	 Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. 			
Inhalation	 Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. 			
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.			
Ingestion	: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.			
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.			

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects	
Eye contact	: Causes serious eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/sympto	u <u>ms</u>
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
4.3 Indication of any immedia	e medical attention and special treatment needed
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
	rom the substance or mixture

Hazards from the substance or mixture	:	In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	:	Decomposition products may include the following materials: carbon oxides

5.3 Advice for firefighters

English ((GR)
Lingiion	

Date of issue/Date of revision

: 9 November 2022

MEGASEAL WBPC Waterbased Epoxy Primer Clear Comp A

SECTION 5: Firefighting measures

Special protective actions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	ote	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
6.3 Methods and material for	со	ntainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

English (GB)	United Kingdom (UK)	4/12

Code : 00333471 Date of issue/Date of revision : 9 November 2022 MEGASEAL WBPC Waterbased Epoxy Primer Clear Comp A

SECTION 7: Handling and storage

7.2 Conditions for safe storage, including any incompatibilities

Do not store above the following temperature: 35°C (95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Occupational exposure limits

No exposure limit value known.

Recommended monitoring : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness procedures of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

No DNELs/DMELs available.

PNECs

controls

No PNECs available

8.2 Exposure controls

Appropriate engineering : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection <u>Skin protection</u>	: Chemical splash goggles.
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended.

Code	: 00333471	Date of issue/Date of revision	: 9 November 2022
MEGASEAL	WBPC Waterbased Epoxy Primer Clea	ar Comp A	

SECTION 8: Exposure controls/personal protection

		The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment. butyl rubber
Body protection	-	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	-	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

English (GB)		United Kingdom (UK) 6/12
Relative density	:	1.09
Evaporation rate	: (0.36 (butyl acetate = 1)
Vapour pressure	: 3	2.3 kPa (17.5 mm Hg)
Partition coefficient: n-octanol/ water	:	Not applicable.
Miscible with water		No.
Solubility in water	:	54.6 g/l
cold water		Not soluble
Media		Result
S <u>olubility(ies)</u>	:	· · ·
Viscosity		Kinematic (40°C): >21 mm²/s
рН		Not applicable. Not applicable. insoluble in water.
	:	Netenplieskle
Auto-ignition temperature Decomposition temperature	-	Not available.
Flash point		Closed cup: 93.33°C (200°F)
explosive limits		
Upper/lower flammability or		Not available.
boiling range Flammability (solid, gas)		liquid
Initial boiling point and	: 3	>37.78°C (>100°F)
Melting point/freezing point	t	May start to solidify at the following temperature: 0°C (32°F) This is based on data for the following ingredient: water.
Odour threshold	:	Not available.
Odour	: (Characteristic.
Colour	:	Clear.
Physical state	:	Liquid.
Appearance		

Code	: 00333471	Date of issue/Date of revision	: 9 November 2022
MEGASEAL	WBPC Waterbased Epoxy Primer Clea	ar Comp A	

SECTION 9: Physical and chemical properties

Explosive properties	: The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.
Oxidising properties Particle characteristics	: Product does not present an oxidizing hazard.
Median particle size	: Not applicable.

SECTION 10: Stabilit	y and reactivity
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products Refer to protective measures listed in sections 7 and 8.
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
10.6 Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides

SECTION 11: Toxicological information

11.1 Information on toxicolo	gical effects
Acute toxicity	
Conclusion/Summary <u>Acute toxicity estimates</u> N/A	: There are no data available on the mixture itself.
Irritation/Corrosion	
Conclusion/Summary	: Not available.
Skin	: There are no data available on the mixture itself.
Eyes	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
<u>Sensitisation</u>	
Conclusion/Summary	
Skin	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
<u>Mutagenicity</u>	
Conclusion/Summary	: There are no data available on the mixture itself.
Carcinogenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Reproductive toxicity	
Conclusion/Summary	: There are no data available on the mixture itself.
<u>Teratogenicity</u>	
Conclusion/Summary	
	There are no data available on the mixture itself.
Specific target organ toxici	ty (single exposure)

Not available.

Code : 00333471 MEGASEAL WBPC Waterbay	Date of issued Epoxy Primer Clear Comp A	e/Date of revision : 9 Novem	nber 2022
SECTION 11: Toxico	<u> </u>		
Specific target organ toxici	•		
Not available.	· · · · · · · · · · · · · · · · · · ·		
Aspiration hazard Not available.			
Information on likely routes of exposure	: Not available.		
Potential acute health effect			
Eye contact	: Causes serious eye irritation.		
Inhalation	: No known significant effects or c	ritical hazards.	
Skin contact	: Causes skin irritation. May caus	e an allergic skin reaction.	
Ingestion	: No known significant effects or c	ritical hazards.	
Symptoms related to the phy	sical, chemical and toxicological	:haracteristics	
Eye contact	: Adverse symptoms may include pain or irritation watering redness	he following:	
Inhalation	: No specific data.		
Skin contact	: Adverse symptoms may include irritation redness	the following:	
Ingestion	: No specific data.		
Delayed and immediate effect	s as well as chronic effects from	short and long-term exposure	
Short term exposure			
Potential immediate effects	: Not available.		
Potential delayed effects	: Not available.		
Long term exposure			
Potential immediate effects	: Not available.		
Potential delayed effects	: Not available.		
Potential chronic health eff	<u>cts</u>		
Not available.			
Conclusion/Summary	: Not available.		
General	: Once sensitized, a severe allergi to very low levels.	c reaction may occur when subsequer	tly expose
Carcinogenicity	: No known significant effects or c	ritical hazards.	
Mutagenicity	: No known significant effects or c	ritical hazards.	
Reproductive toxicity	: No known significant effects or c	ritical hazards.	

Other information

: Not available.

Code<th::</th>::9 November 2022MEGASEAL WBPC Waterbased Epoxy Primer Clear Comp A::9 November 2022

SECTION 12: Ecological information

12.1 Toxicity

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Not available.

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

<u>Product</u>	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	 Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.

Waste catalogue

Waste code	Waste designation	
08 01 99	wastes not otherwise specified	
Packaging Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.	

Type of packaging		Waste catalogue
Container	15 01 06	mixed packaging
Special precautions	This material and its container must be disposed of in a safe way. Care should l taken when handling emptied containers that have not been cleaned or rinsed of Empty containers or liners may retain some product residues. Avoid dispersal o spilt material and runoff and contact with soil, waterways, drains and sewers.	

Code : 00333471

Date of issue/Date of revision

: 9 November 2022

MEGASEAL WBPC Waterbased Epoxy Primer Clear Comp A

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number	UN3082	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin)
	(Epoxy Resin)	(Epoxy Resin)	(Epoxy Resin)	(Epoxy Resin)
14.3 Transport hazard class(es)	9	9	9	9
14.4 Packing group	III	111	111	111
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	Not applicable.	(Epoxy Resin)	Not applicable.
Additional informa	tion	•		•

ADR/RID	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
Tunnel code	: (-)
ADN	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
IMDG	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
ΙΑΤΑ	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.
14.6 Special pro user	ecautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk	1	Not available.
according to IMO		
instruments		

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
UK (GB) /REACH
Annex XIV - List of substances subject to authorisation
Annex XIV
None of the components are listed.

Substances of very high concern

None of the components are listed.

Ozone depleting substances

Not listed.

Code : 00333471

Date of issue/Date of revision

: 9 November 2022

MEGASEAL WBPC Waterbased Epoxy Primer Clear Comp A

SECTION 15: Regulatory information

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category

E2

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and
	Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019
	No. 720 and amendments
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = GB CLP-specific Hazard statement
	N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification

Classification	Justification
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
Skin Sens. 1, H317	Calculation method
Aquatic Chronic 2, H411	Calculation method

Full text of abbreviated H statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

Full text of classifications

Aquatic Chronic 2 Eye Irrit. 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
History	

motory	
Date of issue/ Date of revision	: 11/9/2022
Date of previous issue	: No previous validation
Prepared by	: EHS
Version	: 1
Disclaimer	

Code : 00333471

Date of issue/Date of revision

: 9 November 2022

MEGASEAL WBPC Waterbased Epoxy Primer Clear Comp A

SECTION 16: Other information

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.