## SAFETY DATA SHEET

Date of issue/Date of revision : 10 November 2022 Version : 3



### SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

**Product name** : AMERLOCK SEALER HRD

**Product code** : 00333521

Other means of identification

Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Industrial applications, Used by spraying.

Use of the substance/ : Coating.

mixture

**Uses advised against** : Product is not intended, labelled or packaged for consumer use.

### 1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL Tweemontstraat 104 B-2100 Deurne Belgium Telephone +32-33606311 Fax +32-33606435

e-mail address of person responsible for this SDS

: Product.Stewardship.EMEA@ppg.com

#### 1.4 Emergency telephone number

**Supplier** 

+31 20 4075210

### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Acute Tox. 4, H302 Acute Tox. 4, H332 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2. H351 **STOT SE 3, H335 STOT RE 2, H373** Aquatic Chronic 2, H411

> English (GB) **Europe** 1/19

Code : 00333521 Date of issue/Date of revision : 10 November 2022

AMERLOCK SEALER HRD

### **SECTION 2: Hazards identification**

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

Hazard pictograms









Signal word : Danger

**Hazard statements**: Harmful if swallowed or if inhaled.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction. May cause respiratory irritation. Suspected of causing cancer.

May cause damage to organs through prolonged or repeated exposure.

Toxic to aquatic life with long lasting effects.

### **Precautionary statements**

**Prevention**: Wear protective gloves, protective clothing and eye or face protection. Avoid release to

the environment. Do not breathe vapour.

Response : Collect spillage.

**Storage** : Store in a well-ventilated place. Keep container tightly closed.

Disposal : Dispose of contents and container in accordance with all local, regional, national and

international regulations.

₱280, P273, P260, P391, P403 + P233, P501

Hazardous ingredients : Marfuryl alcohol

Poly[oxy(methyl-1,2-ethanediyl)],  $\alpha$ -(2-aminomethylethyl)- $\omega$ -(2-aminomethylethoxy)-

Formaldehyde, polymer with benzenamine, hydrogenated

4-nonylphenol, branched 3,6-diazaoctanethylenediamin 4,4'-methylenebis(cyclohexylamine)

Supplemental label

elements

: Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

**Special packaging requirements** 

Containers to be fitted

with child-resistant

: Not applicable.

fastenings

Tactile warning of danger : Not applicable.

### 2.3 Other hazards

English (GB) Europe 2/19

**AMERLOCK SEALER HRD** 

### **SECTION 2: Hazards identification**

Product meets the criteria for PBT or vPvB

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification

: Causes digestive tract burns. Prolonged or repeated contact may dry skin and cause irritation. Contains a substance that may emit formaldehyde if stored beyond its shelf life and/or during cure at curing temperatures greater than 60C/140F.

May cause endocrine disruption.

### **SECTION 3: Composition/information on ingredients**

3.2 Mixtures : Mixture

| Product/ingredient name   | Identifiers   | % by<br>weight  | Classification  | Specific Conc.<br>Limits, M-factors<br>and ATEs  | Туре    |
|---|---|-----------------|---|--|---------|
| furfuryl alcohol  | REACH #:<br>01-2119493965-18<br>EC: 202-626-1<br>CAS: 98-00-0<br>Index: 603-018-00-2  | ≥10 - ≤25       | Acute Tox. 4, H302<br>Acute Tox. 4, H312<br>Acute Tox. 3, H331<br>Eye Irrit. 2, H319<br>Carc. 2, H351<br>STOT SE 3, H335<br>STOT RE 2, H373           | ATE [Oral] = 500 mg/<br>kg<br>ATE [Dermal] = 1100<br>mg/kg<br>ATE [Inhalation<br>(vapours)] = 3 mg/l | [1] [2] |
| Poly[oxy(methyl-<br>1,2-ethanediyl)], α-<br>(2-aminomethylethyl)-ω-<br>(2-aminomethylethoxy)- | REACH #:<br>01-2119557899-12<br>EC: 618-561-0<br>CAS: 9046-10-0 (n<br>= 2-6)          | ≥10 - ≤25       | Skin Corr. 1C, H314<br>Eye Dam. 1, H318<br>Aquatic Chronic 3, H412  | -  | [1]     |
| Polyaminoamide  | EC: Polymer<br>CAS: 68082-29-1  | ≥10 - ≤25       | Eye Dam. 1, H318  | -  | [1]     |
| Formaldehyde, polymer with 1,3-dimethylbenzene  | CAS: 26139-75-3   | ≥10 - ≤25       | Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>STOT SE 3, H335  | -  | [1]     |
| benzyl alcohol  | REACH #:<br>01-2119492630-38<br>EC: 202-859-9<br>CAS: 100-51-6<br>Index: 603-057-00-5 | ≥5.0 - ≤10      | Acute Tox. 4, H302<br>Acute Tox. 4, H332<br>Eye Irrit. 2, H319  | ATE [Oral] = 1230 mg/<br>kg<br>ATE [Inhalation (dusts<br>and mists)] = 1.5 mg/l                      | [1] [2] |
| Formaldehyde, polymer with benzenamine, hydrogenated  | REACH #:<br>01-2119983522-33<br>CAS: 135108-88-2                                      | ≥5.0 - <10      | Acute Tox. 4, H302<br>Skin Corr. 1C, H314<br>Eye Dam. 1, H318<br>Skin Sens. 1, H317<br>STOT RE 2, H373<br>(kidneys) (oral)<br>Aquatic Chronic 3, H412 | ATE [Oral] = 500 mg/<br>kg   | [1]     |
| 2,4,6-tris<br>(dimethylaminomethyl)<br>phenol   | REACH #:<br>01-2119560597-27<br>EC: 202-013-9<br>CAS: 90-72-2<br>Index: 603-069-00-0  | ≥1.0 - ≤3.9     | Acute Tox. 4, H302<br>Acute Tox. 4, H312<br>Skin Corr. 1C, H314<br>Eye Dam. 1, H318   | ATE [Oral] = 1200 mg/kg<br>ATE [Dermal] = 1280<br>mg/kg  | [1]     |
| 4-nonylphenol, branched   | REACH #:<br>01-2119510715-45  | ≥0.10 -<br>≤2.2 | Acute Tox. 4, H302<br>Skin Corr. 1B, H314   | ATE [Oral] = 1300 mg/<br>kg  | [1] [3] |

English (GB) Europe 3/19

AMERLOCK SEALER HRD

### **SECTION 3: Composition/information on ingredients**

|  |  |                 | -9  |  |         |
|--|--|-----------------|---|--|---------|
|  | EC: 284-325-5<br>CAS: 84852-15-3<br>Index: 601-053-00-8                              |                 | Eye Dam. 1, H318<br>Repr. 2, H361fd<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410   | M [Acute] = 10<br>M [Chronic] = 10                               |         |
| 3,6-diazaoctanethylenediamin           | EC: 203-950-6<br>CAS: 112-24-3<br>Index: 612-059-00-5                                | ≥0.10 -<br>≤2.2 | Acute Tox. 4, H302<br>Acute Tox. 4, H312<br>Skin Corr. 1B, H314<br>Eye Dam. 1, H318<br>Skin Sens. 1, H317<br>Aquatic Chronic 3, H412  | ATE [Oral] = 1716 mg/<br>kg<br>ATE [Dermal] = 1465<br>mg/kg      | [1] [2] |
| salicylic acid                         | REACH #:<br>01-2119486984-17<br>EC: 200-712-3<br>CAS: 69-72-7<br>Index: 607-732-00-5 | ≥1.0 - <3.0     | Acute Tox. 4, H302<br>Eye Dam. 1, H318<br>Repr. 2, H361d  | ATE [Oral] = 891 mg/<br>kg                                       | [1]     |
| 4,4'-methylenebis<br>(cyclohexylamine) | REACH #:<br>01-2119541673-38<br>EC: 217-168-8<br>CAS: 1761-71-3                      | ≥1.0 - ≤4.6     | Acute Tox. 4, H302<br>Skin Corr. 1B, H314<br>Eye Dam. 1, H318<br>Skin Sens. 1, H317<br>STOT RE 2, H373 (liver)<br>(oral)<br>Aquatic Chronic 2, H411   | ATE [Oral] = 625 mg/<br>kg                                       | [1]     |
| Nonylphenols                           | EC: 294-048-1<br>CAS: 91672-41-2   | <0.25           | Acute Tox. 4, H302<br>Skin Corr. 1B, H314<br>Eye Dam. 1, H318<br>Repr. 2, H361<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410<br>EUH071<br>See Section 16 for<br>the full text of the H<br>statements declared<br>above. | ATE [Oral] = 500 mg/<br>kg<br>M [Acute] = 10<br>M [Chronic] = 10 | [1] [3] |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

### <u>Type</u>

- Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

**Eye contact** 

: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.

Inhalation

: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

| English (GB)   | Europe | 4/19 |
|----------------|--------|------|
| Liigiisii (OD) | Ediopo | 7,10 |

Code : 00333521 Date of issue/Date of revision : 10 November 2022

**AMERLOCK SEALER HRD** 

### **SECTION 4: First aid measures**

**Skin contact**: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water

or use recognised skin cleanser. Do NOT use solvents or thinners.

**Ingestion**: If swallowed, seek medical advice immediately and show the container or label. Keep

person warm and at rest. Do NOT induce vomiting.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is

suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water

before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

### Potential acute health effects

**Eye contact** : Causes serious eye damage.

Inhalation : Harmful if inhaled. May cause respiratory irritation.

**Skin contact**: Causes severe burns. Defatting to the skin. May cause an allergic skin reaction.

Ingestion : Harmful if swallowed. Corrosive to the digestive tract. Causes burns.

Over-exposure signs/symptoms

**Eye contact** : Adverse symptoms may include the following:

pain watering redness

**Inhalation** : Adverse symptoms may include the following:

respiratory tract irritation

coughing

**Skin contact**: Adverse symptoms may include the following:

pain or irritation

redness dryness cracking

blistering may occur

**Ingestion**: Adverse symptoms may include the following:

stomach pains

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments**: No specific treatment.

### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing** 

media

: None known.

#### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

English (GB) Europe 5/19

Code : 00333521 Date of issue/Date of revision : 10 November 2022

AMERLOCK SEALER HRD

### **SECTION 5: Firefighting measures**

**Hazardous combustion** products

: Decomposition products may include the following materials: carbon oxides nitrogen oxides

#### 5.3 Advice for firefighters

**Special precautions for** fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective** equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

Formaldehyde.

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

### 6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### 6.3 Methods and material for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

6/19 English (GB) **Europe** 

AMERLOCK SEALER HRD

### **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

#### **Protective measures**

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

# Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# 7.2 Conditions for safe storage, including any incompatibilities

: Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

See Section 1.2 for Identified uses.

### **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 8.1 Control parameters

#### Occupational exposure limits

| Product/ingredient name      | Exposure limit values                                     |
|------------------------------|---|
| furfuryl alcohol             | ACGIH TLV (United States, 1/2021). Absorbed through skin. |
| •                            | TWA: 0.2 ppm 8 hours.                                     |
| benzyl alcohol               | IPEL (-).   |
| •                            | TWA: 5 ppm  |
|                              | STEL: 10 ppm  |
| 3,6-diazaoctanethylenediamin | IPEL (-). Absorbed through skin.                          |
| •                            | TWA: 1 ppm  |

# Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace

| English (GB) | Europe | 7/19 |
|--------------|--------|------|
|              |        |      |

**AMERLOCK SEALER HRD** 

### **SECTION 8: Exposure controls/personal protection**

atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### **DNELs**

| Product/ingredient name                              | Туре  | Exposure              | Value                  | Population                 | Effects   |
|--|-------|-----------------------|------------------------|----------------------------|-----------|
| furfuryl alcohol                                     | DNEL  | Short term Oral       | 2.4 mg/kg bw/day       | General population         | Systemic  |
|  | DNEL  | Long term Oral        | 2.4 mg/kg bw/day       | General population         | Systemic  |
|  | DNEL  | Long term Dermal      | 2.4 mg/kg bw/day       | General population         | Systemic  |
|  | DNEL  | Long term Dermal      | 4 mg/kg bw/day         | Workers                    | Systemic  |
|  | DNEL  | Short term Inhalation | 8 mg/m³                | General population         | Local     |
|  | DNEL  | Long term Inhalation  | 8 mg/m³                | General population         | Local     |
|  | DNEL  | Short term Inhalation | 8 mg/m³                | Workers                    | Local     |
|  | DNEL  | Long term Inhalation  | 8 mg/m³                | Workers                    | Local     |
|  | DNEL  | Long term Inhalation  | 9.3 mg/m³              | General population         | Systemic  |
|  | DNEL  | Long term Inhalation  | 31 mg/m³               | Workers                    | Systemic  |
|  | DNEL  | Short term Inhalation | 128.5 mg/m³            | General population         | Systemic  |
|  | DNEL  | Short term Inhalation | 143 mg/m³              | Workers                    | Systemic  |
| Poly[oxy(methyl-                                     | DNEL  | Long term Inhalation  | 1.36 mg/m <sup>3</sup> | Workers                    | Systemic  |
| 1,2-ethanediyl)], α-                                 |       |                       | _                      |                            | -         |
| (2-aminomethylethyl)-ω-                              |       |                       |                        |                            |           |
| (2-aminomethylethoxy)-                               |       |                       |                        |                            |           |
| , , , , , , , , , , , , , , , , , , ,                | DNEL  | Long term Dermal      | 2.5 mg/kg bw/day       | Workers                    | Systemic  |
| benzyl alcohol                                       | DNEL  | Long term Oral        | 4 mg/kg bw/day         | General population         | Systemic  |
| •  | DNEL  | Long term Dermal      | 4 mg/kg bw/day         | General population         | Systemic  |
|  | DNEL  | Long term Inhalation  | 5.4 mg/m <sup>3</sup>  | General population         | Systemic  |
|  | DNEL  | Long term Dermal      | 8 mg/kg bw/day         | Workers                    | Systemic  |
|  | DNEL  | Short term Oral       | 20 mg/kg bw/day        | General population         | Systemic  |
|  | DNEL  | Short term Dermal     | 20 mg/kg bw/day        | General population         | Systemic  |
|  | DNEL  | Long term Inhalation  | 22 mg/m³               | Workers                    | Systemic  |
|  | DNEL  | Short term Inhalation | 27 mg/m³               | General population         | Systemic  |
|  | DNEL  | Short term Dermal     | 40 mg/kg bw/day        | Workers                    | Systemic  |
|  | DNEL  | Short term Inhalation | 110 mg/m <sup>3</sup>  | Workers                    | Systemic  |
| Formaldehyde, polymer with benzenamine, hydrogenated | DNEL  | Long term Inhalation  | 0.2 mg/m³              | Workers                    | Systemic  |
| l  | DNEL  | Long term Dermal      | 2 mg/kg bw/day         | Workers                    | Systemic  |
|  | DNEL  | Short term Inhalation | 2 mg/m <sup>3</sup>    | Workers                    | Systemic  |
|  | DNEL  | Short term Dermal     | 6 mg/kg bw/day         | Workers                    | Systemic  |
| 2,4,6-tris   | DNEL  | Long term Oral        | 0.075 mg/kg bw/day     | General population         | Systemic  |
| (dimethylaminomethyl)phenol                          | DIVLL | Long term oral        | 0.075 mg/kg bw/day     | Octional population        | Oysternie |
| (difficulty)aminometry/prienor                       | DNEL  | Short term Dermal     | 0.075 mg/kg bw/day     | General population         | Systemic  |
|  | DNEL  | Long term Dermal      | 0.075 mg/kg bw/day     | General population         | Systemic  |
|  | DNEL  | Short term Inhalation | 0.13 mg/m <sup>3</sup> | General population         | •         |
|  | DNEL  | Long term Inhalation  | •                      | · ·                        | •         |
|  | DNEL  |                       | 0.13 mg/m <sup>3</sup> | General population Workers |           |
|  |       | Long term Dermal      | 0.15 mg/kg bw/day      |                            | Systemic  |
|  | DNEL  | Long term Inhalation  | 0.53 mg/m <sup>3</sup> | Workers                    | Systemic  |
|  | DNEL  | Short term Dermal     | 0.6 mg/kg bw/day       | Workers                    | Systemic  |
| 4  | DNEL  | Short term Inhalation | 2.1 mg/m <sup>3</sup>  | Workers                    | Systemic  |
| 4-nonylphenol, branched                              | DNEL  | Long term Oral        | 0.08 mg/kg bw/day      | General population         | Systemic  |
|  | DNEL  | Short term Oral       | 0.4 mg/kg bw/day       | General population         | Systemic  |
|  | DNEL  | Long term Inhalation  | 0.4 mg/m <sup>3</sup>  | General population         | Systemic  |
|  | DNEL  | Long term Inhalation  | 0.5 mg/m <sup>3</sup>  | Workers                    | Systemic  |
|  | DNEL  | Short term Inhalation | 0.8 mg/m³              | General population         | Systemic  |
|  | DNEL  | Short term Inhalation | 1 mg/m³                | Workers                    | Systemic  |
|  | DNEL  | Long term Dermal      | 3.8 mg/kg bw/day       | General population         | Systemic  |
| I  | 1     | ı                     | ı                      |                            |           |

English (GB) Europe 8/19

AMERLOCK SEALER HRD

### **SECTION 8: Exposure controls/personal protection**

|                   | DNEL | Long term Dermal     | 7.5 mg/kg bw/day       | Workers            | Systemic |
|-------------------|------|----------------------|------------------------|--------------------|----------|
|                   | DNEL | Short term Dermal    | 7.6 mg/kg bw/day       | General population | Systemic |
|                   | DNEL | Short term Dermal    | 15 mg/kg bw/day        | Workers            | Systemic |
| salicylic acid    | DNEL | Long term Oral       | 1 mg/kg bw/day         | General population | Systemic |
|                   | DNEL | Long term Dermal     | 1 mg/kg bw/day         | General population | Systemic |
|                   | DNEL | Long term Dermal     | 2.3 mg/kg bw/day       | Workers            | Systemic |
|                   | DNEL | Short term Oral      | 4 mg/kg bw/day         | General population | Systemic |
|                   | DNEL | Long term Inhalation | 4 mg/m³                | General population | Systemic |
|                   | DNEL | Long term Inhalation | 5 mg/m³                | Workers            | Local    |
|                   | DNEL | Long term Inhalation | 5 mg/m³                | Workers            | Systemic |
| 4,4'-methylenebis | DNEL | Long term Oral       | 0.06 mg/kg bw/day      | General population | Systemic |
| (cyclohexylamine) |      |                      |                        |                    | •        |
|                   | DNEL | Long term Dermal     | 0.06 mg/kg bw/day      | General population | Systemic |
|                   | DNEL | Long term Inhalation | 0.21 mg/m <sup>3</sup> | General population | Systemic |
|                   | DNEL | Long term Dermal     | 0.053 mg/kg bw/day     | Workers            | Systemic |
|                   | DNEL | Long term Inhalation | 0.13 mg/m³             | Workers            | Systemic |
|                   |      |                      |                        |                    |          |

#### **PNECs**

| Product/ingredient name   | Type        | Compartment Detail  | Value   | Method Detail  |
|---|-------------|---|---|--|
| Poly[oxy(methyl-1,2-ethanediyl)], α-<br>(2-aminomethylethyl)-ω-<br>(2-aminomethylethoxy)- | -           | Fresh water   | 0.015 mg/l  | Assessment Factors   |
|   | -<br>-<br>- | Sewage Treatment Plant<br>Fresh water sediment<br>Marine water sediment | 0.014 mg/l<br>7.5 mg/l<br>0.132 mg/kg dwt<br>0.125 mg/kg dwt<br>0.018 mg/kg dwt | Assessment Factors Assessment Factors Equilibrium Partitioning Equilibrium Partitioning Equilibrium Partitioning |

#### 8.2 Exposure controls

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Skin protection

Hand protection

: Chemical splash goggles and face shield. Use eye protection according to EN 166.

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use,

English (GB) Europe 9/19

AMERLOCK SEALER HRD

### SECTION 8: Exposure controls/personal protection

as included in the user's risk assessment.

Gloves : nitrile neoprene

**Body protection**: Personal protective equipment for the body should be selected based on the task

being performed and the risks involved and should be approved by a specialist before

handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected

based on the task being performed and the risks involved and should be approved by

a specialist before handling this product.

**Respiratory protection**: Respirator selection must be based on known or anticipated exposure levels, the

hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and

particulate filter P3

**Environmental exposure** 

controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment

will be necessary to reduce emissions to acceptable levels.

### **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

**Appearance** 

Physical state : Liquid.

Colour : Not available.

Odour : Characteristic.

Odour threshold : Not available.

Melting point/freezing point : May start to solidify at the following temperature: 12°C (53.6°F) This is based on

data for the following ingredient: 3,6-diazaoctanethylenediamin. Weighted average:

-22.66°C (-8.8°F)

Initial boiling point and

boiling range

: >37.78°C

Flammability : Not available.

Upper/lower flammability or

explosive limits

: Greatest known range: Lower: 1.8% Upper: 16.3% (furfuryl alcohol)

Flash point : Closed cup: 100°C

Auto-ignition temperature :

| Ingredient name                    | °C  | °F  | Method  |
|------------------------------------|-----|-----|---------|
| 4,4'-methylenebis(cyclohexylamine) | 300 | 572 | EU A.15 |

**Decomposition temperature** 

: Stable under recommended storage and handling conditions (see Section 7).

pH
Not applicable. insoluble in water.
Viscosity
Kinematic (40°C): >21 mm²/s

Solubility(ies) :

| Media         | Result      |
|---------------|-------------|
| <mark></mark> | Not soluble |

| English (GB) Europe 10/19 |
|---------------------------|
|---------------------------|

Code : 00333521 Date of issue/Date of revision : 10 November 2022

AMERLOCK SEALER HRD

### **SECTION 9: Physical and chemical properties**

Water Solubility at room

temperature

: 21.5 g/l

Partition coefficient: n-octanol/ : Not applicable.

water

Vapour pressure

|   | Vapour Pressure at 20°C |      |        | Vapour pressure at 50°C |      |        |
|---|-------------------------|------|--------|-------------------------|------|--------|
| Ingredient name   | mm Hg                   | kPa  | Method | mm<br>Hg                | kPa  | Method |
| $\begin{array}{l} Poly[oxy(methyl-\\ 1,2-ethanediyl)], \ \alpha-\\ (2-aminomethylethyl)-\omega-\\ (2-aminomethylethoxy)- \end{array}$ | 0.675                   | 0.09 |        | 1.575                   | 0.21 |        |

: Highest known value: 0.04 (furfuryl alcohol) Weighted average: 0.03compared with **Evaporation rate** 

butyl acetate

**Relative density** 

Vapour density

: Highest known value: 15.4 (Air = 1) (1,2-Benzenedicarboxylic acid, di-

C9-11-branched alkyl esters, C10-rich). Weighted average: 6.61 (Air = 1)

: The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.

: Product does not present an oxidizing hazard.

**Oxidising properties** 

**Explosive properties** 

Particle characteristics

Median particle size

: Not applicable.

9.2 Other information

No additional information.

### **SECTION 10: Stability and reactivity**

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products.

Refer to protective measures listed in sections 7 and 8.

10.5 Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions:

oxidising agents, strong alkalis, strong acids.

10.6 Hazardous decomposition products : Depending on conditions, decomposition products may include the following materials:

carbon oxides nitrogen oxides Formaldehyde.

English (GB) 11/19 **Europe** 

**AMERLOCK SEALER HRD** 

### **SECTION 11: Toxicological information**

# 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 <u>Acute toxicity</u>

| Product/ingredient name  | Result                    | Species | Dose                    | Exposure |
|--|---------------------------|---------|-------------------------|----------|
| turfuryl alcohol   | LC50 Inhalation Vapour    | Rat     | 934 mg/m³               | 4 hours  |
| •  | LC50 Inhalation Vapour    | Rat     | 233 ppm                 | 4 hours  |
|  | LD50 Dermal               | Rabbit  | 400 mg/kg               | -        |
|  | LD50 Dermal               | Rat     | 3825 mg/kg              | -        |
|  | LD50 Oral                 | Rat     | 0.132 g/kg              | -        |
| Poly[oxy(methyl-1,2-ethanediyl)], $\alpha$ -(2-aminomethylethyl)- $\omega$ - | LD50 Dermal               | Rat     | 2980 mg/kg              | -        |
| (2-aminomethylethoxy)-   |                           |         |                         |          |
|  | LD50 Oral                 | Rat     | 2885 mg/kg              | -        |
| benzyl alcohol   | LC50 Inhalation Dusts and | Rat     | >4178 mg/m <sup>3</sup> | 4 hours  |
|  | mists                     |         |                         |          |
|  | LD50 Dermal               | Rabbit  | 2000 mg/kg              | -        |
|  | LD50 Oral                 | Rat     | 1.23 g/kg               | -        |
| 2,4,6-tris(dimethylaminomethyl)phenol  | LD50 Dermal               | Rabbit  | 1.28 g/kg               | -        |
|  | LD50 Dermal               | Rat     | 1280 mg/kg              | -        |
|  | LD50 Oral                 | Rat     | 1200 mg/kg              | -        |
| 4-nonylphenol, branched  | LD50 Dermal               | Rabbit  | 2.14 g/kg               | -        |
|  | LD50 Oral                 | Rat     | 1300 mg/kg              | -        |
| 3,6-diazaoctanethylenediamin   | LD50 Dermal               | Rabbit  | 1465 mg/kg              | -        |
| •  | LD50 Oral                 | Rat     | 1716 mg/kg              | -        |
| salicylic acid   | LD50 Oral                 | Rat     | 0.891 g/kg              | -        |
| 4,4'-methylenebis(cyclohexylamine)   | LD50 Dermal               | Rabbit  | 2.11 g/kg               | -        |
|  | LD50 Oral                 | Rat     | 0.625 g/kg              | -        |

**Conclusion/Summary** 

: There are no data available on the mixture itself.

### **Irritation/Corrosion**

| Product/ingredient name               | Result                  | Species | Score | Exposure | Observation |
|---------------------------------------|-------------------------|---------|-------|----------|-------------|
| 2,4,6-tris(dimethylaminomethyl)phenol | Skin - Visible necrosis | Rabbit  | -     | 4 hours  | 7 days      |
| 4-nonylphenol, branched               | Skin - Erythema/Eschar  | Rabbit  | 4     | -        | -           |

### **Conclusion/Summary**

Skin : There are no data available on the mixture itself.
 Eyes : There are no data available on the mixture itself.
 Respiratory : There are no data available on the mixture itself.

#### **Sensitisation**

| Product/ingredient name                              | Route of exposure | Species    | Result      |
|--|-------------------|------------|-------------|
| Formaldehyde, polymer with benzenamine, hydrogenated | skin              | Guinea pig | Sensitising |
| 1, 0   | skin              | Guinea pig | Sensitising |

### **Conclusion/Summary**

Skin : There are no data available on the mixture itself.Respiratory : There are no data available on the mixture itself.

**Mutagenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Carcinogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

English (GB) Europe 12/19

Code : 00333521 Date of issue/Date of revision : 10 November 2022

AMERLOCK SEALER HRD

### **SECTION 11: Toxicological information**

**Reproductive toxicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Teratogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

| Product/ingredient name                        | Category   | Route of exposure | Target organs                |
|--|------------|-------------------|------------------------------|
| furfuryl alcohol                               | Category 3 |                   | Respiratory tract irritation |
| Formaldehyde, polymer with 1,3-dimethylbenzene | Category 3 |                   | Respiratory tract irritation |

### Specific target organ toxicity (repeated exposure)

| Product/ingredient name                              | Category   | Route of exposure | Target organs |
|--|------------|-------------------|---------------|
| furfuryl alcohol                                     | Category 2 | -                 | -             |
| Formaldehyde, polymer with benzenamine, hydrogenated | Category 2 | oral              | kidneys       |
| 4,4'-methylenebis(cyclohexylamine)                   | Category 2 | oral              | liver         |

#### **Aspiration hazard**

Not available.

**Information on likely** : Not available.

routes of exposure

Potential acute health effects

Inhalation : Harmful if inhaled. May cause respiratory irritation.

Ingestion : Harmful if swallowed. Corrosive to the digestive tract. Causes burns.

**Skin contact**: Causes severe burns. Defatting to the skin. May cause an allergic skin reaction.

**Eye contact** : Causes serious eye damage.

Symptoms related to the physical, chemical and toxicological characteristics

**Inhalation** : Adverse symptoms may include the following:

respiratory tract irritation

coughing

**Ingestion** : Adverse symptoms may include the following:

stomach pains

**Skin contact**: Adverse symptoms may include the following:

pain or irritation

redness dryness cracking

blistering may occur

**Eye contact** : Adverse symptoms may include the following:

pain watering redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Short term exposure** 

Potential immediate : Not

effects

: Not available.

Potential delayed effects: Not available.

Long term exposure

English (GB) Europe 13/19

Code : 00333521 Date of issue/Date of revision : 10 November 2022

AMERLOCK SEALER HRD

### **SECTION 11: Toxicological information**

Potential immediate

effects

: Not available.

Potential delayed effects: Not available.

#### Potential chronic health effects

Not available.

Conclusion/Summary

: Not available.

General

: May cause damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to

very low levels.

Carcinogenicity

Other information

: Suspected of causing cancer. Risk of cancer depends on duration and level of

exposure.

Mutagenicity Reproductive toxicity

: No known significant effects or critical hazards. : No known significant effects or critical hazards.

: Not available.

Causes digestive tract burns. Prolonged or repeated contact may dry skin and cause irritation. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Contains a substance that may emit formaldehyde if stored beyond its shelf life and/or during cure at curing temperatures greater than 60C/140F. Avoid contact with skin and clothing.

### 11.2 Information on other hazards

#### 11.2.1 Endocrine disrupting properties

Not available.

#### 11.2.2 Other information

Not available.

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

| Product/ingredient name   | Result                  | Species                        | Exposure |
|---|-------------------------|--------------------------------|----------|
| Foly[oxy(methyl-1,2-ethanediyl)], α-<br>(2-aminomethylethyl)-ω-(2-aminomethylethoxy)- | EC50 15 mg/l            | Algae                          | 72 hours |
| Formaldehyde, polymer with benzenamine, hydrogenated                                  | Acute EC50 63 mg/l      | Fish                           | 96 hours |
| 2,4,6-tris(dimethylaminomethyl)phenol   | Acute LC50 175 mg/l     | Fish                           | 96 hours |
| 4-nonylphenol, branched   | Acute EC50 0.044 mg/l   | Crustaceans - Moina            | 48 hours |
|   |                         | macrocopa                      |          |
|   | Acute LC50 0.221 mg/l   | Fish                           | 96 hours |
| salicylic acid  | Acute EC50 1147.57 mg/l | Daphnia - Daphnia              | 48 hours |
| •   | Fresh water             | longispina - Neonate           |          |
|   | Chronic NOEC 5.6 mg/l   | Daphnia - Daphnia              | 21 days  |
|   | Fresh water             | magna - Neonate                |          |
| Nonylphenols  | Acute LC50 0.017 mg/l   | Fish - Pleuronectes americanus | 96 hours |

**Conclusion/Summary** : There are no data available on the mixture itself.

### 12.2 Persistence and degradability

**Conclusion/Summary** : There are no data available on the mixture itself.

| English (GB)   | Europe | 14/19 |
|----------------|--------|-------|
| Liigiisii (GD) | Luiope | 14/13 |

Code : 00333521 Date of issue/Date of revision : 10 November 2022

AMERLOCK SEALER HRD

### **SECTION 12: Ecological information**

| Product/ingredient name   | Aquatic half-life | Photolysis | Biodegradability |
|---|-------------------|------------|------------------|
| Poly[oxy(methyl-1,2-ethanediyl)], α-<br>(2-aminomethylethyl)-ω-(2-aminomethylethoxy)- | -                 | -          | Not readily      |
| benzyl alcohol  | -                 | -          | Readily          |

#### 12.3 Bioaccumulative potential

| Product/ingredient name                 | LogPow        | BCF        | Potential |
|---|---------------|------------|-----------|
| furfuryl alcohol                        | 0.3           | -          | low       |
| benzyl alcohol                          | 0.87          | -          | low       |
| Formaldehyde, polymer with benzenamine, | -             | 209 to 219 | low       |
| hydrogenated                            |               |            |           |
| 2,4,6-tris(dimethylaminomethyl)phenol   | 0.219         | -          | low       |
| 4-nonylphenol, branched                 | 5.4           | 251.19     | low       |
| 3,6-diazaoctanethylenediamin            | -1.66 to -1.4 | -          | low       |
| salicylic acid                          | 2.21 to 2.26  | -          | low       |
| 4,4'-methylenebis(cyclohexylamine)      | 2.03          | -          | low       |

#### 12.4 Mobility in soil

Soil/water partition

: Not available.

coefficient (Koc)

**Mobility** 

: Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

#### 12.6 Endocrine disrupting properties

May cause endocrine disruption.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

### **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 13.1 Waste treatment methods

#### **Product**

**Methods of disposal** 

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** 

: Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.

**European waste catalogue (EWC)** 

| English (GB)   | Europe | 15/19 |
|----------------|--------|-------|
| Liigiisii (GD) | Luiope | 13/13 |

Code : 00333521 Date of issue/Date of revision : 10 November 2022

AMERLOCK SEALER HRD

### **SECTION 13: Disposal considerations**

| Waste code | Waste designation              |  |
|------------|--------------------------------|--|
| 08 01 99   | wastes not otherwise specified |  |

#### **Packaging**

**Methods of disposal** 

The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

| Type of packaging |          | European waste catalogue (EWC) |
|-------------------|----------|--------------------------------|
| Container         | 15 01 06 | mixed packaging                |

**Special precautions** 

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

### 14. Transport information

|                                  | ADR/RID         | ADN             | IMDG   | IATA   |
|----------------------------------|-----------------|-----------------|--|--|
| 14.1 UN number or ID number      | UN3066          | UN3066          | UN3066   | UN3066   |
| 14.2 UN proper shipping name     | PAINT           | PAINT           | PAINT  | PAINT  |
| 14.3 Transport hazard class(es)  | 8               | 8               | 8  | 8  |
| 14.4 Packing group               | III             | III             | III  | III  |
| 14.5<br>Environmental<br>hazards | Yes.            | Yes.            | Yes.   | Yes. The environmentally hazardous substance mark is not required. |
| Marine pollutant substances      | Not applicable. | Not applicable. | (4-nonylphenol,<br>branched, 4,4'-<br>methylenebis<br>(cyclohexylamine)) | Not applicable.  |

### **Additional information**

ADR/RID : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or

**ADN** : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or

≤5 kg.

: The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. **IMDG** 

: The environmentally hazardous substance mark may appear if required by other transportation **IATA** 

regulations.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

English (GB) 16/19 **Europe** 

Code : 00333521 Date of issue/Date of revision : 10 November 2022

**AMERLOCK SEALER HRD** 

### 14. Transport information

14.7 Maritime transport in bulk according to IMO

: Not applicable.

instruments

### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

**Annex XIV - List of substances subject to authorisation** 

**Annex XIV** 

None of the components are listed.

**Substances of very high concern** 

| Intrinsic property                              | Ingredient name   | Status    | Reference number | Date of revision |
|---|---|-----------|------------------|------------------|
| Substance of equivalent concern for environment | 4-Nonylphenol, branched and linear [substances with a linear and/or branched alkyl chain with a carbon number of 9 covalently bound in position 4 to phenol, covering also UVCB- and well-defined substances which include any of the individual isomers or a combination thereof | Candidate | ED/169/2012      | 10/29/2013       |
| Endocrine disrupting properties for environment | 4-nonylphenol, branched and linear substances with a linear and/or branched alkyl chain with a carbon number of 9 covalently bound in position 4 to phenol, covering also UVCB- and well-defined substances which include any of the individual isomers or a combination thereof  | Candidate | ED/169/2012      | 12/19/2012       |

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

: Not applicable.

Ozone depleting substances (1005/2009/EU)

Not listed.

### **Seveso Directive**

This product is controlled under the Seveso Directive.

### **Danger criteria**

Category
E2

15.2 Chemical safety assessment

: No Chemical Safety Assessment has been carried out.

English (GB) Europe 17/19

**AMERLOCK SEALER HRD** 

### **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

### **Abbreviations and acronyms**

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

PBT = Persistent, Bioaccumulative and Toxic

vPvB = Very Persistent and Very Bioaccumulative

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

IMDG = International Maritime Dangerous Goods

IATA = International Air Transport Association

### **Full text of abbreviated H statements**

| H302   | Harmful if swallowed.  |
|--------|--|
| H312   | Harmful in contact with skin.  |
| H314   | Causes severe skin burns and eye damage.                                 |
| H315   | Causes skin irritation.  |
| H317   | May cause an allergic skin reaction.                                     |
| H318   | Causes serious eye damage.   |
| H319   | Causes serious eye irritation.   |
| H331   | Toxic if inhaled.  |
| H332   | Harmful if inhaled.  |
| H335   | May cause respiratory irritation.  |
| H351   | Suspected of causing cancer.   |
| H361   | Suspected of damaging fertility or the unborn child.                     |
| H361d  | Suspected of damaging the unborn child.                                  |
| H361fd | Suspected of damaging fertility. Suspected of damaging the unborn child. |
| H373   | May cause damage to organs through prolonged or repeated exposure.       |
| H400   | Very toxic to aquatic life.  |
| H410   | Very toxic to aquatic life with long lasting effects.                    |
| H411   | Toxic to aquatic life with long lasting effects.                         |
| H412   | Harmful to aquatic life with long lasting effects.                       |
| EUH071 | Corrosive to the respiratory tract.                                      |

### Full text of classifications [CLP/GHS]

| Full text of classifications [CLP/GHS] |  |  |
|--|--|--|
| Acute Tox. 3                           | ACUTE TOXICITY - Category 3                          |  |
| Acute Tox. 4                           | ACUTE TOXICITY - Category 4                          |  |
| Aquatic Acute 1                        | SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1       |  |
| Aquatic Chronic 1                      | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1      |  |
| Aquatic Chronic 2                      | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2      |  |
| Aquatic Chronic 3                      | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3      |  |
| Carc. 2                                | CARCINOGENICITY - Category 2                         |  |
| Eye Dam. 1                             | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1       |  |
| Eye Irrit. 2                           | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2       |  |
| Repr. 2                                | REPRODUCTIVE TOXICITY - Category 2                   |  |
| Skin Corr. 1B                          | SKIN CORROSION/IRRITATION - Category 1B              |  |
| Skin Corr. 1C                          | SKIN CORROSION/IRRITATION - Category 1C              |  |
| Skin Irrit. 2                          | SKIN CORROSION/IRRITATION - Category 2               |  |
| Skin Sens. 1                           | SKIN SENSITISATION - Category 1                      |  |
| STOT RE 2                              | SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - |  |
|  | Category 2   |  |
|  |  |  |

English (GB) Europe 18/19

Code : 00333521 Date of issue/Date of revision : 10 November 2022

AMERLOCK SEALER HRD

SECTION 16: Other information

STOT SE 3 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

### **History**

Date of issue/ Date of

: 10 November 2022

revision

Date of previous issue : 9 November 2021

Prepared by : EHS Version : 3

### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

English (GB) Europe 19/19