# **SAFETY DATA SHEET**



Date of issue 11/20/2022 (month/day/year)

Version 4.06

### Section 1. Chemical product and company identification

A. Product name : SIGMAZINC 158 HS PIGMENT GREY (K)

Product code : 00322630

B. Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Professional applications, Used by spraying.

Use of the substance/

mixture

: Coating.

**Uses advised against**: Product is not intended, labelled or packaged for consumer use.

C. Supplier's or Importer's

information

**Email Address** 

: PPG SSC (680-090)

19, Yeocheon-ro 217beon-gil, Nam-gu,

Ulsan, Korea

Tel: +82-52-210-8222 Korea.MSDS@PPG.COM

**Emergency telephone** 

number:

: +82-52-210-8222

### Section 2. Hazards identification

A. Hazard classification : AQUATIC HAZARD (ACUTE) - Category 1

AQUATIC HAZARD (LONG-TERM) - Category 1

This product is classified in accordance with the Industrial Safety and Health Act and the Chemical Control Act.

B. GHS label elements, including precautionary statements

Symbol :



Signal word : Warning

**Hazard statements** : H410 - Very toxic to aquatic life with long lasting effects.

**Precautionary statements** 

**Prevention**: P273 - Avoid release to the environment.

Response : P391 - Collect spillage.

Storage : Not applicable.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

Korea (GHS) Page: 1/11

Product code 00322630 Date of issue 11/20/2022 (month/day/year) Version 4.06 **Product name SIGMAZINC 158 HS PIGMENT GREY (K)** 

#### Section 2. Hazards identification

not result in classification

C. Other hazards which do : May form explosible dust-air mixture if dispersed. Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes. skin. nose and throat.

### Section 3. Composition/information on ingredients

#### **CAS** number/other identifiers

**CAS** number : Not applicable.

Chemical name	Common name	Identifiers	%
Zinc powder - zinc dust (stabilized) zinc oxide		CAS: 7440-66-6 CAS: 1314-13-2	90 - 100 1 - <5

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

A. Eye contact

: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

**B.** Skin contact

: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

C. Inhalation

Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

**D.** Ingestion

: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

E. Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

**Specific treatments** 

: No specific treatment.

**Protection of first-aiders** 

: No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

### Section 5. Fire-fighting measures

A. Extinguishing media

Suitable extinguishing

media

: Use dry chemical powder.

**Unsuitable** extinguishing media : Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.

Korea (GHS) Page: 2/11

**Product name SIGMAZINC 158 HS PIGMENT GREY (K)** 

### Section 5. Fire-fighting measures

- from the chemical
- B. Specific hazards arising: May form explosible dust-air mixture if dispersed. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
  - **Hazardous thermal** decomposition products
- : Decomposition products may include the following materials: metal oxide/oxides
- C. Special equipment for fire-fighting
- : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
- Fire-fighting procedures : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

### Section 6. Accidental release measures

- A. Personal precautions, protective equipment and emergency procedures
- : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Put on appropriate personal protective equipment.
- **B. Environmental** precautions
- : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
- C. Methods and materials for containment and cleaning up

**Small spill** 

: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

Large spill

: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

- A. Precautions for safe handling
- Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing dust. Avoid release to the environment. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Korea (GHS) Page: 3/11

**Product name SIGMAZINC 158 HS PIGMENT GREY (K)** 

### Section 7. Handling and storage

- B. Conditions for safe storage, including any incompatibilities
- : Storage temperature: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

#### A. Occupational exposure limits

Ingredient name	Exposure limits
zínc oxide	Ministry of Employment and Labor (Republic of Korea, 1/2020).  TWA: 2 mg/m³ 8 hours. Form: Respirable dust  STEL: 10 mg/m³ 15 minutes.  TWA: 5 mg/m³ 8 hours.

Recommended monitoring procedures

- Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
- B. Appropriate engineering controls
- Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Environmental exposure controls** 

- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
- C. Personal protective equipment

Respiratory protection

: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Eye protection Hand protection

- : Safety glasses with side shields.
- Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Korea (GHS) Page: 4/11

**Product name SIGMAZINC 158 HS PIGMENT GREY (K)** 

### Section 8. Exposure controls/personal protection

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Hygiene measures** 

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

# Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

A. Appearance

**Physical state** : Solid.

Powder.

Color : Various B. Odor Odorless. Not available. C. Odor threshold D. pH Not applicable.

E. Melting/freezing point F. Boiling point/boiling

: Not available. : Not available.

range

G. Flash point Closed cup: Not applicable.

H. Evaporation rate : Not available. Flammability (solid, gas) : Not available. J. Lower and upper : Not available.

explosive (flammable)

limits

Media

L. Solubility(ies)

K. Vapor pressure Not available.

cold water Not soluble

Result

Solubility in water : Not available. Vapor density Not applicable.

**Relative density** 7.14

Partition coefficient: n-

octanol/water

: Not applicable.

**Auto-ignition** : Not applicable.

temperature

: Not available.

**Decomposition** temperature

Kinematic (40°C (104°F)): Not applicable. **Viscosity** 

Flow time (ISO 2431) Not available. **Molecular weight** Not applicable.

Korea (GHS) Page: 5/11

**Product name SIGMAZINC 158 HS PIGMENT GREY (K)** 

### Section 10. Stability and reactivity

A. Chemical stability

: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

B. Conditions to avoid

: When exposed to high temperatures may produce hazardous decomposition

products.

C. Incompatible materials

: Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents, strong alkalis, strong acids.

D. Hazardous decomposition products

: Evolves hydrogen on contact with water. Depending on conditions, decomposition

products may include the following materials: metal oxide/oxides

# **Section 11. Toxicological information**

A. Information on the likely routes of exposure

: Not available.

#### Potential acute health effects

Inhalation : Exposure to airborne concentrations above statutory or recommended exposure limits

may cause irritation of the nose, throat and lungs.

Ingestion : No known significant effects or critical hazards.Skin contact : No known significant effects or critical hazards.

**Eye contact**: Exposure to airborne concentrations above statutory or recommended exposure limits

may cause irritation of the eyes.

#### Over-exposure signs/symptoms

**Inhalation** : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Ingestion : No specific data.

Skin contact : No specific data.

**Eye contact**: Adverse symptoms may include the following:

irritation redness

#### B. Health hazards

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
₹inc powder - zinc dust (stabilized)	LC50 Inhalation Dusts and mists	Rat	>5.4 mg/l	4 hours
	LD50 Oral	Rat	>2000 mg/kg	-
zinc oxide	LC50 Inhalation Dusts and mists	Rat	>5700 mg/m³	4 hours
	LD50 Dermal LD50 Oral	Rat Rat	>2000 mg/kg >5000 mg/kg	-

**Conclusion/Summary**: There are no data available on the mixture itself.

#### **Irritation/Corrosion**

**Conclusion/Summary** 

Korea (GHS) Page: 6/11

**Product name SIGMAZINC 158 HS PIGMENT GREY (K)** 

### **Section 11. Toxicological information**

Skin : There are no data available on the mixture itself.
Eyes : There are no data available on the mixture itself.
Respiratory : There are no data available on the mixture itself.

**Sensitization** 

**Conclusion/Summary** 

Skin : There are no data available on the mixture itself.Respiratory : There are no data available on the mixture itself.

**Mutagenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Carcinogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Reproductive toxicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Teratogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Not available.

#### Potential chronic health effects

General : Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

#### **Additional information**

Sanding and grinding dusts may be harmful if inhaled.

Chemical name	Identifiers	GHS Classification
Zinc powder - zinc dust (stabilized)	CAS: 7440-66-6	SUBSTANCES AND MIXTURES, WHICH IN CONTACT WITH WATER, EMIT FLAMMABLE GASES - Category 3
zinc oxide	CAS: 1314-13-2	AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1 AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1

Korea (GHS) Page: 7/11

Product code 00322630 Date of issue 11/20/2022 (month/day/year) Version 4.06
Product name SIGMAZINC 158 HS PIGMENT GREY (K)

## **Section 12. Ecological information**

#### A. **Ecotoxicity**

Product/ingredient name	Result	Species	Exposure
Zinc powder - zinc dust (stabilized)	· ·	Algae - Pseudokirchneriella subcapitata	72 hours
	Chronic NOEC 0.0727 mg/l Fresh water	Daphnia - Daphnia Magna	21 days
zinc oxide	Acute EC50 0.17 mg/l	Algae	72 hours
	_	Daphnia - Daphnia magna - Neonate	48 hours
	Chronic NOEC 0.017 mg/l Fresh water	Algae	72 hours

#### B. Persistence and degradability

Not available.

#### C. Bioaccumulative potential

Not available.

#### D. Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

#### E. Other adverse effects

: No known significant effects or critical hazards.

# Section 13. Disposal considerations

#### A. Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

#### **B.** Disposal precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# **Section 14. Transport information**

Korea (GHS) Page: 8/11

**Product name SIGMAZINC 158 HS PIGMENT GREY (K)** 

### **Section 14. Transport information**

	UN	IMDG	IATA
A. UN number	UN3077	UN3077	UN3077
B. UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
	(Zinc powder - zinc dust (stabilized), zinc oxide)	(Zinc powder - zinc dust (stabilized), zinc oxide)	(Zinc powder - zinc dust (stabilized), zinc oxide)
C. Transport hazard class(es)	9	9	9
D. Packing group	III	III	III
Environmental hazards	Yes.	Yes.	Yes.
E. Marine pollutant substances	Not applicable.	(Zinc powder - zinc dust (stabilized), zinc oxide)	Not applicable.

#### **Additional information**

UN : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg. **IMDG** 

provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

The segregation group has been manually assigned based upon product analysis.

**IATA** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg,

provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

#### F. Special precaution which a user to be aware of or needs to comply with in connection with transport or tranportation

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according: Not applicable. to IMO instruments

# **Section 15. Regulatory information**

#### A. Regulation according to ISHA

**ISHA** article 117 (Harmful substances prohibited from manufacture)

: None of the components are listed.

**ISHA** article 118 : None of the components are listed.

(Harmful substances requiring permission) **Article 2 of Youth Protection** 

: It is not allowed to sell to persons under the age of 19.

**Act on Substances Hazardous** 

to Youth

#### **Exposure Limits of Chemical Substances and Physical Factors**

Korea (GHS) Page: 9/11

**Product name SIGMAZINC 158 HS PIGMENT GREY (K)** 

### Section 15. Regulatory information

The following components have an OEL:

zinc oxide

**ISHA Enforcement Regs**: None of the components are listed.

**Annex 19 (Exposure** standards established for harmful factors)

**ISHA Enforcement Regs Annex 21 (Harmful** 

: The following components are listed: zinc oxide

factors subject to Work **Environment Measurement)** 

**Annex 22 (Harmful Factors Subject to Special Health Check-**

ISHA Enforcement Regs : The following components are listed: Zinc oxide

up)

**Standard of Industrial Safety and Health Annex 12 (Hazardous** substances subject to control)

: The following components are listed: zinc and its compounds, zinc and its compounds

B. Regulation according to Chemicals Control Act

Article 11 (TRI) : The following components are listed: Zinc and its compounds, Zinc and its

compounds

: Not applicable

Article 18 Prohibited (K-

**Reach Article 27)** 

: None of the components are listed.

**Article 19 Subject to** authorization (K-Reach

Article 25)

: None of the components are listed.

Article 20 Restricted (K-

Reach Article 27)

**Article 20 Toxic** 

: None of the components are listed.

**Chemicals (K-Reach** 

Article 20)

: All components are listed or exempted.

**Korea inventory Article 39 (Accident Precaution Chemicals**)

: None of the components are listed.

C. Dangerous Materials **Safety Management Act** 

: Class: Class 2 - Combustible Solid

Item: 5. Metal powder Threshold: 500 kg Danger category: III

Signal word: Do not allow contact with water.

D. Wastes regulation Dispose of contents and container in accordance with all local, regional, national

and international regulations.

E. Regulation according to other foreign laws

Korea (GHS) Page: 10/11

**Product name SIGMAZINC 158 HS PIGMENT GREY (K)** 

### **Section 15. Regulatory information**

Safety, health and environmental regulations specific for the product : No known specific national and/or regional regulations applicable to this product (including its ingredients).

# **Section 16. Other information**

A. References : Korean Ministry of Environment; Chemical Control Act

Korean Ministry of Labor; Industrial Safety and Health Act

**NIER Notice** 

Registry of Toxic Effects of Chemical Substances (RTECS)

U.S. Environmental Protection Agency, AQUIRE (Aquatic toxicity Information

Retrieval) ECOTOX Database System.

B. Date of issue/Date of

revision

: 11/20/2022

C. Version : 4.06
Prepared by : EHS

D. Other

Indicates information that has changed from previously issued version.

#### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

Korea (GHS) Page: 11/11