# SAFETY DATA SHEET

Date of issue/Date of revision

: 28 November 2022

Version : 15.1



**Europe** 

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	1.1	Prod	uct	iden	tifier
------------------------	-----	------	-----	------	--------

Product name	: NOVAGUARD 840/890 HARDENER CREAM				
Product code	: 00237774				
Other means of identification					
Not available.					

1.2 Relevant identified uses of the substance or mixture and uses advised against				
Product use	: Professional applications, Used by spraying.			
Use of the substance/ mixture	: Coating.			
Uses advised against	: Product is not intended, labelled or packaged for consumer use.			

### 1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL Tweemontstraat 104 B-2100 Deurne Belgium Telephone +32-33606311 Fax +32-33606435

e-mail address of person responsible for this SDS

: Product.Stewardship.EMEA@ppg.com

## 1.4 Emergency telephone number

#### **Supplier**

+31 20 4075210

# **SECTION 2: Hazards identification**

2.1 Classification of the su	bstance or mixture		
Product definition	: Mixture		
Classification according t	o Regulation (EC) No. 1	<u>272/2008 [CLP/GHS]</u>	
Acute Tox. 4, H302			
Acute Tox. 3, H311			
Acute Tox. 3, H331			
Skin Corr. 1A, H314			
Eye Dam. 1, H318			
Skin Sens. 1, H317			
Aquatic Chronic 2, H411			
The product is classified as	hazardous according to F	Regulation (EC) 1272/2008	as amended.
See Section 16 for the full to	ext of the H statements de	eclared above.	

English (US)

Europe

1/15

Code	: 00237774	Date of issue/Date of revision	: 28 November 2022		
NOVAGU	NOVAGUARD 840/890 HARDENER CREAM				

## **SECTION 2: Hazards identification**

See Section 11 for more detailed information on health effects and symptoms.

## 2.2 Label elements

Hazard	pictograms



Signal word	: Danger
Hazard statements	<ul> <li>Harmful if swallowed.</li> <li>Toxic in contact with skin or if inhaled.</li> <li>Causes severe skin burns and eye damage.</li> <li>May cause an allergic skin reaction.</li> <li>Toxic to aquatic life with long lasting effects.</li> </ul>
Precautionary statements	
Prevention	: Wear protective gloves, protective clothing and eye or face protection. Avoid release to the environment.
Response	: Collect spillage. IF INHALED: Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor.
Storage	: Not applicable.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
	P280, P273, P391, P304 + P310, P301 + P310, P501
Hazardous ingredients	: 2,2'-dimethyl-4,4'-methylenebis(cyclohexylamine) N-(3-(trimethoxysilyl)propyl)ethylenediamine
Supplemental label elements	: Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Special packaging requirem	ents
Containers to be fitted with child-resistant fastenings	: Not applicable.
Tactile warning of danger	: Not applicable.
2.3 Other hazards	
Product meets the criteria for PBT or vPvB	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: None known.

Code : 00237774

**NOVAGUARD 840/890 HARDENER CREAM** 

Date of issue/Date of revision

: 28 November 2022

# **SECTION 3: Composition/information on ingredients**

3.2 Mixtures	: Mixture	•			
Product/ingredient name	Identifiers	% by weight	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
2,2'-dimethyl-4,4'- methylenebis (cyclohexylamine)	EC: 229-962-1 CAS: 6864-37-5 Index: 612-110-00-1	≥75 - ≤90	Acute Tox. 4, H302 Acute Tox. 3, H311 Acute Tox. 3, H331 Skin Corr. 1A, H314 Eye Dam. 1, H318 Aquatic Chronic 2, H411	ATE [Oral] = 500 mg/ kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (dusts and mists)] = 0.5 mg/l	[1]
benzyl alcohol	REACH #: 01-2119492630-38 EC: 202-859-9 CAS: 100-51-6 Index: 603-057-00-5	≥10 - ≤15	Acute Tox. 4, H302 Acute Tox. 4, H332 Eye Irrit. 2, H319	ATE [Oral] = 1230 mg/ kg ATE [Inhalation (dusts and mists)] = 1.5 mg/l	[1] [2]
N-(3-(trimethoxysilyl)propyl) ethylenediamine	EC: 217-164-6 CAS: 1760-24-3	≥1.0 - ≤5.0	Acute Tox. 4, H332 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412	ATE [Inhalation (vapours)] = 11 mg/l	[1]
2,4,6-tris (dimethylaminomethyl) phenol	REACH #: 01-2119560597-27 EC: 202-013-9 CAS: 90-72-2 Index: 603-069-00-0	≥1.0 - ≤3.4	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1C, H314 Eye Dam. 1, H318 See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 1200 mg/ kg ATE [Dermal] = 1280 mg/kg	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

# SECTION 4: First aid measures

4.1 Description of firs	t aid measures
Eye contact	: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Inhalation	<ul> <li>Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.</li> </ul>
Skin contact	<ul> <li>Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.</li> </ul>
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

E	nglish (US)	Europe	3/15
	• • •	-	

2020/878	
Code : 00237774 NOVAGUARD 840/890 HARE	Date of issue/Date of revision         : 28 November 2022           DENER CREAM
SECTION 4: First aid	1 measures
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
	ns and effects, both acute and delayed
Potential acute health effect	<u>ets</u>
Eye contact	: Causes serious eye damage.
Inhalation	: Toxic if inhaled.
Skin contact	: Causes severe burns. Toxic in contact with skin. May cause an allergic skin reaction.
Ingestion	: Harmful if swallowed.
Over-exposure signs/symp	<u>itoms</u>
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion	: Adverse symptoms may include the following: stomach pains
4.3 Indication of any immed	iate medical attention and special treatment needed
Notes to physician	<ul> <li>In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.</li> </ul>
Specific treatments	: No specific treatment.
<b>SECTION 5: Firefigh</b>	ting measures
5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising	from the substance or mixture
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides Formaldehyde.

# 5.3 Advice for firefighters

English (US) Europe	4/15
---------------------	------

Code <th::00237774< th="">       Date of issue/Date of revision       : 28 November 2022         NOVAGUARD 840/890 HARDENER CREAM      </th::00237774<>				
SECTION 5: Firefight	ing measures			
Special precautions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident there is a fire. No action shall be taken involving any personal risk or without straining.			
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained apparatus (SCBA) with a full face-piece operated in positive pressure mode.			

for fire-fighters (including helmets, protective boots and gloves) conforming to European

standard EN 469 will provide a basic level of protection for chemical incidents.

# **SECTION 6: Accidental release measures**

6.1 Personal precautions, pro	tective equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
6.3 Methods and materials fo	r containment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.
6.4 Reference to other sections	<ul> <li>See Section 1 for emergency contact information.</li> <li>See Section 8 for information on appropriate personal protective equipment.</li> <li>See Section 13 for additional waste treatment information.</li> </ul>

## **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

## 7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Code NOVAGUA	: 00237774 RD 840/890 HARDENER CREAM	Date of issue/Date of revision	: 28 November 2022
SECTIO	N 7: Handling and storage		

## SECTION 7: Handling and storage

Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
7.2 Conditions for safe storage, including any incompatibilities	: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

#### 7.3 Specific end use(s)

See Section 1.2 for Identified uses.

## **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 8.1 Control parameters

## Occupational exposure limits

Product/ingredient name	Exposure limit values	
benzyl alcohol	IPEL (-). TWA: 5 ppm STEL: 10 ppm	
procedures Standard EN	: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement	

by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**DNELs** 

Product/ingredient name	Туре	Exposure	Value	Population	Effects
2,2'-dimethyl-4,4'- methylenebis (cyclohexylamine)	DNEL	Long term Oral	0.008 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.05 mg/kg bw/day	Workers	Systemic
	DNEL DNEL	Long term Inhalation Long term Inhalation	0.6 mg/m³ 1 mg/m³	Workers Workers	Systemic Local
benzyl alcohol	DNEL DNEL DNEL DNEL DNEL DNEL	Long term Oral Long term Dermal Long term Inhalation Long term Dermal Short term Oral Short term Dermal	4 mg/kg bw/day 4 mg/kg bw/day 5.4 mg/m <sup>3</sup> 8 mg/kg bw/day 20 mg/kg bw/day 20 mg/kg bw/day	General population General population General population Workers General population General population	Systemic Systemic Systemic Systemic Systemic Systemic
English (US)	<u> </u>	I	Europe		6/15

Code : 00237774

Date of issue/Date of revision

: 28 November 2022

NOVAGUARD 840/890 HARDENER CREAM

## **SECTION 8: Exposure controls/personal protection**

	DNEL	Long term Inhalation	22 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Inhalation	27 mg/m³	General population	Systemic
	DNEL	Short term Dermal	40 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	110 mg/m³	Workers	Systemic
N-(3-(trimethoxysilyl)propyl)	DNEL	Long term Inhalation	0.1 mg/m³	General population	Local
ethylenediamine		_	_		
	DNEL	Long term Inhalation	0.6 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	4 mg/m³	General population	Local
	DNEL	Short term Inhalation	5.36 mg/m³	Workers	Local
	DNEL	Short term Inhalation	50 mg/m³	General population	Systemic
	DNEL	Short term Inhalation	260 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Oral	8 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	50 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	260 mg/m³	Workers	Systemic
2,4,6-tris	DNEL	Long term Oral	0.075 mg/kg bw/day	General population	Systemic
(dimethylaminomethyl)phenol		_			-
	DNEL	Short term Dermal	0.075 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.075 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	0.13 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	0.13 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Dermal	0.15 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	0.53 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Dermal	0.6 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	2.1 mg/m <sup>3</sup>	Workers	Systemic
· · · · · · · · · · · · · · · · · · ·	•				

**PNECs** 

PNECs - Not available.

## 8.2 Exposure controls

#### : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation Appropriate engineering or other engineering controls to keep worker exposure to airborne contaminants below controls any recommended or statutory limits. Individual protection measures **Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. **Eye/face protection** : Chemical splash goggles and face shield. Use eye protection according to EN 166. Skin protection : Chemical-resistant, impervious gloves complying with an approved standard should be Hand protection worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use,

English (US)	Furope	7/15
	Europe	1/10

as included in the user's risk assessment.

SECTION 9: Exposure controls/percend protection		
NOVAGUARD 840/890 HARDENER CREAM		
Code : 00237774	Date of issue/Date of revision	: 28 November 2022

## SECTION 8: Exposure controls/personal protection

Gloves	· nitrile_neeprone
Gioves	: nitrile neoprene
Body protection	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapor (Type A) and particulate filter P3
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

# **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Color	: Various
Odor	: Amine-like. [Strong]
Odor threshold	: Not available.
Melting point/freezing point	■ May start to solidify at the following temperature: -7.1°C (19.2°F) This is based or data for the following ingredient: 2,2'-dimethyl-4,4'-methylenebis(cyclohexylamine Weighted average: -8.53°C (16.6°F)
Initial boiling point and boiling range	: >37.78°C
Flammability	: Not available.
Upper/lower flammability or explosive limits	: Greatest known range: Lower: 1.3% Upper: 13% (benzyl alcohol)
Flash point	: Closed cup: 105°C
Auto-ignition temperature	: 426°C (798.8°F)
Decomposition temperature	: Stable under recommended storage and handling conditions (see Section 7).
рН	: Not applicable. insoluble in water.
Viscosity	: Kinematic (40°C): <14 mm²/s
Solubility(ies)	
Media	Result
cold water	Not soluble
Partition coefficient: n-octano water	/ : Not applicable.
Vapor pressure	

Code : 00237774

Date of issue/Date of revision

: 28 November 2022

NOVAGUARD 840/890 HARDENER CREAM

SECTION 9: Physica	l and chemical	properties
--------------------	----------------	------------

		Ingredient name	Vapo	r Press	ure at 20°C	Vapor pressure at 50		ure at 50°C
			mm Hg	kPa	Method	mm Hg	kPa	Method
		N-(3-(trimethoxysilyl) propyl)ethylenediamine	0.3000246	0.04				
Evaporation rate	:	0.007 (benzyl alcoho	l) compa	red with	butyl acetate			•
Relative density	:	0.97						
Vapor density	:	Highest known value	e: 3.7 (Air	-= 1) (b	enzyl alcohol).			
Explosive properties	:	The product itself is not explosive, but the formation of an explosible mixture of vapor or dust with air is possible.						
Oxidizing properties	:	Product does not present an oxidizing hazard.						
Particle characteristics								
Median particle size	:	Not applicable.						
<b>9.2 Other information</b> No additional information.								

<b>SECTION 10: Stabilit</b>	y and reactivity
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
10.6 Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides Formaldehyde. metal oxide/oxides

# **SECTION 11: Toxicological information**

## 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2,2'-dimethyl-4,4'-methylenebis	LC50 Inhalation Dusts and	Rat	420 mg/m <sup>3</sup>	4 hours
(cyclohexylamine)	mists			
	LD50 Dermal	Rabbit	>0.2 g/kg	-
	LD50 Oral	Rat	>0.32 g/kg	-
benzyl alcohol	LC50 Inhalation Dusts and	Rat	>4178 mg/m <sup>3</sup>	4 hours
-	mists			
	LD50 Dermal	Rabbit	2000 mg/kg	-
	LD50 Oral	Rat	1.23 g/kg	-
N-(3-(trimethoxysilyl)propyl)	LD50 Oral	Rat	2413 mg/kg	-
ethylenediamine				
2,4,6-tris(dimethylaminomethyl)phenol	LD50 Dermal	Rabbit	1.28 g/kg	-
	LD50 Dermal	Rat	1280 mg/kg	-
English (US)	Europe	)		9/15

Code	: 00237774	Date of issue/Date of revision	: 28 November 2022
NOVAGUAR	D 840/890 HARDENER CREAM		

# **SECTION 11: Toxicological information**

LD50 Oral

1200 mg/kg

Rat

**Conclusion/Summary** : There are no data available on the mixture itself.

## Irritation/Corrosion

Product/ingredient	name	Result	Species	Score	Exposure	Observatio
2,4,6-tris(dimethylaminome	thyl)phenol	Skin - Visible necrosis	Rabbit	-	4 hours	7 days
Conclusion/Summary			•			•
Skin	: There are	no data available on the	mixture itself			
Eyes	: There are	no data available on the	mixture itself			
Respiratory	: There are	no data available on the	mixture itself	-		
Sensitization						
Conclusion/Summary						
Skin		e no data available on the				
Respiratory	: There are	e no data available on the	mixture itsel	f.		
Mutagenicity						
Conclusion/Summary	: There are	e no data available on the	mixture itsel	f.		
Carcinogenicity				-		
Conclusion/Summary	: There are	e no data available on the	mixture itsel	f.		
Reproductive toxicity						
Conclusion/Summary	: There are	e no data available on the	mixture itsel	f.		
<b>Teratogenicity</b>						
Conclusion/Summary		e no data available on the	mixture itsel	f.		
Specific target organ toxic	<u>city (single exp</u>	<u>posure)</u>				
Not available.						
Specific target organ toxic	ity (repeated)	<u>exposure)</u>				
Not available.						
Aspiration hazard						
Not available.						
	Net such					
Information on the likely routes of exposure	: Not availa	adle.				
Potential acute health effe	cts					
Inhalation	: Toxic if ir	haled				
Ingestion		f swallowed.				
Skin contact		severe burns. Toxic in co	ntact with eki	n Mav	cause an allergic e	kin reaction
Eye contact		serious eye damage.	NGOL WILL SKI	n. way	ause an allerylt s	
Symptoms related to the p			haractorieti	re i		
Inhalation	: No specif		naraotori3ti	<u>~~</u>		
Ingestion	•	symptoms may include th	e following:			
	stomach		e renewing.			
Skin contact		symptoms may include th	e following:			
	pain or in	ritation				
	redness					

Code : 00237774 NOVAGUARD 840/890 HARDI	EN		of issue/Date of revision	: 28 November 2022
SECTION 11: Toxicol	0	ical information		
Eye contact	:	Adverse symptoms may in pain watering redness	clude the following:	
Delayed and immediate effe	cts	and also chronic effects	from short and long term e	<u>xposure</u>
<u>Short term exposure</u>				
Potential immediate effects	:	Not available.		
Potential delayed effects	:	Not available.		
Long term exposure				
Potential immediate effects	:	Not available.		
Potential delayed effects	1	Not available.		
Potential chronic health effe	ect			
Not available.				
Conclusion/Summary		Not available.		
General	:	Once sensitized, a severe very low levels.	allergic reaction may occur w	hen subsequently exposed to
Carcinogenicity	÷	No known significant effect	ts or critical hazards.	

**Mutagenicity** : No known significant effects or critical hazards.

**Reproductive toxicity** : No known significant effects or critical hazards.

Other information : Not available.

Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Trimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness. Contains a substance that may emit formaldehyde if stored beyond its shelf life and/or during cure at curing temperatures greater than 60C (140F).

#### **11.2 Information on other hazards**

**11.2.1 Endocrine disrupting properties** 

Not available.

## 11.2.2 Other information

Not available.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
2,4,6-tris(dimethylaminomethyl)phenol	Acute LC50 175 mg/l	Fish	96 hours

**Conclusion/Summary** : There are no data available on the mixture itself.

### 12.2 Persistence and degradability

Conclusion/Summary

: There are no data available on the mixture itself.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
benzyl alcohol	-	-	Readily

English (US)	Europe	11/15

 Code
 <th::00237774</th>
 Date of issue/Date of revision
 : 28 November 2022

 NOVAGUARD 840/890 HARDENER CREAM

## **SECTION 12: Ecological information**

### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2,2'-dimethyl-4,4'-methylenebis(cyclohexylamine)	1.8	-	low
benzyl alcohol	0.87	-	low
2,4,6-tris(dimethylaminomethyl)phenol	0.219	-	low

#### 12.4 Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

#### **12.6 Endocrine disrupting properties**

Not available.

#### 12.7 Other adverse effects

No known significant effects or critical hazards.

## **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 13.1 Waste treatment methods

# Product

Methods of disposal: The generation of waste should be avoided or minimized wherever possible. Disposal<br/>of this product, solutions and any by-products should at all times comply with the<br/>requirements of environmental protection and waste disposal legislation and any<br/>regional local authority requirements. Dispose of surplus and non-recyclable products<br/>via a licensed waste disposal contractor. Waste should not be disposed of untreated to<br/>the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

## Hazardous waste : Yes.

#### European waste catalogue (EWC)

Waste code	Waste designation	
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	
ackaging		
Methods of disposal	<ul> <li>The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.</li> </ul>	
Type of packaging	European waste catalogue (EWC)	
Container	15 01 06 mixed packaging	
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.	

English (US)	Europe	12/15
--------------	--------	-------

Code : 00237774

**NOVAGUARD 840/890 HARDENER CREAM** 

Date of issue/Date of revision

: 28 November 2022

# 14. Transport information

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number or ID number	UN2922	UN2922	UN2922	UN2922
14.2 UN proper shipping name	CORROSIVE LIQUID, TOXIC, N.O.S.	CORROSIVE LIQUID, TOXIC, N.O.S.	CORROSIVE LIQUID, TOXIC, N.O.S.	CORROSIVE LIQUID, TOXIC, N.O.S.
	(methanol)	(methanol)	(methanol)	(methanol)
14.3 Transport hazard class(es)	8 (6.1)	8 (6.1)	8 (6.1)	8 (6.1)
14.4 Packing group	II	II	II	II
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	Not applicable.	(2,2'-dimethyl-4,4'- methylenebis (cyclohexylamine))	Not applicable.

#### **Additional information**

ADR/RID	<ul> <li>The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.</li> </ul>	
ADN	The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.	
IMDG	: The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.	
ΙΑΤΑ	: The environmentally hazardous substance mark may appear if required by other transportation regulations.	
14.6 Special pree user	cautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.	

**14.7 Maritime transport in :** Not applicable. **bulk according to IMO instruments** 

## **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u> <u>Annex XIV - List of substances subject to authorization</u> <u>Annex XIV</u>

None of the components are listed.

Substances of very high concern

None of the components are listed.

Code	: 00237774	Date of issue/Date of revision	: 28 November 2022
NOVAGUARI	D 840/890 HARDENER CREAM		

## **SECTION 15: Regulatory information**

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

#### Ozone depleting substances (1005/2009/EU)

Not listed.

#### **Seveso Directive**

This product is controlled under the Seveso Directive.

Danger criteria		
	Category	
	H2	
	E2	

#### 15.2 Chemical Safety Assessment

: No Chemical Safety Assessment has been carried out.

# **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

#### Abbreviations and acronyms

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

PBT = Persistent, Bioaccumulative and Toxic

vPvB = Very Persistent and Very Bioaccumulative

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

IMDG = International Maritime Dangerous Goods

IATA = International Air Transport Association

#### Full text of abbreviated H statements

H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

### Full text of classifications [CLP/GHS]

Code : 00237774 NOVAGUARD 840/890 HARDENER CREAM	Date of issue/Date of revision: 28 November 2022
SECTION 16: Other information	
Acute Tox. 3 Acute Tox. 4 Aquatic Chronic 2 Aquatic Chronic 3 Eye Dam. 1 Eye Irrit. 2 Skin Corr. 1A Skin Corr. 1C	ACUTE TOXICITY - Category 3 ACUTE TOXICITY - Category 4 AQUATIC HAZARD (LONG-TERM) - Category 2 AQUATIC HAZARD (LONG-TERM) - Category 3 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 SKIN CORROSION/IRRITATION - Category 1A SKIN CORROSION/IRRITATION - Category 1C
Skin Sens. 1 History	SKIN SENSITIZATION - Category 1

Date of issue/ Date of revision	: 28 November 2022
Date of previous issue	: 31 October 2022
Prepared by	: EHS
Version	: 15.1

## <u>Disclaimer</u>

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.