

SAFETY DATA SHEET



Date of issue/Date of revision

: 9 January 2023

Version

: 2.05

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : NOVAGUARD 890 BASE WHITE**Product code** : 00269262**Product type** : Liquid.**Other means of identification**

Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.**Use of the substance/
mixture** : Coating.**Uses advised against** : Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

Pittsburgh Paints Nigeria Limited
 1, Coker Street, Coker Bus-stop, Badagry Expressway, Orile Iganmu, Lagos
 Nigeria
 Tel: 00 234 (0) 8138672483

**e-mail address of person
responsible for this SDS** : PS.ACEMEA@ppg.com**1.4 Emergency telephone
number** : 00234 127 173 85

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture**Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**

Skin Corr. 1C, H314

Eye Dam. 1, H318

Skin Sens. 1, H317

Repr. 1B, H360F

STOT RE 2, H373

Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :**Signal word** : Danger

SECTION 2: Hazards identification

Hazard statements : Causes severe skin burns and eye damage.
May cause an allergic skin reaction.
May damage fertility.
May cause damage to organs through prolonged or repeated exposure.
Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention : Wear protective gloves, protective clothing and eye or face protection. Avoid release to the environment. Do not breathe vapour.

Response : Collect spillage. IF exposed or concerned: Get medical advice or attention.

Storage : Not applicable.

Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazardous ingredients : Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol
1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-, polymer with 2-(chloromethyl)oxirane
Phenol, polymer with formaldehyde, glycidyl ether (MW≤700)
crystalline silica, respirable powder (<10 microns)
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine

Supplemental label elements : Contains epoxy constituents. May produce an allergic reaction.
Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Restricted to professional users.

Special packaging requirements

Containers to be fitted with child-resistant fastenings : Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : Contains a substance that may emit formaldehyde if stored beyond its shelf life and/or during cure at curing temperatures greater than 60C/140F.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	REACH #: 01-2119454392-40 EC: 500-006-8 CAS: 9003-36-5	≥25 - ≤50	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]
1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-, polymer with 2-(chloromethyl) oxirane	REACH #: 01-2120078341-60 CAS: 30499-70-8	≥10 - ≤25	Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1B, H317 Repr. 1B, H360F (oral) Aquatic Chronic 2, H411	-	[1]

SECTION 3: Composition/information on ingredients

benzyl alcohol	REACH #: 01-2119492630-38 EC: 202-859-9 CAS: 100-51-6 Index: 603-057-00-5	≥5.0 - ≤10	Acute Tox. 4, H302 Acute Tox. 4, H332 Eye Irrit. 2, H319	ATE [Oral] = 1230 mg/kg ATE [Inhalation (dusts and mists)] = 1.5 mg/l	[1] [2]
Phenol, polymer with formaldehyde, glycidyl ether (MW≤700)	CAS: 28064-14-4	≥5.0 - ≤10	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]
crystalline silica, respirable powder (<10 microns)	EC: 238-878-4 CAS: 14808-60-7	≥1.0 - ≤5.0	STOT RE 1, H372 (inhalation)	-	[1] [2]
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	REACH #: 01-2119979085-27 EC: 309-629-8 CAS: 100545-48-0	<1.0	Skin Sens. 1B, H317 Aquatic Chronic 3, H412 See Section 16 for the full text of the H statements declared above.	-	[1]

See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures**4.1 Description of first aid measures**

- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayedPotential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes severe burns. May cause an allergic skin reaction.

SECTION 4: First aid measures

Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:
pain
watering
redness

Inhalation : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations

Skin contact : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
reduced foetal weight
increase in foetal deaths
skeletal malformations

Ingestion : Adverse symptoms may include the following:
stomach pains
reduced foetal weight
increase in foetal deaths
skeletal malformations

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing media : Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products : Decomposition products may include the following materials:
carbon oxides
halogenated compounds
metal oxide/oxides
Formaldehyde.

5.3 Advice for firefighters

Special precautions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections

- : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

SECTION 7: Handling and storage**7.2 Conditions for safe storage, including any incompatibilities**

: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

Recommendations : Not available.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters**Occupational exposure limits**

Product/ingredient name	Exposure limit values
Quartz (SiO ₂)	Ministry of Labor (France, 12/2021). TWA: 0.1 mg/m ³ 8 hours. Form: Respirable fraction

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

8.2 Exposure controls

Appropriate engineering controls : If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Chemical splash goggles and face shield.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or

SECTION 8: Exposure controls/personal protection

frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Gloves : nitrile neoprene

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties**Appearance**

Physical state : Liquid.

Colour : White.

Odour : Aromatic.

Odour threshold : Not available.

Melting point/freezing point : May start to solidify at the following temperature: -15.4°C (4.3°F) This is based on data for the following ingredient: benzyl alcohol. Weighted average: -19.36°C (-2.8°F)

Initial boiling point and boiling range : >37.78°C

Flammability : Not available.

Upper/lower flammability or explosive limits : Greatest known range: Lower: 1.3% Upper: 13% (benzyl alcohol)

Flash point : Open cup: 101°C

Auto-ignition temperature : 110°C (230°F)

Decomposition temperature : Stable under recommended storage and handling conditions (see Section 7).

pH : Not applicable. insoluble in water.

Viscosity : Kinematic (40°C): >21 mm²/s

Viscosity : 60 - 100 s (ISO 6mm)

Solubility(ies) :

Media	Result
cold water	Not soluble

Partition coefficient: n-octanol/ water : Not applicable.

Vapour pressure :

Code : 00269262

Date of issue/Date of revision

: 9 January 2023

NOVAGUARD 890 BASE WHITE

SECTION 9: Physical and chemical properties

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-, polymer with 2-(chloromethyl)oxirane	0.074256089	0.0099				

Evaporation rate	: 0.007 (benzyl alcohol) compared with butyl acetate
Relative density	: 1.52
Vapour density	: Highest known value: 3.7 (Air = 1) (benzyl alcohol).
Explosive properties	: The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.
Oxidising properties	: Product does not present an oxidizing hazard.
Particle characteristics	
Median particle size	: Not applicable.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
10.6 Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides halogenated compounds Formaldehyde. metal oxide/oxides

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol benzyl alcohol	LD50 Oral	Rat	>10000 mg/kg	-
	LC50 Inhalation Dusts and mists	Rat	>4178 mg/m ³	4 hours
	LD50 Dermal	Rabbit	2000 mg/kg	-
	LD50 Oral	Rat	1.23 g/kg	-
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	LC50 Inhalation Dusts and mists	Rat	5.05 mg/l	4 hours
	LD50 Oral	Rat	>2000 mg/kg	-

Conclusion/Summary : There are no data available on the mixture itself.

SECTION 11: Toxicological informationIrritation/Corrosion**Conclusion/Summary****Skin** : There are no data available on the mixture itself.**Eyes** : There are no data available on the mixture itself.**Respiratory** : There are no data available on the mixture itself.Sensitisation

Product/ingredient name	Route of exposure	Species	Result
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	skin	Guinea pig	Sensitising

Conclusion/Summary**Skin** : There are no data available on the mixture itself.**Respiratory** : There are no data available on the mixture itself.Mutagenicity**Conclusion/Summary** : There are no data available on the mixture itself.Carcinogenicity**Conclusion/Summary** : There are no data available on the mixture itself.Reproductive toxicity**Conclusion/Summary** : There are no data available on the mixture itself.Teratogenicity**Conclusion/Summary** : There are no data available on the mixture itself.Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Quartz (SiO ₂)	Category 1	inhalation	-

Aspiration hazard

Not available.

Information on likely routes of exposure : Not available.Potential acute health effects**Inhalation** : No known significant effects or critical hazards.**Ingestion** : No known significant effects or critical hazards.**Skin contact** : Causes severe burns. May cause an allergic skin reaction.**Eye contact** : Causes serious eye damage.Symptoms related to the physical, chemical and toxicological characteristics

Inhalation : Adverse symptoms may include the following:

- reduced foetal weight
- increase in foetal deaths
- skeletal malformations

Ingestion : Adverse symptoms may include the following:

- stomach pains
- reduced foetal weight
- increase in foetal deaths
- skeletal malformations

SECTION 11: Toxicological information

Skin contact : Adverse symptoms may include the following:
 pain or irritation
 redness
 blistering may occur
 reduced foetal weight
 increase in foetal deaths
 skeletal malformations

Eye contact : Adverse symptoms may include the following:
 pain
 watering
 redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Short term exposure**

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Not available.

General : May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : May damage fertility.

Other information : Not available.

Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Contains a substance that may emit formaldehyde if stored beyond its shelf life and/or during cure at curing temperatures greater than 60C/140F.

11.2 Information on other hazards**11.2.1 Endocrine disrupting properties**

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information**12.1 Toxicity**

SECTION 12: Ecological information

Product/ingredient name	Result	Species	Exposure
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	Acute LC50 2.54 mg/l	Fish	96 hours
	Acute EC50 >100 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 >10 mg/l	Daphnia - Daphnia magna	48 hours
	Acute LC50 >10 mg/l	Fish - Oncorhynchus mykiss	96 hours

Conclusion/Summary : There are no data available on the mixture itself.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	301D Ready Biodegradability - Closed Bottle Test	22 % - 28 days	-	-

Conclusion/Summary : There are no data available on the mixture itself.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
benzyl alcohol	-	-	Readily
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	-	-	Inherent

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	2.7	-	low
benzyl alcohol	0.87	-	low
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	>5.86	-	high

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

Code : 00269262

Date of issue/Date of revision

: 9 January 2023

NOVAGUARD 890 BASE WHITE

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods**Product**

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)
Container	15 01 06 mixed packaging

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number or ID number	UN3066	UN3066	UN3066
14.2 UN proper shipping name	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	8	8	8
14.4 Packing group	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	(Epoxy Resin, Epoxy Resin)	Not applicable.

Additional information

ADR/RID : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.

Tunnel code : (E)

IMDG : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.

IATA : The environmentally hazardous substance mark may appear if required by other transportation regulations.

Code : 00269262

Date of issue/Date of revision

: 9 January 2023

NOVAGUARD 890 BASE WHITE

SECTION 14: Transport information

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not applicable.

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****EU Regulation (EC) No. 1907/2006 (REACH)****Annex XIV - List of substances subject to authorisation****Annex XIV**

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Restricted to professional users.

Other national and international regulations.**Ozone depleting substances (1005/2009/EU)**

Not listed.

Social Security Code, Articles L 461-1 to L 461-7 : benzyl alcohol RG 84
 Phenol, polymer with formaldehyde, glycidyl ether (MW <=700) RG 51
 Quartz (SiO₂) RG 25
 Surveillance médicale spéciale selon l'arrêté du 11 juillet 1977:
 Pour les applications des peintures et vernis par pulvérisation

Reinforced medical surveillance : Act of July 11, 1977 determining the list of activities which require reinforced medical surveillance: not applicable

References : Reinforced medical surveillance ; Decree no. 2001-97 of 1 February 2001 establishing specific rules for the prevention of risks from carcinogens, mutagens and reprotoxics and amending the Labour code ; Decree no. 2003-1254 of 23 December 2003 relating to prevention of chemical risks and amending the Labour code ; Decree no. 2004-187 of 26 February 2004 on the placing on the market of biocidal products ; Decree no. 88-1231 of 29/12/1988 relating to poisonous preparations and substances. ; Decree no. 95-517 of 15 May 1997, relating to the classification of dangerous waste. ; Labour code article: R231-53 ; Labour code: Occupational air (ventilation, air purification): Art. R 232-5 to R 232-5-14 ; Labour code: Prevention of chemical risk: Art.R231-51 and R 231-54 to R 231-54-9 ; Labour code: Prevention of fires: Art.R232-12-13 to R 232-12-29 and R 233-30 ; Labour code: provisions applicable to women: Art. L 234-3 to L 236-6 ; Labour code: provisions applicable to young workers: Art. L 234-3 to L 236-6; Art: R234-16 ; Labour code: Sanitary installations: Art. R 232-2 à R 232-2-7 ; Law 76-663 of 19 July 1976 amending and implementing decree of 21 September 1977 relating to classified installations for the protection of the environment ; Tables of anticipated professional diseases according to article R461-3 of the labour code

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 DNEL = Derived No Effect Level
 EUH statement = CLP-specific Hazard statement
 PNEC = Predicted No Effect Concentration
 RRN = REACH Registration Number

Full text of abbreviated H statements

: H302 Harmful if swallowed.
 H314 Causes severe skin burns and eye damage.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H360F May damage fertility.
 H372 Causes damage to organs through prolonged or repeated exposure.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

: Acute Tox. 4 ACUTE TOXICITY - Category 4
 Aquatic Chronic 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
 Aquatic Chronic 3 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
 Eye Dam. 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
 Eye Irrit. 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
 Repr. 1B REPRODUCTIVE TOXICITY - Category 1B
 Skin Corr. 1C SKIN CORROSION/IRRITATION - Category 1C
 Skin Irrit. 2 SKIN CORROSION/IRRITATION - Category 2
 Skin Sens. 1 SKIN SENSITISATION - Category 1
 Skin Sens. 1B SKIN SENSITISATION - Category 1B
 STOT RE 1 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
 STOT RE 2 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2

History

Date of issue/ Date of revision : 9 January 2023

Date of previous issue : 27 September 2022

Prepared by : EHS

Version : 2.05

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.