# SAFETY DATA SHEET

Date of issue/Date of revision

: 10 January 2023

Version : 2.01

**Europe** 

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

**1.1 Product identifier** 

Product name	:	SIGMACOVER 350 BASE BLACK
Product code	:	00393217
Other means of identification	n	

Not available.

1.2 Relevant identified uses	the substance or mixture and uses advised against	
Product use	Professional applications, Used by spraying.	
Use of the substance/ mixture	: Coating.	
Uses advised against	Product is not intended, labelled or packaged for consumer use	•

#### 1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL Tweemontstraat 104 B-2100 Deurne Belgium Telephone +32-33606311 Fax +32-33606435

e-mail address of person responsible for this SDS

: Product.Stewardship.EMEA@ppg.com

#### 1.4 Emergency telephone number

#### **Supplier**

+31 20 4075210

# **SECTION 2: Hazards identification**

2.1 Classification of the sub	stance or mixture		
Product definition	: Mixture		
Classification according to	Regulation (EC) No.	<u>1272/2008 [CLP/GHS]</u>	
Flam. Liq. 3, H226			
Skin Irrit. 2, H315			
Eye Dam. 1, H318			
Skin Sens. 1, H317			
STOT RE 1, H372			
Aquatic Chronic 3, H412			
The product is classified as h	azardous according to	Regulation (EC) 1272/2008	as amended.
See Section 16 for the full tex	kt of the H statements of	leclared above.	

Code : 00393217	Date of issue/Date of revision	: 10 January 2023
SIGMACOVER 350 BASE BLACK		

# **SECTION 2: Hazards identification**

2

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements Hazard pictograms

Signal word	: Danger
Hazard statements	<ul> <li>Flammable liquid and vapour.</li> <li>Causes skin irritation.</li> <li>May cause an allergic skin reaction.</li> <li>Causes serious eye damage.</li> <li>Causes damage to organs through prolonged or repeated exposure.</li> <li>Harmful to aquatic life with long lasting effects.</li> </ul>
Precautionary statements	
Prevention	: Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe vapour.
Response	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Storage	: Not applicable.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
l la servela de la sura d'accéra	P280, P210, P260, P305 + P351 + P338, P310, P501
Hazardous ingredients	<ul> <li>prystalline silica, respirable powder (&lt;10 microns) Epoxy Resin (700<mw<=1100) reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) 2-methylpropan-1-ol Octadecanamide, N,N'-1,6-hexanediylbis[12-hydroxy-</mw<=1100) </li> </ul>
Supplemental label elements	: Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Special packaging requiren	<u>nents</u>
Containers to be fitted with child-resistant fastenings	: Not applicable.
Tactile warning of danger	: Not applicable.
2.3 Other hazards	
Product meets the criteria	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

for PBT or vPvB

Code : 0	00393217	Date of issue/Date of revision	: 10 January 2023
SIGMACOVER 3	350 BASE BLACK		

### **SECTION 2: Hazards identification**

**Other hazards which do** : Prolonged or repeated contact may dry skin and cause irritation. **not result in classification** 

# **SECTION 3: Composition/information on ingredients**

3.2 Mixtures	: Mixture				
Product/ingredient name	Identifiers	% by weight	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
vystalline silica, respirable powder (<10 microns)	EC: 238-878-4 CAS: 14808-60-7	≥10 - ≤25	STOT RE 1, H372 (inhalation)	-	[1] [2]
Epoxy Resin (700 <mw &lt;=1100)</mw 	CAS: 25036-25-3	≥10 - ≤25	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317	-	[1]
xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7 Index: 601-022-00-9	≥10 - ≤15	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Asp. Tox. 1, H304	ATE [Dermal] = 1700 mg/kg ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]
reaction product: bisphenol- A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	REACH #: 01-2119456619-26 EC: 500-033-5 CAS: 25068-38-6 Index: 603-074-00-8	≥5.0 - ≤10	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	Skin Irrit. 2, H315: C ≥ 5% Eye Irrit. 2, H319: C ≥ 5%	[1]
benzyl alcohol	REACH #: 01-2119492630-38 EC: 202-859-9 CAS: 100-51-6 Index: 603-057-00-5	≥1.0 - ≤5.0	Acute Tox. 4, H302 Acute Tox. 4, H332 Eye Irrit. 2, H319	ATE [Oral] = 1230 mg/ kg ATE [Inhalation (dusts and mists)] = 1.5 mg/l	[1] [2]
2-methylpropan-1-ol	REACH #: 01-2119484609-23 EC: 201-148-0 CAS: 78-83-1 Index: 603-108-00-1	≥1.0 - ≤4.5	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 STOT SE 3, H336	-	[1] [2]
ethylbenzene	REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4	≥1.0 - ≤5.0	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Inhalation (vapours)] = 17.8 mg/l	[1] [2]
Octadecanamide, N, N'-1,6-hexanediylbis [12-hydroxy-	CAS: 55349-01-4	≥1.0 - ≤5.0	Skin Sens. 1, H317 Aquatic Chronic 4, H413	-	[1]
English (GB)	1	1	Europe	1	3/18

Code	: 00393217	Date of issue/Date of revision	: 10 January 2023
SIGMACOVE	ER 350 BASE BLACK		

### **SECTION 3: Composition/information on ingredients**

above.
--------

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Xylene: Several REACH registrations cover the REACH registered substance with xylene isomers, ethylbenzene (and toluene). The other REACH Registrations include: 01-2119555267-33 reaction mass of ethylbenzene and m-xylene and p-xylene, 01-2119486136-34 Aromatic hydrocarbons, C8, 01-2119539452-40 reaction mass of ethylbenzene and xylene. <u>Type</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

Eye contact	:	Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Inhalation	:	Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	:	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	:	If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

Potential acute health	<u>effects</u>
Eye contact	: Causes serious eye damage.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/s	symptoms
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: No specific data.

Code : 00393217 SIGMACOVER 350 BASE BL	Date of issue/Date of revision : 10 January 2023 ACK
SECTION 4: First aid	measures
Skin contact	: Adverse symptoms may include the following: pain or irritation redness dryness cracking blistering may occur
Ingestion	: Adverse symptoms may include the following: stomach pains
4.3 Indication of any immedia	ate medical attention and special treatment needed
Notes to physician	<ul> <li>In case of inhalation of decomposition products in a fire, symptoms may be delayed.</li> <li>The exposed person may need to be kept under medical surveillance for 48 hours.</li> </ul>
Specific treatments	: No specific treatment.
SECTION 5: Firefight	ting measures
5.1 Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO <sub>2</sub> , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.
5.2 Special hazards arising f	rom the substance or mixture
Hazards from the substance or mixture	: Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	<ul> <li>Decomposition products may include the following materials: carbon oxides nitrogen oxides halogenated compounds metal oxide/oxides</li> </ul>
5.3 Advice for firefighters	
Special precautions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

### **SECTION 6: Accidental release measures**

6.1 Personal precautions,	protective equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

2020/878	
Code : 00393217 SIGMACOVER 350 BASE BLA	Date of issue/Date of revision : 10 January 2023
<b>SECTION 6: Accident</b>	tal release measures
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
6.3 Methods and material for	containment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.
6.4 Reference to other sections	<ul> <li>See Section 1 for emergency contact information.</li> <li>See Section 8 for information on appropriate personal protective equipment.</li> <li>See Section 13 for additional waste treatment information.</li> </ul>

# **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU)	
2020/878	

Code: 00393217Date of issue/Date of revision: 10 January 2023

SIGMACOVER 350 BASE BLACK

# **SECTION 7: Handling and storage**

<ul> <li>7.2 Conditions for safe storage, including any incompatibilities</li> <li>Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tight closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.</li> </ul>	htly
--	------

#### 7.3 Specific end use(s)

See Section 1.2 for Identified uses.

### **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 8.1 Control parameters

#### **Occupational exposure limits**

Product/ingredient name	Exposure limit values		
vystalline silica, respirable powder (<10 microns)	ACGIH TLV (United States, 1/2022). [Silica, crystalline]		
	TWA: 0.025 mg/m <sup>3</sup> 8 hours. Form: Respirable		
xylene	EU OEL (Europe, 1/2022). [xylene, mixed isomers] Absorbed		
	through skin.		
	STEL: 442 mg/m <sup>3</sup> 15 minutes.		
	STEL: 100 ppm 15 minutes.		
	TWA: 221 mg/m <sup>3</sup> 8 hours.		
	TWA: 50 ppm 8 hours.		
benzyl alcohol	IPEL (-).		
	TWA: 5 ppm		
	STEL: 10 ppm		
2-methylpropan-1-ol	ACGIH TLV (United States, 1/2022).		
	TWA: 152 mg/m <sup>3</sup> 8 hours.		
	TWA: 50 ppm 8 hours.		
ethylbenzene	EU OEL (Europe, 1/2022). Absorbed through skin.		
	STEL: 884 mg/m <sup>3</sup> 15 minutes.		
	STEL: 200 ppm 15 minutes.		
	TWA: 442 mg/m <sup>3</sup> 8 hours.		
	TWA: 100 ppm 8 hours.		
procedures Standard EN 689 by inhalation to c	d be made to monitoring standards, such as the following: European Workplace atmospheres - Guidance for the assessment of exposure hemical agents for comparison with limit values and measurement an Standard EN 14042 (Workplace atmospheres - Guide for the		

by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### **DNELs**

Code : 00393217 SIGMACOVER 350 BASE BLACK Date of issue/Date of revision

: 10 January 2023

# **SECTION 8: Exposure controls/personal protection**

Product/ingredient name	Туре	Exposure	Value	Population	Effects
<b>x</b> ylene	DNEL	Short term Inhalation	260 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Short term Inhalation	260 mg/m <sup>3</sup>	General population	
	DNEL	Long term Dermal	125 mg/kg bw/day	General population	
	DNEL	Long term Inhalation	65.3 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Oral	12.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	221 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Inhalation	442 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Inhalation	221 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	442 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Dermal	212 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	65.3 mg/m <sup>3</sup>	General population	
	DNEL	Short term Inhalation	260 mg/m <sup>3</sup>	General population	
	DNEL	Short term Inhalation	260 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	221 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Oral	12.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	65.3 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Dermal	125 mg/kg bw/day	General population	
	DNEL	Long term Dermal	212 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	221 mg/m³	Workers	Systemic
	DNEL	Short term Inhalation	442 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	442 mg/m <sup>3</sup>	Workers	Systemic
reaction product: bisphenol-A-	DNEL	Long term Inhalation	12.25 mg/m <sup>3</sup>	Workers	Systemic
(epichlorhydrin); epoxy resin					
(number average molecular					
weight ≤ 700)					
	DNEL	Short term Inhalation	12.25 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	8.33 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	8.33 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	3.571 mg/kg bw/day	General	Systemic
				population	
				[Consumers]	
	DNEL	Short term Dermal	3.571 mg/kg bw/day	General	Systemic
				population	
				[Consumers]	
	DNEL	Long term Oral	0.75 mg/kg bw/day	General	Systemic
				population	
				[Consumers]	
	DNEL	Short term Oral	0.75 mg/kg bw/day	General	Systemic
				population	
				[Consumers]	
	DNEL	Short term Oral	0.75 mg/kg bw/day	General population	
	DNEL	Long term Oral	0.75 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	3.571 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	3.571 mg/kg bw/day	General population	
	DNEL	Short term Dermal	8.33 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	8.33 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	12.25 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Inhalation	12.25 mg/m³	Workers	Systemic
benzyl alcohol	DNEL	Long term Oral	4 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	4 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	5.4 mg/m³	General population	Systemic
	DNEL	Long term Dermal	8 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Oral	20 mg/kg bw/day	General population	
	DNEL	Short term Dermal	20 mg/kg bw/day	General population	
	DNEL	Long term Inhalation	22 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Inhalation	27 mg/m³	General population	Systemic
<u> </u>	l				
English (GB)			Europe		8/18

Code : 00393217 SIGMACOVER 350 BASE BLACK Date of issue/Date of revision

: 10 January 2023

# **SECTION 8: Exposure controls/personal protection**

		Short term Dermal	40 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	110 mg/m³	Workers	Systemic
2-methylpropan-1-ol	DNEL	Long term Inhalation	55 mg/m³	General population	Local
	DNEL	Long term Inhalation	310 mg/m <sup>3</sup>	Workers	Local
ethylbenzene	DNEL	Long term Oral	1.6 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	15 mg/m³	General population	Systemic
	DNEL	Long term Inhalation	77 mg/m³	Workers	Systemic
	DNEL	Long term Dermal	180 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	293 mg/m <sup>3</sup>	Workers	Local
	DMEL	Long term Inhalation	442 mg/m <sup>3</sup>	Workers	Local
	DMEL	Short term Inhalation	884 mg/m³	Workers	Systemic

#### **PNECs**

Product/ingredient name	Туре	Compartment Detail	Value	Method Detail
xylene	-	Fresh water	0.327 mg/l	-
-	-	Marine water	0.327 mg/l	-
	-	Sewage Treatment Plant	6.58 mg/l	-
	-	Fresh water sediment	12.46 mg/kg dwt	-
	-	Marine water sediment	12.46 mg/kg dwt	-
	-	Soil	2.31 mg/kg	-
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	-	Fresh water	0.006 mg/l	Assessment Factors
	-	Marine water	0.001 mg/l	Assessment Factors
	-		10 mg/l	Assessment Factors
	-	Fresh water sediment	0.996 mg/kg dwt	Equilibrium Partitioning
	-	Marine water sediment	0.1 mg/kg dwt	Equilibrium Partitioning
2-methylpropan-1-ol	-	Fresh water	0.4 mg/l	Assessment Factors
	-	Marine water	0.04 mg/l	Assessment Factors
	-	Sewage Treatment Plant	10 mg/l	Assessment Factors
	-	Fresh water sediment	1.56 mg/kg dwt	Equilibrium Partitioning
	-	Marine water sediment	0.156 mg/kg dwt	-
	-	Soil	0.076 mg/kg dwt	Equilibrium Partitioning
ethylbenzene	-	Fresh water	0.1 mg/l	Assessment Factors
	-	Marine water	0.01 mg/l	Assessment Factors
	-	Sewage Treatment Plant	9.6 mg/l	Assessment Factors
	-	Fresh water sediment	13.7 mg/kg dwt	Equilibrium Partitioning
	-	Marine water sediment	1.37 mg/kg dwt	Equilibrium Partitioning
	-	Soil	2.68 mg/kg dwt	Equilibrium Partitioning
	-	Secondary Poisoning	20 mg/kg	-

8.2 Exposure controls Appropriate engineering controls	: Use only with adequate ventilation. Use process enclosures, local exhaust or other engineering controls to keep worker exposure to airborne contamination any recommended or statutory limits. The engineering controls also need to vapour or dust concentrations below any lower explosive limits. Use explosive ventilation equipment.	ants below o keep gas,
Individual protection measu	<u>ires</u>	
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated Contaminated work clothing should not be allowed out of the workplace. Wa contaminated clothing before reusing. Ensure that eyewash stations and sa showers are close to the workstation location.	clothing. ash
Eye/face protection	: Chemical splash goggles and face shield. Use eye protection according to I	EN 166.
English (GB)	Europe	9/18

Code : 00393217 SIGMACOVER 350 BASE BL	Date of issue/Date of revision         : 10 January 2023           ACK
<b>SECTION 8: Exposu</b>	re controls/personal protection
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Gloves	: butyl rubber
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti- static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

# **SECTION 9:** Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

English (GB)	Europe	10/18
Flammability	: Not available.	
Initial boiling point and boiling range	: >37.78°C	
Melting point/freezing point	<ul> <li>May start to solidify at the following temperature: 1597°C (290 on data for the following ingredient: triiron tetraoxide. Weighte (521.7°F)</li> </ul>	
Odour threshold	: Not available.	
Odour	: Aromatic.	
Colour	: Black.	
Physical state	: Liquid.	
Appearance		

Code : 00393217 SIGMACOVER 350 BASE BLAC	ск	Date	e of issue	e/Date of	f revision	: 10	January	2023
SECTION 9: Physical	and	chemical pro	perties					
Upper/lower flammability or explosive limits	:	Greatest known rang	ge: Lower	: 1.3% L	Jpper: 13% (b	enzyl alco	hol)	
Flash point	:	Closed cup: 30°C						
Auto-ignition temperature	:							
		Ingredient name		°C	°F	Μ	ethod	
		2-methylpropan-1-ol		415	779			
Decomposition temperature	:	Stable under recomm	mended s	torage a	nd handling co	onditions (	see Sec	tion 7).
рН	:	Not applicable. insol	uble in wa	ater.	-	·		
Viscosity	:	Kinematic (40°C): >2	21 mm²/s					
Solubility(ies)	:							
Media		Result						
cold water		Not soluble						
Partition coefficient: n-octane water	ol/ :	Not applicable.						
Vapour pressure	:							
			Vapou	Ir Press	ure at 20°C	Vapo	ur press	sure at 50°C
		Ingredient name	mm Hg	1	Method	mm Hg	kPa	Method
		2-methylpropan_1-ol	<12	<16		<b>⊢ ॅ</b> ──		1

						iig		
		2-methylpropan-1-ol	<12	<1.6	DIN EN 13016-2			
Evaporation rate	:	Highest known valu butyl acetate	ue: 0.84 (e	ethylbenz	ene) Weight	ed average	9: 0.59cor	npared with
Relative density	:	1.38						
Vapour density	:	Highest known valu	lighest known value: 3.7 (Air = 1) (xylene). Weighted average: 3.52 (Air = 1)					
Explosive properties	:		The product itself is not explosive, but the formation of an explosible mixture of apour or dust with air is possible.					
Oxidising properties	:	Product does not p	roduct does not present an oxidizing hazard.					
Particle characteristics								
Median particle size	:	Not applicable.						
9.2 Other information								

No additional information.

# **SECTION 10: Stability and reactivity**

English (GB)	Europe	11/18
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic r oxidising agents, strong alkalis, strong acids.	eactions:
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomp Refer to protective measures listed in sections 7 and 8.	osition products.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will	not occur.
10.2 Chemical stability	: The product is stable.	
10.1 Reactivity	: No specific test data related to reactivity available for this product or its	ingredients.

Code : 00393217 **SIGMACOVER 350 BASE BLACK**  Date of issue/Date of revision

: 10 January 2023

# SECTION 10: Stability and reactivity

**10.6 Hazardous** decomposition products : Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides halogenated compounds metal oxide/oxides

# **SECTION 11: Toxicological information**

# 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
₽ poxy Resin (700 <mw<=1100)< td=""><td>LD50 Dermal</td><td>Rat</td><td>&gt;2000 mg/kg</td><td>-</td></mw<=1100)<>	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-
xylene	LD50 Dermal	Rabbit	1.7 g/kg	-
	LD50 Oral	Rat	4.3 g/kg	-
reaction product: bisphenol-A-	LD50 Dermal	Rabbit	>2 g/kg	-
(epichlorhydrin); epoxy resin (number			0.0	
average molecular weight $\leq$ 700)				
	LD50 Oral	Rat	>2 g/kg	-
benzyl alcohol	LC50 Inhalation Dusts and	Rat	>4178 mg/m <sup>3</sup>	4 hours
-	mists			
	LD50 Dermal	Rabbit	2000 mg/kg	-
	LD50 Oral	Rat	1.23 g/kg	-
2-methylpropan-1-ol	LC50 Inhalation Vapour	Rat	24.6 mg/l	4 hours
	LD50 Dermal	Rabbit	2460 mg/kg	-
	LD50 Oral	Rat	2830 mg/kg	-
ethylbenzene	LC50 Inhalation Vapour	Rat	17.8 mg/l	4 hours
-	LD50 Dermal	Rabbit	17.8 g/kg	-
	LD50 Oral	Rat	3.5 g/kg	-

**Conclusion/Summary** : There are no data available on the mixture itself.

### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
xylene reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	Skin - Moderate irritant Eyes - Mild irritant	Rabbit Rabbit	-	24 hours 500 mg 100 mg	-
	Eyes - Moderate irritant Skin - Moderate irritant Skin - Moderate irritant Skin - Severe irritant	Rabbit Rabbit Rabbit Rabbit	- - -	- - 24 hours 500 UI 24 hours 2 mg	- - -

#### **Conclusion/Summary**

Skin

: There are no data available on the mixture itself.

- Eyes Respiratory
- : There are no data available on the mixture itself.
- : There are no data available on the mixture itself.

#### **Sensitisation**

Product/ingredient name	Route of exposure	Species	Result	
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	skin	Mouse	Sensitising	
Conclusion/Summary         Skin       : There are no data available on the mixture itself.         Respiratory       : There are no data available on the mixture itself.				

English (GB)	Europe	12/18
--------------	--------	-------

Code : 00393217	Date of issue/Date of revision	: 10 January 2023
SIGMACOVER 350 BASE BLACK		

# **SECTION 11: Toxicological information**

Mutagenicity	
<b>Conclusion/Summary</b>	: There are no data available on the mixture itself.
<b>Carcinogenicity</b>	
<b>Conclusion/Summary</b>	: There are no data available on the mixture itself.
Reproductive toxicity	
<b>Conclusion/Summary</b>	: There are no data available on the mixture itself.
<b>Teratogenicity</b>	
Conclusion/Summary	: There are no data available on the mixture itself.

#### Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
2-methylpropan-1-ol	Category 3 Category 3 Category 3	-	Respiratory tract irritation Respiratory tract irritation Narcotic effects

#### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
<pre></pre>	Category 1	inhalation	-
	Category 2	-	hearing organs

#### Aspiration hazard

Product/ingredient name	Result
	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

Information on likely routes of exposure	: Not available.
Potential acute health eff	fects
Inhalation	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.
Eye contact	: Causes serious eye damage.
Symptoms related to the	physical, chemical and toxicological characteristics
Inhalation	: No specific data.
Ingestion	: Adverse symptoms may include the following: stomach pains
Skin contact	: Adverse symptoms may include the following: pain or irritation redness dryness cracking blistering may occur
Eye contact	: Adverse symptoms may include the following: pain watering redness

Short term exposure

English (	(GB)
	<b>\</b> /

Code	: 00393217	Date of issue/Date of revision	: 10 January 2023
SIGMACOVE	ER 350 BASE BLACK		

# **SECTION 11: Toxicological information**

	-	
Potential immediate effects	1	Not available.
Potential delayed effects	:	Not available.
Long term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Potential chronic health effe	ect	<u>s</u>
Not available.		
Conclusion/Summary	:	Not available.
General	:	Causes damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	:	No known significant effects or critical hazards.
Mutagenicity	:	No known significant effects or critical hazards.
Reproductive toxicity	:	No known significant effects or critical hazards.
Other information	:	Not available.

Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

#### **11.2 Information on other hazards**

#### **11.2.1 Endocrine disrupting properties**

Not available.

#### 11.2.2 Other information

Not available.

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	Chronic NOEC 0.3 mg/l	Daphnia	21 days
2-methylpropan-1-ol ethylbenzene	Acute EC50 1100 mg/l Acute EC50 1.8 mg/l Fresh water	Daphnia Daphnia	48 hours 48 hours
	Chronic NOEC 1 mg/l Fresh water	Daphnia - Ceriodaphnia dubia	-

**Conclusion/Summary** 

: There are no data available on the mixture itself.

#### 12.2 Persistence and degradability

Code	: 00393217	Date of issue/Date of revision	: 10 January 2023
SIGMACOVE	R 350 BASE BLACK		

### **SECTION 12: Ecological information**

Product/ingredient name	Test	Result	Dose	Inoculum
Feaction product: bisphenol- A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	OECD 301F	5 % - 28 days	-	-
ethylbenzene	-	79 % - Readily - 10 days	-	-

**Conclusion/Summary** : There are no data available on the mixture itself.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
xylene	-	-	Readily
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	-	-	Not readily
benzyl alcohol ethylbenzene	-	-	Readily Readily

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
ylene reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	3.12 2.64 to 3.78	7.4 to 18.5 31	low low
benzyl alcohol 2-methylpropan-1-ol ethylbenzene	0.87 1 3.6	- - 79.43	low low low

#### 12.4 Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

#### 12.6 Endocrine disrupting properties

Not available.

#### 12.7 Other adverse effects

No known significant effects or critical hazards.

# **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### **13.1 Waste treatment methods**

Product

Code : 00393 SIGMACOVER 350 B	
SECTION 13: D	isposal considerations
Methods of dispos	<ul> <li>The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.</li> </ul>
Hazardous waste	: Yes.
<u>European waste c</u>	talogue (EWC)
Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
Packaging	
Methods of dispos	al : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Type of packag	ng European waste catalogue (EWC)
Container	15 01 06 mixed packaging
Special precaution	<ul> <li>This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, draine and source.</li> </ul>

# 14. Transport information

drains and sewers.

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number or ID number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3	3	3	3
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	No.	Yes.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.

Additional information			
ADR/RID	: None identified.		
Tunnel code	: (D/E)		
ADN	: The product is only regulated as an environmentally hazardous substance when transported in tank vessels.		
IMDG	: None identified.		
ΙΑΤΑ	: None identified.		

Code	: 00393217	Date of issue/Date of revision	: 10 January 2023
SIGMACOVE	R 350 BASE BLACK		

# 14. Transport information

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Maritime transport in** : Not applicable. bulk according to IMO instruments

### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Ozone depleting substances (1005/2009/EU)

Not listed.

#### Seveso Directive

This product is controlled under the Seveso Directive.

<u>Danger criteria</u>			
Category			
P5c			

15.2 Chemical safety assessment

: No Chemical Safety Assessment has been carried out.

# **SECTION 16: Other information**

✓ Indicates information that has changed from previously issued version.

#### Abbreviations and acronyms

ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number PBT = Persistent, Bioaccumulative and Toxic vPvB = Very Persistent and Very Bioaccumulative ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

IMDG = International Maritime Dangerous Goods

Code : 00393217 SIGMACOVER 350 BASE BLACK	Date of issue/Date of revision : 10 January 2023
SECTION 16: Other informat	tion
IATA = International Air Transport Associa	ation
Full text of abbreviated H statements	
H225 H226 H302 H304 H312 H315 H317 H318 H319 H332 H335 H336 H372 H373	<ul> <li>Highly flammable liquid and vapour.</li> <li>Flammable liquid and vapour.</li> <li>Harmful if swallowed.</li> <li>May be fatal if swallowed and enters airways.</li> <li>Harmful in contact with skin.</li> <li>Causes skin irritation.</li> <li>May cause an allergic skin reaction.</li> <li>Causes serious eye damage.</li> <li>Causes serious eye irritation.</li> <li>Harmful if inhaled.</li> <li>May cause respiratory irritation.</li> <li>May cause drowsiness or dizziness.</li> <li>Causes damage to organs through prolonged or repeated exposure</li> <li>May cause damage to organs through prolonged or repeated</li> </ul>
H411 H412 H413	exposure. Toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects. May cause long lasting harmful effects to aquatic life.
Full text of classifications [CLP/GHS]	
Acute Tox. 4 Aquatic Chronic 2 Aquatic Chronic 3 Aquatic Chronic 4	ACUTE TOXICITY - Category 4 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4

Hist	orv
11131	

Asp. Tox. 1

Eye Dam. 1

Flam. Liq. 2

Flam. Liq. 3

Skin Irrit. 2

Skin Sens. 1

STOT RE 1

STOT RE 2

STOT SE 3

Eye Irrit. 2

motory	
Date of issue/ Date of revision	: 10 January 2023
Date of previous issue	: 4 November 2022
Prepared by	: EHS
Version	: 2.01

#### <u>Disclaimer</u>

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

Category 1

Category 2

Category 3

ASPIRATION HAZARD - Category 1

FLAMMABLE LIQUIDS - Category 2

FLAMMABLE LIQUIDS - Category 3

SKIN SENSITISATION - Category 1

SKIN CORROSION/IRRITATION - Category 2

SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1

SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2

SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE -

SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE -

SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE -