# **SAFETY DATA SHEET**

Safety Data Sheet according to GB/T 16483-2008 and GB/T 17519-2013



Date of issue/Date of revision

Date of issue/Date of revision

11 January 2023

**Version 1** 

# Section 1. Chemical product and company identification

Product code : 00470112

Product name : AMERCOAT 220 SPECIAL COLOR
Product name : AMERCOAT 220 SPECIAL COLOR

Product type : Liquid.

#### Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Professional applications, Used by spraying.

Use of the substance/

mixture

: Coating.

**Uses advised against** 

: Not applicable.

Supplier's details : PPG Coatings (Kunshan) Co., Ltd

53 Jinyang Road, Lujia Town,

215331 Kunshan City, Jiangsu Province, P.R. China Tel: 86 512 57678859 Fax: 86 512 57678857

**Emergency telephone** number (with hours of

operation)

: 00 86 532 83889090

### Section 2. Hazards identification

Classification of the substance or mixture according to GB 13690-2009 and GB 30000-2013

### **Emergency overview**

Liquid. Various

May damage fertility or the unborn child.

Harmful to aquatic life.

IF exposed or concerned: Get medical advice or attention.

See Section 12 for environmental precautions.

Classification of the substance or mixture

: TOXIC TO REPRODUCTION - Category 1B AQUATIC HAZARD (ACUTE) - Category 3

Percentage of the mixture consisting of ingredient(s) of unknown hazards to the

aquatic environment: 31.9%

GHS label elements

Hazard pictograms



China Page: 1/12

**Product name AMERCOAT 220 SPECIAL COLOR** 

### Section 2. Hazards identification

Signal word : Danger

May damage fertility or the unborn child. **Hazard statements** 

Harmful to aquatic life.

**Precautionary statements** 

**Prevention** : Obtain special instructions before use. Do not handle until all safety precautions

have been read and understood. Wear protective gloves, protective clothing and

eye or face protection. Avoid release to the environment.

: IF exposed or concerned: Get medical advice or attention. Response

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

**Storage** : Store locked up.

**Disposal** : Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Physical and chemical

hazards

: No known significant effects or critical hazards.

**Health hazards** : May damage fertility or the unborn child.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : No specific data.

Inhalation : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

: Adverse symptoms may include the following: Ingestion

> reduced fetal weight increase in fetal deaths skeletal malformations

### Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

**Potential immediate** : Not available.

effects

**Potential delayed effects** : Not available.

Long term exposure

**Potential immediate** : Not available.

effects

**Potential delayed effects** : Not available.

**Environmental hazards** : Harmful to aquatic life.

Other hazards which do not : None known.

result in classification

China Page: 2/12

**Product name AMERCOAT 220 SPECIAL COLOR** 

# Section 3. Composition/information on ingredients

Substance/mixture : Mixture

#### **CAS** number/other identifiers

**CAS number** : Not applicable.

Ingredient name	%	CAS number
2-(2-methoxyethoxy)ethanol	1 - <10	111-77-3
isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol	1 - <10	25265-77-4
dibutyl phthalate	1 - <10	84-74-2
ammonia (more than 10%)	0.1 - <1	1336-21-6
nonylphenol ethoxylate	0.1 - <1	9016-45-9

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

### Section 4. First aid measures

### **Description of necessary first aid measures**

**Eye contact**: Remove contact lenses, irrigate copiously with clean, fresh water, holding the

eyelids apart for at least 10 minutes and seek immediate medical advice.

**Inhalation**: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

**Skin contact**: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognized skin cleanser. Do NOT use solvents or thinners.

Ingestion : If swallowed, seek medical advice immediately and show this container or label.

Keep person warm and at rest. Do NOT induce vomiting.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.

### Over-exposure signs/symptoms

Eye contact : No specific data.

**Inhalation** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

China Page: 3/12

**Product name AMERCOAT 220 SPECIAL COLOR** 

### Section 4. First aid measures

Ingestion

: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths

#### Indication of immediate medical attention and special treatment needed, if necessary

skeletal malformations

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments** 

: No specific treatment.

**Protection of first-aiders** 

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

### **Extinguishing media**

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

: None known.

media

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain

Hazardous thermal decomposition products

Decomposition products may include the following materials: carbon oxides metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode

### Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

China Page: 4/12

Product code 00470112

Date of issue 11 January 2023

**Version 1** 

**Product name AMERCOAT 220 SPECIAL COLOR** 

### Section 6. Accidental release measures

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions**: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### Methods and materials for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

**Precautions for safe** handling

: Put on appropriate personal protective equipment (see Section 8). Avoid exposure obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material. kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

including any incompatibilities

Conditions for safe storage, : Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

> China Page: 5/12

Date of issue 11 January 2023 **Version 1** 

**Product name AMERCOAT 220 SPECIAL COLOR** 

# Section 8. Exposure controls/personal protection

#### **Control parameters**

Product code 00470112

#### Occupational exposure limits

Ingredient name	Exposure limits
dibutyl phthalate	GBZ 2.1 (China, 8/2019).
	PC-TWA: 2.5 mg/m <sup>3</sup> 8 hours.
ammonia (more than 10%)	GBZ 2.1 (China, 8/2019). [Ammonia]
	PC-TWA: 20 mg/m³ 8 hours.
	PC-STEL: 30 mg/m³ 15 minutes.

### Recommended monitoring procedures

: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

#### **Environmental exposure** controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

# Eye protection **Skin protection**

Safety glasses with side shields.

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer. check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Gloves** 

: For prolonged or repeated handling, use the following type of gloves:

Recommended: Viton®

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

China Page: 6/12

**Product name AMERCOAT 220 SPECIAL COLOR** 

# Section 8. Exposure controls/personal protection

**Respiratory protection** 

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

# Section 9. Physical and chemical properties

**Appearance** 

**Physical state** : Liquid. Color : Various

**Boiling point** : >37.78°C (>100°F)

Flash point : Closed cup: Not applicable.

Lower and upper explosive

(flammable) limits

: Greatest known range: Lower: 1.6% Upper: 18.1% (2-(2-methoxyethoxy)ethanol)

**Relative density** : 1.17

Media Result Solubility(ies)

cold water Partially soluble

**Viscosity** : Kinematic (40°C): >21 mm<sup>2</sup>/s

### Section 10. Stability and reactivity

: No specific test data related to reactivity available for this product or its ingredients. Reactivity

**Chemical stability** : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition

products.

Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents, strong alkalis, strong acids.

**Hazardous decomposition** 

products

: Depending on conditions, decomposition products may include the following

materials: carbon oxides metal oxide/oxides

# **Section 11. Toxicological information**

Information on toxicological effects

**Acute toxicity** 

China Page: 7/12

**Product name AMERCOAT 220 SPECIAL COLOR** 

# **Section 11. Toxicological information**

Product/ingredient name	Result	Species	Dose	Exposure
2-(2-methoxyethoxy)ethanol	LD50 Oral	Rat	9.2 g/kg	-
isobutyric acid, monoester with	LD50 Dermal	Rabbit	>15.2 g/kg	-
2,2,4-trimethylpentane-1,3-diol				
• •	LD50 Oral	Rat	6.5 g/kg	-
dibutyl phthalate	LD50 Dermal	Rabbit	20000 mg/kg	-
	LD50 Oral	Rat	7499 mg/kg	-
ammonia (more than 10%)	LD50 Oral	Rat	350 mg/kg	-
nonylphenol ethoxylate	LD50 Dermal	Rabbit	2.52 g/kg	-
	LD50 Oral	Rat	4.29 g/kg	-

### **Irritation/Corrosion**

Not available.

#### **Sensitization**

Not available.

### **Mutagenicity**

Not available.

### **Carcinogenicity**

Not available.

### **Reproductive toxicity**

Product/ingredient name	Maternal toxicity	Fertility	Development toxin	Species	Dose	Exposure
dibutyl phthalate	-	-	-	Rat	Oral	-

#### **Teratogenicity**

Not available.

### Specific target organ toxicity (single exposure)

Name		Route of exposure	Target organs
ammonia (more than 10%)	Category 3		Respiratory tract irritation

### Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
nonylphenol ethoxylate	Category 2	-	-

### **Aspiration hazard**

Not available.

Information on the likely

routes of exposure

: Not available.

**Potential acute health effects** 

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.

China Page: 8/12

**Product name AMERCOAT 220 SPECIAL COLOR** 

### **Section 11. Toxicological information**

**Ingestion** : No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : No specific data.

**Inhalation** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

**Ingestion** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

#### Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

Potential immediate

effects

: Not available.

Potential delayed effects : Not available.

**Long term exposure** 

**Potential immediate** 

: Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

General : No known significant effects or critical hazards.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

**Reproductive toxicity**: May damage fertility or the unborn child.

### **Numerical measures of toxicity**

### **Acute toxicity estimates**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
2-(2-methoxyethoxy)ethanol isobutyric acid, monoester with	9200	N/A	N/A	N/A	N/A
	6500	N/A	N/A	N/A	N/A
2,2,4-trimethylpentane-1,3-diol dibutyl phthalate	7499	20000	N/A	N/A	N/A
ammonia (more than 10%) nonylphenol ethoxylate	350	N/A	N/A	N/A	N/A
	4290	2520	N/A	N/A	N/A

#### Other information :

China Page: 9/12

**Product name AMERCOAT 220 SPECIAL COLOR** 

# **Section 11. Toxicological information**

Sanding and grinding dusts may be harmful if inhaled.

# Section 12. Ecological information

### **Toxicity**

Product/ingredient name	Result	Species	Exposure
isobutyric acid, monoester with 2,2,4-trimethylpentane- 1,3-diol	Acute LC50 33 mg/l	Fish	96 hours
dibutyl phthalate	LC50 0.85 mg/l	Fish	96 hours
	Acute EC50 0.6 mg/l	Algae - Dunaliella salina - Exponential growth phase	96 hours
	Acute LC50 2.83 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Chronic NOEC 0.4 mg/l	Algae - Dunaliella salina - Exponential growth phase	96 hours
nonylphenol ethoxylate	Chronic NOEC 0.07 mg/l Fresh water Acute LC50 1.47 mg/l Acute LC50 2.318 mg/l Fresh water	Daphnia - Daphnia magna Crustaceans Daphnia - Daphnia magna	21 days 48 hours 48 hours

### Persistence/degradability

Product/ingredient name	Test	Result	Dose		Inoculum
isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol	OECD 301B	>76 % - Readily - 28 days	-		-
Product/ingredient name	Aquatic half-life	Photolysis		Biodeg	radability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
isobutyric acid, monoester	-	-	Readily
with 2,2,4-trimethylpentane-			
1,3-diol			
dibutyl phthalate	-	-	Readily

### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
- (- :::::::)	-0.47	-	low
isobutyric acid, monoester with 2,2,4-trimethylpentane-	3.2	-	low
1,3-diol			
dibutyl phthalate	4.46	165.96	low

**Mobility in soil** 

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

China Page: 10/12

**Product name AMERCOAT 220 SPECIAL COLOR** 

# Section 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# **Section 14. Transport information**

	China	UN	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-
Transport hazard class(es)	-	-	-	-
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.

#### **Additional information**

CN : None identified. UN : None identified. **IMDG** : None identified. IATA : None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according: Not applicable. to IMO instruments

China Page: 11/12

**Product name AMERCOAT 220 SPECIAL COLOR** 

# Section 15. Regulatory information

China inventory (IECSC)

: All components are listed or exempted.

References

: Production Safety Law of the People's Republic of China

Code of Occupational Disease Prevention of the People's Republic of China

Environmental Protection Law of the People's Republic of China

Fire Control Law of the People's Republic of China

Regulations on the Control over Safety of Dangerous Chemicals

Occupational exposure limits for hazardous agents in the workplace chemical

hazardous agents (GBZ2.1)

General rule for classification and hazard communication of chemicals (GB13690) Safety data sheet for chemical products - Content and order of sections (GB/

T16483)

Guidance on the compilation of safety data sheet for chemical products (GB/

T17519)

General rule for preparation of precautionary label for chemicals (GB15258)

Safety rules for classification, precautionary labeling and precautionary statements

of chemicals (GB30000.2-29)

### Section 16. Other information

**History** 

Date of issue/Date of

revision

Date of previous issue

Version

: 11 January 2023

: No previous validation

: 1 EHS

Key to abbreviations

: ADN = European Provisions concerning the International Carriage of Dangerous

Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of

Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

RID = The Regulations concerning the International Carriage of Dangerous Goods

by Rail

UN = United Nations

✓ Indicates information that has changed from previously issued version.

#### **Notice to reader**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

China Page: 12/12