# SAFETY DATA SHEET



Date of issue 2/2/2023 (month/day/year)

Version 5

# Section 1. Chemical product and company identification

A. Product name : PPG HI-TEMP 808 WHITE

Product code : 00383831

B. Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Professional applications, Used by spraying.

Use of the substance/

mixture

: Coating.

**Uses advised against**: Product is not intended, labelled or packaged for consumer use.

C. Supplier's or Importer's

information

**Email Address** 

: PPG SSC (680-090)

19, Yeocheon-ro 217beon-gil, Nam-gu,

Ulsan, Korea

Tel: +82-52-210-8222 Korea.MSDS@PPG.COM

**Emergency telephone** 

number:

: +82-52-210-8222

# Section 2. Hazards identification

A. Hazard classification : CARCINOGENICITY - Category 1A

AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 2

This product is classified in accordance with the Industrial Safety and Health Act and the Chemical Control Act.

B. GHS label elements, including precautionary statements

Symbol :





Signal word : Danger

**Hazard statements** : ► 350 - May cause cancer.

H400 - Very toxic to aquatic life.

H411 - Toxic to aquatic life with long lasting effects.

**Precautionary statements** 

Prevention : P202 - Do not handle until all safety precautions have been read and understood.

P280 - Wear protective gloves, protective clothing and eye or face protection.

P273 - Avoid release to the environment.

Response : P391 - Collect spillage.

P308 + P313 - IF exposed or concerned: Get medical advice or attention.

Korea (GHS) Page: 1/12

**Product name PPG HI-TEMP 808 WHITE** 

### Section 2. Hazards identification

**Storage** 

: Not applicable.

**Disposal** 

: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

C. Other hazards which do

: None known.

not result in classification

# Section 3. Composition/information on ingredients

#### **CAS** number/other identifiers

**CAS number** : Not applicable.

Chemical name	Common name	Identifiers	%
intanium dioxide silicon dioxide zinc pyrithione 1,2-benzisothiazol-3(2H)-one 3-iodo-2-propynyl butylcarbamate ammonia crystalline silica, respirable powder (<10 microns)	TITANIUM DIOXIDE SILICA pyrithione zinc 1,2-BENZISOTHIAZOLONE 3-lodo-2-propynyl butylcarbamate AMMONIUM HYDROXIDE QUARTZ (<10 microns)	CAS: 13463-67-7 CAS: 7631-86-9 CAS: 13463-41-7 CAS: 2634-33-5 CAS: 55406-53-6 CAS: 1336-21-6 CAS: 14808-60-7	5 - <10 1 - <5 0.1 - <1 0.1 - <1 0.1 - <1 0.1 - <1

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

5	ection 4. First aid	ן נ	measures
Α.	Eye contact	:	Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
В.	Skin contact	:	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
C.	Inhalation	:	Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
D.	Ingestion	:	If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
E.	Notes to physician	:	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
	Specific treatments	:	No specific treatment.
	Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Korea (GHS) Page: 2/12

Date of issue 2/2/2023 (month/day/year) **Version 5** 

**Product name PPG HI-TEMP 808 WHITE** 

#### Section 4. First aid measures

See toxicological information (Section 11)

### Section 5. Fire-fighting measures

A. Extinguishing media

Product code 00383831

Suitable extinguishing

media

**Unsuitable** extinguishing media : Use an extinguishing agent suitable for the surrounding fire.

: None known.

B. Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is very toxic to aquatic life. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous thermal** decomposition products Decomposition products may include the following materials:

carbon oxides metal oxide/oxides

C. Special equipment for fire-fighting

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

mode.

**Fire-fighting procedures** 

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without

suitable training.

### Section 6. Accidental release measures

A. Personal precautions, protective equipment and emergency procedures

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**B. Environmental** precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways. drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

#### C. Methods and materials for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section

> Korea (GHS) Page: 3/12

Date of issue 2/2/2023 (month/day/year) **Version 5** 

**Product name PPG HI-TEMP 808 WHITE** 

#### Section 6. Accidental release measures

13 for waste disposal.

### Section 7. Handling and storage

A. Precautions for safe handling

Product code 00383831

- : Fut on appropriate personal protective equipment (see Section 8). Avoid exposure obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- B. Conditions for safe storage, including any incompatibilities
- Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### Section 8. Exposure controls/personal protection

A. Occupational exposure limits

Ingredient name	Exposure limits
intanium dioxide	Ministry of Employment and Labor (Republic of Korea, 1/2020).  TWA: 10 mg/m³ 8 hours. Form: total dust with less than 1% of free SiO2
ammonia	Ministry of Employment and Labor (Republic of Korea, 1/2020). [Ammonia] STEL: 35 ppm 15 minutes. TWA: 25 ppm 8 hours.
crystalline silica, respirable powder (<10 microns)	Ministry of Employment and Labor (Republic of Korea, 1/2020).  TWA: 0.05 mg/m³ 8 hours. Form: Respirable fraction

Recommended monitoring procedures

- : Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
- controls
- B. Appropriate engineering: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**Environmental** exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

C. Personal protective equipment

Korea (GHS) Page: 4/12 Date of issue 2/2/2023 (month/day/year) Version 5

**Product name PPG HI-TEMP 808 WHITE** 

Product code 00383831

#### Product name PPG HI-TEMP 606 WHITE

### Section 8. Exposure controls/personal protection

Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the

hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed

respirator complying with an approved standard if a risk assessment indicates this is

necessary.

**Eye protection** : Safety glasses with side shields.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer,

check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately

estimated.

Gloves : butyl rubber

Body protection : Personal protective equipment for the body should be selected based on the task

being performed and the risks involved and should be approved by a specialist

before handling this product.

**Hygiene measures** : **₩**ash hands, forearms and face thoroughly after handling chemical products, before

eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing.

Wash contaminated clothing before reusing. Ensure that eyewash stations and

safety showers are close to the workstation location.

### Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

A. Appearance

Physical state : Liquid.
Color : White.

B. Odor : Characteristic.
C. Odor threshold : Not available.
D. pH : Not available.
E. Melting/freezing point : Not available.
F. Boiling point/boiling : >37.78°C (>100°F)

range

G. Flash point : Closed cup: Not applicable.

H. Evaporation rate : Not available.
I. Flammability (solid, gas) : Not available.
J. Lower and upper : Not available.

J. Lower and upper explosive (flammable)

limits

K. Vapor pressure

	Vapor Pressure at 20°C			Vapor pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
water	23.8	3.2				

Korea (GHS) Page: 5/12

**Product name PPG HI-TEMP 808 WHITE** 

### Section 9. Physical and chemical properties

Media Result L. Solubility(ies) cold water Soluble

Not available. Solubility in water Vapor density Not available.

Relative density 0.6 N.

Partition coefficient: n-

octanol/water

: Not applicable.

**Auto-ignition** 

: Not available.

temperature

**Decomposition** : Not available.

temperature

**Viscosity** : Kinematic (40°C (104°F)): >21 mm<sup>2</sup>/s (>21 cSt)

Flow time (ISO 2431) Not available. **Molecular weight** Not applicable.

### Section 10. Stability and reactivity

A. Chemical stability : The product is stable.

**Possibility of hazardous** reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

: When exposed to high temperatures may produce hazardous decomposition B. Conditions to avoid

products.

C. Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents, strong alkalis, strong acids.

: Depending on conditions, decomposition products may include the following D. Hazardous

materials: carbon oxides metal oxide/oxides decomposition products

### **Section 11. Toxicological information**

A. Information on the likely : Not available. routes of exposure

#### Potential acute health effects

Inhalation : No known significant effects or critical hazards. Ingestion : No known significant effects or critical hazards. **Skin contact** : No known significant effects or critical hazards. : No known significant effects or critical hazards. Eye contact

#### Over-exposure signs/symptoms

Inhalation : No specific data. Ingestion : No specific data. **Skin contact** : No specific data. : No specific data. **Eye contact** 

Korea (GHS) Page: 6/12

**Product name PPG HI-TEMP 808 WHITE** 

# **Section 11. Toxicological information**

#### B. Health hazards

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Manium dioxide	LC50 Inhalation Dusts and mists	Rat	>6.82 mg/l	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
silicon dioxide	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-
zinc pyrithione	LC50 Inhalation Dusts and mists	Rat	0.14 mg/l	4 hours
	LD50 Dermal	Rabbit	>2 g/kg	-
	LD50 Oral	Rat	177 mg/kg	-
1,2-benzisothiazol-3(2H)-one	LC50 Inhalation Dusts and mists	Rat	0.4 mg/l	4 hours
	LD50 Oral	Rat	1020 mg/kg	-
3-iodo-2-propynyl butylcarbamate	LC50 Inhalation Dusts and	Rat	0.67 mg/l	4 hours
	mists			
	LD50 Dermal	Rabbit	>2 g/kg	-
	LD50 Oral	Rat	1470 mg/kg	-
ammonia	LD50 Oral	Rat	350 mg/kg	-

**Conclusion/Summary**: There are no data available on the mixture itself.

#### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
1.	Eyes - Cornea opacity Eyes - Severe irritant	Rabbit Rabbit	4 -	24 hours -	24 hours -

**Conclusion/Summary** 

Skin : There are no data available on the mixture itself.
 Eyes : There are no data available on the mixture itself.
 Respiratory : There are no data available on the mixture itself.

#### **Sensitization**

Product/ingredient name	Route of exposure	Species	Result
7,2-benzisothiazol-3(2H)-one	skin	Guinea pig	Sensitizing

**Conclusion/Summary** 

Skin: There are no data available on the mixture itself.Respiratory: There are no data available on the mixture itself.

**Mutagenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Carcinogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

#### **Reproductive toxicity**

Korea (GHS) Page: 7/12

**Product name PPG HI-TEMP 808 WHITE** 

# **Section 11. Toxicological information**

**Conclusion/Summary**: There are no data available on the mixture itself.

**Teratogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

#### Specific target organ toxicity (single exposure)

Name	Classification	Route of exposure	Target organs
ammonia	Category 3	-	Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

Name	Classification	Route of exposure	Target organs
<ul><li>✓nc pyrithione</li><li>3-iodo-2-propynyl butylcarbamate</li></ul>	Category 1 Category 1	-	- trachea

#### **Aspiration hazard**

Not available.

#### Potential chronic health effects

General: No known significant effects or critical hazards.

**Carcinogenicity**: May cause cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity: No known significant effects or critical hazards.Reproductive toxicity: No known significant effects or critical hazards.

#### **Additional information**

Sanding and grinding dusts may be harmful if inhaled.

Chemical name	Identifiers	GHS Classification
manium dioxide	CAS: 13463-67-7	CARCINOGENICITY - Category 2
silicon dioxide	CAS: 7631-86-9	Not classified.
zinc pyrithione	CAS: 13463-41-7	ACUTE TOXICITY (oral) - Category 3
		ACUTE TOXICITY (inhalation) - Category 2
		SERIOUS EYE DAMAGE - Category 1
		TOXIC TO REPRODUCTION - Category 2
		SPECIFIC TARGET ORGAN TOXICITY
		(REPEATED EXPOSURE) - Category 1
		AQUATIC HAZARD (ACUTE) - Category 1
		AQUATIC HAZARD (LONG-TERM) - Category 1
1,2-benzisothiazol-3(2H)-one	CAS: 2634-33-5	ACUTE TOXICITY (oral) - Category 4
		ACUTE TOXICITY (inhalation) - Category 2
		SKIN IRRITATION - Category 2
		SERIOUS EYE DAMAGE - Category 1
		SKIN SENSITIZATION - Category 1
		AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1
3 iodo 2 propynyl hutylearhamete	CAS: 55406-53-6	ACUTE TOXICITY (oral) - Category 4
3-iodo-2-propynyl butylcarbamate	CAS. 55400-55-0	ACUTE TOXICITY (oral) - Category 4  ACUTE TOXICITY (inhalation) - Category 2
		ACOTE TOXICITY (IIIIIaiation) - Category 2

Korea (GHS) Page: 8/12

Product code 00383831 Product name PPG HI-TEMP 808 WHIT		ssue 2/2/2023 (month/day/year)	Version 5			
Section 11. Toxicological information						
ammonia	CAS: 1336-21-6	SERIOUS EYE DAMAGE - Categ SKIN SENSITIZATION - Category SPECIFIC TARGET ORGAN TOX (REPEATED EXPOSURE) - Cate AQUATIC HAZARD (ACUTE) - CA AQUATIC HAZARD (LONG-TERI SERIOUS EYE DAMAGE - Categ SPECIFIC TARGET ORGAN TOX EXPOSURE) (Respiratory tract irr Category 3 AQUATIC HAZARD (ACUTE) - CA	v 1B KICITY gory 1 ategory 1 M) - Category 1 ory 1 KICITY (SINGLE itation) -			
crystalline silica, respirable powder (<10 microns)	CAS: 14808-60-7	CARCINOGENICITY - Category 1				

# Section 12. Ecological information

### A. **Ecotoxicity**

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute LC50 >100 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
silicon dioxide	Acute EC50 2.2 g/L Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 >10000 mg/l	Fish	96 hours
	Chronic NOEC 12.5 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	21 days
zinc pyrithione	Acute EC50 5.513 µg/l Marine water	Algae - Nitzschia pungens	96 hours
	Acute LC50 0.0082 mg/l	Daphnia	48 hours
	Chronic NOEC 1.889 µg/l Marine water	Algae - Nitzschia pungens	96 hours
	Chronic NOEC 0.0027 mg/l	Daphnia	21 days
1,2-benzisothiazol-3(2H)- one	Acute EC50 0.11 mg/l	Algae	72 hours
	Chronic NOEC 0.09 mg/l	Fish	28 days
3-iodo-2-propynyl butylcarbamate	Acute EC50 0.186 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 0.067 mg/l	Fish	96 hours
	Chronic NOEC 0.049 mg/l	Fish	96 hours

### B. Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
<ul><li>Znc pyrithione</li><li>3-iodo-2-propynyl</li><li>butylcarbamate</li></ul>		39 % - 28 days 25 % - Inherent - 28 days	-	-

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
<ul><li>✓nc pyrithione</li><li>1,2-benzisothiazol-3(2H)-</li></ul>	-	50%; < 28 day(s)	Not readily Readily
one 3-iodo-2-propynyl butylcarbamate	-	-	Inherent

### C. Bioaccumulative potential

Korea (GHS) Page: 9/12

**Product name PPG HI-TEMP 808 WHITE** 

# **Section 12. Ecological information**

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
1, 1, 3	0.9 0.7	0.9	low low
one			

D. Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

E. Other adverse effects : No known significant effects or critical hazards.

### Section 13. Disposal considerations

- A. Disposal methods
- : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
- **B.** Disposal precautions
- : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# **Section 14. Transport information**

	UN	IMDG	IATA
A. UN number	UN3082	UN3082	UN3082
B. UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (pyrithione zinc)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (pyrithione zinc)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (pyrithione zinc)
C. Transport hazard class(es)	9	9	9
D. Packing group	III	III	III
Environmental hazards	Yes.	Yes.	Yes.
E. Marine pollutant substances	Not applicable.	(pyrithione zinc)	Not applicable.

#### **Additional information**

UN

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

Korea (GHS) Page: 10/12

**Product name PPG HI-TEMP 808 WHITE** 

### **Section 14. Transport information**

**IMDG** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg,

provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

**IATA** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

# F. Special precaution which a user to be aware of or needs to comply with in connection with transport or transportation

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable.

to IMO instruments

# Section 15. Regulatory information

#### A. Regulation according to ISHA

**ISHA article 117** : None of the components are listed.

(Harmful substances prohibited from manufacture)

**ISHA article 118** : None of the components are listed.

(Harmful substances requiring permission)

Article 2 of Youth Protection : It is not allowed to sell to persons under the age of 19.

Act on Substances Hazardous to Youth

**Exposure Limits of Chemical Substances and Physical Factors** 

The following components have an OEL:

titanium dioxide ammonia

crystalline silica, respirable powder (<10 microns)

ISHA Enforcement Regs : None of the components are listed.

Annex 19 (Exposure standards established for harmful factors)

ISHA Enforcement Regs : The following components are listed: titanium dioxide, silica

Annex 21 (Harmful factors subject to Work

**Environment Measurement**)

**ISHA Enforcement Regs**: None of the components are listed.

Annex 22 (Harmful Factors Subject to Special Health Check-

up)

control)

Standard of Industrial Safety and Health Annex 12 (Hazardous substances subject to : The following components are listed: titanium dioxide

Page: 11/12

Korea (GHS)

**Product name PPG HI-TEMP 808 WHITE** 

### Section 15. Regulatory information

**B.** Regulation according to Chemicals Control Act

Article 11 (TRI) : None of the components are listed.

Article 18 Prohibited (K-

**Reach Article 27)** 

: None of the components are listed.

**Article 19 Subject to** 

authorization (K-Reach Article 25)

: None of the components are listed.

Article 20 Restricted (K-

Reach Article 27)

: None of the components are listed.

**Article 20 Toxic** Chemicals (K-Reach

Article 20)

: Not applicable

**Korea inventory Article 39 (Accident**  : All components are listed or exempted. : None of the components are listed.

**Precaution Chemicals**) C. <u>Dangerous Materials</u>

Safety Management Act

: Not applicable.

D. Wastes regulation

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

E. Regulation according to other foreign laws

Safety, health and environmental regulations specific for

the product

: No known specific national and/or regional regulations applicable to this product

(including its ingredients).

## Section 16. Other information

A. References : Korean Ministry of Environment; Chemical Control Act

Korean Ministry of Labor; Industrial Safety and Health Act

**NIER Notice** 

Registry of Toxic Effects of Chemical Substances (RTECS)

U.S. Environmental Protection Agency, AQUIRE (Aquatic toxicity Information

Retrieval) ECOTOX Database System.

B. Date of issue/Date of

revision

: 2/2/2023

C. Version : 5 : EHS **Prepared by** 

D. Other

Indicates information that has changed from previously issued version.

#### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

> Korea (GHS) Page: 12/12