# **SAFETY DATA SHEET**



## Conforms to Official Mexican Standard NOM-018-STPS-2015

Date of revision 23 February 2023

Version 4

Date of issue 23 February 2023

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

	-
Product name	: PSX 700 COLORANT 42 OXIDE RED
Product code	: 00293926
Other means of identification	: Not applicable.
Product type	: Liquid.
Relevant identified uses of	the substance or mixture and uses advised against
Product use	: Professional applications, Used by spraying.
Use of the substance/ mixture	: Coating.
Uses advised against	: Not applicable.
Manufacturer	: PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272
<u>Emergency telephone</u> <u>number</u>	<ul> <li>(412) 434-4515 (U.S.)</li> <li>(514) 645-1320 (Canada)</li> <li>SETIQ Interior de la República: 800-00-214-00 (México)</li> <li>SETIQ Ciudad de México: (55) 5559-1588 (México)</li> </ul>
Technical Phone Number	: 888-977-4762

# **SECTION 2: Hazards identification**

Classification of the substance or mixture	: TOXIC TO REPRODUCTION - Category 2
	Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 54.1% (oral), 97.7% (dermal), 61% (inhalation)
GHS label elements	
Hazard pictograms	:
Signal word	: Warning
Hazard statements	: 📕 361 - Suspected of damaging fertility or the unborn child.
Precautionary statements	

## Product name PSX 700 COLORANT 42 OXIDE RED

## **SECTION 2: Hazards identification**

Prevention	:	<ul> <li>P201 - Obtain special instructions before use.</li> <li>P202 - Do not handle until all safety precautions have been read and understood.</li> <li>P280 - Wear protective gloves, protective clothing and eye or face protection.</li> </ul>
Response	:	₱308 + P313 - IF exposed or concerned: Get medical advice or attention.
Storage	:	P405 - Store locked up.
Disposal	:	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Other hazards which do not result in classification	:	Sanding and grinding dusts may be harmful if inhaled. Trimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness. Emits toxic fumes when heated.

See toxicological information (Section 11)

## **SECTION 3: Composition/information on ingredients**

Substance/mixture	: Mixture
Product name	: PSX 700 COLORANT 42 OXIDE RED
Other means of identification	: Not applicable.

Ingredient name	%	CAS number
	≥20 - ≤50 ≥1.0 - ≤5.0 <1.0	1309-37-1 68186-90-3 108-88-3

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## **SECTION 4: First aid measures**

#### Description of necessary first aid measures

Eye contact	<ul> <li>Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.</li> </ul>
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	<ul> <li>If swallowed, seek medical advice immediately and show this container or label.</li> <li>Keep person warm and at rest. Do NOT induce vomiting.</li> </ul>

Most important symptoms/effects, acute and delayed			
Potential acute health effects			
Eye contact :	No known significant effects or critical hazards.		
Inhalation :	No known significant effects or critical hazards.		
Skin contact :	No known significant effects or critical hazards.		
Ingestion :	No known significant effects or critical hazards.		

#### **Over-exposure signs/symptoms**

## Product name PSX 700 COLORANT 42 OXIDE RED

## **SECTION 4: First aid measures**

See toxicological information (Section 11)

Indication of immediate medical attention and special treatment needed, if necessary		
Notes to physician	:	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	:	No specific treatment.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

## **SECTION 5: Firefighting measures**

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides halogenated compounds metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	<ul> <li>Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.</li> </ul>

# **SECTION 6: Accidental release measures**

Personal precautions, protective equipment and emergency procedures		
For non-emergency personnel		No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

## Product name PSX 700 COLORANT 42 OXIDE RED

## **SECTION 6: Accidental release measures**

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# SECTION 7: Handling and storage

Precautions for safe handling	1	
Protective measures	-	Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Special precautions	:	Ingestion of product or cured coating may be harmful. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Vapors are heavier than air and may spread along floors. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Product name PSX 700 COLORANT 42 OXIDE RED

# **SECTION 8: Exposure controls/personal protection**

#### **Control parameters**

#### **Occupational exposure limits**

Ingredient name	Exposure limits
diron trioxide chrome antimony titanium buff rutile toluene	<ul> <li>NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 5 mg/m<sup>3</sup> 8 hours. Form: Respirable fraction</li> <li>NOM-010-STPS-2014 (Mexico, 4/2016).</li> <li>[Antimony and compounds]</li> <li>TWA: 0.5 mg/m<sup>3</sup>, (as Sb) 8 hours.</li> <li>NOM-010-STPS-2014 (Mexico, 4/2016).</li> <li>TWA: 20 ppm 8 hours.</li> </ul>
C       = Ceiling Limit         IPEL       = Internal Permissible Exposure Limit	STEL = Short term exposure limit TLV = Threshold Limit Value TWA = Time Weighted Average

#### Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures	:	Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	:	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measure	es	
Hygiene measures		Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	1	Safety glasses with side shields.
Skin protection		
Hand protection	-	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	1	For prolonged or repeated handling, use the following type of gloves:
		Recommended: nitrile rubber
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

## Product name PSX 700 COLORANT 42 OXIDE RED

# **SECTION 8: Exposure controls/personal protection**

Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

# **SECTION 9: Physical and chemical properties**

<u>Appearance</u>		
Physical state	:	Liquid.
Color	:	Red.
Odor	:	Aromatic.
Odor threshold	:	Not available.
Molecular weight	4	Not applicable.
рН	÷	Not applicable.
Melting point		Not available.
Boiling point	4	>37.78°C (>100°F)
Flash point	1	Closed cup: Not applicable.
Auto-ignition temperature	1	Not available.
Decomposition temperature	1	Not available.
Flammability		Not available.
Lower and upper explosive (flammable) limits	1	Not available.
Evaporation rate	:	Not available.
Vapor pressure	:	Not available.
Vapor density	:	Not available.
Relative density	:	1.69
Density(lbs / gal)	:	14.1
		Media Result
Solubility(ies)	1	old water Not soluble
Solubility in water	:	Not available.
Partition coefficient: n- octanol/water	1	Not applicable.
Viscosity	:	Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)
Volatility	:	1% (v/v), 0.591% (w/w)
% Solid. (w/w)	1	99.409

# **SECTION 10: Stability and reactivity**

	Mexico Page: 6/12
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Chemical stability	: The product is stable.
Reactivity	: No specific test data related to reactivity available for this product or its ingredients.

## Product name PSX 700 COLORANT 42 OXIDE RED

# **SECTION 10: Stability and reactivity**

Conditions to avoid	:	When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Incompatible materials	:	Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	:	Depending on conditions, decomposition products may include the following materials carbon oxides nitrogen oxides halogenated compounds metal oxide/oxides

# **SECTION 11: Toxicological information**

## Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result		Species	Dose	Exposure	
díiron trioxide	LC50 Inha	lation Dusts and mists	Rat	>5 mg/l	4 hours	
	LD50 Oral		Rat	10 g/kg	-	
chrome antimony titanium buff rutile	LD50 Oral		Rat	10 g/kg	-	
toluene		lation Vapor	Rat	49 g/m³	4 hours	
	LD50 Dern		Rabbit	8.39 g/kg	-	
	LD50 Oral		Rat	5580 mg/kg	-	
Conclusion/Summary	: There a	re no data available on	the mixture itse	elf.		
Irritation/Corrosion						
Conclusion/Summary						
Skin	: There a	re no data available on	the mixture itse	elf.		
Eyes	: There a	: There are no data available on the mixture itself.				
Respiratory	: There a	re no data available on	the mixture itse	elf.		
Sensitization						
Conclusion/Summary						
Skin	: There a	re no data available on	the mixture itse	elf.		
Respiratory	: There a	re no data available on	the mixture itse	elf.		
<u>Mutagenicity</u>						
Conclusion/Summary	: There a	re no data available on	the mixture itse	elf.		
Carcinogenicity						
Conclusion/Summary	: There a	re no data available on	the mixture itse	elf.		
<b>Classification</b>						
Product/ingredient name	OSHA	IARC NTP				
diiron trioxide	-	3 -				
chrome antimony titanium buff rutile	-	3 -				
titanium dioxide	_	2B -				

Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4 NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen OSHA: + Not listed/not regulated: -

## Product name PSX 700 COLORANT 42 OXIDE RED

## **SECTION 11: Toxicological information**

## **Reproductive toxicity**

**Conclusion/Summary** 

: There are no data available on the mixture itself.

#### **Teratogenicity**

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
toluene	Category 3	-	Narcotic effects

#### Specific target organ toxicity (repeated exposure)

Name		Category	Route of exposure	Target organs
toluene		Category 2	-	-
Target organs	: Contains material which c tract, skin, eyes. Contains material which n	Ū	0 0	

cardiovascular system.

#### Aspiration hazard

Name	Result
toluene	ASPIRATION HAZARD - Category 1

#### Information on the likely routes of exposure

#### Potential acute health effects

: No known significant effects or critical hazards.
: No known significant effects or critical hazards.
: No known significant effects or critical hazards.
: No known significant effects or critical hazards.
<u>ms</u>
: No specific data.
: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
<u>0</u>

Delayed and immediate effects and also chronic effects from short and long term exposure

## Product name PSX 700 COLORANT 42 OXIDE RED

## **SECTION 11: Toxicological information**

Conclusion/Summary	:	There are no data available on the mixture itself. Trimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness. For many products, TiO2 is utilized as a raw material in a liquid coating formulation. In this case, the TiO2 particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of TiO2 when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/or engineering controls (see Section 8). If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.
Short term exposure		
Potential immediate effects	:	There are no data available on the mixture itself.
Potential delayed effects	:	There are no data available on the mixture itself.
Long term exposure		
Potential immediate effects	:	There are no data available on the mixture itself.
Potential delayed effects	:	There are no data available on the mixture itself.
Potential chronic health effe	octs	
General	:	No known significant effects or critical hazards.
Carcinogenicity	:	No known significant effects or critical hazards.

- **Mutagenicity** : No known significant effects or critical hazards.
- **Reproductive toxicity** : Suspected of damaging fertility or the unborn child.

## Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Miron trioxide	10000	N/A	N/A	N/A	N/A
chrome antimony titanium buff rutile	10000	N/A	N/A	N/A	N/A
toluene	5580	8390	N/A	49	N/A

# **SECTION 12: Ecological information**

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
diiron trioxide	Acute EC50 >100 mg/l	Daphnia	48 hours

#### Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
voluene	-	-	Readily

#### **Bioaccumulative potential**

	Mexico	Page: 9/12
--	--------	------------

Date of issue 23 February 2023 Version 4

Product name PSX 700 COLORANT 42 OXIDE RED

## **SECTION 12: Ecological information**

Product/ingredient name	LogPow	BCF	Potential
toluene	2.73	8.32	low

#### Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

Other adverse effects : No known significant effects or critical hazards.

## **SECTION 13: Disposal considerations**

Dispo	sal	meth	ods

S : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

# **SECTION 14: Transport information**

	Mexico Classification	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

#### Additional information

Mexico	: None identified.
IMDG	: None identified.
ΙΑΤΑ	: None identified.

Product name PSX 700 COLORANT 42 OXIDE RED

## **SECTION 14: Transport information**

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

## **SECTION 15: Regulatory information**

#### <u>Mexico</u>

Classification

Flammability : 0 Health : 2 Reactivity : 1

#### International regulations

**Montreal Protocol** 

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

## **SECTION 16: Other information**

Hazardous Material Information System (U.S.A.)

Health : 2 \* Flammability : 0 Physical hazards : 1 (\*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Date of previous issue Organization that prepared the SDS	: 1/3/2019 : EHS
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations
Indicator information that	has changed from providually issued version

Indicates information that has changed from previously issued version.

## Product name PSX 700 COLORANT 42 OXIDE RED

## **SECTION 16: Other information**

#### Notice to reader

The information, which is based on the current knowledge of the chemical substance or mixture and applies to appropriate safety precautions for the product, is deemed correct but is not exhaustive and will be used only as a guide.

#### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.