SAFETY DATA SHEET



The information in this Safety Data Sheet is required pursuant to GHS UN rev. 7

Date of issue/Date of revision 23 February 2023 Version 1.02

Section 1. Identification

Product code	: 00291656		
Product name	: PSX 700 A RAL 1021 RESIN		
Product type	: Liquid.		
Other means of identification Not available.			
Relevant identified uses of the substance or mixture and uses advised against			
Product use	Coating. Professional applications, Used by spraying.		
Uses advised against	: Product is not intended, labelled or packaged for consumer use.		
Supplier's information	: PPG Asian Paints Private Limited 6A Shanti Nagar Santa Cruz (East) Mumbai - 400055 India		
Emergency telephone number:	: +91 22 6815 8700		

Section 2. Hazards identification

Classification of the substance or mixture	 FLAMMABLE LIQUIDS - Category 4 ACUTE TOXICITY (dermal) - Category 5 SKIN SENSITISATION - Category 1 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 3 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 Percentage of the mixture consisting of ingredient(s) of unknown acute dermal toxicity: 68.4%
	Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 53.1%
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	: Combustible liquid. May be harmful in contact with skin. May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects.
Precautionary statements	

Section 2. Hazards identification

Prevention	:	Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment. Avoid breathing vapour. Contaminated work clothing should not be allowed out of the workplace.
Response	:	Take off contaminated clothing and wash it before reuse. IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention.
Storage	1	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Other hazards which do not	:	None known.

result in classification

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

CAS number/other identifiers

CAS number	: Not applicable.
	• • • • • • • • • • • • • • • • • • •

Ingredient name	%	CAS number
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	25 - <50	30583-72-3
barium sulfate	20 - <25	7727-43-7
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	1 - <3	41556-26-7
Polyamide	1 - <3	SUB100538
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	0.3 - <1	82919-37-7
toluene	0.3 - <1	108-88-3

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Section 4. First aid measures

Description of necessary first aid measuresEye contact: Remove contact lenses, irrigate copiously with clean, fresh water, holding the
eyelids apart for at least 10 minutes and seek immediate medical advice.Inhalation: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is
irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by
trained personnel.Skin contact: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and
water or use recognised skin cleanser. Do NOT use solvents or thinners.Ingestion: If swallowed, seek medical advice immediately and show the container or label.
Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and d	elayed

Potential acute health effects	2	
Eye contact	:	No known significant effects or critical hazards.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	÷	May be harmful in contact with skin. May cause an allergic skin reaction.

Section 4. First aid measures

Ingestion	: No known significant effects or critical hazards.		
Over-exposure signs/symp	<u>otoms</u>		
Eye contact	: No specific data.		
Inhalation	: No specific data.		
Skin contact	: Adverse symptoms may include the following: irritation redness		
Ingestion	: No specific data.		
Indication of immediate medical attention and special treatment needed, if necessary			
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.		
Specific treatments	: No specific treatment.		
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.		

See toxicological information (Section 11)

Section 5. Firefighting measures

	-
Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.
Specific hazards arising from the chemical	: Combustible liquid. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides sulfur oxides halogenated compounds metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

Section 6. Accidental release measures

For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
Methods and material for con	tainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Version 1.02

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name			Exposure limits
<mark>p</mark> ∕arium sulfate toluene			ACGIH TLV (United States, 1/2022). TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction ACGIH TLV (United States, 1/2022). Ototoxicant. TWA: 20 ppm 8 hours.
Recommended monitoring procedures	:		iate monitoring standards. Reference to nods for the determination of hazardous
Appropriate engineering controls	:	contaminants below any recommende also need to keep gas, vapour or dust limits. Use explosion-proof ventilation	Is to keep worker exposure to airborne of or statutory limits. The engineering controls concentrations below any lower explosive equipment.
Environmental exposure controls	:		
Individual protection measure	<u>es</u>		
Hygiene measures	:	eating, smoking and using the lavator Appropriate techniques should be use Contaminated work clothing should no	d to remove potentially contaminated clothing. of be allowed out of the workplace. Wash Ensure that eyewash stations and safety
Eye/face protection	:	Safety eyewear complying with an app assessment indicates this is necessar gases or dusts. If contact is possible,	proved standard should be used when a risk y to avoid exposure to liquid splashes, mists, the following protection should be worn, her degree of protection: safety glasses with
Hand protection	:	be worn at all times when handling ch this is necessary. Considering the par check during use that the gloves are s should be noted that the time to break	a complying with an approved standard should emical products if a risk assessment indicates rameters specified by the glove manufacturer, still retaining their protective properties. It through for any glove material may be rers. In the case of mixtures, consisting of e of the gloves cannot be accurately
Gloves	:	butyl rubber	
Body protection	:	Personal protective equipment for the	body should be selected based on the task d and should be approved by a specialist
Other skin protection	:	Appropriate footwear and any addition selected based on the task being perfe approved by a specialist before handli	ormed and the risks involved and should be

Product code 00291656 Product name PSX 700 A RAL 1021 RESIN

Section 8. Exposure controls/personal protection

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

<u>Appearance</u>					
Physical state	:	Liquid.			
Colour	:	Yellow.			
Odour	1	Aromatic.			
Odour threshold	:	Not available.			
Melting point/freezing point	:	Not available.			
Boiling point, initial boiling point, and boiling range	1	>37.78°C (>100°F)			
Flammability	:	Not available.			
Lower and upper explosive (flammable) limits	1	Not available.			
Flash point	:	Closed cup: 80°C (176°F)			
Auto-ignition temperature	:	Not available.	Not available.		
Decomposition temperature	:	Not available.			
рН	:	Not applicable.			
Viscosity	:	Kinematic (40°C): >21 mm	¹² /s		
Solubility(ies)		Media	Result		
Solubility(les)	ľ	old water	Not soluble		
Partition coefficient: n- octanol/water	1	Not applicable.			
Vapour pressure	:	Not available.			
Relative density	1	1.53			
Relative vapour density	:	Not available.			
Particle characteristics					
Median particle size	4	Not applicable.			
Evaporation rate	:	Not available.			
	_				

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

roduct code 00291656 roduct name PSX 700 A RA		ate of issue	23 February 2023	Version 1.02
Section 10. Stabili	ty and reactivity			
lazardous decomposition products	: Depending on conditions, deco materials: carbon oxides nitro metal oxide/oxides			
lazardous polymerisation	: Under normal conditions of sto occur.	orage and use	, hazardous polyme	risation will not
Section 11. LOXICO	ological information			
nformation on toxicological	•			
nformation on toxicological	•	Species	Dose	Exposure
nformation on toxicological Acute toxicity	effects Result LD50 Dermal	Rat	>2000 mg/kg	Exposure
nformation on toxicological Acute toxicity Product/ingredient name Parium sulfate	effects Result LD50 Dermal LD50 Oral	Rat Rat	>2000 mg/kg >5000 mg/kg	
nformation on toxicological Acute toxicity Product/ingredient name	effects Result LD50 Dermal	Rat	>2000 mg/kg	-
Acute toxicity Product/ingredient name arium sulfate bis(1,2,2,6,6-pentamethyl-	effects Result LD50 Dermal LD50 Oral	Rat Rat Rat	>2000 mg/kg >5000 mg/kg	-
Acute toxicity Product/ingredient name arium sulfate bis(1,2,2,6,6-pentamethyl- 4-piperidyl) sebacate	effects Result LD50 Dermal LD50 Oral LD50 Oral	Rat Rat Rat	>2000 mg/kg >5000 mg/kg 3.125 g/kg	-
Acute toxicity Product/ingredient name Parium sulfate bis(1,2,2,6,6-pentamethyl- 4-piperidyl) sebacate	effects Result LD50 Dermal LD50 Oral LD50 Oral LD50 Oral LC50 Inhalation Dusts and mists	Rat Rat Rat Rat	>2000 mg/kg >5000 mg/kg 3.125 g/kg >6.3 mg/l	- - - 4 hours

Product/ingredient name	Result	Species	Dose	Exposure	
<mark>⊳</mark> arium sulfate	LD50 Dermal	Rat	>2000 mg/kg	-	
	LD50 Oral	Rat	>5000 mg/kg	-	
bis(1,2,2,6,6-pentamethyl- 4-piperidyl) sebacate	LD50 Oral	Rat	3.125 g/kg	-	
Polyamide	LC50 Inhalation Dusts and m	ists Rat	>6.3 mg/l	4 hours	
5	LD50 Dermal	Rat	>2000 mg/kg	-	
	LD50 Oral	Rat	>2000 mg/kg	-	
methyl	LD50 Oral	Rat	3.125 g/kg	-	
1,2,2,6,6-pentamethyl-					
4-piperidyl sebacate					
toluene	LC50 Inhalation Vapour	Rat	49 g/m³	4 hours	
	LD50 Dermal	Rabbit	8.39 g/kg	-	
	LD50 Oral	Rat	5580 mg/kg	-	
Conclusion/Summary	: There are no data availabl	e on the mixture its	elf.		
Irritation/Corrosion					
Conclusion/Summary					
Skin	: There are no data availabl	e on the mixture its	elf.		
Eyes	: There are no data availabl	e on the mixture its	elf.		
Respiratory	: There are no data availabl	e on the mixture its	elf.		
<u>Sensitisation</u>					
Conclusion/Summary					
Skin	: There are no data availabl	e on the mixture its	elf.		
Respiratory	: There are no data availabl	e on the mixture its	elf.		
<u>Mutagenicity</u>					
Conclusion/Summary	: There are no data availabl	e on the mixture its	elf.		
Carcinogenicity					
Conclusion/Summary	: There are no data availabl	e on the mixture its	elf.		
Reproductive toxicity					
Conclusion/Summary					
Teratogenicity					
Conclusion/Summary					
Specific target organ toxici	t <mark>y (single exposure)</mark>				
Name		Category	Route of exposure	Target organs	
toluene		Category 3	-	Narcotic effects	

Section 11. Toxicological information

Specific target organ toxicity (repeated exposure)			
Name	Category	Route of exposure	Target organs
toluene	Category 2	-	-

Aspiration hazard

Name	Result
toluene	ASPIRATION HAZARD - Category 1

Information on likely routes of exposure	:	Not available.
Potential acute health effects	2	
Eye contact	:	No known significant effects or critical hazards.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	1	May be harmful in contact with skin. May cause an allergic skin reaction.
Ingestion	:	No known significant effects or critical hazards.
Symptoms related to the phy	sic	cal, chemical and toxicological characteristics
Eye contact		No specific data.
Inhalation		No specific data.
Skin contact	÷	Adverse symptoms may include the following: irritation
		redness
Ingestion	:	No specific data.
Delayed and immediate effect	ts	as well as chronic effects from short and long-term exposure
Short term exposure		
Potential immediate effects	;	Not available.
Potential delayed effects	:	Not available.
Long term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Potential chronic health effe	ect	<u>s</u>
Not available.		
General	:	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	1	No known significant effects or critical hazards.
Mutagenicity	1	No known significant effects or critical hazards.
Reproductive toxicity	:	No known significant effects or critical hazards.
Numerical measures of toxic	itv	

Numerical measures of toxicity

Acute toxicity estimates

Version 1.02

Section 11. Toxicological information

Route	ATE value
Oral	47032.24 mg/kg
Dermal	3598.68 mg/kg

Other information

Sanding and grinding dusts may be harmful if inhaled. Trimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness.

Section 12. Ecological information

<u>Toxicity</u>					
Product/ingredient name	Result	Species	Exposure		
4.4'- Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro- 2,3-epoxypropane	LC50 11.5 mg/l	Fish	96 hours		

Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
voluene	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
koluene	2.73	8.32	low

Mobility in soil

Other adverse effects

Soil/water partition: Not available.coefficient (Koc)

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods :	The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.
--------------------	--

Section 14. Transport information

	UN	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

Additional information

- UN: None identified.IMDG: None identified.
- IATA : None identified.

Special precautions for user :**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Section 15. Regulatory information

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Section 16. Other information

<u>History</u>	
Date of issue/Date of revision	: 23 February 2023
Date of previous issue	: 5/20/2021
Version	: 1.02
Prepared by	: EHS
Key to abbreviations	 ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships,

Product code 00291656 Product name PSX 700 A RAL 1021 RESIN

Section 16. Other information

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations

Procedure used to derive the classification

Classification	Justification
FLAMMABLE LIQUIDS - Category 4	On basis of test data
ACUTE TOXICITY (dermal) - Category 5	Calculation method
SKIN SENSITISATION - Category 1	Calculation method
SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 3	Calculation method
LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3	Calculation method

Indicates information that has changed from previously issued version.

Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.