SAFETY DATA SHEET

Date of issue/Date of revision

: 23 February 2023 Version : 3.01



SECTION 1: Identification of the substance/mixture and of the company/ undertaking

_	
1.1 Product identifier	
Product name	: PSX 700 RESIN
Product code	: 00296464
Product type	: Liquid.
Other means of identification	ation
Not available.	
1.2 Relevant identified use	es of the substance or mixture and uses advised against
Product use	: Professional applications, Used by spraying.
Use of the substance/ mixture	: Coating.

Uses advised against : Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

Sigma Paint Saudi Arabia Ltd. PO Box 7509, Dammam 3147 Saudi Arabia Tel: 00966 138 47 31 00 Fax: 00966 138 47 17 34	
e-mail address of person responsible for this SDS	: PS.ACEMEA@ppg.com
1.4 Emergency telephone number	: 00966 138473100 extn 1001

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture
Product definition : Mixture Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]
Skin Sens. 1, H317 Aquatic Chronic 3, H412
The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.
See Section 16 for the full text of the H statements declared above.
See Section 11 for more detailed information on health effects and symptoms.
2.2 Label elements

Hazard pictograms



Signal word	: Warning
Hazard statements	: May cause an allergic skin reaction.
	Harmful to aquatic life with long lasting effects.

Precautionary statements

English (GB)

Code : 00296464		Date of issue/Date of revision : 23 February 2023		
PSX 700 RESIN				
SECTION 2: Hazards identification				
Prevention	:	Wear protective gloves. Avoid release to the environment. Avoid breathing vapour.		
Response	:	✓ake off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water.		
Storage	:	Not applicable.		
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.		
Hazardous ingredients	:	4.4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro- 2,3-epoxypropane Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate		
Supplemental label elements	:	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.		
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.		
Special packaging require	men	<u>ts</u>		
Containers to be fitted with child-resistant fastenings	:	Not applicable.		
Tactile warning of danger	:	Not applicable.		
2.3 Other hazards				
Product meets the criteria for PBT or vPvB	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.		
Other hazards which do	:	None known.		

not result in classification

SECTION 3: Composition/information on ingredients

3.2 Mixtures	: Mixture				
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
4,4'- Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro- 2,3-epoxypropane	REACH #: 01-2119959495-22 EC: 500-070-7 CAS: 30583-72-3	≥25 - ≤50	Skin Sens. 1, H317 Aquatic Chronic 3, H412	-	[1]
Reaction mass of bis (1,2,2,6,6-pentamethyl- 4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl- 4-piperidyl sebacate	REACH #: 01-2119491304-40 EC: 915-687-0 CAS: 1065336-91-5	≥0.30 - <2.5	Skin Sens. 1A, H317 Repr. 2, H361 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1]
toluene	REACH #: 01-2119471310-51 EC: 203-625-9 CAS: 108-88-3 Index: 601-021-00-3	<1.0	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304	-	[1] [2]
	·	English	(GB) Saudi	Arabia	2/13

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II				
Code : 00296464	Date of issue/Date of revision	: 23 February 2023		
PSX 700 RESIN				
SECTION 3: Composition/information on ingredients				

See Section 16 for	
the full text of the H	
statements declared	
above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

1 Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	 Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	 If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects Eye contact : No known significant effects or critical hazards. Inhalation : No known significant effects or critical hazards. **Skin contact** : May cause an allergic skin reaction. Ingestion : No known significant effects or critical hazards. **Over-exposure signs/symptoms** Eye contact : No specific data. Inhalation : No specific data. **Skin contact** : Adverse symptoms may include the following: irritation redness Ingestion : No specific data. 4.3 Indication of any immediate medical attention and special treatment needed : In case of inhalation of decomposition products in a fire, symptoms may be delayed. Notes to physician The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : No specific treatment.

Conforms to Regulation (EC	
Code : 00296464	Date of issue/Date of revision : 23 February 2023
PSX 700 RESIN	
SECTION 5: Firefigh	iting measures
5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising	from the substance or mixture
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides sulfur oxides halogenated compounds metal oxide/oxides
5.3 Advice for firefighters	
Special precautions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	tective equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
6.3 Methods and material for	containment and cleaning up
Ownell and II	Chan la shift uith such siste. Maus a such is an forma anill and a Dilute with water and many un-

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Conforms to Regulation	n (EC) No. 1907/2006 (REACH), Annex II
Code : 0029646	Date of issue/Date of revision: 23 February 2023
PSX 700 RESIN	
SECTION 6: Acci	idental release measures
Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product.
6.4 Reference to other sections	 See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
7.2 Conditions for safe storage, including any incompatibilities	: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

Recommendations	: Not available.
Industrial sector specific	: Not available.
solutions	

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Code : 00296464 PSX 700 RESIN Date of issue/Date of revision

SECTION 8: Exposure controls/personal protection

Product/ingredie	nt name	Exposure limit values			
toluene		EU OEL (Europe, 1/2022). Absorbed through skin. STEL: 384 mg/m ³ 15 minutes. STEL: 100 ppm 15 minutes. TWA: 192 mg/m ³ 8 hours. TWA: 50 ppm 8 hours.			
Recommended monitoring procedures	Standard EN 689 by inhalation to o strategy) Europe application and u biological agents requirements for agents) Referen	Id be made to monitoring standards, such as the following: European 9 (Workplace atmospheres - Guidance for the assessment of exposure chemical agents for comparison with limit values and measurement ean Standard EN 14042 (Workplace atmospheres - Guide for the use of procedures for the assessment of exposure to chemical and s) European Standard EN 482 (Workplace atmospheres - General r the performance of procedures for the measurement of chemical nce to national guidance documents for methods for the determination bstances will also be required.			
8.2 Exposure controls					
Appropriate engineering controls	: Good general ve contaminants.	ntilation should be sufficient to control worker exposure to airborne			
Individual protection measu	res				
Hygiene measures	eating, smoking Appropriate tech Contaminated w contaminated clo	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.			
Eye/face protection <u>Skin protection</u>	: Safety glasses w	vith side shields.			
Hand protection	worn at all times necessary. Con- during use that the noted that the tim glove manufactu protection time of frequently repear (breakthrough tin When only brief (breakthrough tin The user must co product is the mo	ant, impervious gloves complying with an approved standard should be when handling chemical products if a risk assessment indicates this is sidering the parameters specified by the glove manufacturer, check he gloves are still retaining their protective properties. It should be ne to breakthrough for any glove material may be different for different rers. In the case of mixtures, consisting of several substances, the of the gloves cannot be accurately estimated. When prolonged or ted contact may occur, a glove with a protection class of 6 me greater than 480 minutes according to EN 374) is recommended. contact is expected, a glove with a protection class of 2 or higher me greater than 30 minutes according to EN 374) is recommended. heck that the final choice of type of glove selected for handling this ost appropriate and takes into account the particular conditions of use, e user's risk assessment.			
Gloves	: butyl rubber				
Body protection		ive equipment for the body should be selected based on the task being ne risks involved and should be approved by a specialist before duct.			
Other skin protection	based on the tas	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.			
Respiratory protection	hazards of the pr are exposed to c certified respirate	tion must be based on known or anticipated exposure levels, the roduct and the safe working limits of the selected respirator. If workers concentrations above the exposure limit, they must use appropriate, ors. Use a properly fitted, air-purifying or air-fed respirator complying d standard if a risk assessment indicates this is necessary.			

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II					
Code	: 00296464	Date of issue/Date of revision	: 23 February 2023		
PSX 700 F	RESIN				
SECTIO	ON 8: Exposu	re controls/personal protection			
Environ controls	mental exposure	: Emissions from ventilation or work process equipment should b they comply with the requirements of environmental protection I			

will be necessary to reduce emissions to acceptable levels.

cases, fume scrubbers, filters or engineering modifications to the process equipment

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

3.1 mormation on basic physic	and chemical properties
<u>Appearance</u>	
Physical state	Liquid.
Colour	: Various
Odour	Not available.
Odour threshold	Not available.
Melting point/freezing point	 May start to solidify at the following temperature: -12.9°C (8.8°F) This is based of data for the following ingredient: 4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane.
Initial boiling point and boiling range	: >37.78°C
Flammability	Not available.
Upper/lower flammability or explosive limits	Not available.
Flash point	Closed cup: 80°C
Auto-ignition temperature	Not available.
Decomposition temperature	Stable under recommended storage and handling conditions (see Section 7).
рН	Not applicable. insoluble in water.
Viscosity	: Kinematic (40°C): >21 mm²/s
Viscosity	: >100 s (ISO 6mm)
Solubility(ies)	
Media	Result

	Result
	Not soluble
: N	ot applicable.
: N	ot available.
: N	ot available.
: 1.	45
	he product itself is not explosive, but the formation of an explosible mixture of apour or dust with air is possible.
: P	roduct does not present an oxidizing hazard.
: N	ot applicable.
	: N : N : 1. : T va : P

9.2 Other information

No additional information.

Code : 00296464 PSX 700 RESIN	Date of issue/Date of revision: 23 February 2023			
SECTION 10: Stabilit	y and reactivity			
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.			
10.2 Chemical stability	: The product is stable.			
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.			
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products Refer to protective measures listed in sections 7 and 8.			
10.5 Incompatible materials	rials : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.			
10.6 Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides sulfur oxides halogenated compounds metal oxide/ oxides			

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Reaction mass of bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	LD50 Dermal	Rat	>3170 mg/kg	-
	LD50 Oral	Rat - Male, Female	3230 mg/kg	-
toluene	LC50 Inhalation Vapour LD50 Dermal LD50 Oral	Rat Rabbit Rat	49 g/m³ 8.39 g/kg 5580 mg/kg	4 hours - -

Conclusion/Summary	: There are no data available on the mixture itself.
Irritation/Corrosion	
Conclusion/Summary	
Skin	: There are no data available on the mixture itself.
Eyes	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
Sensitisation	
Conclusion/Summary	
Skin	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
Mutagenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Carcinogenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Reproductive toxicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Teratogenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Specific target organ toxic	<u>ity (single exposure)</u>

ode : 00296464		Date of issu	e/Date of revision	: 23 February 202	
SX 700 RESIN					
ECTION 11: Toxic	ological information	n			
Product/in	gredient name	Categor	/ Route of exposure	Target organs	
toluene		Category	3 -	Narcotic effects	
Specific target organ toxi	city (repeated exposure)				
Product/in	gredient name	Categor	/ Route of exposure	Target organs	
toluene		Category	-	-	
Aspiration hazard					
	t/ingredient name			Result	
toluene	anigi edient name	۵۵	PIRATION HAZAR		
	NI-4				
Information on likely routes of exposure	: Not available.				
Potential acute health effe	ects				
Inhalation	: No known significant e	ffects or critical	nazards.		
Ingestion	: No known significant e	ffects or critical	nazards.		
Skin contact	: May cause an allergic	skin reaction.			
Eye contact	: No known significant e	ffects or critical	nazards.		
Symptoms related to the	ohysical, chemical and toxi	cological chara	<u>icteristics</u>		
Inhalation	: No specific data.				
Ingestion	: No specific data.				
Skin contact	: Adverse symptoms ma irritation redness	Adverse symptoms may include the following: irritation			
Eye contact	: No specific data.				
Delayed and immediate ef	fects as well as chronic eff	fects from shor	t and long-term ex	<u>posure</u>	
Short term exposure			_		
Potential immediate effects	: Not available.				
Potential delayed effect	s: Not available.				
Long term exposure					
Potential immediate effects	: Not available.				
Potential delayed effect	s: Not available.				
Potential chronic health e	<u>ffects</u>				
Not available.					
Conclusion/Summary	: Not available.				
General	: Once sensitized, a sev very low levels.	ere allergic reac	tion may occur whe	n subsequently exposed to	
Carcinogenicity	: No known significant e	ffects or critical	nazards.		
Mutagenicity	: No known significant e	ffects or critical	nazards.		
Reproductive toxicity	: No known significant e	ffects or critical	nazards.		
Other information	: Not available.				
	may be harmful if inhaled. Ti nanol may be harmful or fatal			ming methanol if hydrolyzed	

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

English (GB)

Code : 00296464

PSX 700 RESIN

Date of issue/Date of revision

: 23 February 2023

SECTION 11: Toxicological information

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
4.4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	LC50 11.5 mg/l	Fish	96 hours
Reaction mass of bis(1,2,2,6,6-pentamethyl- 4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	EC50 1.68 mg/l	Algae	72 hours
··-,,,	LC50 0.9 mg/l	Fish	96 hours

Conclusion/Summary : There are no data available on the mixture itself.

12.2 Persistence and degradability

Conclusion/Summary : There are no data available on the mixture itself.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
toluene	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
K luene	2.73	8.32	low

12.4 Mobility in soil	
Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

onforms to Regulation (E	EC) No. 1907/2006 (REACH), Annex II	
ode : 00296464	Date of issue/Date of revision : 23 February 2023	
SX 700 RESIN		
ECTION 13: Dispo	osal considerations	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.	
Hazardous waste	: Yes.	
European waste catalog	<u>gue (EWC)</u>	
Waste code	Waste designation	
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	
Packaging		
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.	
Type of packaging	European waste catalogue (EWC)	
Container	15 01 06 mixed packaging	
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.	

SECTION 14: Transport information

	ADR/RID	IMDG	ΙΑΤΑ
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

Additional information

ADR/RID	: None identified.
IMDG	: None identified.
ΙΑΤΑ	: None identified.

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk: Not applicable.according to IMOinstruments

Code : 00296464 PSX 700 RESIN Date of issue/Date of revision

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
EU Regulation (EC) No. 1907/2006 (REACH)
Annex XIV - List of substances subject to authorisation
Annex XIV
None of the components are listed.
Substances of very high concern
None of the components are listed.
Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles
Other national and international regulations.
Ozone depleting substances (1005/2009/EU)
Not listed.
15.2 Chemical safety : No Chemical Safety Assessment has been carried out.

assessment

. No chemical Salety Assessment has been carried of

SECTION 16: Other information

Indicates information that	has changed from previously is	ssued version.	
Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number 		
Full text of abbreviated H statements	H304May be fatal if sH315Causes skin irriH317May cause skin irriH317May cause an aH336May cause drowH361Suspected of daH361dSuspected of daH373May cause damH400Very toxic to aqH410Very toxic to aq	 Highly flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. d Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. 	
Full text of classifications [CLP/GHS]	: Aquatic Acute 1 Aquatic Chronic 1 Aquatic Chronic 3 Asp. Tox. 1 Flam. Liq. 2 Repr. 2 Skin Irrit. 2 Skin Sens. 1 Skin Sens. 1A STOT RE 2 STOT SE 3	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 ASPIRATION HAZARD - Category 1 FLAMMABLE LIQUIDS - Category 2 REPRODUCTIVE TOXICITY - Category 2 SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITISATION - Category 1 SKIN SENSITISATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3	
<u>History</u>			

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II			
Code : 00296464		Date of issue/Date of revision	: 23 February 2023
PSX 700 RESIN			
SECTION 16: Other	r information		
Date of issue/ Date of revision	: 23 February 2023		
Date of previous issue	: 9 March 2022		
Prepared by	: EHS		
Version	: 3.01		
D : 1 ·			

<u>Disclaimer</u>

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.