## **SAFETY DATA SHEET**



Date of issue/Date of revision27 February 2023Version 2.1

Section 1. Identification		
Product code	: 00355613	
Product name	: PSX 700 A BASE (TINTED)	
Product type	: Liquid.	
Relevant identified uses o	f the substance or mixture and uses advised against	
Product use	Coating. Professional applications, Used by spraying.	
Supplier's details	: PPG Industries (Singapore) Pte. Ltd., No. 1 Tuas Basin Close, Singapore 638803. Tel +65 68653737	
Emergency telephone number (with hours of operation)	: CHEMTREC +(65)-31581349 (CCN 17704)	

## Section 2. Hazards identification

Classification of the substance or mixture	:	SKIN SENSITIZATION - Category 1
GHS label elements, includin	g	precautionary statements
Hazard pictograms	:	
Signal word	:	Warning
Hazard statements	:	May cause an allergic skin reaction.
Precautionary statements		
Prevention	1	Wear protective gloves. Avoid breathing vapor.
Response	:	Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention.
Storage	1	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Other hazards which do not result in classification	:	None known.

Singapore	English (US)	Page: 1/11
-----------	--------------	------------

## Section 3. Composition/information on ingredients

: Mixture

Substance/mixture

#### **CAS number/other identifiers**

CAS number	: Not applicable.
EC number	: Mixture.

Ingredient name	%	CAS number
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with	25 - <50	30583-72-3
1-chloro-2,3-epoxypropane		
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	1 - <3	41556-26-7
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	0.3 - <1	82919-37-7
toluene	0.3 - <1	108-88-3

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

#### Section 4. First aid measures

#### Description of necessary first aid measures

Eye contact	: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	<ul> <li>Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.</li> </ul>
Skin contact	<ul> <li>Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.</li> </ul>
Ingestion	<ul> <li>If swallowed, seek medical advice immediately and show this container or label.</li> <li>Keep person warm and at rest. Do NOT induce vomiting.</li> </ul>

#### Most important symptoms/effects, acute and delayed

Potential acute health effects			
Eye contact :	No known significant effects or critical hazards.		
Inhalation :	No known significant effects or critical hazards.		
Skin contact :	May cause an allergic skin reaction.		
Ingestion :	No known significant effects or critical hazards.		
Over-exposure signs/symptoms			
Eye contact :	No specific data.		
Inhalation :	No specific data.		
Skin contact :	Adverse symptoms may include the following: irritation redness		
Ingestion :	No specific data.		

Singapore	English (US)	Page: 2/11
-----------	--------------	------------

## Section 4. First aid measures

Indication of immediate medical attention and special treatment needed, if necessary		
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be dela The exposed person may need to be kept under medical surveillance for 48 ho	
Specific treatments	: No specific treatment.	
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. may be dangerous to the person providing aid to give mouth-to-mouth resuscita Wash contaminated clothing thoroughly with water before removing it, or wear gloves.	

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides sulfur oxides halogenated compounds metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

Personal precautions, protec	<u>tiv</u>	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Product name PSX 700 A BASE (TINTED)

#### Section 6. Accidental release measures

**Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materia	als for containment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

# Precautions for safe handling Protective measures : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use.

		container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, ncluding any ncompatibilities	:	Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed unti ready for use. Containers that have been opened must be carefully resealed and

incompatible materials before handling or use.

Empty containers retain product residue and can be hazardous. Do not reuse

kept upright to prevent leakage. Do not store in unlabeled containers. Use

appropriate containment to avoid environmental contamination. See Section 10 for

## Section 8. Exposure controls/personal protection

#### **Control parameters**

#### **Occupational exposure limits**

Ingredient name			Exposure limits
toluene			Workplace Safety and Health Act (Singapore, 2/2006). PEL (long term): 188 mg/m <sup>3</sup> 8 hours. PEL (long term): 50 ppm 8 hours.
Recommended monitoring procedures	:		riate monitoring standards. Reference to nods for the determination of hazardous
Appropriate engineering controls	:	Good general ventilation should be su contaminants.	fficient to control worker exposure to airborne
Environmental exposure controls	:		
Individual protection measure	es		
Hygiene measures	:	eating, smoking and using the lavatory Appropriate techniques should be use Contaminated work clothing should no	bughly after handling chemical products, before y and at the end of the working period. In the end of the working period. In the allowed out of the workplace. Wash Ensure that eyewash stations and safety ocation.
Eye/face protection	1	Safety glasses with side shields.	
Skin protection			
Hand protection	:	be worn at all times when handling ch this is necessary. Considering the par check during use that the gloves are s should be noted that the time to break	s complying with an approved standard should emical products if a risk assessment indicates rameters specified by the glove manufacturer, still retaining their protective properties. It through for any glove material may be rers. In the case of mixtures, consisting of the gloves cannot be accurately
Gloves	:	butyl rubber	
Body protection	:		body should be selected based on the task d and should be approved by a specialist
Other skin protection	:		nal skin protection measures should be ormed and the risks involved and should be ng this product.

Product name PSX 700 A BASE (TINTED)

## Section 8. Exposure controls/personal protection

Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
------------------------	--

## Section 9. Physical and chemical properties

<u>Appearance</u>		
Physical state	Liquid.	
Color	Various	
Odor	Aromatic.	
рН	insoluble in water.	
Boiling point	>37.78°C (>100°F)	
Flash point	Closed cup: Not applicable.	
Evaporation rate	Not available.	
Flammability (solid, gas)	liquid	
Vapor pressure	Not available.	
Relative density	1.44	
Solubility(ies)	Media Result	
Solubility(les)	cold water Not soluble	
Auto-ignition temperature	Not available.	]
Viscosity	Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)	

## Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides sulfur oxides halogenated compounds metal oxide/oxides

Singapore	English (US)	Page: 6/11
-----------	--------------	------------

Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Specie	s Dose	Exposure	
bis(1,2,2,6,6-pentamethyl-	LD50 Oral	Rat	3.125 g/kg	-	
4-piperidyl) sebacate methyl 1,2,2,6,6-pentamethyl-	LD50 Oral	Rat	3.125 g/kg	-	
4-piperidyl sebacate					
toluene	LC50 Inhalation Vapor	Rat Rabbit	49 g/m <sup>3</sup>	4 hours	
	LD50 Dermal LD50 Oral	Rabbit	8.39 g/kg 5580 mg/kg	-	
Conclusion/Summary :	There are no data available o	on the mixture		Į	
rritation/Corrosion					
Conclusion/Summary					
Skin :	There are no data available of	on the mixture	itself.		
Eyes :	There are no data available o	on the mixture	itself.		
Respiratory :	There are no data available of	on the mixture	itself.		
Sensitization					
Conclusion/Summary					
	There are no data available o	on the mixture	itself.		
Respiratory :	There are no data available o	on the mixture	itself.		
<u>Mutagenicity</u>					
Conclusion/Summary :	There are no data available	on the mixture	itself.		
Carcinogenicity					
Conclusion/Summary :	There are no data available	on the mixture	itself.		
Reproductive toxicity					
Conclusion/Summary :	There are no data available	on the mixture	itself.		
<u>Feratogenicity</u>					
Conclusion/Summary :	There are no data available	on the mixture	itself.		
<u>Specific target organ toxici</u>	t <u>y (single exposure)</u>				
Name		Category	Route of exposure	Target organs	
toluene		Category 3	-	Narcotic effects	
Specific target organ toxici	ty (repeated exposure)		1		
Name		Category	Route of exposure	Target organs	
toluene		Category 2	-	-	
Aspiration hazard			I	I	
Name			Result		
toluene			ASPIRATION HAZARD - Category 1		

tol	luene	

## Section 11. Toxicological information

Information on the likely routes of exposure	: Not available.
Potential acute health effect	<u>ts</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the ph	ysical, chemical and toxicological characteristics
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
Delayed and immediate effe	ects and also chronic effects from short and long term exposure
Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.

Potential chronic health effects

General	Once sensitized, a severe allergic reaction may occur when subsequently expos to very low levels.	ed
Carcinogenicity	No known significant effects or critical hazards.	
Mutagenicity	No known significant effects or critical hazards.	

Reproductive toxicity	: No known significant effects or critical hazards.
-----------------------	---

ż

#### **Numerical measures of toxicity**

#### Acute toxicity estimates

Not available.

#### **Other information**

Sanding and grinding dusts may be harmful if inhaled. Trimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness.

Singapore	English (US)	Page: 8/11
-----------	--------------	------------

## Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
4,4'- Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro- 2,3-epoxypropane	LC50 11.5 mg/l	Fish	96 hours
Conclusion/Summary	: There are no data available on the mixture itself.		

#### Persistence/degradability

Conclusion/Summary	: There are no data available on the mixture itself.		
Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
toluene	-	-	Readily

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
toluene	2.73	8.32	low

#### Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

**Other adverse effects** : No known significant effects or critical hazards.

### Section 13. Disposal considerations

Disposal methods
------------------

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Section 14. Transport information

	UN	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

#### **Additional information**

UN	: None identified.
IMDG	: None identified.
ΙΑΤΑ	: None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

## Section 15. Regulatory information

Singapore - hazardous chemicals under government control

None.

International regulations

**Montreal Protocol** 

Not listed.

Stockholm Convention on Persistent Organic Pollutants Not listed.

## Section 16. Other information

<u>History</u>	
Date of issue/Date of revision	: 27 February 2023
Date of previous issue	: 7/25/2022
Version	: 2.1
Prepared by	: EHS
Key to abbreviations	<ul> <li>ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations</li> </ul>

Indicates information that has changed from previously issued version.

#### Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.