SAFETY DATA SHEET



Date of issue 21 March 2023

Version 7.04

Section 1. Product and company identification

Product name
Product code
Other means of identification
Product type

: PSX 700 BASE LIGHT TINT

- : 00289168
- : Not available.
 - : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Coating. Paints. Painting-related materials.

Uses advised against	Reason
Not applicable.	

Supplier's details:	
Supplier	 PPG Industries Colombia Ltda Calle 51 # 40-13 Municipio de Itagüí Antioquia, Colombia (57) (4) 3787400 (Porteria)
Email address:	: HazComLatam@ppg.com
Emergency telephone number	: Colombia: 01 8000 916012 (CISPROQUIM) + 571 288 6012 (CISPROQUIM) Ecuador: 1800-59-3005 (CISPROQUIM) Peru: 080-050-847 (CISPROQUIM)

Section 2. Hazards identification

Classification of the substance or mixture	: FLAMMABLE LIQUIDS - Category 4 SKIN SENSITIZATION - Category 1 TOXIC TO REPRODUCTION - Category 2 AQUATIC HAZARD (ACUTE) - Category 3 AQUATIC HAZARD (LONG-TERM) - Category 3
Target organs	 Contains material which causes damage to the following organs: upper respiratory tract, skin, eyes. Contains material which may cause damage to the following organs: kidneys, lungs, immune system.
	Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 34.4%

Section 2. Hazards identification

GHS label elements		
Hazard pictograms		
Signal word	arning	
Hazard statements	ombustible liquid. ay cause an allergic skin reaction. uspected of damaging fertility or the unborn child. armful to aquatic life with long lasting effects.	
Precautionary statements		
Prevention	btain special instructions before use. Wear protective gloves, protective clo nd eye or face protection. Keep away from flames and hot surfaces. No sm /oid release to the environment. Avoid breathing vapor.	
Response	exposed or concerned: Get medical advice or attention. Take off contamir othing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If itation or rash occurs: Get medical advice or attention.	
Storage	ore in a well-ventilated place. Keep cool.	
Disposal	spose of contents and container in accordance with all local, regional, nation international regulations.	onal
Other hazards which do not	one known.	

result in classification

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Not available.
identification	

CAS number/other identifiers

CAS number : Not applicable.		
Ingredient name	%	CAS number
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	30 - <60	30583-72-3
titanium dioxide barium sulfate	20 - <30 2 - <3	13463-67-7 7727-43-7
Polyamide bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	1 - <2 1 - <2	SUB100538 41556-26-7
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate toluene	0.2 - <0.5 0.2 - <0.5	82919-37-7 108-88-3

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

21 March 2023

Section 4. First aid measures

Description of necessary fire	st a	id measures
Eye contact	-	Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	-	Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	:	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	:	If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
Indication of immediate med	<u>dica</u>	l attention and special treatment needed, if necessary
Notes to physician	÷ .	In case of inhalation of decomposition products in a fire, symptoms may be delayed.
Specific treatments		The exposed person may need to be kept under medical surveillance for 48 hours. No specific treatment.
	:	The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	:	The exposed person may need to be kept under medical surveillance for 48 hours. No specific treatment. No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear
Specific treatments Protection of first-aiders	: : : : :	The exposed person may need to be kept under medical surveillance for 48 hours. No specific treatment. No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.
Specific hazards arising from the chemical	: Combustible liquid. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides sulfur oxides halogenated compounds metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Section 5. Fire-fighting measures

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	 No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responder	
	 Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
Methods and materials for	containment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13).

Section 7. Handling and storage

Precautions for safe handling	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools.
	lighting and material handling) equipment. Use only non-sparking tools. Empty

Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for

emergency contact information and Section 13 for waste disposal.

	English (US)	Colombia
--	--------------	----------

21 Ma

Section 7. Handling and storage

containers retain product residue and can be hazardous. Do not reuse container.

Conditions for safe storage,	1	Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in
including any		accordance with local regulations. Store in a segregated and approved area. Store
incompatibilities		in original container protected from direct sunlight in a dry, cool and well-ventilated
-		area, away from incompatible materials (see Section 10) and food and drink. Store
		locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep
		container tightly closed and sealed until ready for use. Containers that have been
		opened must be carefully resealed and kept upright to prevent leakage. Do not
		store in unlabeled containers. Use appropriate containment to avoid environmental
		contamination. See Section 10 for incompatible materials before handling or use.

Date of issue

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name		Exposure limits	
Manium dioxide barium sulfate		ACGIH TLV (United States, 1/2022). TWA: 2.5 mg/m ³ 8 hours. Form: respirable fraction, finescale particles ACGIH TLV (United States, 1/2022). TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction	
Recommended monitoring procedures		ppropriate monitoring standards. Reference to r methods for the determination of hazardous	
Appropriate engineering controls	ventilation or other engineering of contaminants below any recomm	on. Use process enclosures, local exhaust controls to keep worker exposure to airborne nended or statutory limits. The engineering controls dust concentrations below any lower explosive ilation equipment.	
Environmental exposure controls	 Emissions from ventilation or work process equipment should be checked to ensuthey comply with the requirements of environmental protection legislation. In som cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. 		
ndividual protection measur	<u>es</u>		
Hygiene measures	before eating, smoking and using Appropriate techniques should b Contaminated work clothing sho	thoroughly after handling chemical products, g the lavatory and at the end of the working period. e used to remove potentially contaminated clothing. uld not be allowed out of the workplace. Wash using. Ensure that eyewash stations and safety ation location.	
Eye protection <u>Skin protection</u>	: Safety glasses with side shields.		

7.04

Section 8. Exposure controls/personal protection

•	• •
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	: butyl rubber
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

<u>Appearance</u>					
Physical state	1	Liquid.			
Color	1	Various			
Odor	:	Aromatic. [Slight]			
рН	:	Not applicable.			
Melting point	:	Not available.			
Boiling point	:	>37.78°C (>100°F)			
Flash point	:	Closed cup: 80°C (176°F)			
Evaporation rate	:	Not available.			
Flammability (solid, gas)	:	Not available.			
Lower and upper explosive (flammable) limits	;	Not available.			
Vapor pressure	:	Not available.			
Vapor density	:	Not available.			
Relative density	:	1.43			
Bulk density (g/cm³)	:	1.44			
Solubility(ies)		Media	Result		
oordonity(ies)	1	cold water	Not soluble		
Partition coefficient: n- octanol/water	:	Not applicable.]
Auto-ignition temperature	:	Not available.			
Decomposition temperature	:	Not available.			
Viscosity	:	Kinematic (40°C (104°F)):	>21 mm²/s (>21 cSt)		
			English (US)	Colombia 6/	12

7.04

Section 9. Physical and chemical properties

Viscosity : > 100 s (ISO 6mm)

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides sulfur oxides halogenated compounds metal oxide/ oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
titanium dioxide	LC50 Inhalation Dusts and mists	Rat	>6.82 mg/l	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
barium sulfate	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Polyamide	LC50 Inhalation Dusts and mists	Rat	>6.3 mg/l	4 hours
-	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-
bis(1,2,2,6,6-pentamethyl- 4-piperidyl) sebacate	LD50 Oral	Rat	3.125 g/kg	-
methyl 1,2,2,6,6-pentamethyl- 4-piperidyl sebacate	LD50 Oral	Rat	3.125 g/kg	-
toluene	LC50 Inhalation Vapor	Rat	49 g/m³	4 hours
	LD50 Dermal	Rabbit	8.39 g/kg	-
	LD50 Oral	Rat	5580 mg/kg	-

Conclusion/Summary

: There are no data available on the mixture itself.

Irritation/Corrosion

Not available.

Conclusion/Summary	
Skin	: There are no data available on the mixture itself.
Eyes	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
Sensitization	

Section 11. Toxicological information

Not available.

Conclusion/Summary				
Skin	:	There are	e no data a	available on the mixture itself.
Respiratory	1	There are	e no data a	available on the mixture itself.
<u>Mutagenicity</u>				
Not available.				
Conclusion/Summary	:	There are	e no data a	available on the mixture itself.
<u>Carcinogenicity</u>				
Not available.				
Conclusion/Summary	:	There are	e no data a	available on the mixture itself.
Classification				
Product/ingredient name		OSHA	IARC	NTP

Product/ingredient name	OSHA	IARC	NTP
titanium dioxide	-	2B	-
toluene	-	3	-

Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4 NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen OSHA: + Not listed/not regulated: -

Reproductive toxicity

Not available.

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Not available.

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Name		Route of exposure	Target organs
toluene	Category 3	-	Narcotic effects

Specific target organ toxicity (repeated exposure)

Name	•••	Route of exposure	Target organs
toluene	Category 2	-	-

Target organs

: Contains material which causes damage to the following organs: upper respiratory tract, skin, eyes. Contains material which may cause damage to the following organs: kidneys, lungs, immune system.

Aspiration hazard

Code00289168Product nameP	SX 700 BASE LIGHT TIN	Date of issue	21 March 2023	Version 7.04
Section 11. T	oxicological	l information		
Name			Result	
toluene			ASPIRATION HAZ	ARD - Category 1
Information on the lik routes of exposure	xely : Not avail	lable.		
Potential acute health	<u>ı effects</u>			
Eye contact	: No know	/n significant effects or ci	ritical hazards.	
Inhalation	: No know	/n significant effects or ci	ritical hazards.	
Skin contact	: May cau	se an allergic skin reacti	on.	
Ingestion	: No know	n significant effects or c	ritical hazards.	
Symptoms related to	the physical, chem	ical and toxicological o	haracteristics	
Eye contact	: No spec	ific data.		
Inhalation	reduced increase	symptoms may include t fetal weight in fetal deaths malformations	the following:	
Skin contact	irritation redness reduced increase	symptoms may include t fetal weight in fetal deaths malformations	he following:	
Ingestion	reduced increase	symptoms may include t fetal weight in fetal deaths malformations	he following:	
Delayed and immedia	te effects and also	chronic effects from sl	hort and long term expo	<u>sure</u>
Conclusion/Summ	forming or fatal of a liquid of with no r the produ- from spr- exposure engineer irritation vomiting and also oral, inha	methanol if hydrolyzed of or cause blindness. For r coating formulation. In the meaningful potential for h uct is applied with a brus ay applications may be h e and require the use of a ring controls (see Section and reversible damage. . This takes into account o chronic effects of compo-	e mixture itself. Trimetho r ingested. If swallowed, n many products, TiO2 is uti its case, the TiO2 particles numan exposure to unboun h or roller. Sanding the co appropriate personal prote n 8). If splashed in the eye Ingestion may cause nau t, where known, delayed a onents from short-term an s of exposure and eye cor	nethanol may be harmful ilized as a raw material in s are bound in a matrix nd particles of TiO2 when oating surface or mist duration and level of ective equipment and/or es, the liquid may cause usea, diarrhea and and immediate effects ad long-term exposure by
Short term exposure Potential immediat effects		e no data available on th	e mixture itself.	
Potential delayed e		e no data available on th	e mixture itself.	
Long term exposure	<u> </u>			

Code	00289168	Date of issue	21 March 2023	Version	7.04
Product na	me PSX 700 BASE LIGHT TINT				

Section 11. Toxicological information

Potential immediate effects	: There are no data available on the mixture itself.
Potential delayed effects	: There are no data available on the mixture itself.
Potential chronic health effe	octs
Not available.	
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

: Suspected of damaging fertility or the unborn child.

Carcinogenicity : N	o known significant effects or critical hazards.
---------------------	--

: No known significant effects or critical hazards.

Reproductive toxicity

Mutagenicity

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
PSX 700 BASE LIGHT TINT	34301.8	23262.4	N/A	N/A	N/A
barium sulfate	N/A	2500	N/A	N/A	N/A
Polyamide	2500	2500	N/A	N/A	N/A
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	3125	N/A	N/A	N/A	N/A
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	3125	N/A	N/A	N/A	N/A
toluene	5580	8390	N/A	49	N/A

Other information

: Not available.

Section 12. Ecological information

Ecotoxicity

Product/ingredient name	Result	Species	Exposure
4,4'- Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro- 2,3-epoxypropane	LC50 11.5 mg/l	Fish	96 hours
titanium dioxide	Acute LC50 >100 mg/l Fresh water	Daphnia - Daphnia magna	48 hours

Persistence/degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
toluene	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
toluene	2.73	8.32	low

English (US)	Colombia	10/12
--------------	----------	-------

21 March 2023

7.04

Section 12. Ecological information

<u>Mobility in soil</u>

Soil/water partition
coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	Brazil (ANTT)	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-
Transport hazard class(es)	-	-	-	-
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.

Additional information

UN	: None identified.
Brazil	: None identified.
Risk number	: Not available.
IMDG	: None identified.
ΙΑΤΑ	: None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

English (US)	Colombia	11/12

21 March 2023

Section 14. Transport information

Transport in bulk according : Not applicable. to IMO instruments

Section 15. Regulatory information

Safety, health and
environmental regulations: No known specific national and/or regional regulations applicable to this product
(including its ingredients).specific for the product:

Date of issue

Section 16. Other information

History Date of previous issue : 8/26/2022 Version : 7.04 EHS Key to abbreviations : ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail UN = United Nations References : ABNT NBR 14725-4: 2014 ANTT - National Land Transportation Agency

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.