SAFETY DATA SHEET

Date of issue/Date of revision

: 30 March 2023

Version : 3.01



SECTION 1: Identification of the substance/mixture and of the company/ undertaking

U	
1.1 Product identifier	
Product name	: SIGMAZINC 9 PIGMENT GREY
Product code	: 00332052
Product type	: Powder.
Other means of identification	ation
Not available.	
1.2 Relevant identified use	es of the substance or mixture and uses advised against
Product use	: Professional applications, Used by spraying.
Use of the substance/ mixture	: Coating.
Uses advised against	: Product is not intended, labelled or packaged for consumer use.
1.3 Details of the supplier	of the safety data sheet
Sigma Paint Saudi Arabia I PO Box 7509, Dammam 3	

PÕ Box 7509, Dammam 3147 Saudi Arabia Tel: 00966 138 47 31 00 Fax: 00966 138 47 17 34	72
e-mail address of person responsible for this SDS	: PS.ACEMEA@ppg.com
1.4 Emergency telephone	: 00966 138473100 extn 1001

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Product definition : Mixture Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] Aquatic Acute 1, H400 Aquatic Chronic 1, H410 The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended. See Section 16 for the full text of the H statements declared above. See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

number

Hazard pictograms



: Warning

Signal word Hazard statements <u>Precautionary statements</u>

: Very toxic to aquatic life with long lasting effects.

English (GB)

Conforms to Regulation (EC)	No	o. 1907/2006 (REACH), Annex II
Code : 00332052		Date of issue/Date of revision : 30 March 2023
SIGMAZINC 9 PIGMENT GRE	ΕY	
SECTION 2: Hazards	; ic	lentification
Prevention	1	Avoid release to the environment.
Response	:	Collect spillage.
Storage	:	Not applicable.
Disposal	:	Sispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	:	Not applicable.
Supplemental label elements	:	Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	-	Not applicable.
Special packaging requiren	nen	<u>ts</u>
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	May form explosible dust-air mixture if dispersed. Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes, skin,

nose and throat. **SECTION 3: Composition/information on ingredients**

3.2 Mixtures	: Mixture				
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
zinc powder zinc dust (stabilised)	REACH #: 01-2119467174-37 EC: 231-175-3 CAS: 7440-66-6 Index: 030-001-01-9	≥90	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1]
zinc oxide	REACH #: 01-2119463881-32 EC: 215-222-5 CAS: 1314-13-2 Index: 030-013-00-7	≥1.0 - ≤5.0	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1] [2]
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

English (GB) Sau	di Arabia
------------------	-----------

Date of issue/Date of revision

SIGMAZINC 9 PIGMENT GREY

: 00332052

Code

SECTION 3: Composition/information on ingredients

1 Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid m	neasures
Eye contact	: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	: \mathbf{N} o action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

r otoritiar addite rioarti	
Eye contact	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.
Inhalation	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs	/symptoms
Eye contact	: Adverse symptoms may include the following: irritation redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	: No specific data.
Ingestion	: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media	: Use dry chemical powder.
Media Unsuitable extinguishing media	: Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.

5.2 Special hazards arising from the substance or mixture

English (GB)

5.3 Advice for firefighters		
Special precautions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incider there is a fire. No action shall be taken involving any personal risk or without suit training. Move containers from fire area if this can be done without risk. Use wat spray to keep fire-exposed containers cool.	able
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained bro apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clo for fire-fighters (including helmets, protective boots and gloves) conforming to Eu standard EN 469 will provide a basic level of protection for chemical incidents.	thing

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	ote	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
6.3 Methods and material for	со	ntainment and cleaning up
Small spill	:	Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labelled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Code : 00332052	C) No. 1907/2006 (REACH), Annex II Date of issue/Date of revision : 30 March 2023
SIGMAZINC 9 PIGMENT GI	
SECTION 7: Handli	ing and storage
Protective measures	: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing dust. Avoid release to the environment. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
7.2 Conditions for safe storage, including any incompatibilities	: Store between the following temperatures: 5 to 25°C (41 to 77°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

Recommendations	: Not available.
Industrial sector specific solutions	: Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values		
Źínc oxide	ACGIH TLV (United States, 1/2022). STEL: 10 mg/m ³ 15 minutes. Form: Respirable fraction TWA: 2 mg/m ³ 8 hours. Form: Respirable fraction		
procedures Standard EN 689 by inhalation to o strategy) Europe application and u biological agents requirements for agents) Referen	d be made to monitoring standards, such as the following: European 9 (Workplace atmospheres - Guidance for the assessment of exposure chemical agents for comparison with limit values and measurement ean Standard EN 14042 (Workplace atmospheres - Guide for the use of procedures for the assessment of exposure to chemical and b) European Standard EN 482 (Workplace atmospheres - General the performance of procedures for the measurement of chemical nee to national guidance documents for methods for the determination bstances will also be required.		

8.2 Exposure controls

English (GB)	Saudi Arabia	5/12

Conforms to Regulation (EC) No	. 1907/2006 (REACH), Annex II
Code : 00332052		Date of issue/Date of revision : 30 March 2023
SIGMAZINC 9 PIGMENT GR	ΕY	
SECTION 8: Exposu	re	controls/personal protection
Appropriate engineering controls	:	Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Individual protection meas	<u>ures</u>	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection Skin protection	:	Safety glasses with side shields.
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Gloves		nitrile rubber, butyl rubber, PVC, Viton®
Body protection	-	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection		Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

.1 Information on basic p	physical and chemical properties
<u>Appearance</u>	
Physical state	: Solid.
Product type	: Powder.
Colour	: Grey.
Odour	: Aromatic.
Odour threshold	: Not available.

Conforms to Regulation (EC) No	. 1907	· · · ·	
Code : 00332052		Date of issue/Date of revision	: 30 March 2023
SIGMAZINC 9 PIGMENT GREY			
SECTION 9: Physical a	nd o	chemical properties	
Melting point/freezing point	: N	lot available.	
Initial boiling point and boiling range	: N	lot available.	
Flammability	: N	lot available.	
Minimum explosive concentration (MEC)	: 1	0 g/m³	
Flash point	: 0	Closed cup: Not applicable.	
Auto-ignition temperature	: N	lot applicable.	
Decomposition temperature	: 5	Stable under recommended storage and handling condition	ons (see Section 7).
рН	: N	lot applicable. insoluble in water.	
Viscosity	: K	Kinematic (40°C): Not applicable.	
Solubility(ies)	:		
Media		Result	
		N	

cold water		Not soluble
Partition coefficient: n-octanol/ water	: N	lot applicable.
Vapour pressure	: N	lot available.
Evaporation rate	: N	lot available.
Relative density	: 7	.14
Bulk density (g/cm³)	: 7	.1
Vapour density	: H	lighest known value: 5.47 (Air = 1) (zinc oxide).
Explosive properties		he product itself is not explosive, but the formation of an explosible mixture of apour or dust with air is possible.
Oxidising properties	: F	roduct does not present an oxidizing hazard.
Particle characteristics		
Median particle size	: 🕨	ot available.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity				
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.			
10.2 Chemical stability	: The product is stable.			
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.			
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.			
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.			
10.6 Hazardous decomposition products	: Evolves hydrogen on contact with water. Depending on conditions, decomposition products may include the following materials: metal oxide/oxides			

Code : 00332052 SIGMAZINC 9 PIGMENT GREY Date of issue/Date of revision

: 30 March 2023

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name		Result	Species	Dose	Exposure
Zinc powder - zinc dust (sta zinc oxide	abilized)	LC50 Inhalation Dusts and mists LD50 Oral LC50 Inhalation Dusts and	Rat Rat Rat	>5.4 mg/l >2000 mg/kg >5700 mg/m ³	4 hours - 4 hours
		mists LD50 Dermal LD50 Oral	Rat Rat	>2000 mg/kg >5000 mg/kg	-
Conclusion/Summary	: There are	no data available on the mixture	e itself.	0.0	
Irritation/Corrosion					
Conclusion/Summary					
Skin	: There are n	no data available on the mixture	itself.		
Eyes	: There are n	no data available on the mixture	itself.		
Respiratory	: There are n	no data available on the mixture	itself.		
Sensitisation					
Conclusion/Summary					
Skin	: There are	no data available on the mixture	e itself.		
Respiratory	: There are	no data available on the mixture	e itself.		
<u>Mutagenicity</u>					
Conclusion/Summary	: There are	no data available on the mixture	e itself.		
Carcinogenicity					
Conclusion/Summary	: There are	no data available on the mixture	e itself.		
Reproductive toxicity			1		
Conclusion/Summary	: There are	no data available on the mixture	e itseit.		
Teratogenicity			:4		
Conclusion/Summary		no data available on the mixture	e itseit.		
Specific target organ toxi Not available.	<u>city (single expo</u>	<u>osurej</u>			
Specific target organ toxi	city (repeated ex	<u>xposure)</u>			
Not available.					
Aspiration hazard					
Not available.					
Information on likely	: Not availat	ble.			
routes of exposure	i not dranak				
Potential acute health effe	ects				
Inhalation		to airborne concentrations abov e irritation of the nose, throat and		recommended ex	posure limits
Ingestion	-	significant effects or critical haz	•		
Skin contact	: No known	significant effects or critical haz	ards.		
Eye contact		to airborne concentrations abov e irritation of the eyes.	e statutory or	recommended ex	posure limits
Symptoms related to the	physical, chemi	cal and toxicological characte	eristics		
Inhalation		mptoms may include the follow tract irritation	/ing:		

Code : 00332052		Date of issue/Date of revision : 30 March 2023		
	\sim	Date of Issue/Date of Tevision . 50 March 2023		
SIGMAZINC 9 PIGMENT GRE	Y			
SECTION 11: Toxicol	0	gical information		
Ingestion	:	No specific data.		
Skin contact	:	No specific data.		
Eye contact	1	Adverse symptoms may include the following: irritation redness		
Delayed and immediate effe	ct	as well as chronic effects from short and long-term exposure		
Short term exposure				
Potential immediate effects	1	Not available.		
Potential delayed effects	:	Not available.		
Long term exposure				
Potential immediate effects	1	Not available.		
Potential delayed effects	:	Not available.		
Potential chronic health effe	ect	<u>s</u>		
Not available.				
Conclusion/Summary	:	Not available.		
General	:	Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.		
Carcinogenicity	:	No known significant effects or critical hazards.		
Mutagenicity	:	No known significant effects or critical hazards.		
Reproductive toxicity	:	No known significant effects or critical hazards.		
Other information	:	Not available.		
Sanding and grinding dusts m	ay	be harmful if inhaled.		
11.2 Information on other ha	aza	urds		
11.2.1 Endocrine disrupting	g r	properties		

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure	
Zinc powder - zinc dust (stabilized)	Acute EC50 0.106 mg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours	
	Chronic NOEC 0.0727 mg/l Fresh water	Daphnia - Daphnia Magna	21 days	
zinc oxide	Acute EC50 0.17 mg/l Acute EC50 0.481 mg/l Fresh water	Algae Daphnia - Daphnia magna - Neonate	72 hours 48 hours	
	Chronic NOEC 0.017 mg/l Fresh water	Algae	72 hours	

Conclusion/Summary

: There are no data available on the mixture itself.

12.2 Persistence and degradability

Conclusion/Summary : There are no data available on the mixture itself.

12.3 Bioaccumulative potential

Not available.

English (GB)

Code : 00332052 SIGMAZINC 9 PIGMENT GREY Date of issue/Date of revision

SECTION 12: Ecological information

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.

European waste catalogue (EWC)

Waste code	Waste designation	
08 02 01	waste coating powders	
Packaging		

Packaging

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)		
Container	15 01 06 mixed packaging		
Special precautions	This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.		

Code : 00332052 SIGMAZINC 9 PIGMENT GREY Date of issue/Date of revision

: 30 March 2023

SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number or ID number	UN3077	UN3077	UN3077
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Zinc powder - zinc dust (stabilized), zinc oxide)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
14.3 Transport hazard class(es)	9	9	9
14.4 Packing group	Ш	Ш	III
14.5 Environmental hazards	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	(Zinc powder - zinc dust (stabilized), zinc oxide)	Not applicable.

Additional information

ADR/RID	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.	
Tunnel code	: (-)	
IMDG	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. The segregation group has been manually assigned based upon product analysis.	
ΙΑΤΑ	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.	
14.6 Special prec user	autions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.	
14.7 Transport in according to IMO instruments	bulk : Not applicable.	
	Desulaters information	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
<u>EU Regulation (EC) No. 1907/2006 (REACH)</u>
<u>Annex XIV - List of substances subject to authorisation</u>
<u>Annex XIV</u>
None of the components are listed.
<u>Substances of very high concern</u>
None of the components are listed.

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain

dangerous substances, mixtures and articles

Other national and international regulations.

Conforms to Regulation (EC)) No. 1907/2006 (REACH), A	nnex II	
Code : 00332052		Date of issue/Date of revision	: 30 March 2023
SIGMAZINC 9 PIGMENT GRE	ΞY		
SECTION 15: Regula	atory information		
Ozone depleting substance	es (1005/2009/EU)		
Not listed.			
15.2 Chemical safety assessment	: No Chemical Safety Asse	essment has been carried out.	
SECTION 16: Other i	information		
Indicates information that	has changed from previously	issued version.	
Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number 		
Full text of abbreviated H statements	 H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. 		
Full text of classifications [CLP/GHS]	: Aquatic Acute 1 Aquatic Chronic 1	SHORT-TERM (ACUTE) AQUATI LONG-TERM (CHRONIC) AQUAT	
<u>History</u>			
Date of issue/ Date of revision	: 30 March 2023		
Date of previous issue	: 7 November 2021		
Prepared by	: EHS		
Version	: 3.01		
<u>Disclaimer</u>			

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.