SAFETY DATA SHEET



Date of issue 5/10/2023 (month/day/year)

Version 6

Section 1. Chemical product and company identification

A. Product name : SIGMALINE 855 HARDENER

Product code : 00184962

B. Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.

Use of the substance/

mixture

: Coating.

Uses advised against: Product is not intended, labelled or packaged for consumer use.

C. Supplier's or Importer's

information

Email Address

: PPG SSC (680-090)

19, Yeocheon-ro 217beon-gil, Nam-gu,

Ulsan, Korea

Tel: +82-52-210-8222 Korea.MSDS@PPG.COM

Emergency telephone

number:

: +82-52-210-8222

Section 2. Hazards identification

A. Hazard classification : ACUTE TOXICITY (inhalation) - Category 4

SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A

RESPIRATORY SENSITIZATION - Category 1

SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract

irritation) - Category 3

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2

This product is classified in accordance with the Industrial Safety and Health Act and the Chemical Control Act.

B. GHS label elements, including precautionary statements

Symbol :



Signal word : Danger

Korea (GHS) Page: 1/13

Product name SIGMALINE 855 HARDENER

Section 2. Hazards identification

Hazard statements

: H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

H332 - Harmful if inhaled.

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 - May cause respiratory irritation. H351 - Suspected of causing cancer.

H373 - May cause damage to organs through prolonged or repeated exposure.

(respiratory system)

Precautionary statements

Prevention

: P202 - Do not handle until all safety precautions have been read and understood.

P280 - Wear protective gloves, protective clothing and eye or face protection.

P284 - Wear respiratory protection.

P260 - Do not breathe vapor.

P264 - Wash thoroughly after handling.

P308 + P313 - IF exposed or concerned: Get medical advice or attention. Response

P304 + P340, P312 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. P342 + P311 - If experiencing respiratory symptoms: Call a POISON CENTER or

P362 + P364 - Take off contaminated clothing and wash it before reuse.

P302 + P352 - IF ON SKIN: Wash with plenty of water.

P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical advice or attention.

Storage : P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

: P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

C. Other hazards which do : None known.

not result in classification

Disposal

Section 3. Composition/information on ingredients

Chemical name : Polymethylenepolyphenyl isocyanate

CAS number/other identifiers

CAS number : Not applicable.

Chemical name	Common name	Identifiers	%
Socyanic acid, polymethylenepolyphenylene ester Diphenylmethane 4,4'-diisocyanate	and homologues		50 - <60 30 - <40
methylene diphenyl diisocyanate methylene diphenyl diisocyanate		CAS: 5873-54-1 CAS: 2536-05-2	10 -<20 1 - <5

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Korea (GHS) Page: 2/13

Product name SIGMALINE 855 HARDENER

Section 3. Composition/information on ingredients

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

A. Eye contact : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

B. Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

C. Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

D. Ingestion : If swallowed, seek medical advice immediately and show this container or label.
 Keep person warm and at rest. Do NOT induce vomiting.

E. Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

No specific treatment.
No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

A. Extinguishing media

Specific treatments

Protection of first-aiders

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media

: None known.

B. Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products

: Decomposition products may include the following materials:

carbon oxides nitrogen oxides

Cyanate and isocyanate. hydrogen cyanide

C. Special equipment for fire-fighting

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Fire-fighting procedures:

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without

suitable training.

Korea (GHS) Page: 3/13

Date of issue 5/10/2023 (month/day/year)

Product code 00184962

Product name SIGMALINE 855 HARDENER

Version 6

Section 6. Accidental release measures

- A. Personal precautions, protective equipment and emergency procedures
- : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- B. Environmental precautions
- : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

C. Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Special provisions

: Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Place in a suitable container. The contaminated area should be cleaned immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises (by volume): water (45 parts), ethanol or isopropyl alcohol (50 parts) and concentrated (d: 0,880) ammonia solution (5 parts). A non-flammable alternative is sodium carbonate (5 parts) and water (95 parts). Add the same decontaminant to the remnants and let stand for several days until no further reaction in an unsealed container. Once this stage is reached, close container and dispose of according to local regulations (see section 13). Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

Section 7. Handling and storage

A. Precautions for safe handling

Fut on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Korea (GHS) Page: 4/13

Product name SIGMALINE 855 HARDENER

Section 7. Handling and storage

B. Conditions for safe storage, including any incompatibilities

Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Precautions should be taken to minimize exposure to atmospheric humidity or water. CO₂ will be formed, which, in closed containers, could result in pressurization.

Section 8. Exposure controls/personal protection

A. Occupational exposure limits

Ingredient name	Exposure limits
	Ministry of Employment and Labor (Republic of Korea, 1/2020). TWA: 0.005 ppm 8 hours.

Recommended monitoring procedures

: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

B. Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

C. Personal protective equipment

Respiratory protection

: Use an air-fed respirator unless a site-specific assessment determines that an air-fed respirator is not necessary, in which case the results of the risk assessment should be utilized to determine whether respiratory protection is necessary and what type of protection is appropriate. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Eye protection Hand protection : Chemical splash goggles.

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Gloves

: butyl rubber

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Korea (GHS) Page: 5/13

Product name SIGMALINE 855 HARDENER

Section 8. Exposure controls/personal protection

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the layatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Restrictions on use

Persons with a history of asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

A. Appearance

Physical state : Liquid. Color : Colorless. B. Odor : Amine-like. C. Odor threshold : Not available. D. pH : Not applicable. E. Melting/freezing point : Not available. F. Boiling point/boiling : >37.78°C (>100°F)

range

G. Flash point : Closed cup: Not applicable.

Not available. H. Evaporation rate Flammability (solid, gas) : Not available. J. Lower and upper : Not available.

explosive (flammable)

limits

K. Vapor pressure

	Vapor Pressure at 20°C			Vapor pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
2/2'-methylenediphenyl diisocyanate	0.000061	0.0000081	OECD 104			

Media Result L. Solubility(ies)

cold water Not soluble

Not available. Solubility in water Vapor density Not available.

Relative density 1.23

Partition coefficient: n-

octanol/water

: Not applicable.

Auto-ignition temperature

Ingredient name	°C	°F	Method
4,4'-methylenediphenyl diisocyanate	>601	>1113.8	EU A.15

Korea (GHS) Page: 6/13

Product name SIGMALINE 855 HARDENER

Section 9. Physical and chemical properties

Q. Decomposition temperature

: Not available.

_ Viscosity

: Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)

Flow time (ISO 2431)

Not available.

Molecular weight

: Not applicable.

Section 10. Stability and reactivity

A. Chemical stability

: The product is stable.

Possibility of hazardous

: Under normal conditions of storage and use, hazardous reactions will not occur.

reactions

B. Conditions to avoid

: In a fire, hazardous decomposition products may be produced.

C. Incompatible materials

: Keep away from: oxidizing agents, strong alkalis, strong acids, amines, alcohols,

water. Uncontrolled exothermic reactions occur with amines and alcohols.

D. Hazardous

decomposition products

: Depending on conditions, decomposition products may include the following materials: Cyanate and isocyanate. carbon oxides nitrogen oxides hydrogen

cyanide

Section 11. Toxicological information

Information on the likely routes of exposure

: Not available.

Potential acute health effects

Inhalation

: Harmful if inhaled. May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Ingestion

: No known significant effects or critical hazards.

Skin contact

: Causes skin irritation. May cause an allergic skin reaction.

Eye contact

: Causes serious eye irritation.

Over-exposure signs/symptoms

Inhalation

: Adverse symptoms may include the following:

respiratory tract irritation

coughing

wheezing and breathing difficulties

asthma

Ingestion

: No specific data.

Skin contact

Adverse symptoms may include the following:

irritation redness

Eye contact

: Adverse symptoms may include the following:

pain or irritation

watering redness

B. Health hazards

Acute toxicity

Korea (GHS) Page: 7/13

Product code 00184962 Date of issue 5/10/2023 (month/day/year) Version 6
Product name SIGMALINE 855 HARDENER

Section 11. Toxicological information

Product/ingredient name	Result	Species	Dose	Exposure
socyanic acid, polymethylenepolyphenylene ester	LD50 Dermal	Rabbit	>9400 mg/kg	-
Diphenylmethane 4,4'-diisocyanate	LD50 Oral LD50 Oral	Rat Rat	49 g/kg 9200 mg/kg	-

Conclusion/Summary: There are no data available on the mixture itself.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Diphenylmethane 4,4'-diisocyanate	Skin - Irritant	Rabbit	-	•	-

Conclusion/Summary

Skin: There are no data available on the mixture itself.Eyes: There are no data available on the mixture itself.Respiratory: There are no data available on the mixture itself.

Sensitization

Product/ingredient name	Route of exposure	Species	Result
Diphenylmethane 4,4'-diisocyanate	Respiratory	Guinea pig	Sensitizing
dioosyanato	skin	Mouse	Sensitizing

Conclusion/Summary

Skin : There are no data available on the mixture itself.Respiratory : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary: There are no data available on the mixture itself.

Carcinogenicity

Product/ingredient name	Result	Species	Dose	Exposure
Diphenylmethane 4,4'- diisocyanate	Positive - Inhalation - TC	Rat	0 to 6 mg/m ³	2 years; 5 days per week

Conclusion/Summary: There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary: There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Korea (GHS) Page: 8/13

Product code 00184962	Date of issue 5/10/2023 (month/day/year)	Version 6
Product name SIGMALINE 855 HARDENER		

Section 11. Toxicological information

Name	Classification	Route of exposure	Target organs
Socyanic acid, polymethylenepolyphenylene ester	Category 3	-	Respiratory tract irritation
Diphenylmethane 4,4'-diisocyanate	Category 3	-	Respiratory tract irritation
methylene diphenyl diisocyanate	Category 3	-	Respiratory tract irritation
methylene diphenyl diisocyanate	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Name	Classification	Route of exposure	Target organs
Socyanic acid, polymethylenepolyphenylene ester Diphenylmethane 4,4'-diisocyanate methylene diphenyl diisocyanate methylene diphenyl diisocyanate		inhalation inhalation - -	respiratory system -

Aspiration hazard

Not available.

Potential chronic health effects

General : May cause damage to organs through prolonged or repeated exposure. Once

sensitized, a severe allergic reaction may occur when subsequently exposed to very low

levels.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of

exposure.

Mutagenicity: No known significant effects or critical hazards.

Reproductive toxicity: No known significant effects or critical hazards.

Additional information

Based on the properties of the isocyanate components and considering toxicological data on similar mixtures, this mixture may cause acute irritation and/or sensitization of the respiratory system, leading to an asthmatic condition, wheezing and tightness of the chest. Sensitized persons may subsequently show asthmatic symptoms when exposed to atmospheric concentrations well below the OEL. Persons with a history of skin sensitization problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Repeated exposure may lead to permanent respiratory disability. Moisture-sensitive material.

Chemical name	Identifiers	GHS Classification
socyanic acid, polymethylenepolyphenylene ester	CAS: 9016-87-9	ACUTE TOXICITY (inhalation) - Category 4
		SKIN IRRITATION - Category 2
		EYE IRRITATION - Category 2A
		RESPIRATORY SENSITIZATION - Category 1A
		SKIN SENSITIZATION - Category 1A
		CARCINOGENICITY - Category 2
		SPECIFIC TARGET ORGAN TOXICITY (SINGLE
		EXPOSURE) (Respiratory tract irritation) -
		Category 3

Korea (GHS) Page: 9/13

Product code 00184962	Date of issue 5/10/2023 (month/day/year)	Version 6
Product name SIGMALINE 855 HARDENER		

Section 11. Toxicological information

		SPECIFIC TARGET ORGAN TOXICITY
Diphenylmethane 4,4'-diisocyanate	CAS: 101-68-8	(REPEATED EXPOSURE) - Category 2 ACUTE TOXICITY (inhalation) - Category 4
Diplienyimethane 4,4 -diisocyanate	OAG. 101-00-0	SKIN IRRITATION - Category 2
		EYE IRRITATION - Category 2A
		RESPIRATORY SENSITIZATION - Category 1
		SKIN SENSITIZATION - Category 1
		CARCINOGENICITY - Category 2
		SPECIFIC TARGET ORGAN TOXICITY (SINGLE
		EXPOSURE) (Respiratory tract irritation) -
		Category 3
		SPECIFIC TARGET ORGAN TOXICITY
		(REPEATED EXPOSURE) - Category 2
methylene diphenyl diisocyanate	CAS: 5873-54-1	ACUTE TOXICITY (inhalation) - Category 3
		SKIN IRRITATION - Category 2
		EYE IRRITATION - Category 2A
		RESPIRATORY SENSITIZATION - Category 1
		SKIN SENSITIZATION - Category 1
		CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE
		EXPOSURE) (Respiratory tract irritation) -
		Category 3
		SPECIFIC TARGET ORGAN TOXICITY
		(REPEATED EXPOSURE) - Category 2
methylene diphenyl diisocyanate	CAS: 2536-05-2	ACUTE TOXICITY (inhalation) - Category 3
		SKIN IRRITATION - Category 2
		EYE IRRITATION - Category 2A
		RESPIRATORY SENSITIZATION - Category 1
		SKIN SENSITIZATION - Category 1
		CARCINOGENICITY - Category 2
		SPECIFIC TARGET ORGAN TOXICITY (SINGLE
		EXPOSURE) (Respiratory tract irritation) -
		Category 3 SPECIFIC TARGET ORGAN TOXICITY
		(REPEATED EXPOSURE) - Category 2
		AQUATIC HAZARD (LONG-TERM) - Category 4
		AGOATIO HAZARD (LONG-TERM) - Calegory 4

Section 12. Ecological information

A. **Ecotoxicity**

Not available.

B. Persistence and degradability

Not available.

C. Bioaccumulative potential

Korea (GHS) Page: 10/13

Product code 00184962 Date of issue 5/10/2023 (month/day/year) Version 6
Product name SIGMALINE 855 HARDENER

Section 12. Ecological information

Product/ingredient name	LogPow	BCF	Potential
Diphenylmethane 4,4'-diisocyanate	4.51	-	high
methylene diphenyl diisocyanate	4.51	-	high
methylene diphenyl diisocyanate	5.22	-	high

D. Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

E. Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

- A. Disposal methods
- : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
- **B.** Disposal precautions
- : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	IMDG	IATA
A. UN number	Not regulated.	Not regulated.	Not regulated.
B. UN proper shipping name	-	-	-
C. Transport hazard class(es)	-	-	-
D. Packing group	-	-	-
Environmental hazards	No.	No.	No.
E. Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

Additional information

UN : None identified.

Korea (GHS) Page: 11/13

Product name SIGMALINE 855 HARDENER

Section 14. Transport information

: None identified. **IMDG IATA** : None identified.

F. Special precaution which a user to be aware of or needs to comply with in connection with transport or tranportation

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according: Not applicable.

to IMO instruments

Section 15. Regulatory information

A. Regulation according to ISHA

ISHA article 117 : None of the components are listed.

(Harmful substances prohibited from manufacture)

ISHA article 118 : None of the components are listed.

(Harmful substances requiring permission)

Article 2 of Youth Protection : It is not allowed to sell to persons under the age of 19.

Act on Substances Hazardous to Youth

Exposure Limits of Chemical Substances and Physical Factors

The following components have an OEL: Diphenylmethane 4,4'-diisocyanate

ISHA Enforcement Regs : The following components are listed: methylene bis(phenyl isocyanate)

Annex 19 (Exposure standards established for harmful factors)

ISHA Enforcement Regs : The following components are listed: methylene bis(phenyl isocyanate)

Annex 21 (Harmful factors subject to Work

Environment Measurement)

ISHA Enforcement Regs : The following components are listed: Methylene bis(phenyl isocyanate)

Annex 22 (Harmful Factors Subject to Special Health Check-

up)

Standard of Industrial : The following components are listed: methylene bis(phenyl isocyanate) Safety and Health

Annex 12 (Hazardous substances subject to control)

B. Regulation according to Chemicals Control Act

Article 11 (TRI) : The following components are listed: Diphenylmethane 4,4'-diisocyanate

Page: 12/13 Korea (GHS)

Product name SIGMALINE 855 HARDENER

Section 15. Regulatory information

Reach Article 27)

Article 18 Prohibited (K- : None of the components are listed.

Article 19 Subject to

authorization (K-Reach

Article 25)

: None of the components are listed.

Article 20 Restricted (K-

Reach Article 27)

: None of the components are listed.

Article 20 Toxic Chemicals (K-Reach

Article 20)

Korea inventory

Article 39 (Accident

: All components are listed or exempted. : None of the components are listed.

Precaution Chemicals) C. Dangerous Materials

: Not applicable.

: Toxic

Safety Management Act

D. Wastes regulation

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

E. Regulation according to other foreign laws

Safety, health and environmental regulations specific for

: No known specific national and/or regional regulations applicable to this product (including its ingredients).

the product

Section 16. Other information

: Korean Ministry of Environment; Chemical Control Act A. References

Korean Ministry of Labor; Industrial Safety and Health Act

NIER Notice

Registry of Toxic Effects of Chemical Substances (RTECS)

U.S. Environmental Protection Agency, AQUIRE (Aquatic toxicity Information

Retrieval) ECOTOX Database System.

B. Date of issue/Date of

revision

: 5/10/2023

C. Version : 6 : EHS Prepared by

D. Other

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

> Korea (GHS) Page: 13/13