SAFETY DATA SHEET



Date of issue/Date of revision 10 May 2023 Version 5.01

Section 1. Identification				
Product code	: 00184962			
Product name	: SIGMALINE 855 HARDENER			
Chemical name	: Polymethylenepolyphenyl isocyanate			
Product type	: Liquid.			
Relevant identified uses o	f the substance or mixture and uses advised against			
Product use	Coating. Professional applications, Used by spraying.			
Supplier's details	: PPG Industries (Singapore) Pte. Ltd., No. 1 Tuas Basin Close, Singapore 638803. Tel +65 68653737			
Emergency telephone number (with hours of operation)	: CHEMTREC +(65)-31581349 (CCN 17704)			

Section 2. Hazards identification

Classification of the substance or mixture	: ACUTE TOXICITY (inhalation) - Category 4 SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A RESPIRATORY SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2

GHS label elements, including precautionary statements

÷.

Hazard pictograms



Signal word

: Danger

Product code 00184962

Product name SIGMALINE 855 HARDENER

Section 2. Hazards identification

Hazard statements	: Causes skin irritation.
	May cause an allergic skin reaction.
	Causes serious eye irritation.
	Harmful if inhaled.
	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
	May cause respiratory irritation.
	Suspected of causing cancer.
	May cause damage to organs through prolonged or repeated exposure. (respiratory system)
Precautionary statements	
Prevention	: po not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Wear respiratory protection. Do not breathe vapor. Wash thoroughly after handling.
Response	: IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. If experiencing respiratory symptoms: Call a POISON CENTER or doctor. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Storage	: Store in a well-ventilated place. Keep container tightly closed.
Disposal	: Not applicable.

Other hazards which do not : None known. result in classification

Section 3. Composition/information on ingredients

Substance/mixture	:	Mixture
Chemical name	1	Polymethylenepolyphenyl isocyanate

CAS number/other identifiers

CAS number	: Not applicable.
EC number	: Mixture.
Ingredient name	

Ingredient name	%	CAS number
Kocyanic acid, polymethylenepolyphenylene ester	50 - 100	9016-87-9
4,4'-methylenediphenyl diisocyanate	25 - <50	101-68-8
o-(p-isocyanatobenzyl)phenyl isocyanate	10 - <20	5873-54-1
2,2'-methylenediphenyl diisocyanate	1 - <3	2536-05-2

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Singapore	English (US)	Page: 2/13
-----------	--------------	------------

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	 Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	 Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	 If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most im	portant s	ym i	otoms/effects,	acute	and	delaye	d

wost important symptoms/e	inects, acute and delayed
Potential acute health effe	<u>ots</u>
Eye contact	: Causes serious eye irritation.
Inhalation	 Harmful if inhaled. May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/symp	u <u>toms</u>
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing wheezing and breathing difficulties asthma
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
Indication of immediate mediate	lical attention and special treatment needed, if necessary
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Singapore	English (US)	Page: 3/13
-----------	--------------	------------

Section 5. Fire-fighting measures

an avtinguishing agant auitable for the aurrounding fire
an avtinguishing agant auitable for the aurrounding fire
e an extinguishing agent suitable for the surrounding fire.
ne known.
fire or if heated, a pressure increase will occur and the container may burst.
composition products may include the following materials: bon oxides ogen oxides anate and isocyanate. rogen cyanide
mptly isolate the scene by removing all persons from the vicinity of the incident if re is a fire. No action shall be taken involving any personal risk or without able training.
e-fighters should wear appropriate protective equipment and self-contained athing apparatus (SCBA) with a full face-piece operated in positive pressure de.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill: Stop leak if without risk. Move containers from spill area. Dilute with water and mop
up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry
material and place in an appropriate waste disposal container. Dispose of via a
licensed waste disposal contractor.

Product name SIGMALINE 855 HARDENER

Section 6. Accidental release measures

Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.
Special provisions	: Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Place in a suitable container. The contaminated area should be cleaned immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises (by volume): water (45 parts), ethanol or isopropyl alcohol (50 parts) and concentrated (d: 0,880) ammonia solution (5 parts). A non-flammable alternative is sodium carbonate (5 parts) and water (95 parts). Add the same decontaminant to the remnants and let stand for several days until no further reaction in an unsealed container. Once this stage is reached, close container and dispose of according to local regulations (see section 13). Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	• Fut on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10

Section 7. Handling and storage

for incompatible materials before handling or use.

Precautions should be taken to minimize exposure to atmospheric humidity or water. CO_2 will be formed, which, in closed containers, could result in pressurization.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name			Exposure limits			
4,4'-methylenediphenyl diisocyanate			Workplace Safety and Health Act (Singapore, 2/2006). PEL (long term): 0.051 mg/m ³ 8 hours. PEL (long term): 0.005 ppm 8 hours.			
Recommended monitoring procedures	:		riate monitoring standards. Reference to nods for the determination of hazardous			
Appropriate engineering controls	:	Use only with adequate ventilation. U ventilation or other engineering contro contaminants below any recommended	ls to keep worker exposure to airborne			
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.				
Individual protection measur	es					
Hygiene measures	:	eating, smoking and using the lavator Appropriate techniques should be use Contaminated work clothing should no	bughly after handling chemical products, before y and at the end of the working period. ed to remove potentially contaminated clothing. ot be allowed out of the workplace. Wash Ensure that eyewash stations and safety location.			
Eye/face protection	:	Chemical splash goggles.				
Skin protection						
Hand protection	:	be worn at all times when handling ch this is necessary. Considering the pa check during use that the gloves are s should be noted that the time to break	s complying with an approved standard should emical products if a risk assessment indicates rameters specified by the glove manufacturer, still retaining their protective properties. It athrough for any glove material may be rers. In the case of mixtures, consisting of the of the gloves cannot be accurately			
Gloves	:	butyl rubber				
Body protection	:		body should be selected based on the task d and should be approved by a specialist			

Singapore	English (US)	Page: 6/13
-----------	--------------	------------

Version 5.01

Product name SIGMALINE 855 HARDENER

Section 8. Exposure controls/personal protection

-	
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Use an air-fed respirator unless a site-specific assessment determines that an air- fed respirator is not necessary, in which case the results of the risk assessment should be utilized to determine whether respiratory protection is necessary and what type of protection is appropriate. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Restrictions on use	 Persons with a history of asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used.

Section 9. Physical and chemical properties

<u>Appearance</u>					
Physical state	Liquid.				
Color	Colorless.				
Odor	Amine-like.				
рН	insoluble in water.				
Boiling point	>37.78°C (>100°F)				
Flash point	Closed cup: Not applicable.				
Evaporation rate	Not available.				
Flammability (solid, gas)	liquid	liquid			
Vapor pressure	Ħghest known value: 8e-006 kPa (6e-005 mm Hg) (at 20°C) (2,2'- methylenediphenyl diisocyanate). Weighted average: 1e-006 kPa (8e-006 mm Hg) (at 20°C)				
Relative density	1.23				
Solubility/icc)	Media Result				
Solubility(ies)	Not soluble				
Auto-ignition temperature	Lowest known value: >601°C (>1113.8°F) (2,2'-methylenediphenyl diisocyanat	e).			
Viscosity	Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)				

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: In a fire, hazardous decomposition products may be produced.
	Keep away from: oxidizing agents, strong alkalis, strong acids, amines, alcohols, water. Uncontrolled exothermic reactions occur with amines and alcohols.
Singapore English (US)	Page: 7/13

per week

Section 10. Stability and reactivity

Incompatible materials

Hazardous	decomposition
products	

: Depending on conditions, decomposition products may include the following materials: Cyanate and isocyanate. carbon oxides nitrogen oxides hydrogen cyanide

Section 11. Toxicological information

÷.

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Socyanic acid, polymethylenepolyphenylene ester	LD50 Dermal	Rabbit	>9400 mg/kg	-
4,4'-methylenediphenyl diisocyanate	LD50 Oral LD50 Oral	Rat Rat	49 g/kg 9200 mg/kg	-

Conclusion/Summary : There are no data available on the mixture itself.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
4,4'-methylenediphenyl diisocyanate	Skin - Irritant	Rabbit	-	-	-

Conclusion/Summary

- : There are no data available on the mixture itself.
- Eyes
- There are no data available on the mixture itself.There are no data available on the mixture itself.
- Respiratory Sensitization

diisocyanate

Skin

Product/ingredient nameRoute of
exposureSpeciesResult#,4'-methylenediphenyl
diisocyanateRespiratory
skinGuinea pig
MouseSensitizing
Sensitizing
Sensitizing

	Conclusion/Summary						
	Skin :	There are no data available on	the mixture itself.				
	Respiratory :	There are no data available on	the mixture itself.				
	<u>Mutagenicity</u>						
	Conclusion/Summary : There are no data available on the mixture itself.						
9	Carcinogenicity						
	Product/ingredient name	Result	Species	Dose	Exposure		
	4,4'-methylenediphenyl	Positive - Inhalation - TC	Rat	0 to 6 mg/m ³	2 years; 5 days		

 Conclusion/Summary
 : There are no data available on the mixture itself.

 Singapore
 English (US)

 Page: 8/13

Product name SIGMALINE 855 HARDENER

Section 11. Toxicological information

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Isocyanic acid, polymethylenepolyphenylene ester	Category 3	-	Respiratory tract irritation
4,4'-methylenediphenyl diisocyanate	Category 3	-	Respiratory tract irritation
o-(p-isocyanatobenzyl)phenyl isocyanate	Category 3	-	Respiratory tract irritation
2,2'-methylenediphenyl diisocyanate	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
4,4'-methylenediphenyl diisocyanate o-(p-isocyanatobenzyl)phenyl isocyanate	Category 2 Category 2 Category 2 Category 2	inhalation inhalation - -	- respiratory system - -

Aspiration hazard

Not available.

: Not available. Information on the likely

routes	of	exposure	-	
routes	υ	exposure		

Potential acute health effects

Eye contact	: Causes serious eye irritation.
Inhalation	 Harmful if inhaled. May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing wheezing and breathing difficulties asthma

Section 11. Toxicological information

	5
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
Delayed and immediate effe	cts and also chronic effects from short and long term exposure
Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	<u>ects</u>
General	: May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Inhalation (vapors)	25.58 mg/l
Inhalation (dusts and mists)	2.14 mg/l

Other information

Based on the properties of the isocyanate components and considering toxicological data on similar mixtures, this mixture may cause acute irritation and/or sensitization of the respiratory system, leading to an asthmatic condition, wheezing and tightness of the chest. Sensitized persons may subsequently show asthmatic symptoms when exposed to atmospheric concentrations well below the OEL. Persons with a history of skin sensitization problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Repeated exposure may lead to permanent respiratory disability. Moisture-sensitive material.

Section 12. Ecological information

Toxicity

Not available.

Conclusion/Summary	: There are no data available on the mixture itself.
Persistence/degradability	
Not available.	

Conclusion/Summary : There are no data available on the mixture itself.

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
4'-methylenediphenyl diisocyanate	4.51	-	high
o-(p-isocyanatobenzyl) phenyl isocyanate	4.51	-	high
2,2'-methylenediphenyl diisocyanate	5.22	-	high

Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its
	container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

Additional information

UN	: None identified.
IMDG	: None identified.
IATA	: None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Section 15. Regulatory information

Singapore - hazardous chemicals under government control

Ingredient name	Status
I socyanates	Listed
Isocyanates	Listed
Isocyanates	Listed
Isocyanates	Listed

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Section 16. Other information

<u>History</u>	
Date of issue/Date of revision	: 10 May 2023
Date of previous issue	: 3/28/2021
Version	: 5.01
Prepared by	: EHS
Key to abbreviations	 ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations

Indicates information that has changed from previously issued version.

Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.