SAFETY DATA SHEET



Conforms to Official Mexican Standard NOM-018-STPS-2015

Date of revision 16 May 2023

Version 2

Date of issue 16 May 2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

| Product name | : 🖻 🛛 JOINT FILLER CLEAR - A |
|---|---|
| Product code | : 00465278 |
| Other means of identification | : Not applicable. |
| Product type | : Liquid. |
| Relevant identified uses or | f the substance or mixture and uses advised against |
| Product use | : Industrial applications, Professional applications, Used by spraying. |
| Use of the substance/ mixture | : Coating. |
| Uses advised against | Not applicable. |
| Manufacturer | : PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272 |
| <u>Emergency telephone</u> <u>number</u> | : (412) 434-4515 (U.S.) (514) 645-1320 (Canada) SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México) |
| Technical Phone Number | : 888-977-4762 |

SECTION 2: Hazards identification

| 17.4% (oral), 94.3% (dermal), 53% (inhalation) | Classification of the substance or mixture | ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A RESPIRATORY SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 17.4% (oral), 94.3% (dermal), 53% (inhalation) |
|--|--|--|
|--|--|--|

GHS label elements

Product name SL90 JOINT FILLER CLEAR - A

SECTION 2: Hazards identification

1

| Hazard | pictograms |
|--------|------------|
|--------|------------|



| | ★ ★ |
|---|--|
| Signal word | : Danger |
| Hazard statements | H302 + H332 - Harmful if swallowed or if inhaled. H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 - May cause respiratory irritation. H351 - Suspected of causing cancer. H373 - May cause damage to organs through prolonged or repeated exposure. (respiratory system) |
| Precautionary statements | |
| Prevention | P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P280 - Wear protective gloves, protective clothing and eye or face protection. P284 - Wear respiratory protection. P271 - Use only outdoors or in a well-ventilated area. P260 - Do not breathe vapor. P270 - Do not eat, drink or smoke when using this product. P264 - Wash thoroughly after handling. P272 - Contaminated work clothing should not be allowed out of the workplace. |
| Response | P308 + P313 - IF exposed or concerned: Get medical advice or attention. P304 + P340, P312 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. P342 + P311 - If experiencing respiratory symptoms: Call a POISON CENTER or doctor. P301 + P312, P330 - IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell. Rinse mouth. P362 + P364 - Take off contaminated clothing and wash it before reuse. P302 + P352 - IF ON SKIN: Wash with plenty of water. P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical advice or attention. |
| Storage | : P405 - Store locked up. P403 + P233 - Store in a well-ventilated place. Keep container tightly closed. |
| Disposal | : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations. |
| Other hazards which do not result in classification | : Skin contact to isocyanate monomer may lead to allergic lung reaction. Based on the properties of the isocyanate components and considering toxicological data on similar mixtures, this mixture may cause acute irritation and/or sensitization of the respiratory system, leading to an asthmatic condition, wheezing and tightness of the chest. Sensitized persons may subsequently show asthmatic symptoms when exposed to atmospheric concentrations well below the OEL. Persons with a history of skin sensitization problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Repeated exposure may lead to permanent respiratory disability. Moisture-sensitive material. Emits toxic fumes when heated. |

Product name SL90 JOINT FILLER CLEAR - A

SECTION 2: Hazards identification

| Supplemental label elements (First aid measures): | Photosensitive agents : In case of accidental eye contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation or blistering occurs after contact. In case of accidental skin contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation, rash or |
|---|---|
| | These reactions can be delayed – get medical attention if pain, irritation, rash or blistering occurs after contact. |

See toxicological information (Section 11)

SECTION 3: Composition/information on ingredients

Substance/mixture Product name Other means of identification : SL90 JOINT FILLER CLEAR - A

: Not applicable.

| Ingredient name | % | CAS number |
|---|-------------|------------|
| Propane-1,2-diol, propoxylated | ≥20 - ≤50 | 25322-69-4 |
| 4,4'-methylenediphenyl diisocyanate | ≥20 - ≤29 | 101-68-8 |
| o-(p-isocyanatobenzyl)phenyl isocyanate | ≥10 - ≤19 | 5873-54-1 |
| propylene carbonate | ≥5.0 - ≤10 | 108-32-7 |
| Isocyanic acid, polymethylenepolyphenylene ester | ≥1.0 - ≤5.0 | 9016-87-9 |
| 2,2'-methylenediphenyl diisocyanate | ≤2.0 | 2536-05-2 |
| methylenediphenyl diisocyanate | ≤1.5 | 26447-40-5 |
| 2,4-dioxo-1,3-diazetidine-1,3-diylbis[p-phenylenemethylene-p-phenylene] diisocyanate | <1.0 | 17589-24-1 |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

Description of necessary first aid measures

| Eye contact | Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. In case of accidental eye contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation or blistering occurs after contact. |
|--------------|--|
| Inhalation | : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. |
| Skin contact | Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. In case of accidental skin contact, avoid direct exposure to the sun or other sources of UV light as severe irritation including burns may result. These reactions can be delayed – get medical attention if pain, irritation, rash or blistering occurs after contact. |
| Ingestion | : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting. |

Most important symptoms/effects, acute and delayed

SECTION 4: First aid measures

| Potential acute health effects | |
|--------------------------------|--|
| Eye contact | : Causes serious eye irritation. |
| Inhalation | : Harmful if inhaled. May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| | Causes skin irritation. May cause an allergic skin reaction. Harmful if swallowed. |

Over-exposure signs/symptoms

See toxicological information (Section 11)

| Indication of immediate med | attention and special treatment needed, if necessary | |
|-----------------------------|--|---------|
| Notes to physician | In case of inhalation of decomposition products in a fire, symptoms may be dela The exposed person may need to be kept under medical surveillance for 48 ho | |
| Specific treatments | No specific treatment. | |
| Protection of first-aiders | No action shall be taken involving any personal risk or without suitable training. is suspected that fumes are still present, the rescuer should wear an appropriat mask or self-contained breathing apparatus. It may be dangerous to the perso providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothin thoroughly with water before removing it, or wear gloves. | te n |

SECTION 5: Firefighting measures

| Extinguishing media | |
|--|---|
| Suitable extinguishing media | : Use an extinguishing agent suitable for the surrounding fire. |
| Unsuitable extinguishing media | : None known. |
| Specific hazards arising from the chemical | : In a fire or if heated, a pressure increase will occur and the container may burst. |
| Hazardous thermal decomposition products | : Decomposition products may include the following materials: carbon oxides nitrogen oxides Cyanate and isocyanate. hydrogen cyanide |
| Special protective actions for fire-fighters | : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. |
| Special protective equipment for fire-fighters | Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. |

SECTION 6: Accidental release measures

| Personal precautions, protect | :tiv | e equipment and emergency procedures | |
|--------------------------------|------|--|--------------------|
| For non-emergency personnel | : | No action shall be taken involving any personal risk or without suitable train Evacuate surrounding areas. Keep unnecessary and unprotected personn entering. Do not touch or walk through spilled material. Avoid breathing va mist. Provide adequate ventilation. Wear appropriate respirator when ven inadequate. Put on appropriate personal protective equipment. | el from apor or |
| For emergency responders | : | If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". | 1 |
| | | Mexico | Page: 4/14 |

Product name SL90 JOINT FILLER CLEAR - A

SECTION 6: Accidental release measures

| Environmental precautions | : | Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). |
|------------------------------|-----|---|
| Methods and materials for co | ont | ainment and cleaning up |
| Small spill | : | Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. |
| Large spill | : | Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal. |
| Special provisions | : | Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Place in a suitable container. The contaminated area should be cleaned immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises (by volume): water (45 parts), ethanol or isopropyl alcohol (50 parts) and concentrated (d: 0,880) ammonia solution (5 parts). A non-flammable alternative is sodium carbonate (5 parts) and water (95 parts). Add the same decontaminant to the remnants and let stand for several days until no further reaction in an unsealed container. Once this stage is reached, close container and dispose of according to local regulations (see section 13). Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations. |

SECTION 7: Handling and storage

| Precautions for safe handling | |
|-------------------------------|--|
| Protective measures : | Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. |
| Special precautions : | Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Vapors are heavier than air and may spread along floors. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts. |

SECTION 7: Handling and storage

| Advice on general occupational hygiene | : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. |
|--|---|
| Conditions for safe storage, including any incompatibilities | : Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Precautions should be taken to minimize exposure to atmospheric humidity or water. CO ₂ will be formed, which, in closed containers, could result in pressurization. |

SECTION 8: Exposure controls/personal protection

Control parameters

Occupational exposure limits

| Ingredient name | Exposure limits |
|--|--|
| Propane-1,2-diol, propoxylated 4,4'-methylenediphenyl diisocyanate | None. NOM-010-STPS-2014 (Mexico, 4/2016). |
| ·,· ·································· | TWA: 0.005 ppm 8 hours. |
| o-(p-isocyanatobenzyl)phenyl isocyanate | None. |
| propylene carbonate | None. |
| Isocyanic acid, polymethylenepolyphenylene ester | None. |
| 2,2'-methylenediphenyl diisocyanate | None. |
| methylenediphenyl diisocyanate | None. |
| 2,4-dioxo-1,3-diazetidine-1,3-diylbis[p-phenylenemethylene-p-phenylene] diisocyanate | None. |

Key to abbreviations

| С | = Ceiling Limit | STEL = Short term exposure limit |
|------|---------------------------------------|----------------------------------|
| IPEL | = Internal Permissible Exposure Limit | TLV = Threshold Limit Value |
| | | TWA = Time Weighted Average |

Consult local authorities for acceptable exposure limits.

| Recommended monitoring procedures | : | Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required. |
|-----------------------------------|---|---|
| Appropriate engineering controls | : | Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. |
| Environmental exposure controls | : | Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. |

Individual protection measures

Product name SL90 JOINT FILLER CLEAR - A

SECTION 8: Exposure controls/personal protection

| Hygiene measures | : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. |
|------------------------|---|
| Eye/face protection | : Chemical splash goggles. |
| Skin protection | |
| Hand protection | : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. |
| Gloves | : polyethylene butyl rubber |
| Body protection | Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Other skin protection | Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Respiratory protection | : Use an air-fed respirator unless a site-specific assessment determines that an air- fed respirator is not necessary, in which case the results of the risk assessment should be utilized to determine whether respiratory protection is necessary and what type of protection is appropriate. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. |
| Restrictions on use | Persons with a history of asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. |

SECTION 9: Physical and chemical properties

| <u>Appearance</u> | |
|--|-------------------------------|
| Physical state | : Liquid. |
| Color | : Various |
| Odor | : Faint odor. |
| Odor threshold | : Not available. |
| Molecular weight | : Not applicable. |
| рН | : Not applicable. |
| Melting point | : Not available. |
| Boiling point | : >37.78°C (>100°F) |
| Flash point | : Closed cup: 219°C (426.2°F) |
| Auto-ignition temperature | : Not available. |
| Decomposition temperature | : Not available. |
| Flammability | : Not available. |
| Lower and upper explosive (flammable) limits | : Not available. |
| Evaporation rate | : Not available. |
| Vapor pressure | : Not available. |
| Vapor density | : Not available. |
| | |

Product name SL90 JOINT FILLER CLEAR - A

SECTION 9: Physical and chemical properties

| Relative density | : 1.1 | | |
|--|----------------------|------------------------------|--|
| Density(lbs / gal) | : 9.18 | | |
| | Media | Result | |
| Solubility(ies) | cold water | Not soluble | |
| Solubility in water | : Not available. | | |
| Partition coefficient: n- octanol/water | : Not applicable. | | |
| Viscosity | : Kinematic (40°C (1 | 104°F)): >21 mm²/s (>21 cSt) | |
| Volatility | : 6% (v/v), 7% (w/w) |) | |
| % Solid. (w/w) | : 93 | | |

SECTION 10: Stability and reactivity

| Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |
|------------------------------------|--|
| Chemical stability | : The product is stable. |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| Conditions to avoid | : In a fire, hazardous decomposition products may be produced. Refer to protective measures listed in sections 7 and 8. |
| Incompatible materials | : Keep away from: oxidizing agents, strong alkalis, strong acids, amines, alcohols, water. Uncontrolled exothermic reactions occur with amines and alcohols. |
| Hazardous decomposition products | Depending on conditions, decomposition products may include the following materials: Cyanate and isocyanate. carbon oxides nitrogen oxides hydrogen cyanide |

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|--|----------------------------------|--------------------|--------------|----------|
| 4,4'-methylenediphenyl diisocyanate | LD50 Oral | Rat | 9200 mg/kg | - |
| propylene carbonate | LD50 Oral | Rat | 29 g/kg | - |
| Isocyanic acid, polymethylenepolyphenylene ester | LD50 Dermal | Rabbit | >9400 mg/kg | - |
| | LD50 Oral | Rat | 49 g/kg | - |
| methylenediphenyl diisocyanate | LD50 Dermal | Rabbit | >9400 mg/kg | - |
| | LD50 Oral | Rat | >10000 mg/kg | - |
| Conclusion/Summary | : There are no data available or | n the mixture itse | If. | |

Irritation/Corrosion

Mexico Page: 8/14

Product name SL90 JOINT FILLER CLEAR - A

SECTION 11: Toxicological information

| Product/ingredient name | Result | | S | species | Scor | e E | xposure | Observatior |
|---|---|--|--|---|--------------|---------------------------------------|---------|-----------------|
| 4,4'-methylenediphenyl diisocyanate | Skin - Irrit | tant | F | Rabbit | - | - | | - |
| Conclusion/Summary | | | | | | | | |
| Skin | | | a available | | | | | |
| Eyes | : There are no data available on the mixture its | | | | | | | |
| Respiratory | : There a | ire no dat | a available | on the mix | ture itsel | f. | | |
| ensitization | | | | | | | | |
| Product/ingredient name | Route of exposure | ę | Species | | | Result | | |
| 4,4'-methylenediphenyl diisocyanate | Respirato | - | Guinea pig | | | Sensitizi | - | |
| | skin | | Mouse | | | Sensitizi | • | |
| methylenediphenyl diisocyanate | Respirator | ry (| Guinea pig | | | Sensitizi | ing | |
| anooyanate | skin | | Guinea pig | | | Sensitizi | ing | |
| Conclusion/Summary | <u></u> | | | | | ļ | 5 | |
| Skin | : There a | ire no dat | a available | on the mix | ture itsel | f. | | |
| Respiratory | | | a available | | | | | |
| lutagenicity | | | | | | | | |
| Conclusion/Summary | : There a | ire no dat | | 4l ¹ - | | c . | | |
| oonclusion/ounnary | | | | on the mix | TI ILA ITCAI | T | | |
| arcinogenicity | | | a avaliable | on the mix | ture itsei | T. | | |
| Carcinogenicity Product/ingredient name | Result | | | | | | | Exposure |
| Product/ingredient name | Result | | | Species | | Dose | | Exposure |
| Carcinogenicity Product/ingredient name 4,4'-methylenediphenyl diisocyanate | Result Positive - | | | | | | g/m³ | |
| Product/ingredient name 4,4'-methylenediphenyl | Positive - | Inhalatior | | Species Rat | | Dose 0 to 6 m | g/m³ | 2 years; 5 days |
| Product/ingredient name 4,4'-methylenediphenyl diisocyanate | Positive - | Inhalatior | ı - TC | Species Rat | | Dose 0 to 6 m | g/m³ | 2 years; 5 days |
| Product/ingredient name 4,4'-methylenediphenyl diisocyanate Conclusion/Summary | Positive - | Inhalatior | ı - TC | Species Rat | | Dose 0 to 6 m | g/m³ | 2 years; 5 days |
| Product/ingredient name 4,4'-methylenediphenyl diisocyanate Conclusion/Summary Classification Product/ingredient name 4,4'-methylenediphenyl | Positive - : There a | Inhalatior re no dat | n - TC a available | Species Rat | | Dose 0 to 6 m | g/m³ | 2 years; 5 days |
| Product/ingredient name 4,4'-methylenediphenyl diisocyanate Conclusion/Summary Classification Product/ingredient name 4,4'-methylenediphenyl diisocyanate Isocyanic acid, | Positive - : There a OSHA - - | Inhalatior ire no dat | n - TC a available | Species Rat | | Dose 0 to 6 m | g/m³ | 2 years; 5 days |
| Product/ingredient name 4,4'-methylenediphenyl diisocyanate Conclusion/Summary Classification Product/ingredient name 4,4'-methylenediphenyl diisocyanate | Positive - : There a OSHA - - | Inhalatior re no dat IARC 3 | n - TC a available | Species Rat | | Dose 0 to 6 m | g/m³ | 2 years; 5 days |
| Product/ingredient name 4,4'-methylenediphenyl diisocyanate Conclusion/Summary <u>Classification</u> Product/ingredient name 4,4'-methylenediphenyl diisocyanate Isocyanic acid, polymethylenepolyphenylene | Positive - : There a OSHA - - | Inhalatior re no dat IARC 3 | n - TC a available | Species Rat | | Dose 0 to 6 m | g/m³ | 2 years; 5 days |
| Product/ingredient name 4,4'-methylenediphenyl diisocyanate Conclusion/Summary Classification Product/ingredient name 4,4'-methylenediphenyl diisocyanate Isocyanic acid, polymethylenepolyphenylene ester | Positive - : There a OSHA - - - | Inhalatior re no dat IARC 3 3 | n - TC a available NTP - - | Species Rat on the mix | ture itsel | Dose 0 to 6 m f. | g/m³ | 2 years; 5 days |
| Product/ingredient name 4,4'-methylenediphenyl diisocyanate Conclusion/Summary Classification Product/ingredient name 4,4'-methylenediphenyl diisocyanate Isocyanic acid, polymethylenepolyphenylene ester Carcinogen Classification IARC: 1, 2A, 2B, 3 NTP: Known to b | Positive - : There a OSHA - - - n code: , 4 e a human ca | Inhalatior re no dat IARC 3 3 | n - TC a available NTP - - | Species Rat on the mix | ture itsel | Dose 0 to 6 m f. | g/m³ | 2 years; 5 days |
| Product/ingredient name 4,4'-methylenediphenyl diisocyanate Conclusion/Summary Classification Product/ingredient name 4,4'-methylenediphenyl diisocyanate Isocyanic acid, polymethylenepolyphenylene ester Carcinogen Classification IARC: 1, 2A, 2B, 3 NTP: Known to b OSHA: + Not listed/not reg | Positive - : There a OSHA - - - n code: , 4 e a human ca | Inhalatior re no dat IARC 3 3 | n - TC a available NTP - - | Species Rat on the mix | ture itsel | Dose 0 to 6 m f. | g/m³ | 2 years; 5 days |
| Product/ingredient name 4,4'-methylenediphenyl diisocyanate Conclusion/Summary Classification Product/ingredient name 4,4'-methylenediphenyl diisocyanate Isocyanic acid, polymethylenepolyphenylene ester Carcinogen Classification IARC: 1, 2A, 2B, 3 NTP: Known to b OSHA: + Not listed/not reg | Positive - : There a OSHA - - n code: , 4 e a human ca ulated: - | Inhalatior ire no dat IARC 3 3 3 | n - TC a available NTP - - | Species Rat on the mix anticipated to | ture itsel | Dose 0 to 6 m f. | g/m³ | 2 years; 5 days |
| Product/ingredient name 4,4'-methylenediphenyl diisocyanate Conclusion/Summary Classification Product/ingredient name 4,4'-methylenediphenyl diisocyanate Isocyanic acid, polymethylenepolyphenylene ester Carcinogen Classification IARC: 1, 2A, 2B, 3 NTP: Known to b OSHA: + Not listed/not reg | Positive - : There a OSHA - - n code: , 4 e a human ca ulated: - | Inhalatior ire no dat IARC 3 3 3 | n - TC a available NTP - - Reasonably | Species Rat on the mix anticipated to | ture itsel | Dose 0 to 6 m f. | g/m³ | 2 years; 5 days |
| Product/ingredient name 4,4'-methylenediphenyl diisocyanate Conclusion/Summary Classification Product/ingredient name 4,4'-methylenediphenyl diisocyanate Isocyanic acid, polymethylenepolyphenylene ester Carcinogen Classification IARC: 1, 2A, 2B, 3 NTP: Known to b OSHA: + | Positive - : There a OSHA - - n code: , 4 e a human ca ulated: - : There a | Inhalatior ire no dat IARC 3 3 arcinogen; | n - TC a available NTP - - Reasonably | Species Rat on the mix | o be a hum | Dose 0 to 6 m f. nan carcino | g/m³ | 2 years; 5 days |

SECTION 11: Toxicological information

| Name | Category | Route of exposure | Target organs |
|--|------------|-------------------|------------------------------|
| 4,4'-methylenediphenyl diisocyanate | Category 3 | - | Respiratory tract irritation |
| o-(p-isocyanatobenzyl)phenyl isocyanate | Category 3 | - | Respiratory tract irritation |
| Isocyanic acid, polymethylenepolyphenylene ester | Category 3 | - | Respiratory tract irritation |
| 2,2'-methylenediphenyl diisocyanate | Category 3 | - | Respiratory tract irritation |
| methylenediphenyl diisocyanate | Category 3 | - | Respiratory tract irritation |
| 2,4-dioxo-1,3-diazetidine-1,3-diylbis[p- phenylenemethylene-p-phenylene] diisocyanate | Category 3 | - | Respiratory tract irritation |

Specific target organ toxicity (repeated exposure)

| Name | Category | Route of exposure | Target organs |
|--|------------|-------------------|--------------------|
| 4,4'-methylenediphenyl diisocyanate | Category 2 | inhalation | respiratory system |
| o-(p-isocyanatobenzyl)phenyl isocyanate | Category 2 | - | - |
| Isocyanic acid, polymethylenepolyphenylene ester | Category 2 | inhalation | - |
| 2,2'-methylenediphenyl diisocyanate | Category 2 | - | - |
| methylenediphenyl diisocyanate | Category 2 | - | - |
| 2,4-dioxo-1,3-diazetidine-1,3-diylbis[p- phenylenemethylene-p-phenylene] diisocyanate | Category 2 | inhalation | nose/sinuses |

Target organs

: Contains material which causes damage to the following organs: lungs, upper respiratory tract, eyes, nose/sinuses, throat.

Contains material which may cause damage to the following organs: skin.

Aspiration hazard

Not available.

Information on the likely routes of exposure

| | Mexico Pag | e: 10/14 |
|--------------------------------|--|----------|
| Skin contact | verse symptoms may include the following: tation Iness | |
| Inhalation | verse symptoms may include the following: spiratory tract irritation ughing eezing and breathing difficulties thma | |
| Eye contact | verse symptoms may include the following: in or irritation tering Iness | |
| Over-exposure signs/sympto | | |
| Ingestion | rmful if swallowed. | |
| Skin contact | uses skin irritation. May cause an allergic skin reaction. | |
| Inhalation | rmful if inhaled. May cause respiratory irritation. May cause allergy or ast nptoms or breathing difficulties if inhaled. | hma |
| Eye contact | uses serious eye irritation. | |
| Potential acute health effects | | |

SECTION 11: Toxicological information

| Ingestion | 1 | No specific data. |
|--------------------------------|------------|---|
| Delayed and immediate effe | <u>cts</u> | and also chronic effects from short and long term exposure |
| Conclusion/Summary | | There are no data available on the mixture itself. Skin contact to isocyanate monomer may lead to allergic lung reaction. Based on the properties of the isocyanate components and considering toxicological data on similar mixtures, this mixture may cause acute irritation and/or sensitization of the respiratory system, leading to an asthmatic condition, wheezing and tightness of the chest. Repeated exposure may lead to permanent respiratory disability. Acrylate components of the mixture have irritating properties. Prolonged or repeated contact with skin or mucous membrane may result in irritation symptoms, such as redness, blistering, dermatitis etc. May cause allergic skin reactions with repeated exposure. The inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract. Ingestion may cause nausea, weakness and central nervous system effects. If splashed in the eyes, the liquid may cause irritation and reversible damage. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. |
| <u>Short term exposure</u> | | |
| Potential immediate effects | : | There are no data available on the mixture itself. |
| Potential delayed effects | : | There are no data available on the mixture itself. |
| <u>Long term exposure</u> | | |
| Potential immediate effects | : | There are no data available on the mixture itself. |
| Potential delayed effects | | There are no data available on the mixture itself. |
| Potential chronic health effe | ects | |
| General | | May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. |
| Carcinogenicity | : | Suspected of causing cancer. Risk of cancer depends on duration and level of exposure. |
| Mutagenicity | : | No known significant effects or critical hazards. |
| Reproductive toxicity | : | No known significant effects or critical hazards. |

Numerical measures of toxicity

Acute toxicity estimates

| Product/ingredient name | Oral (mg/ kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapors) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|--|------------------|-------------------|--------------------------------|----------------------------------|--|
| SL90 JOINT FILLER CLEAR - A | 897.9 | N/A | N/A | 12.1 | 3.1 |
| Propane-1,2-diol, propoxylated | 500 | N/A | N/A | N/A | N/A |
| 4,4'-methylenediphenyl diisocyanate | 9200 | N/A | N/A | 11 | N/A |
| o-(p-isocyanatobenzyl)phenyl isocyanate | N/A | N/A | N/A | 11 | 1.5 |
| propylene carbonate | 29000 | N/A | N/A | N/A | N/A |
| Isocyanic acid, polymethylenepolyphenylene ester | 49000 | N/A | N/A | N/A | 1.5 |
| 2,2'-methylenediphenyl diisocyanate | N/A | N/A | N/A | 11 | 1.5 |
| methylenediphenyl diisocyanate | N/A | N/A | N/A | 11 | 1.5 |
| 2,4-dioxo-1,3-diazetidine-1,3-diylbis[p- phenylenemethylene-p-phenylene] diisocyanate | N/A | N/A | N/A | N/A | 1.5 |

SECTION 12: Ecological information

Toxicity

| Product/ingredient name | Result | Species | Exposure |
|-----------------------------------|----------------------|---------|----------|
| methylenediphenyl diisocyanate | Acute LC50 >100 mg/l | Fish | 96 hours |

Persistence and degradability

Not available.

Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|---|---------------|-----|-----------|
| Propane-1,2-diol, propoxylated | -0.68 to 0.01 | - | low |
| 4,4'-methylenediphenyl diisocyanate | 4.51 | - | high |
| o-(p-isocyanatobenzyl) phenyl isocyanate | 4.51 | - | high |
| propylene carbonate | -0.41 | - | low |
| 2,2'-methylenediphenyl diisocyanate | 5.22 | - | high |
| methylenediphenyl diisocyanate | 4.51 | - | high |

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

SECTION 13: Disposal considerations

| Disposal methods | : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled |
|------------------|--|
| | containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. |

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

SECTION 14: Transport information

| | Mexico Classification | IMDG | ΙΑΤΑ |
|-----------------------------------|-----------------------|-----------------|-----------------|
| UN number | Not regulated. | Not regulated. | Not regulated. |
| UN proper shipping name | - | - | - |
| Transport hazard class(es) | - | - | - |
| Packing group | - | - | - |
| Environmental hazards | No. | No. | No. |
| Marine pollutant substances | Not applicable. | Not applicable. | Not applicable. |
| Product RQ (lbs) | Not applicable. | Not applicable. | Not applicable. |
| RQ substances | Not applicable. | Not applicable. | Not applicable. |

Additional information

| Mexico | : None identified. |
|--------|--------------------|
| IMDG | : None identified. |
| ΙΑΤΑ | : None identified. |

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

SECTION 15: Regulatory information

| <u>Mexico</u> |
|---|
| Classification |
| Flammability : 1 Health : 3 Reactivity : 1 |
| International regulations |
| Montreal Protocol |
| Not listed. |
| Stockholm Convention on Persistent Organic Pollutants |
| Not listed. |
| Rotterdam Convention on Prior Informed Consent (PIC) |

Not listed.

Mariaa

SECTION 16: Other information

Hazardous Material Information System (U.S.A.)

Health : 3 * Flammability : 1 Physical hazards : 1 (*) - Chronic

effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

| Date of previous issue | : 7/14/2022 |
|------------------------------------|---|
| Organization that prepared the SDS | : EHS |
| Key to abbreviations | ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations |

Indicates information that has changed from previously issued version.

Notice to reader

The information, which is based on the current knowledge of the chemical substance or mixture and applies to appropriate safety precautions for the product, is deemed correct but is not exhaustive and will be used only as a guide.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.