# SAFETY DATA SHEET



Date of issue Version 1 17 May 2023

# Section 1. Product and company identification

Product name : SIGMAZINC 158/SIGMAGUARD 750 PIGMENT

Product code : 00444811

Other means of identification : Not available.

Product type : Powder.

#### Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** 

Coating. Paints. Painting-related materials.

Uses advised against	Reason
Not applicable.	

Supplier's details:

Supplier : PPG Industries Colombia Ltda

Calle 51 # 40-13 Municipio de Itagüí Antioquia, Colombia (57) (4) 3787400 (Porteria)

Email address: : HazComLatam@ppg.com

Emergency telephone number

Colombia: 01 8000 916012 (CISPROQUIM)

+ 571 288 6012 (CISPROQUIM) Ecuador: 1800-59-3005 (CISPROQUIM) Peru: 080-050-847 (CISPROQUIM)

### Section 2. Hazards identification

Classification of the : AQUATIC HAZARD (ACUTE) - Category 1 substance or mixture : AQUATIC HAZARD (LONG-TERM) - Category 1

**GHS** label elements

Hazard pictograms :



Signal word : Warning

**Hazard statements** : Very toxic to aquatic life with long lasting effects.

**Precautionary statements** 

Code 00444811 Date of issue 17 May 2023 Version **Product name SIGMAZINC 158/SIGMAGUARD 750 PIGMENT** 

### Section 2. Hazards identification

**Prevention** : Avoid release to the environment.

Response Collect spillage. **Storage** : Not applicable.

: Dispose of contents and container in accordance with all local, regional, national **Disposal** 

and international regulations.

result in classification

Other hazards which do not : May form explosible dust-air mixture if dispersed. Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes,

skin, nose and throat.

## Section 3. Composition/information on ingredients

Substance/mixture : Mixture Not available. Other means of

#### **CAS** number/other identifiers

identification

**CAS** number : Not applicable.

Ingredient name	%	CAS number
Zinc powder - zinc dust (stabilized) zinc oxide	60 - 100 0.5 - <1	7440-66-6 1314-13-2

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

### Section 4. First aid measures

### **Description of necessary first aid measures**

Eye contact : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognized skin cleanser. Do NOT use solvents or thinners.

Ingestion : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large **Specific treatments** 

quantities have been ingested or inhaled.

No specific treatment.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

Potential acute health effects

**Eye contact** 

Exposure to airborne concentrations above statutory or recommended exposure

limits may cause irritation of the eyes.

English (US) Colombia 2/11 Code 00444811 Date of issue 17 May 2023 Version

**Product name** SIGMAZINC 158/SIGMAGUARD 750 PIGMENT

### Section 4. First aid measures

Inhalation

: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.

**Skin contact** Ingestion

: No known significant effects or critical hazards. : No known significant effects or critical hazards.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### **Extinguishing media**

Suitable extinguishing media

Unsuitable extinguishing media

: Use dry chemical powder.

: Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.

Specific hazards arising from the chemical

: May form explosible dust-air mixture if dispersed. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous thermal** decomposition products : Decomposition products may include the following materials: metal oxide/oxides

**Special protective actions** for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective** equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions**: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

#### Methods and materials for containment and cleaning up

Small spill

: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

English (US) Colombia 3/11 Code 00444811 Date of issue 17 May 2023 Version

SIGMAZINC 158/SIGMAGUARD 750 PIGMENT **Product name** 

### Section 6. Accidental release measures

Large spill

: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### Section 7. Handling and storage

### **Precautions for safe** handling

: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing dust. Avoid release to the environment. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

# including any incompatibilities

Conditions for safe storage, : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

#### **Control parameters**

Occupational exposure limits

None.

### **Recommended monitoring** procedures

: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### Appropriate engineering controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

#### **Environmental exposure** controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

English (US) Colombia 4/11 
 Code
 00444811
 Date of issue
 17 May 2023
 Version
 1

Product name SIGMAZINC 158/SIGMAGUARD 750 PIGMENT

## Section 8. Exposure controls/personal protection

#### **Individual protection measures**

**Hygiene measures**: Wash hands, forearms and face thoroughly after handling chemical products,

before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and

safety showers are close to the workstation location.

Eye protection
Skin protection
Hand protection

: Safety glasses with side shields.

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately

estimated.

**Body protection** : Personal protective equipment for the body should be selected based on the task

being performed and the risks involved and should be approved by a specialist

before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

**Respiratory protection**: Respirator selection must be based on known or anticipated exposure levels, the

hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is

necessary.

# Section 9. Physical and chemical properties

**Appearance** 

Physical state : Solid.

Powder.

Color : Various

Odor : Characteristic.
pH : Not applicable.

Melting point : Not available.

Boiling point : Not available.

Flash point : Closed cup: Not applicable.

Evaporation rate : Not available.

Flammability (solid, gas) : Not available.

Lower and upper explosive : Not applicable.

(flammable) limits

Vapor pressure : Not available.Vapor density : Not applicable.

Relative density : 7.14

English (US) Colombia 5/11

Code 00444811 Date of issue 17 May 2023 Version 1
Product name SIGMAZINC 158/SIGMAGUARD 750 PIGMENT

# Section 9. Physical and chemical properties

Solubility(ies) : Media Result

cold water Not soluble

Partition coefficient: n-

octanol/water

: Not applicable.

Auto-ignition temperature

Decomposition temperature

: Not applicable.: Not available.

Viscosity : Kinematic (40°C (104°F)): Not applicable.

## Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability**: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition

products.

**Incompatible materials**: Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents, strong alkalis, strong acids.

Hazardous decomposition products

: Evolves hydrogen on contact with water. Depending on conditions, decomposition

products may include the following materials: metal oxide/oxides

# Section 11. Toxicological information

#### Information on toxicological effects

### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Zinc powder - zinc dust (stabilized)	LC50 Inhalation Dusts and mists	Rat	>5.4 mg/l	4 hours
zinc oxide	LD50 Oral LC50 Inhalation Dusts and mists	Rat Rat	>2000 mg/kg >5700 mg/m <sup>3</sup>	- 4 hours
Zine Gauge	LD50 Dermal LD50 Oral	Rat Rat	>2000 mg/kg >5000 mg/kg	-

**Conclusion/Summary** 

Irritation/Corrosion

Not available.

**Conclusion/Summary** 

Skin

There are no data available on the mixture itself.There are no data available on the mixture itself.

: There are no data available on the mixture itself.

**Respiratory**: There are no data available on the mixture itself.

**Sensitization** 

**Eyes** 

Not available.

**Conclusion/Summary** 

English (US) Colombia 6/11

Code 00444811 Date of issue 17 May 2023 Version 1

Product name SIGMAZINC 158/SIGMAGUARD 750 PIGMENT

## Section 11. Toxicological information

Skin : There are no data available on the mixture itself.

**Respiratory**: There are no data available on the mixture itself.

Mutagenicity
Not available.

**Conclusion/Summary**: There are no data available on the mixture itself.

Carcinogenicity

Not available.

**Conclusion/Summary**: There are no data available on the mixture itself.

**Reproductive toxicity** 

Not available.

**Conclusion/Summary**: There are no data available on the mixture itself.

Teratogenicity

Not available.

**Conclusion/Summary**: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

**Aspiration hazard** 

Not available.

**Information on the likely**: Not available.

routes of exposure

Potential acute health effects

**Eye contact** : Exposure to airborne concentrations above statutory or recommended exposure

limits may cause irritation of the eyes.

Inhalation : Exposure to airborne concentrations above statutory or recommended exposure

limits may cause irritation of the nose, throat and lungs.

Skin contactIngestionNo known significant effects or critical hazards.No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:

irritation redness

**Inhalation** : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact : No specific data.
Ingestion : No specific data.

English (US) Colombia 7/11

Code 00444811 Date of issue 17 May 2023 Version 1
Product name SIGMAZINC 158/SIGMAGUARD 750 PIGMENT

## **Section 11. Toxicological information**

### Delayed and immediate effects and also chronic effects from short and long term exposure

**Conclusion/Summary** 

: There are no data available on the mixture itself. Repeated exposure of the eyes to a low level of dust can produce eye irritation. Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and longterm exposure by oral, inhalation and dermal routes of exposure and eye contact.

**Short term exposure** 

**Potential immediate** 

effects

: There are no data available on the mixture itself.

Potential delayed effects

: There are no data available on the mixture itself.

Long term exposure

**Potential immediate** 

: There are no data available on the mixture itself.

effects

Potential delayed effects : There are no data available on the mixture itself.

Potential chronic health effects

Not available.

**General**: Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

#### **Numerical measures of toxicity**

#### **Acute toxicity estimates**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
zinc oxide	N/A	2500	N/A	N/A	N/A

Other information : Not available.

# Section 12. Ecological information

#### **Ecotoxicity**

Product/ingredient name	Result	Species	Exposure
Zinc powder - zinc dust (stabilized)	Acute EC50 0.106 mg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
,	Chronic NOEC 0.0727 mg/l Fresh water	Daphnia - Daphnia Magna	21 days
zinc oxide	Acute EC50 0.17 mg/l	Algae	72 hours
	Acute EC50 0.481 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Chronic NOEC 0.017 mg/l Fresh water	Algae	72 hours

#### Persistence/degradability

	English (US	Colombia	8/11
--	-------------	----------	------

 Code
 00444811
 Date of issue
 17 May 2023
 Version
 1

Product name SIGMAZINC 158/SIGMAGUARD 750 PIGMENT

## Section 12. Ecological information

Not available.

#### **Bioaccumulative potential**

Not available.

**Mobility in soil** 

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

# Section 13. Disposal considerations

**Disposal methods** 

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### **Section 14. Transport information**

	UN	Brazil (ANTT)	IMDG	IATA
UN number	UN3077	UN3077	UN3077	UN3077
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.  ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.	
	(Zinc powder - zinc dust (stabilized))	(Zinc powder - zinc dust (stabilized))	(Zinc powder - zinc dust (stabilized))	(Zinc powder - zinc dust (stabilized))
Transport hazard class(es)	9	9	9	9
Packing group	III	III	III	III
Environmental hazards	Yes.	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	Not applicable.	(Zinc powder - zinc dust (stabilized))	Not applicable.

#### **Additional information**

UN

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

English (US) Colombia 9/11

Code 00444811 Date of issue 17 May 2023 Version

**Product name** SIGMAZINC 158/SIGMAGUARD 750 PIGMENT

### Section 14. Transport information

**Brazil** 

**IMDG** 

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

Risk number

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. The segregation group has been manually assigned based upon product analysis.

**IATA** 

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg. provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable.

to IMO instruments

## Section 15. Regulatory information

Safety, health and environmental regulations specific for the product

: No known specific national and/or regional regulations applicable to this product (including its ingredients).

### Section 16. Other information

**History** 

Date of previous issue

: No previous validation

Version

: 1 **EHS** 

Key to abbreviations

: ADN = European Provisions concerning the International Carriage of Dangerous

Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of

Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

RID = The Regulations concerning the International Carriage of Dangerous Goods

by Rail

UN = United Nations

References : ABNT NBR 14725-4: 2014

ANTT - National Land Transportation Agency

Indicates information that has changed from previously issued version.

**Disclaimer** 

English (US) Colombia 10/11 Code 00444811 Date of issue 17 May 2023 Version 1
Product name SIGMAZINC 158/SIGMAGUARD 750 PIGMENT

### **Section 16. Other information**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

English (US) Colombia 11/11