SAFETY DATA SHEET

Date of issue/Date of revision

: 6 June 2023

Version

: 2



SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: PITT-CHAR XP HARDENER BLACK PF
Product code	: 000001104813
Other means of identification	tion
00352602; 00354399	
1.2 Relevant identified use Product use	s of the substance or mixture and uses advised against : Professional applications, Used by spraying.
Use of the substance/ mixture	: Coating.
Uses advised against	. Dreduct is not intended, lebelled or necks and for concurrences
oooo aariooa agamot	: Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

Sigma Paints Egypt Villa#8, street 279	
New Maadi, Cairo	
Egypt	
Tel: 00202 516 223 797	
Fax: 00202 516 38 04	
e-mail address of person responsible for this SDS	: PS.ACEMEA@ppg.com

1.4 Emergency telephone : +20 2 6840902 number

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Product definition : Mixture Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2, H351 Repr. 2, H361f STOT RE 2, H373 Aquatic Chronic 2, H411 The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.



Code : 000001104813

Date of issue/Date of revision

: 6 June 2023

PITT-CHAR XP HARDENER BLACK PF

SECTION 2: Hazards identification

Signal word	: Danger
Hazard statements	 Causes severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of causing cancer. Suspected of damaging fertility. May cause damage to organs through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.
Precautionary statements	
Prevention	: Wear protective gloves, protective clothing and eye or face protection. Avoid release to the environment. Do not breathe vapour.
Response	: 🖉ollect spillage. IF INHALED: Immediately call a POISON CENTER or doctor.
Storage	: Not applicable.
Disposal	 Dispose of contents and container in accordance with all local, regional, national and international regulations. P280, P273, P260, P391, P304 + P310, P501
Hazardous ingredients	 Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 1,3,5-triazine-2,4,6-triamine 2,4,6-tris(dimethylaminomethyl)phenol 3,6-diazaoctanethylenediamin N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide)
Supplemental label elements	: Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Special packaging requiren	ients
Containers to be fitted with child-resistant fastenings	: Not applicable.
Tactile warning of danger	: Not applicable.
2.3 Other hazards	
Product meets the criteria for PBT or vPvB	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: Causes digestive tract burns.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

: Mixture

Code: 000001104813Date of issue/Date of revision: 6 June 2023PITT-CHAR XP HARDENER BLACK PF

SECTION 3: Composition/information on ingredients

L		1	<u> </u>		
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	REACH #: 01-2119972320-44 EC: 500-191-5 CAS: 68082-29-1	≥25 - ≤50	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Chronic 2, H411	-	[1]
1,3,5-triazine-2,4,6-triamine	REACH #: 01-2119485947-16 EC: 203-615-4 CAS: 108-78-1 Index: 613-345-00-2	≥10 - ≤25	Carc. 2, H351 Repr. 2, H361f STOT RE 2, H373 (urinary system)	-	[1]
4,4'-Isopropylidenediphenol, ethoxylated	EC: polymer CAS: 32492-61-8 (EO> 4.5 moles)	≥5.0 - ≤10	Aquatic Chronic 3, H412	-	[1]
2,4,6-tris (dimethylaminomethyl) phenol	REACH #: 01-2119560597-27 EC: 202-013-9 CAS: 90-72-2 Index: 603-069-00-0	≥5.0 - ≤10	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1C, H314 Eye Dam. 1, H318	ATE [Oral] = 1200 mg/ kg ATE [Dermal] = 1280 mg/kg	[1]
3,6-diazaoctanethylenediamin	EC: 203-950-6 CAS: 112-24-3 Index: 612-059-00-5	≥1.0 - <5.0	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412	ATE [Oral] = 1716 mg/ kg ATE [Dermal] = 1465 mg/kg	[1] [2]
N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan- 1-amide)	REACH #: 01-2119978265-26 EC: 204-613-6 CAS: 123-26-2	<1.0	Skin Sens. 1B, H317 Aquatic Chronic 3, H412	-	[1] [2]
			See Section 16 for the full text of the H statements declared above.		

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Inhalation	 Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

English (GB)	
--------------	--

Code : 00000110481	13	Date of issue/Date of revision	: 6 June 2023
PITT-CHAR XP HARDENER	BLACK PF		
SECTION 4: First ai	d measures		
Ingestion		medical advice immediately and show the c at rest. Do NOT induce vomiting.	ontainer or label. Keep
Protection of first-aiders	rs : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.		
4.2 Most important sympton	ms and effects, both ac	cute and delayed	
Potential acute health effe	<u>cts</u>		
Eye contact	: Causes serious ey	e damage.	
Inhalation	: No known significa	nt effects or critical hazards.	
Skin contact	: Causes severe bur	ns. May cause an allergic skin reaction.	
Ingestion	: Corrosive to the dig	gestive tract. Causes burns.	
Over-exposure signs/sym	<u>ptoms</u>		
Eye contact	: Adverse symptom pain watering redness	s may include the following:	
Inhalation	: Adverse symptom reduced foetal wei increase in foetal o skeletal malformat	deaths	
Skin contact	: Adverse symptom pain or irritation redness blistering may occ reduced foetal wei increase in foetal of skeletal malformat	ight deaths	
Ingestion	: Adverse symptoms stomach pains reduced foetal wei increase in foetal o	deaths	

4.3 Indication of any immediate medical attention and special treatment needed

skeletal malformations

Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.

5.2 Special hazards arising from the substance or mixture

Code: 000001104813Date of issue/Date of revision: 6 June 2023PITT-CHAR XP HARDENER BLACK PF

SECTION 5: Firefighting measures

Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway,
	sewer or drain.
Hazardous combustion products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides
5.3 Advice for firefighters	
Special precautions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	ote	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and material for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product.
6.4 Reference to other sections	 See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

Code : 000001104813

Date of issue/Date of revision

PITT-CHAR XP HARDENER BLACK PF

: 6 June 2023

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Fut on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
7.2 Conditions for safe storage, including any incompatibilities	: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
glass, oxide, chemicals	 ACGIH TLV (United States). TWA: 1 f/cc Form: Continuous filament glass fibres TWA: 5 mg/m³, (Inhalable) Form: Continuous filament glass fibres TWA: 3 mg/m³ Form: Respirable TWA: 10 mg/m³ Form: Total dust ACGIH TLV (United States, 1/2022). [Continuous filament glass fibers] TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction TWA: 1 f/cc 8 hours. Form: Respirable fibers: length greater than 5 uM; aspect ratio equal to or greater than 3:1 as determined by the membrane filter method at 400-450X magnification (4-mm objective) phase contrast illumination.

2020/878		
Code : 00000110481	Date of issue/Date of	revision : 6 June 2023
PITT-CHAR XP HARDENER I	PF	
Recommended monitoring procedures	ference should be made to monitoring standard andard EN 689 (Workplace atmospheres - Guid inhalation to chemical agents for comparison w ategy) European Standard EN 14042 (Workpla plication and use of procedures for the assess logical agents) European Standard EN 482 (W juirements for the performance of procedures f ents) Reference to national guidance documer hazardous substances will also be required.	lance for the assessment of exposure with limit values and measurement ace atmospheres - Guide for the ment of exposure to chemical and Vorkplace atmospheres - General or the measurement of chemical
8.2 Exposure controls		
Appropriate engineering controls	iser operations generate dust, fumes, gas, vap al exhaust ventilation or other engineering cont borne contaminants below any recommended o	rols to keep worker exposure to
Individual protection measu		
Hygiene measures	ash hands, forearms and face thoroughly after ting, smoking and using the lavatory and at the propriate techniques should be used to remove ntaminated work clothing should not be allowed ntaminated clothing before reusing. Ensure that owers are close to the workstation location.	end of the working period. potentially contaminated clothing. d out of the workplace. Wash
Eye/face protection <u>Skin protection</u>	emical splash goggles and face shield.	
Hand protection	emical-resistant, impervious gloves complying rn at all times when handling chemical product cessary. Considering the parameters specified ring use that the gloves are still retaining their p ted that the time to breakthrough for any glove ve manufacturers. In the case of mixtures, con otection time of the gloves cannot be accurately quently repeated contact may occur, a glove with eakthrough time greater than 480 minutes accor- nen only brief contact is expected, a glove with eakthrough time greater than 30 minutes accor- e user must check that the final choice of type oduct is the most appropriate and takes into acc- included in the user's risk assessment.	s if a risk assessment indicates this is by the glove manufacturer, check rotective properties. It should be material may be different for different isisting of several substances, the estimated. When prolonged or th a protection class of 6 ording to EN 374) is recommended. a protection class of 2 or higher ding to EN 374) is recommended. of glove selected for handling this
Gloves	ile neoprene	
Body protection	rsonal protective equipment for the body should formed and the risks involved and should be a ndling this product.	
Other skin protection	propriate footwear and any additional skin prote sed on the task being performed and the risks i ecialist before handling this product.	
Respiratory protection		
Environmental exposure controls	nissions from ventilation or work process equip by comply with the requirements of environments ses, fume scrubbers, filters or engineering mod be necessary to reduce emissions to acceptal	al protection legislation. In some ifications to the process equipment

- Code : 000001104813
- Date of issue/Date of revision: 6 June 2023

PITT-CHAR XP HARDENER BLACK PF

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Physical state	: Liquid.						
Colour	Black.						
Ddour	Amine-like. [Strong]						
Ddour threshold	: Not available.						
Melting point/freezing point	: May start to solidify a data for the following -55.6°C (-68.1°F)						
Initial boiling point and boiling range	: >37.78°C						
Flammability	: Not available.						
Jpper/lower flammability or explosive limits	: Greatest known rang	ge: Lower:	1.1% U	Ipper: 6.4% (3	3,6-diaza	aoctanethy	/lenediamin)
Flash point	: Closed cup: 120°C						
Auto-ignition temperature	: Ingredient name		°C	°F		Method	
	3,6-diazaoctanethylened	iamin	337.78	640			
/iscosity /iscosity	 Not applicable. insol Kinematic (40°C): >2 > 100 s (ISO 6mm) 						
pH Viscosity Viscosity Partition coefficient: n-octanol/ water Vapour pressure	: Kinematic (40°C): >2 : > 100 s (ISO 6mm) : Not applicable. :	21 mm²/s		ure at 20°C	Var	oour pres	sure at 50°C
Viscosity Viscosity Partition coefficient: n-octanol/ water	: Kinematic (40°C): >2 : > 100 s (ISO 6mm)	21 mm²/s	ur Press	ure at 20°C Method	Var mm Hg	oour press	sure at 50°C Method
Viscosity Viscosity Partition coefficient: n-octanol/ water	: Kinematic (40°C): >2 : > 100 s (ISO 6mm) : Not applicable. :	21 mm²/s	ur Press	1	mm		
/iscosity /iscosity Partition coefficient: n-octanol/ vater /apour pressure	 Kinematic (40°C): >2 > 100 s (ISO 6mm) Not applicable. Ingredient name 4,6-tris (dimethylaminomethyl) 	21 mm²/s Vapor mm Hg	ur Press kPa	Method	mm		
/iscosity /iscosity Partition coefficient: n-octanol/ vater /apour pressure Evaporation rate	 Kinematic (40°C): >2 > 100 s (ISO 6mm) Not applicable. Ingredient name A,6-tris (dimethylaminomethyl) phenol 	21 mm²/s Vapor mm Hg	ur Press kPa	Method	mm		sure at 50°C Method
/iscosity /iscosity Partition coefficient: n-octanol/ vater /apour pressure Evaporation rate Relative density /apour density	 Kinematic (40°C): >2 > 100 s (ISO 6mm) Not applicable. Ingredient name A,6-tris (dimethylaminomethyl) phenol Not available. 1.14 Highest known value 	21 mm ² /s Vapor mm Hg 0.056 e: 5.04 (A	ur Press kPa 0.0075 ir = 1) (3	Method EU A.4	mm Hg	kPa ediamin).	Method
Viscosity Viscosity Partition coefficient: n-octanol/ water Vapour pressure Evaporation rate Relative density Vapour density Explosive properties	 Kinematic (40°C): >2 > 100 s (ISO 6mm) Not applicable. Ingredient name 4,6-tris (dimethylaminomethyl) phenol Not available. 1.14 Highest known value The product itself is vapour or dust with a 	21 mm²/s Vapor mm Hg 0.056 e: 5.04 (A not explos air is poss	ur Press kPa 0.0075 ir = 1) (3 sive, but ible.	Method EU A.4 3,6-diazaoctar the formation	mm Hg	kPa ediamin).	Method
/iscosity /iscosity Partition coefficient: n-octanol/ water /apour pressure Evaporation rate Relative density /apour density Explosive properties Dxidising properties	 Kinematic (40°C): >2 > 100 s (ISO 6mm) Not applicable. Ingredient name 4,6-tris (dimethylaminomethyl) phenol Not available. 1.14 Highest known value The product itself is 	21 mm²/s Vapor mm Hg 0.056 e: 5.04 (A not explos air is poss	ur Press kPa 0.0075 ir = 1) (3 sive, but ible.	Method EU A.4 3,6-diazaoctar the formation	mm Hg	kPa ediamin).	Method
/iscosity /iscosity Partition coefficient: n-octanol/ vater /apour pressure Evaporation rate Relative density /apour density Explosive properties Dxidising properties article characteristics	 Kinematic (40°C): >2 > 100 s (ISO 6mm) Not applicable. Ingredient name ,4,6-tris (dimethylaminomethyl) phenol Not available. 1.14 Highest known value The product itself is vapour or dust with a Product does not present 	21 mm²/s Vapor mm Hg 0.056 e: 5.04 (A not explos air is poss	ur Press kPa 0.0075 ir = 1) (3 sive, but ible.	Method EU A.4 3,6-diazaoctar the formation	mm Hg	kPa ediamin).	Method
Viscosity Viscosity Partition coefficient: n-octanol/ water Vapour pressure Evaporation rate Relative density Vapour density	 Kinematic (40°C): >2 > 100 s (ISO 6mm) Not applicable. Ingredient name 4,6-tris (dimethylaminomethyl) phenol Not available. 1.14 Highest known value The product itself is vapour or dust with a 	21 mm²/s Vapor mm Hg 0.056 e: 5.04 (A not explos air is poss	ur Press kPa 0.0075 ir = 1) (3 sive, but ible.	Method EU A.4 3,6-diazaoctar the formation	mm Hg	kPa ediamin).	Method
Viscosity Viscosity Partition coefficient: n-octanol/ water Vapour pressure Evaporation rate Relative density Vapour density Explosive properties Oxidising properties article characteristics	 Kinematic (40°C): >2 > 100 s (ISO 6mm) Not applicable. Ingredient name ,4,6-tris (dimethylaminomethyl) phenol Not available. 1.14 Highest known value The product itself is vapour or dust with a Product does not present 	21 mm²/s Vapor mm Hg 0.056 e: 5.04 (A not explos air is poss	ur Press kPa 0.0075 ir = 1) (3 sive, but ible.	Method EU A.4 3,6-diazaoctar the formation	mm Hg	kPa ediamin).	Method

Code	: 000001104813	Date of issue/Date of revision	: 6 June 2023
PITT-CHAR >	P HARDENER BLACK PF		

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
10.6 Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Atty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-
melamine	LC50 Inhalation Dusts and mists	Rat	>5190 mg/m ³	4 hours
	LD50 Oral	Rat	3161 mg/kg	-
2,4,6-tris(dimethylaminomethyl)phenol	LD50 Dermal	Rabbit	1.28 g/kg	-
	LD50 Dermal	Rat	1280 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-
3,6-diazaoctanethylenediamin	LD50 Dermal	Rabbit	1465 mg/kg	-
	LD50 Oral	Rat	1716 mg/kg	-
N,N'-ethane-1,2-diylbis	LC50 Inhalation Dusts and	Rat	>5.11 mg/l	4 hours
(12-hydroxyoctadecan-1-amide)	mists		_	
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-

Conclusion/Summary : There are no data available on the mixture itself.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation	
✓atty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	Eyes - Severe irritant	Rabbit	-	-	-	
	Skin - Irritant	Human	-	-	-	
2,4,6-tris(dimethylaminomethyl)phenol	Skin - Visible necrosis	Rabbit	-	4 hours	7 days	
Conclusion/Summary						
Skin : There are	e no data available on the	mixture itself				

Sensitisation	
Respiratory	: There are no data available on the mixture itself.
Eyes	: There are no data available on the mixture itself.
SKIN	: I here are no data available on the mixture itself.

Code	: 000001104813	Date of issue/Date of revision	: 6 June 2023
PITT-CHAR >	XP HARDENER BLACK PF		

SECTION 11: Toxicological information

Product/ingredient name		Route of exposure	Species	Result
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 3,6-diazaoctanethylenediamin		skin skin	Mouse Guinea pig	Sensitising Sensitising
		SKIII	Guinea pig	Sensitising
Conclusion/Summary				
Skin	: There are no data avail	able on the mixtur	e itself.	
Respiratory	: There are no data avail	able on the mixtur	e itself.	
<u>Mutagenicity</u>				
Conclusion/Summary	: There are no data avail	able on the mixtur	e itself.	
<u>Carcinogenicity</u>				
Conclusion/Summary : There are no data available on the mixture itself.				
Reproductive toxicity				
Conclusion/Summary : There are no data available on the mixture itself.				
Teratogenicity				
Conclusion/Summary	: There are no data avail	able on the mixtur	e itself.	
Specific target organ tox	<u>icity (single exposure)</u>			
Not available.				

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
₮,3,5-triazine-2,4,6-triamine	Category 2	-	urinary system

Aspiration hazard

Not available.

Information on likely : Not available.

routes of exposure
Potential acute health effects

<u>Potential acute nealth ener</u>	<u>515</u>	
Inhalation	:	No known significant effects or critical hazards.
Ingestion	:	Corrosive to the digestive tract. Causes burns.
Skin contact	:	Causes severe burns. May cause an allergic skin reaction.
Eye contact	:	Causes serious eye damage.
Symptoms related to the p	<u>hys</u> i	ical, chemical and toxicological characteristics
Inhalation	:	Adverse symptoms may include the following: reduced foetal weight increase in foetal deaths skeletal malformations
Ingestion	:	Adverse symptoms may include the following: stomach pains reduced foetal weight increase in foetal deaths skeletal malformations
Skin contact	:	Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced foetal weight increase in foetal deaths skeletal malformations

English (GB)

Code : 000001104813		Date of issue/Date of revision	: 6 June 2023
PITT-CHAR XP HARDENER B	LACK PF		
SECTION 11: Toxicol	ogical informatior	ו	
Eye contact	: Adverse symptoms ma pain watering redness	y include the following:	
Delayed and immediate effe	<u>cts as well as chronic eff</u>	ects from short and long-term expos	<u>sure</u>
Short term exposure			
Potential immediate effects	: Not available.		
Potential delayed effects	: Not available.		
Long term exposure			
Potential immediate effects	: Not available.		
Potential delayed effects	: Not available.		
Potential chronic health effe	ects		
Not available.			
Conclusion/Summary	: Not available.		
General		organs through prolonged or repeated ergic reaction may occur when subseq	
Carcinogenicity	: Suspected of causing c exposure.	ancer. Risk of cancer depends on dur	ation and level of
Mutagenicity	: No known significant ef	fects or critical hazards.	
Reproductive toxicity	: Suspected of damaging	g fertility.	
Other information	: Not available.		

Causes digestive tract burns. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	EC10 1.78 mg/l	Algae	72 hours
melamine	Acute EC50 200 mg/l	Daphnia	48 hours
2,4,6-tris(dimethylaminomethyl)phenol	Acute LC50 175 mg/l	Fish	96 hours
N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-	Acute EC50 29 to 43 mg/l	Algae -	72 hours
1-amide)		Pseudokirchneriella	
		subcapitata	
	Acute EC50 94 mg/l	Daphnia - Daphnia	48 hours
		magna	

Conclusion/Summary

: There are no data available on the mixture itself.

12.2 Persistence and degradability

English (GB)

Code	: 000001104813	Date of issue/Date of revision	: 6 June 2023	
PITT-CHAR	XP HARDENER BLACK PF			

SECTION 12: Ecological information

Product/ingredient name	Test	Result		Dose	Inoculum
N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan- 1-amide)	-	63 % - 28 days		-	-
Conclusion/Summary	: There are no da	ata available on the mixtu	re itself.		
Product/ingredient name		Aquatic half-life	Photo	olysis	Biodegradability
Atty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan- 1-amide)		-	-		Not readily Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
7,3,5-triazine-2,4,6-triamine	-1.22	3.8	low
2,4,6-tris(dimethylaminomethyl)phenol	0.219	-	low
3,6-diazaoctanethylenediamin	-1.66 to -1.4	-	low
N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-	>6	-	high
1-amide)			

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

<u>Product</u>	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.
European waste catalog	ue (EWC)

English (GB)

Code : 000001104813 Date of issue/Date of revision

: 6 June 2023

PITT-CHAR XP HARDENER BLACK PF

SECTION 13: Disposal considerations

Waste code	Waste designation
Ø 8 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
Packaging	
Methods of disposal	 The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)		
Container	15 01 06 mixed packaging		
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.		

SECTION 14: Transport information

	ADR/RID	IMDG	ΙΑΤΑ
14.1 UN number or ID number	UN3066	UN3066	UN3066
14.2 UN proper shipping name	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	8	8	8
14.4 Packing group	M	M	W
14.5 Environmental hazards	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	(Polyamide)	Not applicable.

Additional information

ADR/RID : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.				
Tunnel code	: (E)			
IMDG	: The marine pollutant mark is not required when transported in sizes of $\leq 5 \text{ L}$ or $\leq 5 \text{ kg}$.			
ΙΑΤΑ	: The environmentally hazardous substance mark may appear if required by other transportation regulations.			
14.6 Special pre user	cautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.			
14.7 Transport in according to IM instruments				

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 Code : 000001104813 : 6 June 2023

PITT-CHAR XP HARDENER BLACK PF

Date of issue/Date of revision

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture				
EU Regulation (EC) No. 1907/2006 (REACH)				
Annex XIV - List of substances subject to authorisation				
Annex XIV				
None of the components are listed.				
Substances of very high concern				
None of the components are listed.				
Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles				
Other national and international regulations.				
Ozone depleting substances (1005/2009/EU)				
Not listed.				
15.2 Chemical safety : No Chemical Safety Assessment has been carried out. assessment				

SECTION 16: Other information

	STOT RE 2	SPECIFIC TARGET OR EXPOSURE - Category 2		EATED	
	Skin Sens. 1A Skin Sens. 1B	SKIN SENSITISATION - SKIN SENSITISATION -	Category 1B		
	Skin Sens. 1	SKIN SENSITISATION -			
	Skin Irrit. 2		SKIN CORROSION/IRRITATION - Category 2		
Repr. 2 Skin Corr. 1B Skin Corr. 1C		SKIN CORROSION/IRRITATION - Category 1C			
		SKIN CORROSION/IRRITATION - Category 1B			
	Eye Dam. 1		SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 REPRODUCTIVE TOXICITY - Category 2		
	Carc. 2	CARCINOGENICITY - C			
	Aquatic Chronic 3	LONG-TERM (CHRONIC		- Category 3	
[CLP/GHS]	Aquatic Chronic 2	LONG-TERM (CHRONIC	C) AQUATIC HAZARD		
Full text of classifications	: Acute Tox. 4	ACUTE TOXICITY - Cate	egory 4		
	 H351 Suspected of causing cancer. H361f Suspected of damaging fertility. H373 May cause damage to organs through prolonged or re H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. 				
		is eye damage. causing cancer.			
	-	allergic skin reaction.			
	H315 Causes skin ir				
		e skin burns and eye damag	Э.		
Full text of abbreviated H statements	 H302 Harmful if swallowed. H312 Harmful in contact with skin. 				
	EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number				
-	1272/2008] DNEL = Derived No Effect Level				
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.				
 Indicates information that has changed from previously issued version. Abbreviations and : ATE = Acute Toxicity Estimate 					

Code : 000001104813	Date of issue/Date of revision	: 6 June 2023			
PITT-CHAR XP HARDENER BLACK PF					
SECTION 16: Other information					

<u>History</u>	
Date of issue/ Date of revision	: 6 June 2023
Date of previous issue	: 23 June 2022
Prepared by	: EHS
Version	: 2

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.