# **SAFETY DATA SHEET**

Date of issue/Date of revision

: 6 June 2023

Version

: 2



pPG

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: PITT-CHAR XP HARDENER BLACK PF
Product code	: 000001104813
Other means of identification 00352602; 00354399	on
1.2 Relevant identified uses of	of the substance or mixture and uses advised against
Product use	: Professional applications, Used by spraying.
Use of the substance/ mixture	: Coating.
Uses advised against	: Product is not intended, labelled or packaged for consumer use.
1.3 Details of the supplier of	the safety data sheet
Pittsburgh Paints Nigeria Limi	ted
Nigeria	op, Badagry Expressway, Orile Iganmu, Lagos
Tel: 00 234 (0) 8138672483 e-mail address of person	: PS.ACEMEA@ppg.com
responsible for this SDS	
1.4 Emergency telephone number	: 00234 127 173 85

# **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture


Product definition : Mixture Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] Skin Corr. 1C, H314

Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2, H351 Repr. 2, H361f STOT RE 2, H373 Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.



Date of issue/Date of revision

: 6 June 2023

Code : 000001104813

PITT-CHAR XP HARDENER BLACK PF

SECTION 2: Hazards identification

SECTION 2: Hazards	Identification
Hazard statements	<ul> <li>Causes severe skin burns and eye damage.</li> <li>May cause an allergic skin reaction.</li> <li>Suspected of causing cancer.</li> <li>Suspected of damaging fertility.</li> <li>May cause damage to organs through prolonged or repeated exposure.</li> <li>Toxic to aquatic life with long lasting effects.</li> </ul>
Precautionary statements	
Prevention	: Wear protective gloves, protective clothing and eye or face protection. Avoid release to the environment. Do not breathe vapour.
Response	: 🖉 ollect spillage. IF INHALED: Immediately call a POISON CENTER or doctor.
Storage	: Not applicable.
Disposal	<ul> <li>Dispose of contents and container in accordance with all local, regional, national and international regulations.</li> <li>P280, P273, P260, P391, P304 + P310, P501</li> </ul>
Hazardous ingredients	<ul> <li>Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 1,3,5-triazine-2,4,6-triamine 2,4,6-tris(dimethylaminomethyl)phenol 3,6-diazaoctanethylenediamin N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide)</li> </ul>
Supplemental label elements	: Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Special packaging requirem	<u>ients</u>
Containers to be fitted with child-resistant fastenings	: Not applicable.
Tactile warning of danger	: Not applicable.
2.3 Other hazards	
Product meets the criteria for PBT or vPvB	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: Causes digestive tract burns.

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

: Mixture

Code: 000001104813Date of issue/Date of revision: 6 June 2023PITT-CHAR XP HARDENER BLACK PF

**SECTION 3: Composition/information on ingredients** 

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	REACH #: 01-2119972320-44 EC: 500-191-5 CAS: 68082-29-1	≥25 - ≤50	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Chronic 2, H411	-	[1]
1,3,5-triazine-2,4,6-triamine	REACH #: 01-2119485947-16 EC: 203-615-4 CAS: 108-78-1 Index: 613-345-00-2	≥10 - ≤25	Carc. 2, H351 Repr. 2, H361f STOT RE 2, H373 (urinary system)	-	[1]
4,4'-Isopropylidenediphenol, ethoxylated	EC: polymer CAS: 32492-61-8 (EO> 4.5 moles)	≥5.0 - ≤10	Aquatic Chronic 3, H412	-	[1]
2,4,6-tris (dimethylaminomethyl) phenol	REACH #: 01-2119560597-27 EC: 202-013-9 CAS: 90-72-2 Index: 603-069-00-0	≥5.0 - ≤10	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1C, H314 Eye Dam. 1, H318	ATE [Oral] = 1200 mg/ kg ATE [Dermal] = 1280 mg/kg	[1]
3,6-diazaoctanethylenediamin	EC: 203-950-6 CAS: 112-24-3 Index: 612-059-00-5	≥1.0 - <5.0	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412	ATE [Oral] = 1716 mg/ kg ATE [Dermal] = 1465 mg/kg	[1] [2]
N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan- 1-amide)	REACH #: 01-2119978265-26 EC: 204-613-6 CAS: 123-26-2	<1.0	Skin Sens. 1B, H317 Aquatic Chronic 3, H412	-	[1] [2]
			See Section 16 for the full text of the H statements declared above.		

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

Eye contact	: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Inhalation	<ul> <li>Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.</li> </ul>
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

English (GB)	
--------------	--

Code : 00000110481 PITT-CHAR XP HARDENER	
SECTION 4: First aid	d measures
Ingestion	: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid t give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
4.2 Most important sympton	ns and effects, both acute and delayed
Potential acute health effe	<u>cts</u>
Eye contact	: Causes serious eye damage.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes severe burns. May cause an allergic skin reaction.
Ingestion	: Corrosive to the digestive tract. Causes burns.
Over-exposure signs/symp	<u>otoms</u>
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: Adverse symptoms may include the following: reduced foetal weight increase in foetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced foetal weight increase in foetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: stomach pains reduced foetal weight increase in foetal deaths skeletal malformations

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	<ul> <li>In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.</li> </ul>
Specific treatments	: No specific treatment.

# SECTION 5: Firefighting measures

5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.

#### 5.2 Special hazards arising from the substance or mixture

Code: 000001104813Date of issue/Date of revision: 6 June 2023PITT-CHAR XP HARDENER BLACK PF

### **SECTION 5: Firefighting measures**

Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway,
	sewer or drain.
Hazardous combustion products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides
5.3 Advice for firefighters	
Special precautions for fire-fighters	<ul> <li>Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.</li> </ul>
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

# SECTION 6: Accidental release measures

6.1 Personal precautions, pro	ote	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

#### 6.3 Methods and material for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product.
6.4 Reference to other sections	<ul> <li>See Section 1 for emergency contact information.</li> <li>See Section 8 for information on appropriate personal protective equipment.</li> <li>See Section 13 for additional waste treatment information.</li> </ul>

Code : 000001104813 Date of issue/Date of revision

PITT-CHAR XP HARDENER BLACK PF

: 6 June 2023

**SECTION 7: Handling and storage** 

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
7.2 Conditions for safe storage, including any incompatibilities	: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

#### 7.3 Specific end use(s)

See Section 1.2 for Identified uses.

## **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 8.1 Control parameters

#### **Occupational exposure limits**

Product/ingredient name	Exposure limit values         IPEL (-). Absorbed through skin.         TWA: 1 ppm         ACGIH TLV (United States).         TWA: 3 mg/m³ Form: Respirable         TWA: 10 mg/m³ Form: Total dust				
3,6-diazaoctanethylenediamin					
N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan- 1-amide)					
procedures Standard EN 689 by inhalation to o strategy) Europe application and u biological agents requirements for agents) Referen	d be made to monitoring standards, such as the following: European O (Workplace atmospheres - Guidance for the assessment of exposure themical agents for comparison with limit values and measurement ean Standard EN 14042 (Workplace atmospheres - Guide for the use of procedures for the assessment of exposure to chemical and O European Standard EN 482 (Workplace atmospheres - General the performance of procedures for the measurement of chemical ce to national guidance documents for methods for the determination postances will also be required.				

English (GB)

6/14

Code : 000001104813 Date of issue/Date of revision	n : 6 June 2023
PITT-CHAR XP HARDENER BLACK PF	

8.2 Exposure controls	
Appropriate engineering controls	: If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Individual protection meas	<u>ires</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection Skin protection	: Chemical splash goggles and face shield.
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Gloves	: pritrile neoprene
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
<b>Respiratory protection</b>	
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

# **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

Appearance	
Physical state	: Liquid.
Colour	: Black.
Odour	: Amine-like. [Strong]
Odour threshold	: Not available.
Melting point/freezing point	<ul> <li>May start to solidify at the following temperature: 12°C (53.6°F) This is based on data for the following ingredient: 3,6-diazaoctanethylenediamin. Weighted average: -55.6°C (-68.1°F)</li> </ul>
Initial boiling point and boiling range	: >37.78°C

Code : 000001104813 PITT-CHAR XP HARDENER BLA	CK	PF	Date of	issue/E	ate of	revisio	n	: 6 Jur	ne 2023
SECTION 9: Physical a	nd	l chemical prop	perties						
Flammability	:	Not available.							
Upper/lower flammability or explosive limits	:	: Greatest known range: Lower: 1.1% Upper: 6.4% (3,6-diazaoctanethylenediamin)							
Flash point	:	Closed cup: 120°C							
Auto-ignition temperature	:	Ingredient name		°C		°F		Method	
		3,6-diazaoctanethylened	iamin	337.78		640			
Decomposition temperature	:	Stable under recomr	nended st	orage a	nd hand	lling co	nditions	s (see Sec	tion 7).
рН	:	Not applicable. insoluble in water.							
Viscosity	:	Kinematic (40°C): >2	21 mm²/s						
Viscosity	:	> 100 s (ISO 6mm)							
Partition coefficient: n-octano water	I/ :	Not applicable.							
Vapour pressure	:		Vapour Pressure at 20°		20°C	Vapour pressure at 50		sure at 50°C	
		Ingredient name	mm Hg	kPa	Meth	od	mm Hg	kPa	Method
		4,6-tris (dimethylaminomethyl) phenol	0.056	0.0075	EU A.4				
Evaporation rate	:	Not available.			•				
Relative density	:	1.14							
Vapour density	1	Highest known value	: 5.04 (Ai	r = 1) (3	3,6-diaz	aoctan	ethylen	ediamin).	
Explosive properties	:	The product itself is vapour or dust with a			the forr	nation	of an e>	kplosible m	nixture of
Oxidising properties	:	Product does not pre	esent an o	xidizing	hazard				
Particle characteristics									

#### 9.2 Other information

No additional information.

SECTION 10: Stability and reactivity				
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.			
10.2 Chemical stability	: The product is stable.			
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.			
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.			
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.			
10.6 Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides			

Code : 000001104813

Date of issue/Date of revision

: 6 June 2023

PITT-CHAR XP HARDENER BLACK PF

# **SECTION 11: Toxicological information**

#### **11.1 Information on toxicological effects**

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	_
melamine	LC50 Inhalation Dusts and mists	Rat	>5190 mg/m <sup>3</sup>	4 hours
	LD50 Oral	Rat	3161 mg/kg	-
2,4,6-tris(dimethylaminomethyl)phenol	LD50 Dermal	Rabbit	1.28 g/kg	-
	LD50 Dermal	Rat	1280 mg/kg	-
3,6-diazaoctanethylenediamin	LD50 Oral LD50 Dermal	Rat Rabbit	1200 mg/kg 1465 mg/kg	-
	LD50 Oral	Rat	1716 mg/kg	-
N,N'-ethane-1,2-diylbis	LC50 Inhalation Dusts and	Rat	>5.11 mg/l	4 hours
(12-hydroxyoctadecan-1-amide)	mists		J J	
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	Eyes - Severe irritant	Rabbit	-	-	-
2,4,6-tris(dimethylaminomethyl)phenol		Human Rabbit	-	- 4 hours	- 7 days

#### **Conclusion/Summary**

: There are no data available on the mixture itself.

Eyes

Skin

: There are no data available on the mixture itself.

: There are no data available on the mixture itself.

#### Respiratory Sensitisation

Product/ingredient name	Route of exposure	Species	Result
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	skin	Mouse	Sensitising
3,6-diazaoctanethylenediamin	skin	Guinea pig	Sensitising
Conclusion/Summary			

Skin	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
<u>Mutagenicity</u>	
<b>Conclusion/Summary</b>	: There are no data available on the mixture itself.
<b>Carcinogenicity</b>	
<b>Conclusion/Summary</b>	: There are no data available on the mixture itself.
Reproductive toxicity	
<b>Conclusion/Summary</b>	: There are no data available on the mixture itself.
<b>Teratogenicity</b>	
<b>Conclusion/Summary</b>	: There are no data available on the mixture itself.
Specific target organ toxi	<u>city (single exposure)</u>

Code: 000001104813Date of issue/Date of revision: 6 June 2023PITT-CHAR XP HARDENER BLACK PF

### **SECTION 11: Toxicological information**

Not available.

#### Specific target organ toxicity (repeated exposure)

Product/ingredient name			Category	Route of exposure	Target organs
7,3,5-triazine-2,4,6-triamine			Category 2	-	urinary system
Aspiration hazard Not available.			1		
Information on likely routes of exposure	:	Not available.			
Potential acute health effect	t <u>s</u>				
Inhalation	4	No known significant effects	or critical haz	zards.	
Ingestion	4	Corrosive to the digestive tra	act. Causes b	ourns.	
Skin contact	4	Causes severe burns. May	cause an alle	rgic skin reaction.	
Eye contact	4	Causes serious eye damage	Э.		
Symptoms related to the ph	ys	ical, chemical and toxicolog	gical charact	<u>eristics</u>	
Inhalation	:	Adverse symptoms may inc reduced foetal weight increase in foetal deaths skeletal malformations		-	
Ingestion	:	Adverse symptoms may inc stomach pains reduced foetal weight increase in foetal deaths skeletal malformations	lude the follow	ving:	
Skin contact	:	Adverse symptoms may incl pain or irritation redness blistering may occur reduced foetal weight increase in foetal deaths skeletal malformations	lude the follow	<i>v</i> ing:	
Eye contact	:	Adverse symptoms may inc pain watering redness	lude the follow	<i>v</i> ing:	
Delayed and immediate effe	cts	as well as chronic effects	from short a	<u>nd long-term exp</u>	<u>osure</u>
Short term exposure					
Potential immediate effects	:	Not available.			
Potential delayed effects	1	Not available.			
Long term exposure Potential immediate effects	:	Not available.			
Potential delayed effects Potential chronic health effe					
Not available.	<u>+CI</u>	2			
Conclusion/Summary	1	Not available.			

Code: 000001104813Date of issue/Date of revision: 6 June 2023

PITT-CHAR XP HARDENER BLACK PF

### **SECTION 11: Toxicological information**

General	: May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: Suspected of damaging fertility.
Other information	: Not available.

Causes digestive tract burns. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death.

#### 11.2 Information on other hazards

**11.2.1 Endocrine disrupting properties** 

Not available.

#### **11.2.2 Other information**

Not available.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Atty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	EC10 1.78 mg/l	Algae	72 hours
melamine	Acute EC50 200 mg/l	Daphnia	48 hours
2,4,6-tris(dimethylaminomethyl)phenol	Acute LC50 175 mg/l	Fish	96 hours
N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan- 1-amide)	Acute EC50 29 to 43 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 94 mg/l	Daphnia - Daphnia magna	48 hours

**Conclusion/Summary** : There are no data available on the mixture itself.

#### 12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan- 1-amide)	-	63 % - 28 days	-	-
Conclusion/Summary	There are no da	ata available on the mixtu	re itself.	
Product/ingredient name		Aquatic half-life	Photolysis	Biodegradability
Atty acids, C18-unsatd., dimer reaction products with tall-oil fa triethylenetetramine N,N'-ethane-1,2-diylbis(12-hydr	itty acids and	-	-	Not readily Readily

#### 12.3 Bioaccumulative potential

1-amide)

Code: 000001104813Date of issue/Date of revision: 6 June 2023PITT-CHAR XP HARDENER BLACK PF

## **SECTION 12: Ecological information**

Product/ingredient name	LogPow	BCF	Potential	
7,3,5-triazine-2,4,6-triamine 2,4,6-tris(dimethylaminomethyl)phenol 3,6-diazaoctanethylenediamin N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan- 1-amide)	-1.22 0.219 -1.66 to -1.4 >6	3.8 - - -	low low low high	

#### **12.4 Mobility in soil**

Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

#### **12.6 Endocrine disrupting properties**

Not available.

#### 12.7 Other adverse effects

No known significant effects or critical hazards.

## **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.

#### European waste catalogue (EWC)

Waste code	Waste designation           waste paint and varnish containing organic solvents or other hazardous substances		
<b>Ø</b> 8 01 11*			
ackaging			
Methods of disposal	<ul> <li>The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.</li> </ul>		
Type of packaging	European waste catalogue (EWC)		
Container	15 01 06 mixed packaging		
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spill material and runoff and contact with soil, waterways, drains and sewers.		

Code: 000001104813Date of issue/Date of revision: 6 June 2023PITT-CHAR XP HARDENER BLACK PF

### **SECTION 14: Transport information**

	ADR/RID	IMDG	IATA
14.1 UN number or ID number	UN3066	UN3066	UN3066
14.2 UN proper shipping name	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	8	8	8
14.4 Packing group	M	W	M
14.5 Environmental hazards	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	(Polyamide)	Not applicable.

#### **Additional information**

ADR/RID	<ul> <li>The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.</li> </ul>
Tunnel code	: (E)
IMDG	: The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.
ΙΑΤΑ	: The environmentally hazardous substance mark may appear if required by other transportation regulations.
14.6 Special pre user	cautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
14.7 Transport i	<b>bulk :</b> Not applicable.

## **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

Annex XIV - List of substances subject to authorisation

#### Annex XIV

according to IMO instruments

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

### Other national and international regulations.

Ozone depleting substances (1005/2009/EU)

Not listed.

201101 2020/878	NO. 1907/2006 (REACH), Annex	II, as amended by Commission Regulation (EU)
Code : 00000110481	3 Dat	e of issue/Date of revision : 6 June 2023
PITT-CHAR XP HARDENER	BLACK PF	
SECTION 15: Regula	tory information	
15.2 Chemical safety assessment	: No Chemical Safety Assessme	ent has been carried out.
SECTION 16: Other	nformation	
Indicates information that	nas changed from previously issue	d version.
Abbreviations and acronyms	: ATE = Acute Toxicity Estimate CLP = Classification, Labelling 1272/2008] DNEL = Derived No Effect Lev EUH statement = CLP-specific PNEC = Predicted No Effect C RRN = REACH Registration N	g and Packaging Regulation [Regulation (EC) No. vel c Hazard statement Concentration
Full text of abbreviated H statements	<ul> <li>H302 Harmful if swallower</li> <li>H312 Harmful in contact v</li> <li>H314 Causes severe skin</li> <li>H315 Causes skin irritatio</li> <li>H317 May cause an allerg</li> <li>H318 Causes serious eye</li> <li>H351 Suspected of causir</li> <li>H361f Suspected of damage</li> <li>H373 May cause damage</li> <li>H411 Toxic to aquatic life</li> </ul>	d. vith skin. burns and eye damage. n. jic skin reaction. damage. ng cancer.
Full text of classifications [CLP/GHS]	Aquatic Chronic 2LCAquatic Chronic 3LCCarc. 2C/Eye Dam. 1SIRepr. 2RISkin Corr. 1BSISkin Corr. 1CSISkin Sens. 1SISkin Sens. 1ASISkin Sens. 1BSIStin Sens. 1BSISTOT RE 2SI	CUTE TOXICITY - Category 4 ONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 ONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 ARCINOGENICITY - Category 2 ERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 EPRODUCTIVE TOXICITY - Category 2 (IN CORROSION/IRRITATION - Category 1B (IN CORROSION/IRRITATION - Category 1C (IN CORROSION/IRRITATION - Category 1C (IN SENSITISATION - Category 1 (IN SENSITISATION - CATEGORY 1 CATEGORY 1 (IN SENSITISATION - CATEGORY 1 (IN SENSITISATION - CATEGORY 1 CATEGORY 1 (IN SENSITISATION - CATEGORY 1 (IN
<u>History</u>		
Date of issue/ Date of revision	: 6 June 2023	
Date of previous issue	: 23 June 2022	
Prepared by	: EHS	

#### <u>Disclaimer</u>

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.