Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

SAFETY DATA SHEET

Date of issue/Date of revision

: 18 June 2023

Version : 1.01



SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: NOVAGUARD 810/810ER YELLOW CURE
Product code	: 00348951
Product description	1 · · · · · · · · · · · · · · · · · · ·
Product type	: Liquid.
Other means of identification	: Not available.
1.2 Relevant identified uses	s of the substance or mixture and uses advised against
Product use	: Industrial applications, Used by spraying.
Use of the substance/ mixture	: Hardener.; Coating.
Uses advised against	: Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL Tweemontstraat 104 B-2100 Deurne Belgium Telephone +32-33606311 Fax +32-33606435

e-mail address of person :

: Product.Stewardship.EMEA@ppg.com

responsible for this SDS

1.4 Emergency telephone number

<u>Supplier</u>

+31 20 4075210

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture Classification according to UK CLP/GHS

Flam. Liq. 3, H226 Acute Tox. 4, H302 Skin Corr. 1A, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 2, H411

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word

: Danger

Code : 00348951		Date of issue/Date of revision : 18 June 2023
NOVAGUARD 810/810ER YE	LLC	DW CURE
SECTION 2: Hazards	id	lentification
Hazard statements	:	Flammable liquid and vapour. Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction.
		Toxic to aquatic life with long lasting effects.
Precautionary statements		
Prevention	:	Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment.
Response	:	Collect spillage. IF INHALED: Immediately call a POISON CENTER or doctor.
Storage	:	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
		P280, P210, P273, P391, P304 + P310, P501
Supplemental label elements	-	Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Special packaging requirem	<u>nen</u>	<u>ts</u>
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Testile wereine of denser		

- Tactile warning of danger : Not applicable.
- 2.3 Other hazards
- Product meets the criteria : This mixture does not contain any substances that are assessed to be a PBT or a for PBT or vPvB according vPvB.

Other hazards which do : None known.

not result in classification

to Regulation (EC) No. 1907/2006, Annex XIII

SECTION 3: Composition/information on ingredients

Mixture

3.2 Mixtures

Product/ingredient name	Identifiers	%	Classification	Туре
7,3-Cyclohexanedimethanamine	EC: 219-941-5 CAS: 2579-20-6	≥25 - ≤50	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1A, H314 Eye Dam. 1, H318 Aquatic Chronic 3, H412	[1]
benzyl alcohol	REACH #: 01-2119492630-38 EC: 202-859-9 CAS: 100-51-6 Index: 603-057-00-5	≥10 - ≤25	Acute Tox. 4, H302 Acute Tox. 4, H332 Eye Irrit. 2, H319	[1]
Formaldehyde, polymer with N,N- dimethyl-1,3-propanediamine and phenol	CAS: 445498-00-0	≥5.0 - ≤10	Acute Tox. 4, H302 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
N-(3-(trimethoxysilyl)propyl)	EC: 217-164-6	≥1.0 - ≤5.0	Eye Dam. 1, H318	[1]

Code : 00348951 NOVAGUARD 810/810ER YELLOW CURE	Date of issue/Date of revision	: 18 June 2023
SECTION 3: Composition/information on ingredients		

ethylenediamine	CAS: 1760-24-3		Skin Sens. 1B, H317 STOT SE 3, H335	
2,4,6-tris(dimethylaminomethyl) phenol	REACH #: 01-2119560597-27 EC: 202-013-9 CAS: 90-72-2 Index: 603-069-00-0	≥1.0 - ≤4.0	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1C, H314 Eye Dam. 1, H318	[1]
Alpha, Alpha"-(1,3-Xylenediyl)Bis (12-Hydroxy-Octadecanamide)	CAS: SUB101970	≥1.0 - ≤5.0	Eye Irrit. 2, H319 STOT SE 3, H335	[1]
3-aminopropyldimethylamine	REACH #: 01-2119486842-27 EC: 203-680-9 CAS: 109-55-7 Index: 612-061-00-6	<1.0	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317	[1]
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. <u>Type</u>

[1] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid m	easures
Eye contact	: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effect	<u>s</u>	
Eye contact	: Causes serious eye damage.	
Inhalation	: No known significant effects or critical hazards.	
Skin contact	: Causes severe burns. May cause an allergic skin reaction.	
Ingestion	: Harmful if swallowed.	
Over-exposure signs/symp	utoms	
Eye contact	: Adverse symptoms may include the following: pain watering redness	
Inhalation	: No specific data.	
English (GB)	United Kingdom (UK)	3/14

Code : 00348951 NOVAGUARD 810/810ER	Date of issue/Date of revision : 18 June 2023 YELLOW CURE
SECTION 4: First a	aid measures
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion	: Adverse symptoms may include the following: stomach pains
4.3 Indication of any imm	ediate medical attention and special treatment needed
Notes to physician	 In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.

5.1 Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.
5.2 Special hazards arising f	om the substance or mixture
Hazards from the substance or mixture	: Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides Formaldehyde.
5.3 Advice for firefighters	
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	ective equipment and emergency procedures	
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources No flares, smoking or flames in hazard area. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.	
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".	
6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drain and sewers. Inform the relevant authorities if the product has caused environme pollution (sewers, waterways, soil or air). Water polluting material. May be harm to the environment if released in large quantities. Collect spillage.	ntal
English (GB)	United Kingdom (UK)	4/14

Code : 00348951

Date of issue/Date of revision

: 18 June 2023

NOVAGUARD 810/810ER YELLOW CURE

SECTION 6: Accidental release measures

6.3 Methods and material for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

Code

- : 00348951 **NOVAGUARD 810/810ER YELLOW CURE**
- Date of issue/Date of revision

: 18 June 2023

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Occupational exposure limits

No exposure limit value known.

Recommended monitoring	: Reference should be made to appropriate monitoring standards. Reference to
procedures	national guidance documents for methods for the determination of hazardous
	substances will also be required.

DNELs/DMELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
7,3-Cyclohexanedimethanamine	DNEL	Long term Inhalation	9.47 µg/m³	Workers	Local
	DNEL	Long term Dermal	0.1 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	25.2 mg/kg bw/day	Workers	Systemic
benzyl alcohol	DNEL	Long term Oral	4 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	4 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	5.4 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	8 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Oral	20 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	20 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	22 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	27 mg/m ³	General population	Systemic
	DNEL	Short term Dermal	40 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	110 mg/m ³	Workers	Systemic
N-(3-(trimethoxysilyl)propyl) ethylenediamine	DNEL	Long term Inhalation	0.1 mg/m ³	General population	Local
	DNEL	Long term Inhalation	0.6 mg/m ³	Workers	Local
	DNEL	Short term Inhalation	4 mg/m ³	General population	Local
	DNEL	Short term Inhalation	5.36 mg/m ³	Workers	Local
	DNEL	Short term Inhalation	50 mg/m³	General population	Systemic
	DNEL	Short term Inhalation	260 mg/m ³	Workers	Systemic
	DNEL	Long term Oral	8 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	50 mg/m³	General population	Systemic
	DNEL	Long term Inhalation	260 mg/m ³	Workers	Systemic
2,4,6-tris	DNEL	Long term Oral	0.075 mg/kg bw/day	General population	Systemic
(dimethylaminomethyl)phenol					
	DNEL	Short term Dermal	0.075 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.075 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	0.13 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	0.13 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	0.15 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	0.53 mg/m³	Workers	Systemic
	DNEL	Short term Dermal	0.6 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	2.1 mg/m ³	Workers	Systemic
3-aminopropyldimethylamine	DNEL	Long term Inhalation	1.2 mg/m³	Workers	Systemic

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
3-aminopropyldimethylamine	Fresh water	0.034 mg/l	Assessment Factors
	Marine water	0.003 mg/l	Assessment Factors
	Sewage Treatment Plant	69.5 mg/l	Assessment Factors
	Fresh water sediment	0.221 mg/kg dwt	Equilibrium Partitioning
	Marine water sediment	0.022 mg/kg dwt	Equilibrium Partitioning
	Soil	0.024 mg/kg dwt	Equilibrium Partitioning

8.2 Exposure controls

controlsor other engineering controls to keep worker exposure to althorne contaminants beke any recommended or statutory limits. The engineering controls also need to keep gr vapour or dust concentrations below any lower explosive limits. Use explosion-proor ventilation equipment.Individual protection measures: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techning before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.Eyeiface protection: Chemical-resistant, impervious gloves complying with an approved standard should worm at all times when handling chemical products if a risk assessment indicates this necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for differ glove manufacturers. In the case of mixtures, consisting of Several substances, the protection time of the gloves canned by estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended When only brie fooritact is expected, a glove with a protection class of use most appropriate and takes into account the particular conditions of us as is forther engineer and any additional skin protection form static citection. The user's insk assessment. nitile neopreneBody protection: Personal protective equipment for the body should be approved by a specialist before handling this product. When there is a risk of ignition from static discharges, clothing should include anti-tsatic overalls, boots	Conforms to Regulation (EC) N	o. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758
Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilatio or other engineering controls to keep worker exposure to airbiome contaminants belo any recommended or statutory limits. The engineering controls also need to keep give vapour or dust concentrations below any lower explosive limits. Use explosion-proor ventilation equipment. Individual protection measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated (othing, Contaminated work clothing should not be allowed out of the working. Wash contaminated out clothing should not be allowed out of the working contaminated (othing Contaminated work clothing should not be allowed out of the working contaminated is showers are close to the working in location. Eye/face protection : Chemical-resistant, impervious gloves complying with an approved standard should worm at all times when handling chemical products if a risk assessment indicates this necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 2 or higher (breakthrough time greater than 480 minutes according to EN74) is recommended When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes account the particular conditions of us as included in the user's risk assessment. Intitle neoprene Body protection : Personal protective equipment for the body should be selected based on the task be performed and the risks involved and should be appro		
controlsor other engineering controls to keep worker exposure to altoorne contaminants beke any recommended or statutory limits. The engineering controls also need to keep gi vapour or dust concentrations below any lower explosive limits. Use explosion-proor ventilation equipment.Individual protection measures: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated dothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.Eyelface protection: Chemical-resistant, impervious gloves complying with an approved standard should wom at all times when handling chemical products if a risk assessment indicates thi necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves and the Quow annufacturer, check during use that the gloves and may be different for differ glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves care that Quo the protection class of 6 (treakthrough time greater than 480 minutes according to EN 374) is recommended When only brief contact is expected, a glove with a protection class of 0 us as included in the user's risk assessment. Intel neopreneBody protection: Perportiate footwear and any additional shin product. When the is a risk of ignition from static discharges, clothing should in the user's risk assessment.Body protection: Perportiate footwear and any additional shin protection from static discharges, clothing should in the user's risk assessment.	SECTION 8: Exposu	e controls/personal protection
Hygiene measures: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing, Contaminated clothing before reusing. Ensure that eyewash stations and safety 		: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated work clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.Eyelface protection Skin protection: Chemical splash goggles and face shield.Hand protection Hand protection: Chemical-resistant, impervious gloves complying with an approved standard should worn at all times when handling chemical products if a risk assessment indicates this necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for differ glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 2 or higher (breakthrough time greater than 480 minutes according to EN 374) is recommended When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product. When there is a risk of ignition from static discharges, clothing should include anti-static overalls, boots and gloves.Other skin protection: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.Respira	Individual protection measu	<u>ires</u>
Skin protection : Chemical-resistant, impervious gloves complying with an approved standard should worn at all times when handling chemical products if a risk assessment indicates this necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 30 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of us as included in the user's risk assessment. Body protection : Personal protective equipment for the body should be selected based on the task be performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear and static protective clothing. For the greatest protection measures should be selected based on the task being performed and the risks involved and should be approved by approved by specialist before handling this product. Respiratory protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by specialist before hanadling this product. <td< td=""><td>Hygiene measures</td><td>Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety</td></td<>	Hygiene measures	Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety
worn at all times when handling chemical products if a risk assessment indicates this necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for differe glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 		: Chemical splash goggles and face shield.
Other skin protectionPerformed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear and static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.Other skin protection: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by specialist before handling this product.Respiratory protection: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If work are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3Environmental exposure controls: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment	Hand protection	noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
 Respiratory protection Respiratory protection Respiratory protection Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If work are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3 Environmental exposure controls Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment 	Body protection	handling this product. When there is a risk of ignition from static electricity, wear anti- static protective clothing. For the greatest protection from static discharges, clothing
 hazards of the product and the safe working limits of the selected respirator. If work are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3 Environmental exposure controls Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment 	Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
controls they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipmen	Respiratory protection	hazards of the product and the safe working limits of the selected respirator. If worker are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate
		cases, fume scrubbers, filters or engineering modifications to the process equipment

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Colour	: Yellow.
Odour	: Characteristic.
Odour threshold	: Not available.

English (GB)

Code NOVAGUA	: 00348951 ARD 810/810ER YELLOW CURE	Date of issue/Date of revision	: 18 June 2023	
OFOTION O. Developland chamical preventice				

SECTION 9: Physica	I and c	hemical	properties
--------------------	---------	---------	------------

Melting point/freezing point	 May start to solidify at the following temperature: -15.4°C (4.3°F) This is based on data for the following ingredient: benzyl alcohol. Weighted average: -22.84°C (-9.1°
Initial boiling point and boiling range	: >37.78°C (>100°F)
Flammability (solid, gas)	: liquid
Upper/lower flammability or explosive limits	: Greatest known range: Lower: 1.3% Upper: 13% (benzyl alcohol)
Flash point	: Closed cup: 50°C (122°F)
Auto-ignition temperature	1 · · · · · · · · · · · · · · · · · · ·

Ingredient name	°C	°F	Method
2,4,6-tris(dimethylaminomethyl)phenol	382	719.6	EU A.15

Decomposition temperature	:	
рН	:	Not applicable.
		Not applicable. insoluble in water.
Viscosity	:	Kinematic (40°C): >21 mm²/s
Solubility(ies)	:	
Media		Result
cold water		Not soluble
Solubility in water	:	1 g/l
Miscible with water	:	No.
Partition coefficient: n-octanol/ water	:	Not applicable.
Vapour pressure	:	0.36 kPa (2.7 mm Hg)
Evaporation rate	:	0.04 (butyl acetate = 1)
Relative density	:	1.28
Vapour density	:	Highest known value: 3.7 (Air = 1) (benzyl alcohol).
Explosive properties	:	The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.
Oxidising properties Particle characteristics	:	Product does not present an oxidizing hazard.
Median particle size	:	Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
10.6 Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides Formaldehyde. metal oxide/oxides

English (GB)	United Kingdom (UK)	8/14

Code : 00348951

Date of issue/Date of revision

: 18 June 2023

NOVAGUARD 810/810ER YELLOW CURE

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure	
73-Cyclohexanedimethanamine	LD50 Dermal	Rabbit	1700 mg/kg	-	
	LD50 Oral	Rat	700 mg/kg	-	
benzyl alcohol	LC50 Inhalation Dusts and mists	Rat	>4178 mg/m ³	4 hours	
	LD50 Dermal	Rabbit	2000 mg/kg	-	
	LD50 Oral	Rat	1.23 g/kg	-	
N-(3-(trimethoxysilyl)propyl) ethylenediamine	LD50 Dermal	Rabbit	>2000 mg/kg	-	
	LD50 Oral	Rat	2413 mg/kg	-	
2,4,6-tris (dimethylaminomethyl) phenol	LD50 Dermal	Rabbit	1.28 g/kg	-	
P	LD50 Dermal	Rat	1280 mg/kg	-	
	LD50 Oral	Rat	1200 mg/kg	-	
3-aminopropyldimethylamine	LD50 Dermal	Rabbit	>1000 mg/kg	-	
· · · ·	LD50 Oral	Rat	410 mg/kg	-	

Conclusion/Summary Acute toxicity estimates : There are no data available on the mixture itself.

Inhalation **Product/ingredient name** Oral (mg/ Dermal Inhalation Inhalation kg) (mg/kg) (gases) (vapours) (dusts and mists) (ppm) (mg/l) (mg/l) NOVAGUARD 810/810ER YELLOW CURE 1326.6 4981.2 N/A N/A 7.6 1,3-Cyclohexanedimethanamine 700 1700 N/A N/A N/A benzyl alcohol 1230 N/A N/A N/A 1.5 Formaldehyde, polymer with N,N-dimethyl-500 N/A N/A N/A N/A 1,3-propanediamine and phenol N-(3-(trimethoxysilyl)propyl)ethylenediamine N/A N/A N/A N/A 2413 2,4,6-tris(dimethylaminomethyl)phenol 1280 1200 N/A N/A N/A 3-aminopropyldimethylamine 410 1100 N/A N/A N/A

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation		
2,4,6-tris (dimethylaminomethyl)phenol	Skin - Visible necrosis	Rabbit	-	4 hours	7 days		
Conclusion/Summary	Not available.			-			
Skin	: There are no data available or	the mixture its	self.				
Eyes	There are no data available or	the mixture it	self.				
Respiratory	: There are no data available or	the mixture its	self.				
Sensitisation							
Conclusion/Summary							
Skin	: There are no data available or	the mixture its	self.				
Respiratory	: There are no data available or	There are no data available on the mixture itself.					
Mutagenicity							
Conclusion/Summary	: There are no data available or	the mixture its	self.				
Carcinogenicity							
Conclusion/Summary	: There are no data available or	the mixture its	self.				
Reproductive toxicity							
Conclusion/Summary	: There are no data available on the mixture itself.						
Teratogenicity							
Conclusion/Summary	:						
					• • • •		

English (GB)

Code

: 00348951

Date of issue/Date of revision

: 18 June 2023

NOVAGUARD 810/810ER YELLOW CURE

SECTION 11: Toxicological information

There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
N-(3-(trimethoxysilyl)propyl)ethylenediamine	Category 3	-	Respiratory tract irritation
Alpha, Alpha"-(1,3-Xylenediyl)Bis(12-Hydroxy- Octadecanamide)	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes	: Not available.
of exposure	

Potential acute health effect	Potential	acute	health	effects
-------------------------------	-----------	-------	--------	---------

Eye contact	: Causes serious eye damage.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes severe burns. May cause an allergic skin reaction.
Ingestion	: Harmful if swallowed.

Symptoms related to the	physical, chemical and	toxicological characteristics

Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion	: Adverse symptoms may include the following: stomach pains

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure		
Potential immediate effects	Not available.	
Potential delayed effects	Not available.	
Long term exposure		
Potential immediate effects	Not available.	
Potential delayed effects	Not available.	
Potential chronic health effe		
Not available.		
Conclusion/Summary	lot available.	
General	Dnce sensitized, a severe allergic reaction may occur when subsequently o very low levels.	y exposed
Carcinogenicity	lo known significant effects or critical hazards.	
Mutagenicity	No known significant effects or critical hazards.	

English (GB)

United Kingdom (UK)

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

Code	: 00348951	Date of issue/Date of revision	: 18 June 2023
NOVAGUARI	0 810/810ER YELLOW CURE		

SECTION 11: Toxicological information

Reproductive toxicity

: No known significant effects or critical hazards.

Other information : Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
1,3-Cyclohexanedimethanamine	LC50 130 mg/l	Fish - golden orfe	96 hours
N-(3-(trimethoxysilyl)propyl) ethylenediamine	EC50 597 mg/l	Fish	96 hours
2,4,6-tris (dimethylaminomethyl) phenol	Acute LC50 175 mg/l	Fish	96 hours
3-aminopropyldimethylamine	Acute LC50 122 mg/l	Fish	96 hours
Conclusion/Summary	: Not available.	·	•

12.2 Persistence and degradability

Product/ingredient name	Test	Result		Dose	Inoculum
3-aminopropyldimethylamine	OECD 301D	69 % - Readily - 20	days	-	-
Conclusion/Summary : Not available.					
Product/ingredient name	Aquatic half-life		Photolysis	5	Biodegradability
benzyl alcohol 3-aminopropyldimethylamine	-		-		Readily Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
1,3-Cyclohexanedimethanamine	0.783	-	Low
benzyl alcohol	0.87	-	Low
2,4,6-tris	0.219	-	Low
(dimethylaminomethyl)			
phenol			
3-aminopropyldimethylamine	-0.352	-	Low

12.4 Mobility in soil

Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

Code	: 00348951	Date of issue/Date of revision	: 18 June 2023
NOVAGUAR	D 810/810ER YELLOW CURE		

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods Product Methods of disposal The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Hazardous waste Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.

Waste code Waste designation 08 01 99 wastes not otherwise specified

Packaging

- **Methods of disposal**
- : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	Waste catalogue	
Container	15 01 06 mixed packaging	
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.	

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number	UN3470	UN3470	UN3470	UN3470
14.2 UN proper shipping name	PAINT, CORROSIVE, FLAMMABLE	PAINT, CORROSIVE, FLAMMABLE	PAINT, CORROSIVE, FLAMMABLE	PAINT, CORROSIVE, FLAMMABLE
14.3 Transport hazard class(es)	8 (3)	8 (3)	8 (3)	8 (3)
14.4 Packing group	11	11	11	
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	Not applicable.	(Formaldehyde, polymer with N,N- dimethyl- 1,3-propanediamine and phenol)	Not applicable.

Additional information

ADR/RID

: The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.

	0348951 10/810ER YELLOV	Date of issue/Date of revision : 18 June 2023 CURE
SECTION 1	4: Transport	Iformation
ADN	: The environme ≤5 kg.	ally hazardous substance mark is not required when transported in sizes of \leq 5 L or
IMDG	: The marine pol	tant mark is not required when transported in sizes of ≤5 L or ≤5 kg.
IATA	: The environme regulations.	ally hazardous substance mark may appear if required by other transportation
14.6 Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.		
14.7 Transport i according to IM instruments		available.
SECTION 1	5: Regulatory	nformation

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>UK (GB)/REACH</u>

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Ozone depleting substances

Not listed.

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

P5c	Category			
EZ	P5c E2			

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations a	nd : ATE = Acute Toxicity Estimate
acronyms	GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and
	Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019
	No. 720 and amendments
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = GB CLP-specific Hazard statement
	N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative
_	

Procedure used to derive the classification

Code : 00348951 Date of issue/Date of revision	: 18 June 2023
--	----------------

NOVAGUARD 810/810ER YELLOW CURE

SECTION 16: Other information

Classification	Justification
Flam. Liq. 3, H226	On basis of test data
Acute Tox. 4, H302	Calculation method
Skin Corr. 1A, H314	Calculation method
Eye Dam. 1, H318	Calculation method
Skin Sens. 1, H317	Calculation method
Aquatic Chronic 2, H411	Calculation method

Full text of abbreviated H statements

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) ĂQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Skin Corr. 1A	SKIN CORROSION/IRRITATION - Category 1A
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1B	SKIN SENSITISATION - Category 1B
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

<u>History</u>

Date of issue/ Date of revision	: 18 June 2023
Date of previous issue	: 7 November 2022
Prepared by	: EHS
Version	: 1.01

<u>Disclaimer</u>

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.