## **SAFETY DATA SHEET**



Date of issue 7/12/2023 (month/day/year)

Version 12.02

## Section 1. Chemical product and company identification

A. Product name : PPG AQUACOVER 45 (TINTED)

Product code : 00191490

B. Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Professional applications, Used by spraying.

**Use of the substance/** 

mixture

: Coating.

**Uses advised against**: Product is not intended, labelled or packaged for consumer use.

C. Supplier's or Importer's

information

**Email Address** 

: PPG SSC (680-090)

19, Yeocheon-ro 217beon-gil, Nam-gu,

Ulsan, Korea

Tel: +82-52-210-8222 Korea.MSDS@PPG.COM

**Emergency telephone** 

number:

: +82-52-210-8222

## Section 2. Hazards identification

A. Hazard classification : CARCINOGENICITY - Category 2

AQUATIC HAZARD (LONG-TERM) - Category 2

This product is classified in accordance with the Industrial Safety and Health Act and the Chemical Control Act.

B. GHS label elements, including precautionary statements

Symbol :





Signal word : Warning

**Hazard statements**: H351 - Suspected of causing cancer.

H411 - Toxic to aquatic life with long lasting effects.

**Precautionary statements** 

**Prevention**: P202 - Do not handle until all safety precautions have been read and understood.

P280 - Wear protective gloves, protective clothing and eye or face protection.

P273 - Avoid release to the environment.

Response : P391 - Collect spillage.

P308 + P313 - IF exposed or concerned: Get medical advice or attention.

Storage : Not applicable.

Korea (GHS) Page: 1/13

**Product name PPG AQUACOVER 45 (TINTED)** 

#### Section 2. Hazards identification

**Disposal** 

: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

C. Other hazards which do not result in classification

Prolonged or repeated contact may dry skin and cause irritation. Contains isothiazolinones. May cause allergic reaction.

## **Section 3. Composition/information on ingredients**

#### **CAS** number/other identifiers

**CAS number** : Not applicable.

Chemical name	Common name	Identifiers	%
tranium dioxide	TITANIUM DIOXIDE	CAS: 13463-67-7	10 -<20
(2-methoxymethylethoxy)propanol	DIPROPYLENE GLYCOL	CAS: 34590-94-8	1 - <5
	MONOMETHYL ETHER		
tetraamminezinc(2+) carbonate	tetraamminezinc(2+) carbonate	CAS: 38714-47-5	0.1 - <1
propylidynetrimethanol	TRIMETHYLOLPROPANE	CAS: 77-99-6	0.1 - <1
ammonia	AMMONIUM HYDROXIDE	CAS: 1336-21-6	0.1 - <1
4,5-Dichloro-2-N-octyl-4-isothizaolin-	4,5-Dichloro-2-octyl-2H-isothiazol-3-one	CAS: 64359-81-5	<0.1
3-one	_		
3-iodo-2-propynyl butylcarbamate	3-lodo-2-propynyl butylcarbamate	CAS: 55406-53-6	<0.1
octamethylcyclotetrasiloxane	OCTAMETHYLCYCLOTETRASILOXANE	CAS: 556-67-2	<0.1
zinc pyrithione	pyrithione zinc	CAS: 13463-41-7	<0.1

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

<b>A</b> 41	4 = :	4	
CASTIAN	7 L 1 L	-	measures
300000	4 611	CI AIM	HIDSCHILD
OCCHOIL	<b>-T.</b> 1 11	JL UIU	IIICasaics

A.	Eye contact	:	Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
В.	Skin contact	:	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

C. Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

D. Ingestion : If swallowed, seek medical advice immediately and show this container or label.
 Keep person warm and at rest. Do NOT induce vomiting.

E. Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Korea (GHS) Page: 2/13

**Product name PPG AQUACOVER 45 (TINTED)** 

#### Section 4. First aid measures

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

A. Extinguishing media

Suitable extinguishing

media

Unsuitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

: None known.

B. Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

 Decomposition products may include the following materials: carbon oxides

metal oxide/oxides

C. Special equipment for fire-fighting

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

**Fire-fighting procedures** 

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

### Section 6. Accidental release measures

A. Personal precautions, protective equipment and emergency procedures

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

B. Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

#### C. Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Korea (GHS) Page: 3/13

## Section 7. Handling and storage

#### A. Precautions for safe handling

- : Put on appropriate personal protective equipment (see Section 8). Avoid exposure obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- **B.** Conditions for safe storage, including any incompatibilities
- : Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

#### A. Occupational exposure limits

Ingredient name	Exposure limits
irtanium dioxide	Ministry of Employment and Labor (Republic of Korea, 1/2020).
	TWA: 10 mg/m³ 8 hours. Form: total dust with less than 1% of free SiO2
(2-methoxymethylethoxy)propanol	Ministry of Employment and Labor (Republic of Korea, 1/2020). [Dipropylene glycol methyl ether]
	Absorbed through skin. STEL: 150 ppm 15 minutes. TWA: 100 ppm 8 hours.
ammonia	Ministry of Employment and Labor (Republic of Korea, 1/2020). [Ammonia] STEL: 35 ppm 15 minutes. TWA: 25 ppm 8 hours.

Recommended monitoring procedures

- Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
- controls
- B. Appropriate engineering: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**Environmental** exposure controls

- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
- C. Personal protective equipment

Korea (GHS) Page: 4/13

**Product name PPG AQUACOVER 45 (TINTED)** 

## Section 8. Exposure controls/personal protection

Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the

> hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is

necessary.

**Eye protection** : Safety glasses with side shields.

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer,

check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately

estimated.

: For prolonged or repeated handling, use the following type of gloves: **Gloves** 

Recommended: butyl rubber, Viton®, nitrile rubber

**Body protection** : Personal protective equipment for the body should be selected based on the task

being performed and the risks involved and should be approved by a specialist

before handling this product.

: Wash hands, forearms and face thoroughly after handling chemical products, before **Hygiene measures** 

eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and

safety showers are close to the workstation location.

## Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

A. Appearance

**Physical state** : Liquid. : Various Color B. Odor : Amine-like. : Not available. C. Odor threshold

D. pH

E. Melting/freezing point : Not available.

F. Boiling point/boiling : >37.78°C (>100°F)

range

G. Flash point : Closed cup: 120°C (248°F)

: Not available. H. Evaporation rate Flammability (solid, gas) : Not available.

J. Lower and upper

K. Vapor pressure

explosive (flammable) limits

: Greatest known range: Lower: 1.1% Upper: 14% ((2-methoxymethylethoxy)

propanol)

Korea (GHS) Page: 5/13

**Product name PPG AQUACOVER 45 (TINTED)** 

## Section 9. Physical and chemical properties

	Vapor Pressure at 20°C			Vapor pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
water	17.5	2.3				

Media Result L. Solubility(ies)

> cold water Partially soluble

: Not available. Solubility in water Vapor density Not available.

1.25 **Relative density** 

Partition coefficient: n-

: Not applicable.

octanol/water

: 207°C (404.6°F) **Auto-ignition** 

temperature

**Decomposition** 

Not available.

temperature **Viscosity** 

S.

Kinematic (40°C (104°F)): >21 mm<sup>2</sup>/s (>21 cSt)

Flow time (ISO 2431) : Not available. **Molecular weight** : Not applicable.

## Section 10. Stability and reactivity

A. Chemical stability : The product is stable.

reactions

Possibility of hazardous: Under normal conditions of storage and use, hazardous reactions will not occur.

B. Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition

products.

: Keep away from the following materials to prevent strong exothermic reactions: C. Incompatible materials

oxidizing agents, strong alkalis, strong acids.

D. Hazardous : Depending on conditions, decomposition products may include the following

materials: carbon oxides metal oxide/oxides decomposition products

## **Section 11. Toxicological information**

A. Information on the likely : Not available. routes of exposure

#### Potential acute health effects

Inhalation : No known significant effects or critical hazards. : No known significant effects or critical hazards. Ingestion

: Defatting to the skin. May cause skin dryness and irritation. **Skin contact** 

: No known significant effects or critical hazards. **Eye contact** 

#### Over-exposure signs/symptoms

Korea (GHS) Page: 6/13

**Product name PPG AQUACOVER 45 (TINTED)** 

## **Section 11. Toxicological information**

Inhalation: No specific data.Ingestion: No specific data.

**Skin contact**: Adverse symptoms may include the following:

irritation dryness cracking

**Eye contact** : No specific data.

#### **B.** Health hazards

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
iranium dioxide	LC50 Inhalation Dusts and	Rat	>6.82 mg/l	4 hours
	mists			
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
(2-methoxymethylethoxy)propanol	LC50 Inhalation Vapor	Rat	500 ppm	4 hours
, , , , , , , , , , , , , , , , , , , ,	LD50 Dermal	Rabbit	9.5 g/kg	-
	LD50 Oral	Rat	5.23 g/kg	-
propylidynetrimethanol	LD50 Dermal	Rabbit	10 g/kg	-
, ,	LD50 Oral	Rat	14000 mg/kg	-
ammonia	LD50 Oral	Rat	350 mg/kg	-
4,5-Dichloro-2-N-octyl-4-isothizaolin-	LC50 Inhalation Dusts and	Rat	0.16 mg/l	4 hours
3-one	mists			
	LD50 Dermal	Rabbit	3.9 g/kg	-
	LD50 Oral	Rat	567 mg/kg	-
3-iodo-2-propynyl butylcarbamate	LC50 Inhalation Dusts and	Rat	0.67 mg/l	4 hours
, .	mists			
	LD50 Dermal	Rabbit	>2 g/kg	-
	LD50 Oral	Rat	1470 mg/kg	-
octamethylcyclotetrasiloxane	LC50 Inhalation Vapor	Rat	36 g/m³	4 hours
• •	LD50 Dermal	Rat	>2375 mg/kg	-
	LD50 Oral	Rat	>4800 mg/kg	-
zinc pyrithione	LC50 Inhalation Dusts and	Rat	0.14 mg/l	4 hours
• •	mists			
	LD50 Dermal	Rabbit	>2 g/kg	-
	LD50 Oral	Rat	177 mg/kg	-

**Conclusion/Summary**: There are no data available on the mixture itself.

#### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
	Eyes - Severe irritant	Rabbit	-	-	-
zinc pyrithione	Eyes - Cornea opacity	Rabbit	4	24 hours	24 hours

**Conclusion/Summary** 

Skin : There are no data available on the mixture itself.

Eyes : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

**Sensitization** 

**Conclusion/Summary** 

Korea (GHS) Page: 7/13

**Product name PPG AQUACOVER 45 (TINTED)** 

## **Section 11. Toxicological information**

Skin : There are no data available on the mixture itself.Respiratory : There are no data available on the mixture itself.

**Mutagenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Carcinogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Reproductive toxicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Teratogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

#### Specific target organ toxicity (single exposure)

Name	Classification	Route of exposure	Target organs
ammonia	Category 3		Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

Name	Classification	Route of exposure	Target organs
	Category 1 Category 1	-	trachea -

#### **Aspiration hazard**

Not available.

#### Potential chronic health effects

General: Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or

dermatitis.

**Carcinogenicity**: Suspected of causing cancer. Risk of cancer depends on duration and level of

exposure.

Mutagenicity: No known significant effects or critical hazards.Reproductive toxicity: No known significant effects or critical hazards.

#### **Additional information**

Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Contains isothiazolinones. May cause allergic reaction. Avoid contact with skin and clothing.

Korea (GHS) Page: 8/13

Product code 00191490	Date of issue 7/12/2023 (month/day/year)	Version 12.02
<b>Product name PPG AQUACOVER 45 (TINTED</b>	0)	

## Section 11. Toxicological information

ranium dioxide (2-methoxymethylethoxy)propanol tetraamminezinc(2+) carbonate  propylidynetrimethanol ammonia	CAS: 13463-67-7 CAS: 34590-94-8 CAS: 38714-47-5 CAS: 77-99-6 CAS: 1336-21-6	CARCINOGENICITY - Category 2 FLAMMABLE LIQUIDS - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1 TOXIC TO REPRODUCTION - Category 2
tetraamminezinc(2+) carbonate propylidynetrimethanol	CAS: 38714-47-5  CAS: 77-99-6	SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1 TOXIC TO REPRODUCTION - Category 2
propylidynetrimethanol	CAS: 77-99-6	EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1 TOXIC TO REPRODUCTION - Category 2
1		SKIN SENSITIZATION - Category 1 AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1 TOXIC TO REPRODUCTION - Category 2
1		AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1 TOXIC TO REPRODUCTION - Category 2
1		AQUATIC HAZARD (LONG-TERM) - Category 1 TOXIC TO REPRODUCTION - Category 2
1		TOXIC TO REPRODUCTION - Category 2
1		
ammonia	CAS: 1336-21-6	T CEDIOTIC EVE DAMACE Cotogory 1
		SERIOUS EYE DAMAGE - Category 1
		SPECIFIC TARGET ORGAN TOXICITY (SINGLE
		EXPOSURE) (Respiratory tract irritation) -
1		Category 3
4,5-Dichloro-2-N-octyl-4-isothizaolin-	CAS: 64359-81-5	AQUATIC HAZARD (ACUTE) - Category 1 ACUTE TOXICITY (oral) - Category 4
3-one	CAS. 04339-01-3	ACOTE TOXICITY (Grai) - Category 4
3-one		ACUTE TOXICITY (dermal) - Category 3
		ACUTE TOXICITY (inhalation) - Category 2
		AQUATIC HAZARD (ACUTE) - Category 1
		AQUATIC HAZARD (LONG-TERM) - Category 1
3-iodo-2-propynyl butylcarbamate	CAS: 55406-53-6	ACUTE TOXICITY (oral) - Category 4
a atam athy day relatatra ailay an a	CAC, 556 67 0	
octamethylcyclotetrasiloxane	CAS. 550-67-2	
zinc pyrithione	CAS: 13463-41-7	
Zano pyridilorio	J. 10-100-41-1	
		SPECIFIC TARGET ORGAN TOXICITY
		(REPEATED EXPOSURE) - Category 1
		AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1
3-iodo-2-propynyl butylcarbamate  octamethylcyclotetrasiloxane  zinc pyrithione	CAS: 55406-53-6  CAS: 556-67-2  CAS: 13463-41-7	SKIN CORROSION - Category 1 SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1 AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1 ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (inhalation) - Category 2 SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1B SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1 AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1 FLAMMABLE LIQUIDS - Category 3 TOXIC TO REPRODUCTION - Category 2 AQUATIC HAZARD (LONG-TERM) - Category 1 ACUTE TOXICITY (oral) - Category 3 ACUTE TOXICITY (inhalation) - Category 2 SERIOUS EYE DAMAGE - Category 1 TOXIC TO REPRODUCTION - Category 2 SPECIFIC TARGET ORGAN TOXICITY

# Section 12. Ecological information

A. **Ecotoxicity** 

Korea (GHS) Page: 9/13

Product code 00191490	Date of issue 7/12/2023 (month/day/year)	Version 12.02
Product name PPG AQUACOVER 45 (TINTED)	)	

## Section 12. Ecological information

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute LC50 >100 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
(2-methoxymethylethoxy) propanol	Acute EC50 1919 mg/l	Daphnia	48 hours
propylidynetrimethanol	Acute LC50 >1000 mg/l	Fish	96 hours
4,5-Dichloro-2-N-octyl- 4-isothizaolin-3-one	Acute EC50 267.368 µg/l Marine water	Algae - Nitzschia pungens	96 hours
	Acute LC50 0.318 mg/l Marine water	Crustaceans - Artemia sp.	48 hours
	Acute LC50 0.0027 mg/l Fresh water	Fish	96 hours
	Chronic NOEC 19.789 µg/l Marine water	Algae - <i>Nitzschia pungens</i>	96 hours
	Chronic NOEC 0.00056 mg/l Fresh water	Fish	97 days
3-iodo-2-propynyl butylcarbamate	Acute EC50 0.186 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 0.067 mg/l	Fish	96 hours
	Chronic NOEC 0.049 mg/l	Fish	96 hours
zinc pyrithione	Acute EC50 5.513 µg/l Marine water	Algae - Nitzschia pungens	96 hours
	Acute LC50 0.0082 mg/l	Daphnia	48 hours
	Chronic NOEC 1.889 µg/l Marine water	Algae - <i>Nitzschia pungens</i>	96 hours
	Chronic NOEC 0.0027 mg/l	Daphnia	21 days

#### B. Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
3-iodo-2-propynyl butvlcarbamate	-	25 % - Inherent - 28 days	-	-
zinc pyrithione	-	39 % - 28 days	-	-

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
3-iodo-2-propynyl butylcarbamate	-	-	Inherent
zinc pyrithione	-	50%; < 28 day(s)	Not readily

#### C. Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
-methoxymethylethoxy)	0.004	-	Low
propanol			
propylidynetrimethanol	-0.47	-	Low
octamethylcyclotetrasiloxane	6.488	-	High
zinc pyrithione	0.9	0.9	Low

#### D. Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

E. Other adverse effects : No known significant effects or critical hazards.

Korea (GHS) Page: 10/13

Date of issue 7/12/2023 (month/day/year) Version 12.02

**Product name PPG AQUACOVER 45 (TINTED)** 

## Section 13. Disposal considerations

#### A. Disposal methods

Product code 00191490

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

#### **B.** Disposal precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## **Section 14. Transport information**

	UN	IMDG	IATA
A. UN number	UN3082	UN3082	UN3082
B. UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
	(tetraamminezinc(2+) carbonate)	(tetraamminezinc(2+) carbonate)	(tetraamminezinc(2+) carbonate)
C. Transport hazard class(es)	9	9	9
D. Packing group	III	III	III
Environmental hazards	Yes.	Yes.	Yes.
E. Marine pollutant substances	Not applicable.	(tetraamminezinc(2+) carbonate)	Not applicable.

#### **Additional information**

UN : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg,

provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

**IMDG** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg,

provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

IATA : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg,

provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

# F. Special precaution which a user to be aware of or needs to comply with in connection with transport or transportation

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Korea (GHS) Page: 11/13

**Product name PPG AQUACOVER 45 (TINTED)** 

## Section 15. Regulatory information

#### A. Regulation according to ISHA

ISHA article 117 (Harmful substances prohibited from manufacture) : None of the components are listed.

ISHA article 118 (Harmful substances requiring permission) : None of the components are listed.

Article 2 of Youth Protection Act on Substances Hazardous

: It is not allowed to sell to persons under the age of 19.

to Youth

#### **Exposure Limits of Chemical Substances and Physical Factors**

The following components have an OEL:

titanium dioxide

(2-methoxymethylethoxy)propanol

ammonia

**ISHA Enforcement Regs**: None of the components are listed.

Annex 19 (Exposure standards established for harmful factors)

ISHA Enforcement Regs : The following components are listed: titanium dioxide

Annex 21 (Harmful factors subject to Work

**Environment Measurement**)

ISHA Enforcement Regs : None of the components are listed.

Annex 22 (Harmful Factors Subject to Special Health Check-

up)

Standard of Industrial : The following components are listed: titanium dioxide

Safety and Health

Safety and Health Annex 12 (Hazardous substances subject to control)

B. Regulation according to Chemicals Control Act

Article 11 (TRI) : None of the components are listed.

Article 18 Prohibited (K- : None of the components are listed.

Reach Article 27)

: None of the components are listed.

Article 19 Subject to authorization (K-Reach

Article 25)

Article 20 Restricted (K-Reach Article 27)

cted (K- : None of the components are listed.

Article 20 Toxic : Not applicable

Chemicals (K-Reach

Article 20)

**Korea inventory** : At least one component is not listed.

Korea (GHS) Page: 12/13

**Product name PPG AQUACOVER 45 (TINTED)** 

### **Section 15. Regulatory information**

**Article 39 (Accident Precaution Chemicals)** 

: None of the components are listed.

C. <u>Dangerous Materials</u> <u>Safety Management Act</u>

: Class: Class 4 - Flammable Liquid

Item: 5. Class 3 petroleums - Water soluble liquid

Threshold: 4000 L Danger category: III

Signal word: Contact with sources of ignition prohibited

D. <u>Wastes regulation</u>: Dispose of c

: Dispose of contents and container in accordance with all local, regional, national

and international regulations.

E. Regulation according to other foreign laws

Safety, health and environmental regulations specific for the product : No known specific national and/or regional regulations applicable to this product (including its ingredients).

#### Section 16. Other information

A. References : Korean Ministry of Environment; Chemical Control Act

Korean Ministry of Labor; Industrial Safety and Health Act

**NIER Notice** 

Registry of Toxic Effects of Chemical Substances (RTECS)

U.S. Environmental Protection Agency, AQUIRE (Aquatic toxicity Information

Retrieval) ECOTOX Database System.

B. Date of issue/Date of

revision

: 7/12/2023

C. Version : 12.02
Prepared by : EHS

D. Other

**▼** Indicates information that has changed from previously issued version.

#### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

Korea (GHS) Page: 13/13