# SAFETY DATA SHEET

Date of issue/Date of revision : 25 July 2023 **Version** : 2.02



# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

**Product name** : SIGMASHIELD 1090 HARDENER 0.4G

**Product code** : 00197525

Other means of identification

Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Professional applications, Used by spraying.

Use of the substance/

mixture

: Coating.

: Product is not intended, labelled or packaged for consumer use. **Uses advised against** 

1.3 Details of the supplier of the safety data sheet

Sigma Paint Saudi Arabia Ltd.

PO Box 7509 **Dammam 31472** Saudi Arabia

Tel: 00966 138 47 31 00 Fax: 00966 138 47 17 34

e-mail address of person responsible for this SDS

: ndpic@sfda.gov.sa

1.4 Emergency telephone

number

: 00966 138473100 extn 1001

# **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

: Mixture **Product definition** 

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Repr. 2, H361 **STOT RE 2, H373** 

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

Code : 00197525 Date of issue/Date of revision : 25 July 2023

SIGMASHIELD 1090 HARDENER 0.4G

# **SECTION 2: Hazards identification**

**Hazard pictograms** 







Signal word : Danger

**Hazard statements**: Harmful if swallowed.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure.

Harmful to aquatic life with long lasting effects.

**Precautionary statements** 

**Prevention**: Wear protective gloves, protective clothing and eye or face protection. Do not breathe

vapour.

Response : IF INHALED: Immediately call a POISON CENTER or doctor. IF SWALLOWED:

Immediately call a POISON CENTER or doctor. IF ON SKIN (or hair): Take off

immediately all contaminated clothing. Rinse skin with water.

Storage : Not applicable.

Disposal : Dispose of contents and container in accordance with all local, regional, national and

international regulations.

7280, P260, P304 + P310, P301 + P310, P303 + P361 + P353, P501

Hazardous ingredients : 3-aminomethyl-3,5,5-trimethylcyclohexylamine

2-piperazin-1-ylethylamine 2,2'-iminodiethylamine

Supplemental label

elements

articles

: Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and : Not applicable.

**Special packaging requirements** 

**Containers to be fitted** 

with child-resistant

: Not applicable.

fastenings

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria

for PBT or vPvB

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification

: None known.

Code : 00197525 Date of issue/Date of revision : 25 July 2023

SIGMASHIELD 1090 HARDENER 0.4G

# **SECTION 3: Composition/information on ingredients**

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
<b>3</b> -aminomethyl- 3,5,5-trimethylcyclohexylamine	REACH #: 01-2119514687-32 EC: 220-666-8 CAS: 2855-13-2 Index: 612-067-00-9	≥25 - ≤50	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317	ATE [Oral] = 1030 mg/ kg Skin Sens. 1, H317: C ≥ 0.001%	[1]
Poly[oxy(methyl- 1,2-ethanediyl)], α- (2-aminomethylethyl)-ω- (2-aminomethylethoxy)-	REACH #: 01-2119557899-12 EC: 618-561-0 CAS: 9046-10-0 (n = 2-6)	≥25 - ≤50	Skin Corr. 1C, H314 Eye Dam. 1, H318 Aquatic Chronic 3, H412	-	[1]
2-piperazin-1-ylethylamine	REACH #: 01-2119471486-30 EC: 205-411-0 CAS: 140-31-8 Index: 612-105-00-4	≥5.0 - <10	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Repr. 2, H361 (oral) STOT RE 1, H372 (respiratory tract) (inhalation) Aquatic Chronic 3, H412	ATE [Oral] = 500 mg/ kg ATE [Dermal] = 1100 mg/kg	[1]
2,2'-iminodiethylamine	REACH #: 01-2119473793-27 EC: 203-865-4 CAS: 111-40-0 Index: 612-058-00-X	≤0.30	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335 See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 1080 mg/kg ATE [Dermal] = 1090 mg/kg ATE [Inhalation (dusts and mists)] = 0.05 mg/l	[1] [2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Code : 00197525 Date of issue/Date of revision : 25 July 2023

SIGMASHIELD 1090 HARDENER 0.4G

# **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

**Eye contact**: Check for and remove any contact lenses. Immediately flush eyes with running water for

at least 15 minutes, keeping eyelids open. Seek immediate medical attention.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained

personnel.

**Skin contact**: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water

or use recognised skin cleanser. Do NOT use solvents or thinners.

**Ingestion**: If swallowed, seek medical advice immediately and show the container or label. Keep

person warm and at rest. Do NOT induce vomiting.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is

suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water

before removing it, or wear gloves.

# 4.2 Most important symptoms and effects, both acute and delayed

#### Potential acute health effects

**Eye contact** : Causes serious eye damage.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact**: Causes severe burns. May cause an allergic skin reaction.

**Ingestion**: Harmful if swallowed.

# Over-exposure signs/symptoms

**Eye contact** : Adverse symptoms may include the following:

pain watering redness

**Inhalation** : Adverse symptoms may include the following:

reduced foetal weight increase in foetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur reduced foetal weight increase in foetal deaths skeletal malformations

**Ingestion** : Adverse symptoms may include the following:

stomach pains

reduced foetal weight increase in foetal deaths skeletal malformations

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments**: No specific treatment.

Code : 00197525 Date of issue/Date of revision : 25 July 2023

SIGMASHIELD 1090 HARDENER 0.4G

# **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing** media

: None known.

# 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous combustion** products

Decomposition products may include the following materials: carbon oxides nitrogen oxides

#### 5.3 Advice for firefighters

Special precautions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective** equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

# SECTION 6: Accidental release measures

# 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

### 6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### 6.3 Methods and material for containment and cleaning up

**Small spill** 

Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

# Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

> English (GB) **United Arab Emirates** 5/14

Code : 00197525 Date of issue/Date of revision : 25 July 2023

SIGMASHIELD 1090 HARDENER 0.4G

# **SECTION 6: Accidental release measures**

6.4 Reference to other sections

: See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

# **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

# 7.1 Precautions for safe handling

**Protective measures** 

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

#### 7.3 Specific end use(s)

See Section 1.2 for Identified uses.

# **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

# 8.1 Control parameters

#### Occupational exposure limits

No exposure limit value known.

Recommended monitoring procedures

Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

English (GB) United Arab Emirates 6/14

Code : 00197525 Date of issue/Date of revision : 25 July 2023

SIGMASHIELD 1090 HARDENER 0.4G

#### 8.2 Exposure controls

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

# Eye/face protection Skin protection Hand protection

: Chemical splash goggles and face shield.

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

**Gloves** 

butyl rubber

**Body protection** 

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

. .

**Environmental exposure** controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

# **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

**Appearance** 

Physical state : Liquid.

Colour : Colourless.

Odour : Characteristic.

Odour threshold : Not available.

Melting point/freezing point

: May start to solidify at the following temperature: 8°C (46.4°F) This is based on data for the following ingredient: 3-aminomethyl-3,5,5-trimethylcyclohexylamine.

Weighted average: 2.38°C (36.3°F)

Initial boiling point and

boiling range

: >37.78°C

**Flammability** 

: Not available.

English (GB) United Arab Emirates 7/14

Code : 00197525 Date of issue/Date of revision : 25 July 2023

SIGMASHIELD 1090 HARDENER 0.4G

# SECTION 9: Physical and chemical properties

Upper/lower flammability or

explosive limits

: Greatest known range: Lower: 1.1% Upper: 9.4% (2-piperazin-1-ylethylamine)

Flash point

: Closed cup: 234°C

**Auto-ignition temperature** 

Ingredient name	°C	°F	Method
piperazin-1-ylethylamine	>300	>572	

**Decomposition temperature** 

: Stable under recommended storage and handling conditions (see Section 7).

pН **Viscosity**  Not applicable, insoluble in water. Kinematic (40°C): >21 mm<sup>2</sup>/s

Solubility(ies)

Media Result cold water Not soluble

Partition coefficient: n-octanol/ : Not applicable.

water

Vapour pressure

Ingredient neme	Vapour Pressure at 20°C		Vapour pressure at 5		ire at 50°C	
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
<mark>w</mark> áter	17.5	2.3				

**Evaporation rate** : 0.007 (2-piperazin-1-ylethylamine) compared with butyl acetate

**Relative density** : 0.95

Vapour density : Highest known value: 4.4 (Air = 1) (2-piperazin-1-ylethylamine).

The product itself is not explosive, but the formation of an explosible mixture of **Explosive properties** 

: Product does not present an oxidizing hazard.

vapour or dust with air is possible.

**Oxidising properties** 

Particle characteristics

: Not applicable. Median particle size

9.2 Other information

No additional information.

# SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

: The product is stable. 10.2 Chemical stability

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products.

Refer to protective measures listed in sections 7 and 8.

10.5 Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions:

oxidising agents, strong alkalis, strong acids.

10.6 Hazardous decomposition products Depending on conditions, decomposition products may include the following materials:

carbon oxides nitrogen oxides

English (GB) United Arab Emirates 8/14

Code : 00197525 Date of issue/Date of revision : 25 July 2023

SIGMASHIELD 1090 HARDENER 0.4G

# **SECTION 11: Toxicological information**

# 11.1 Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
3-aminomethyl-	LC50 Inhalation Dusts and	Rat	>5.01 mg/l	4 hours
3,5,5-trimethylcyclohexylamine	mists			
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	1030 mg/kg	-
Poly[oxy(methyl-1,2-ethanediyl)], α- (2-aminomethylethyl)-ω- (2-aminomethylethoxy)-	LD50 Dermal	Rat	2980 mg/kg	-
	LD50 Oral	Rat	2885 mg/kg	_
2-piperazin-1-ylethylamine	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours
	LD50 Dermal	Rabbit	866 mg/kg	-
	LD50 Oral	Rat	2140 mg/kg	-
2,2'-iminodiethylamine	LC50 Inhalation Dusts and	Rat	0.07 to 0.3 mg/l	4 hours
,	mists			
	LD50 Dermal	Rabbit	1090 mg/kg	-
	LD50 Oral	Rat	1080 mg/kg	-

Conclusion/Summary

: There are no data available on the mixture itself.

Irritation/Corrosion

**Conclusion/Summary** 

Skin : There are no data available on the mixture itself.
 Eyes : There are no data available on the mixture itself.
 Respiratory : There are no data available on the mixture itself.

**Sensitisation** 

Product/ingredient name	Route of exposure	Species	Result
3-aminomethyl-3,5,5-trimethylcyclohexylamine 2-piperazin-1-ylethylamine	skin	Guinea pig	Sensitising
	skin	Guinea pig	Sensitising

**Conclusion/Summary** 

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

**Mutagenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Carcinogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Reproductive toxicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Teratogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
2,2'-iminodiethylamine	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

English (GB)	United Arab Emirates	9/14

Code : 00197525 Date of issue/Date of revision : 25 July 2023

SIGMASHIELD 1090 HARDENER 0.4G

# **SECTION 11: Toxicological information**

Product/ingredient name	Category	Route of exposure	Target organs
2-piperazin-1-ylethylamine	Category 1	inhalation	respiratory tract

# **Aspiration hazard**

Not available.

Information on likely

: Not available.

routes of exposure

Potential acute health effects

**Inhalation** : No known significant effects or critical hazards.

**Ingestion**: Harmful if swallowed.

**Skin contact**: Causes severe burns. May cause an allergic skin reaction.

**Eye contact** : Causes serious eye damage.

Symptoms related to the physical, chemical and toxicological characteristics

**Inhalation** : Adverse symptoms may include the following:

reduced foetal weight increase in foetal deaths skeletal malformations

**Ingestion** : Adverse symptoms may include the following:

stomach pains reduced foetal weight increase in foetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur reduced foetal weight increase in foetal deaths skeletal malformations

**Eye contact** : Adverse symptoms may include the following:

pain watering redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Short term exposure** 

Potential immediate :

: Not available.

effects

Potential delayed effects: Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects: Not available.

Potential chronic health effects

Not available.

**Conclusion/Summary**: Not available.

General : May cause damage to organs through prolonged or repeated exposure. Once

sensitized, a severe allergic reaction may occur when subsequently exposed to very low

levels.

**Carcinogenicity**: No known significant effects or critical hazards.

English (GB) United Arab Emirates 10/14

Code : 00197525 Date of issue/Date of revision : 25 July 2023

SIGMASHIELD 1090 HARDENER 0.4G

# **SECTION 11: Toxicological information**

Mutagenicity : No known significant effects or critical hazards.Reproductive toxicity : Suspected of damaging fertility or the unborn child.

Other information : Not available.

None known.

#### 11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

# **SECTION 12: Ecological information**

#### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Foly[oxy(methyl-1,2-ethanediyl)], α- (2-aminomethylethyl)-ω-(2-aminomethylethoxy)-	EC50 15 mg/l	Algae	72 hours
2-piperazin-1-ylethylamine 2,2'-iminodiethylamine	Acute EC50 58 mg/l Acute LC50 430 mg/l	Daphnia Fish	48 hours 96 hours

**Conclusion/Summary**: There are no data available on the mixture itself.

### 12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
<ul><li>✓piperazin-1-ylethylamine</li><li>2,2'-iminodiethylamine</li></ul>		0 % - Not readily - 28 days 87 % - Readily - 21 days	-	-

**Conclusion/Summary**: There are no data available on the mixture itself.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Poly[oxy(methyl-1,2-ethanediyl)], α-	-	-	Not readily
(2-aminomethylethyl)-ω-(2-aminomethylethoxy)-			
2-piperazin-1-ylethylamine	-	-	Not readily
2,2'-iminodiethylamine	-	-	Readily

### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
3-aminomethyl-3,5,5-trimethylcyclohexylamine	0.99	-	Low
2-piperazin-1-ylethylamine	-1.48	-	Low
2,2'-iminodiethylamine	-5.58	4.47	Low

# **12.4 Mobility in soil**

Soil/water partition : Not available.

coefficient (Koc)

Mobility : Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

### 12.6 Endocrine disrupting properties

Not available.

English (GB)	United Arab Emirates	11/14

Code : 00197525 Date of issue/Date of revision : 25 July 2023

SIGMASHIELD 1090 HARDENER 0.4G

# **SECTION 12: Ecological information**

#### 12.7 Other adverse effects

No known significant effects or critical hazards.

# **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### **Product**

**Methods of disposal** 

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** 

Yes.

### **European waste catalogue (EWC)**

Waste code	Waste designation	
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	

### **Packaging**

**Methods of disposal** 

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)	
Container	15 01 06	mixed packaging

**Special precautions** 

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

# **SECTION 14: Transport information**

	ADR/RID	IMDG	IATA
14.1 UN number or ID number	UN3066	UN3066	UN3066
14.2 UN proper shipping name	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	8	8	8
14.4 Packing group	II	II	II
14.5 Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

#### **Additional information**

ADR/RID : None identified.

Tunnel code : (€)

English (GB) United Arab Emirates 12/14

Code : 00197525 Date of issue/Date of revision : 25 July 2023

SIGMASHIELD 1090 HARDENER 0.4G

# **SECTION 14: Transport information**

: None identified. **IMDG IATA** : None identified.

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the

event of an accident or spillage.

14.7 Transport in bulk according to IMO

: Not applicable.

instruments

# SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

**Annex XIV** 

None of the components are listed.

Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions** : Not applicable.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Other national and international regulations.

Ozone depleting substances (1005/2009/EU)

Not listed.

15.2 Chemical safety

: No Chemical Safety Assessment has been carried out.

assessment

# SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and

acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

Full text of abbreviated H

statements

: H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

Fatal if inhaled. H330

H335 May cause respiratory irritation.

H361 Suspected of damaging fertility or the unborn child.

Causes damage to organs through prolonged or repeated exposure. H372 May cause damage to organs through prolonged or repeated exposure. H373

H412 Harmful to aquatic life with long lasting effects.

> English (GB) United Arab Emirates 13/14

Code : 00197525 Date of issue/Date of revision : 25 July 2023

SIGMASHIELD 1090 HARDENER 0.4G

# **SECTION 16: Other information**

Full text of classifications [CLP/GHS]

ACUTE TOXICITY - Category 2
Acute Tox. 4

ACUTE TOXICITY - Category 4

Aquatic Chronic 3 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 Eye Dam. 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1

Repr. 2 REPRODUCTIVE TOXICITY - Category 2
Skin Corr. 1B SKIN CORROSION/IRRITATION - Category 1B
Skin Corr. 1C SKIN CORROSION/IRRITATION - Category 1C

Skin Sens. 1 SKIN SENSITISATION - Category 1
Skin Sens. 1A SKIN SENSITISATION - Category 1A

STOT RE 1 SPECIFIC TARGET ORGAN TOXICITY - REPEATED

EXPOSURE - Category 1

STOT RE 2 SPECIFIC TARGET ORGAN TOXICITY - REPEATED

EXPOSURE - Category 2

STOT SE 3 SPECIFIC TARGET ORGAN TOXICITY - SINGLE

**EXPOSURE - Category 3** 

**History** 

Date of issue/ Date of : 25 July 2023

revision

Date of previous issue : 31 January 2022

Prepared by : EHS Version : 2.02

#### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

English (GB) United Arab Emirates 14/14