SAFETY DATA SHEET

Date of issue/Date of revision

: 29 August 2023

Version : 9.04

pPG

France

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1	Prod	luct id	lentifier

Product name	: SIGMAZINC 158/SIGMAGUARD 750 PIGMENT
Product code	: 00140360
Other means of identified	cation
Not available.	

1.2 Relevant identified uses	of the substance or mixture and uses advised against
Product use	: Professional applications, Used by spraying.
Use of the substance/ mixture	: Coating.
Uses advised against	: Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL Tweemontstraat 104 B-2100 Deurne Belgium Telephone +32-33606311 Fax +32-33606435

e-mail address of person : Product.Stewardship.EMEA@ppg.com responsible for this SDS

1.4 Emergency telephone number

National advisory body/Poison Centre

Numéro de téléphone d'appel d'urgence : 01 45 42 59 59 (Association ORFILA, organisme agréé prévu au 4ème alinéa de l'article L231-7 du code du travail)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture <u>Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]</u> Aquatic Acute 1, H400

Aquatic Chronic 1, H410

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

English (GB)

2020/878	······································
Code : 00140360 SIGMAZINC 158/SIGMAGUA	Date of issue/Date of revision : 29 August 2023 D 750 PIGMENT
SECTION 2: Hazards	identification
Hazard pictograms	
Signal word	: Warning
Hazard statements	: Very toxic to aquatic life with long lasting effects.
Precautionary statements	
Prevention	: Avoid release to the environment.
Response	: Collect spillage.
Storage	: Not applicable.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
	P273, P391, P501
Hazardous ingredients	: Not applicable.
Supplemental label elements	: Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Special packaging requirem	ents
Containers to be fitted with child-resistant fastenings	: Not applicable.
Tactile warning of danger	: Not applicable.
2.3 Other hazards	
Product meets the criteria for PBT or vPvB	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: May form explosible dust-air mixture if dispersed. Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes, skin, nose and throat.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

: Mixture

Code : 00140360 Date of issue/Date of revision

: 29 August 2023

SIGMAZINC 158/SIGMAGUARD 750 PIGMENT

SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	% by weight	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
zinc powder zinc dust (stabilised)	REACH #: 01-2119467174-37 EC: 231-175-3 CAS: 7440-66-6 Index: 030-001-01-9	≥90	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1]
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

an Booonption of mot and m	
Eye contact	: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

English (CD)	France 2/44
Skin contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Eye contact	: Adverse symptoms may include the following: irritation redness
Over-exposure signs/s	<u>ymptoms</u>
Ingestion	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Inhalation	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
Eye contact	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.
Potential acute health	<u>effects</u>

Code : 00140360 SIGMAZINC 158/SIGMAGUA	Date of issue/Date of revision : 29 August 2023
SECTION 4: First aid	
Ingestion	: No specific data.
4.3 Indication of any immed	iate medical attention and special treatment needed
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
SECTION 5: Firefigh	iting measures
5.1 Extinguishing media	
Suitable extinguishing media	: Use dry chemical powder.
Unsuitable extinguishing media	: Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.
5.2 Special hazards arising	from the substance or mixture
Hazards from the substance or mixture	: May form explosible dust-air mixture if dispersed. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	: Decomposition products may include the following materials: metal oxide/oxides
5.3 Advice for firefighters	
Special precautions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
On a stat whether stines	

Special protective	1	Fire-fighters should wear appropriate protective equipment and self-contained breathing
equipment for fire-fighters		apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing
		for fire-fighters (including helmets, protective boots and gloves) conforming to European
		standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and material for containment and cleaning up

Code : 00140360 SIGMAZINC 158/SIGMAG	Date of issue/Date of revision : 29 August 2023 UARD 750 PIGMENT : 29 August 2023
SECTION 6: Accid	ental release measures
Small spill	: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor.
Large spill	: Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labelled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other	: See Section 1 for emergency contact information.

See Section 13 for additional waste treatment information.

See Section 8 for information on appropriate personal protective equipment.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

sections

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing dust. Avoid release to the environment. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
7.2 Conditions for safe storage, including any incompatibilities	: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s) See Section 1.2 for Identified uses.

Code	: 00140360	Date of issue/Date of revision	: 29 August 2023
SIGMAZIN	C 158/SIGMAGUARD 750 PIGMENT		

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Recommended monitoring

Reference should be made to monitoring standards, such as the following: European 12 Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure procedures by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
zinc powder zinc dust (stabilised)	DNEL	Long term Oral	0.83 mg/kg bw/day	General population	Systemic
	DNEL DNEL DNEL DNEL	Long term Inhalation Long term Inhalation Long term Dermal Long term Dermal	2.5 mg/m ³ 5 mg/m ³ 83 mg/kg bw/day 83 mg/kg bw/day	General population Workers General population Workers	Systemic

PNECs

Product/ingredient name	Туре	Compartment Detail	Value	Method Detail
zinc powder zinc dust (stabilised)	- -	Marine water Sewage Treatment Plant Fresh water sediment Marine water sediment	20.6 μg/l 6.1 μg/l 100 μg/l 118 mg/kg dwt 56.5 mg/kg dwt 35.6 mg/kg dwt	Sensitivity Distribution Sensitivity Distribution Assessment Factors Sensitivity Distribution Equilibrium Partitioning Sensitivity Distribution

8.2 Exposure controls Appropriate engineering controls	: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Individual protection measured	<u>res</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection Skin protection	: Safety glasses with side shields. Use eye protection according to EN 166.
Hand protection	:

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (E	U)
2020/878	

: 00140360 Code

SIGMAZINC 158/SIGMAGUARD 750 PIGMENT

Date of issue/Date of revision

: 29 August 2023

SECTION 8: Exposure controls/personal protection

	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Gloves	: nitrile rubber, butyl rubber, PVC, Viton®
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: P3
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

	-	- 14 4
Decomposition temperature	: Stable under recommended storage and handling conditions (see Section 7).	
Auto-ignition temperature	: Not applicable.	
Flash point	: Closed cup: Not applicable.	
Minimum explosive concentration (MEC)	: 10 g/m ³	
Flammability	: Not available.	
Initial boiling point and boiling range	: Not available.	
Melting point/freezing point	: Not available.	
Odour threshold	: Not available.	
Odour	: Aromatic.	
Colour	: Not available.	
Product type	: Powder.	
Physical state	: Solid.	
<u>Appearance</u>		

2020/878						
Code : 00140360		Date of issue/Date of revision	: 29 August 2023			
SIGMAZINC 158/SIGMAGUARD 750 PIGMENT						
SECTION 9: Physica	l and chemica	l properties				
рН	: Not applicabl	le. insoluble in water.				
Viscosity	: Kinematic (40	0°C): Not applicable.				
Solubility(ies)	:					
Media	Result					
cold water	Not soluble	e				
Partition coefficient: n-octa water	nol/ : Not applicabl	le.				
Vapour pressure	: Not available	2.				
Evaporation rate	: Not available	ð.				
Relative density	: 7.1					
Explosive properties : The product its		itself is not explosive, but the formation	of an explosible mixture of			

	vapour or dust with air is possible.
Oxidising properties	: Product does not present an oxidizing hazard.
Particle characteristics	
Median particle size	: 10 - 100 μm
9.2 Other information	

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
10.6 Hazardous decomposition products	: Evolves hydrogen on contact with water. Depending on conditions, decomposition products may include the following materials: metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
zinc powder zinc dust (stabilised)	LC50 Inhalation Dusts and mists	Rat	>5.4 mg/l	4 hours
	LD50 Oral	Rat	>2000 mg/kg	-
Conclusion/Summary : There are no data available on the mixture itself.				

Irritation/Corrosion

Conclusion/Summary

Skin

: There are no data available on the mixture itself.

English (GB)

France

Code : 00140360	Date of issue/Date of revision : 29 August 2023
SIGMAZINC 158/SIGMAGU	ARD 750 PIGMENT
SECTION 11: Toxic	ological information
Eyes	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
Sensitisation	
Conclusion/Summary	
Skin	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
Mutagenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Carcinogenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Reproductive toxicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Teratogenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Specific target organ toxi	<u>city (single exposure)</u>
Not available.	
Specific target organ toxi	city (repeated exposure)
Not available.	
Aspiration hazard	
Not available.	
NOT available.	
Information on likely	: Not available.
routes of exposure	
Potential acute health effe	
Inhalation	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
Ingestion	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Eye contact	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.
Symptoms related to the	physical, chemical and toxicological characteristics
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Ingestion	: No specific data.
Skin contact	: No specific data.
Eye contact	: Adverse symptoms may include the following: irritation redness
Delayed and immediate of	ffects as well as chronic effects from short and long-term exposure
Short term exposure	neers as wen as chronic eneers nom short and long-term exposure
Potential immediate effects	: Not available.
	te : Not available
Potential delayed effect	
Long term exposure	

020/878		Dete of issue/Dete of revision	
Code : 00140360 SIGMAZINC 158/SIGMAGUAF	RD 750 PIGMENT	Date of issue/Date of revision	: 29 August 2023
SECTION 11: Toxico		ation	
Potential immediate effects	: Not available.		
Potential delayed effects	: Not available.		
Potential chronic health effe	ects		
Not available.			
Conclusion/Summary	: Not available.		
General	: Repeated or prol	longed inhalation of dust may lead to ch	nronic respiratory irritation
Carcinogenicity	: No known signific	cant effects or critical hazards.	
Mutagenicity	: No known signific	cant effects or critical hazards.	
Reproductive toxicity	: No known signific	cant effects or critical hazards.	
Other information	: Not available.		
Sanding and grinding dusts m	ay be harmful if inha	led.	
11.2 Information on other ha	zards		
11.2.1 Endocrine disrupting	properties		
Not available.			
11.2.2 Other information			
Notavailable			

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Źnc powder zinc dust (stabilised)	Acute EC50 0.106 mg/l Fresh water Chronic NOEC 0.0727 mg/l Fresh water	Algae - Pseudokirchneriella subcapitata Daphnia - Daphnia Magna	72 hours 21 days

Conclusion/Summary

: There are no data available on the mixture itself.

12.2 Persistence and degradability

Conclusion/Summary : There are no data available on the mixture itself.

12.3 Bioaccumulative potential

Not available.

12.4 Mobility in soil	
Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

English ((GB)
	~~_/

Code	: 00140360	Date of issue/Date of revision	: 29 August 2023
SIGMAZINC	158/SIGMAGUARD 750 PIGMENT		

SECTION 12: Ecological information

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hozordovo wooto	. Within the present knowledge of the supplier, this product is not regarded as bezordeus

Within the present knowledge of the supplier, this product is not regarded as hazardous Hazardous waste waste, as defined by EU Directive 2008/98/EC.

European waste catalogue (EWC)

Waste code	Waste designation		
08 02 01	waste coating powders		
Packaging Mothods of disposal	. The generation of waste should be availed or minimized wherever pessible. Waste		

Methods of disposal

The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)	
Container	15 01 06 mixed packaging	
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.	

14. Transport information

•				
	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN3077	UN3077	UN3077	UN3077
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
	(Zinc powder - zinc dust (stabilized))	(Zinc powder - zinc dust (stabilized))	(Zinc powder - zinc dust (stabilized))	(Zinc powder - zinc dust (stabilized))
14.3 Transport hazard class(es)	9	9	9	9
14.4 Packing group	111			
English (G	 B)	Fra	nce	11/14

Code	: 00140360	Date of issue/Date of revision	: 29 August 2023
SIGMAZINC	158/SIGMAGUARD 750 PIGMENT		

14. Transport information

_				
14.5	Yes.	Yes.	Yes.	Yes.
Environmental hazards				
Marine pollutant substances	Not applicable.	Not applicable.	(Zinc powder - zinc dust (stabilized))	Not applicable.

Additional information

ADR/RID	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
Tunnel code	: (-)
ADN	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
IMDG	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. The segregation group has been manually assigned based upon product analysis.
ΙΑΤΑ	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.
14.6 Special pre user	cautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
14.7 Maritime tra bulk according t	

instruments

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH) Annex XIV - List of substances subject to authorisation **Annex XIV** None of the components are listed. Substances of very high concern None of the components are listed. Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable. **Explosive precursors** Ozone depleting substances (1005/2009/EU) Not listed. **Seveso Directive** This product is controlled under the Seveso Directive. **Danger criteria** Category E1

English (GB)

12/14

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation ((EU)
2020/878	

Code : 00140360	Date of issue/Date of revision : 29 August 2023					
SIGMAZINC 158/SIGMAGUARD 750 PIGMENT						
SECTION 15: Regulatory information						
National regulations						
	Surveillance médicale spéciale selon l'arrêté du 11 juillet 1977: Pour les applications des peintures et vernis par pulvérisation					
Reinforced medical surveillance	: Act of July 11, 1977 determining the list of activities which require reinforced medical surveillance: not applicable					

: Reinforced medical surveillance ; Decree no. 2001-97 of 1 February 2001 establishing References specific rules for the prevention of risks from carcinogens, mutagens and reprotoxics and amending the Labour code; Decree no. 2003-1254 of 23 December 2003 relating to prevention of chemical risks and amending the Labour code; Decree no. 2004-187 of 26 February 2004 on the placing on the market of biocidal products ; Decree no. 88-1231 of 29/12/1988 relating to poisonous preparations and substances. ; Decree no. 95-517 of 15 May 1997, relating to the classification of dangerous waste. ; Labour code article: R231-53 ; Labour code: Occupational air (ventilation, air purification): Art. R 232-5 to R 232-5-14 ; Labour code: Prevention of chemical risk: Art.R231-51 and R 231-54 to R 231-54-9 ; Labour code: Prevention of fires: Art.R232-12-13 to R 232-12-29 and R 233-30 ; Labour code: provisions applicable to women: Art. L 234-3 to L 236-6 ; Labour code: provisions applicable to young workers: Art. L 234-3 to L 236-6; Art: R234-16 ; Labour code: Sanitary installations: Art. R 232-2 à R 232-2-7 ; Law 76-663 of 19 July 1976 amending and implementing decree of 21 September 1977 relating to classified installations for the protection of the environment ; Tables of anticipated professional diseases according to article R461-3 of the labour code

15.2 Chemical safety

: No Chemical Safety Assessment has been carried out.

assessment

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

PBT = Persistent, Bioaccumulative and Toxic

vPvB = Very Persistent and Very Bioaccumulative

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

IMDG = International Maritime Dangerous Goods

IATA = International Air Transport Association

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Aquatic Acute 1, H400	Calculation method
Aquatic Chronic 1, H410	Calculation method

Full text of abbreviated H statements

H400	Very toxic to aquatic life.			
H410	Very toxic to aquatic life with long lasting effects.			
Full text of classifications [CLP/GHS]				
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1			
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1			

Code : 00140360 SIGMAZINC 158/SIGMAGU	IARD 750 PIGMENT	Date of issue/Date of revision	: 29 August 2023		
SECTION 16: Other information					
History					
Date of issue/ Date of revision	: 29 August 2023				
Date of previous issue	: 31 October 2022				
Prepared by	: EHS				

Version : 9.04

<u>Disclaimer</u>

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.