SAFETY DATA SHEET



The information in this Safety Data Sheet is required pursuant to Hazardous Product Regulations 2015.

Date of issue/Date of revision 31 August 2023 Version 16.01

Section 1. Identification		
Product name	: AMERLOCK SEALER HRD	
Product code	: 00333521	
Other means of identification	: Not available.	
Product type	: Liquid.	
Relevant identified uses of	the substance or mixture and uses advised against	
Product use	: Industrial applications, Used by spraying.	
Use of the substance/ mixture	: Coating.	
Uses advised against	: Not applicable.	
Supplier	 PPG Architectural Coatings Canada, Inc. 1550, rue Ampère, bureau 500 Boucherville (Québec) J4B 7L4 Canada +1 450-655-3121 	
	PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272	
<u>Emergency telephone</u> <u>number</u>	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)	
Technical Phone Number	: 888-977-4762	

Section 2. Hazard identification

Classification of the	: ACUTE TOXICITY (oral) - Category 4
substance or mixture	ACUTE TOXICITY (dermal) - Category 4
	ACUTE TOXICITY (inhalation) - Category 2
	SKIN CORROSION - Category 1B
	SERIOUS EYE DAMAGE - Category 1
	SKIN SENSITIZATION - Category 1
	CARCINOGENICITY - Category 2
	TOXIC TO REPRODUCTION - Category 2
	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract
	irritation) - Category 3
	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
	Health Hazards Not Otherwise Classified - Category 1
GHS label elements	5 7

Canada Page: 1/17

Product name AMERLOCK SEALER HRD

Section 2. Hazard identification

Hazard pictograms	
Signal word	: Danger
Hazard statements	 Harmful if swallowed or in contact with skin. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Fatal if inhaled. May cause respiratory irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. (kidneys) Causes digestive tract burns. Prolonged or repeated contact may dry skin and cause irritation.
Precautionary statements	
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. In case of inadequate ventilation wear respiratory protection. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.
Response	: IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor. Wash contaminated clothing before reuse. IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Storage	: Store locked up. Store in a well-ventilated place. Keep container tightly closed.
Disposal	 Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	 Do not taste or swallow. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. This product either contains formaldehyde or is capable of releasing formaldehyde above 0.5 ppm under certain conditions. Formaldehyde is a known cancer hazard, a skin sensitizer and a respiratory sensitizer. Avoid contact with skin and clothing. Wash thoroughly after handling. Emits toxic fumes when heated. Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 25.9% (oral), 35.6% (dermal), 69% (inhalation)

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Product name	: AMERLOCK SEALER HRD
Other means of identification	: Not available.

CAS number/other identifiers

Ingredient name	Synonyms	% (w/w)	CAS number
furfuryl alcohol	2-Furanmethanol; Alcohol, furfuryl; 2-Hydroxymethylfuran; 2-Furylmethanol; FURFURANOL; 2-Furylcarbinol; alpha- Furylcarbinol; Furfuralcohol; FURFURYLCARB; 2-Furancarbinol; Furfural alcohol	10 - 30*	98-00-0
Poly[oxy(methyl-1,2-ethanediyl)], α- (2-aminomethylethyl)-ω- (2-aminomethylethoxy)-	Poly[oxy(methyl-1,2-ethanediyl)], .alpha (2-aminomethylethoxy)-; Poly[oxy(methyl- 1,2-ethanediyl)], alpha- (2-aminomethylethoxy)-; .alpha.,.omega (2-aminomethylethoxy)-; .alpha.,.omega Diaminopolypropylene glycol; Jeffamine 400; Jeffamine D 600; polyoxypropylenediamine; Diaminopolypropylene glycol; Poly(oxy (methyl-1,2-ethanediyl)), alpha- (2-aminomethylethyl)-omega- (2-aminomethylethoxy)-; poly (oxypropylene)diamine; Poly(oxy(methyl- 1,2-ethanediyl)), .alpha (2-aminomethylethyl)omega (2-aminomethylethyl)omega (2-aminomethylethoxy)-; JEFFAMINE D- 2000	10 - 30*	9046-10-0 (n = 2-6)
Polyaminoamide	Fatty acids, C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine; C36 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polyamide; C36 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer; Dimer acid, triethylenetetramine, tall oil fatty acids polymer; Dimer fatty acids, tall oil fatty acids, triethylenetetramine polymer; Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine; Tall oil acids and fatty acids, C18-unsaturated, dimer, condensate with triethylene tetramine; Triethylenetetramine, dimer fatty acids, tall oil fatty acids polymer; Fatty acids, tall oil fatty acids and triethylenetetramine dimers, polymers with tall oil fatty acids, tall oil fatty acids and triethylenetetramine	7 - 13*	68082-29-1
Formaldehyde, polymer with 1,3-dimethylbenzene	Formaldehyde, 1,3-dimethylbenzene polymer; Xylene formaldehyde resin; Polymer of formaldehyde / m-xylene;	7 - 13*	26139-75-3

Product name AMERLOCK SEALER HRD

Section 3. Composition/information on ingredients

		0	ada Page: 4/17
3,6-diazaoctanethylenediamin	triethylenetetramine; trientine; 1,2-Ethanediamine, N1,N2-bis (2-aminoethyl)-; 1,2-Ethanediamine, N,N'- bis(2-aminoethyl)-; N,N'-Bis(2-aminoethyl) -1,2-ethanediamine; 3,6-diazaoctamethylenediamine; N,N'-bis (2-aminoethyl)ethane-1,2-diamine; N1,	0.5 - 1.5*	112-24-3
4-nonylphenol, branched	Phenol, 4-nonyl-, branched; Branched 4-nonylphenol (mixed isomers); Nonylphenol, 4-branched; N- NONYLPHENOL; Nonylphenol; C9- Branched alkyl phenol; Branched p- nonylphenol; 4-Nonylphenol (branched); Monoalkyl(C3-9)phenol; C9 branched alkyl phenol; Branched 4-nonylphenol	0.5 - 1.5*	84852-15-3
2,4,6-tris(dimethylaminomethyl)phenol	Phenol, 2,4,6-tris[(dimethylamino)methyl]-; Phenol, 2,4,6-tris(dimethylaminomethyl)-; 2,4,6-tris((dimethylamino)methyl)phenol; Phenol, 2,4,6-tris{(dimethylamino)methyl)phenol; 2,4,6-Tris[(dimethylaminomethyl)phenol; 2,4,6-Tris(N,N-dimethylaminomethyl)phenol; 2,4,6-Tridimethylaminomethylphenol; 2,4,6-Tridimethylaminomethylphenol; TRIS (2,4,6-DIMETHYLAMINOMONOMETHYL) PHENOL; TRIS (2,4,6-DIMETHYLAMINOMETHYL) PHENOL; TRIS[(DIMETHYLAMINO) METHYL]PHENOL, 2,4,6-		90-72-2
Formaldehyde, polymer with benzenamine, hydrogenated	poly(methylenecyclohexanamine); High- boiling fraction of hydrogenation products of (reaction products of aniline and formaldehyde); Hydrogenated polymer of aniline / formaldehyde; Copolymer of benzenamine and formaldehyde, hydrogenated; Methyleneoxide, polymer with benzenamine, hydrogenated	5 - 10*	135108-88-2
benzyl alcohol	Benzenemethanol; .alpha Hydroxytoluene; Phenylcarbinol; Phenylmethanol; E 1519; α- hydroxytoluene; Phenylmethyl alcohol; toluenol, alpha-; (hydroxymethyl)benzene; BENZENECARBINOL; alpha- Hydroxytoluene	5 - 10*	100-51-6
	Xylene (or mesitylene)-Formaldehyde polycondensate; POLYMER, FORMALDEHYDE WITH 1,3-DIMETHYLBENZENE; M-XYLENE- FORMALDEHYDE RESIN; Formaldehyde, polymers, polymer with 1,3-dimethylbenzene		

Product name AMERLOCK SEALER HRD

Section 3. Composition/information on ingredients

	0		
	N2-bis(2-Aminoethyl)-1,2-ethanediamine; 1,4,7,10-Tetraazadecane; 3,6-Diazaoctane-1,8-diamine; N,N'-Bis (2-aminoethyl)ethylenediamine		
salicylic acid	Benzoic acid, 2-hydroxy-; 2-hydroxybenzoic acid; 2-Carboxyphenol; 2-Hydroxybenzenecarboxylic acid; HYDROXYBENZOIC ACID, O-; Salicylic acid (8CA); o-Hydroxybenzoic acid; Hydroxybenzoic acid; ORTHOHYDROXY BENZOIC ACID; SALICYCLIC ACID	0.5 - 1.5*	69-72-7
4,4'-methylenebis(cyclohexylamine)	Cyclohexanamine, 4,4'-methylenebis-; Bis (4-aminocyclohexyl)methane; Cyclohexylamine, 4,4'-methylenebis-; 4,4'- methylenebis(cyclohexan-1-amine); Diaminodicyclohexylmethane; 4,4'- Methylenebiscyclohexylamine; 4,4'- Diaminodicyclohexylmethane; BIS (CYCLOHEXYLAMINE), 4,4'- METHYLENE-; Methylenebiscyclohexanamine, 4,4'-; 4,4 diaminodicyclohexylmethane; Cyclohexanamine, 4,4'-methylenebis-	0.5 - 1.5*	1761-71-3
Phenol, 2-nonyl-, branched	2-nonylphenol, branched; 2-(Branched nonyl)phenol; Monoalkyl(C3-9)phenol; Branched 2-nonylphenol	0.1 - 1*	91672-41-2

*Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

SUB codes represent substances without registered CAS Numbers.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Description of necessary first aid measures

Eye contact	 Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Inhalation	 Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Section 4. First-aid measures

Most important symptoms/effects, acute and delayed		
Potential acute health effe	<u>ets</u>	
Eye contact	: Causes serious eye damage.	
Inhalation	: Fatal if inhaled. May cause respiratory irritation.	
Skin contact	: Causes severe burns. Harmful in contact with skin. Defatting to the skin. May cause an allergic skin reaction.	
Ingestion	: Harmful if swallowed. Corrosive to the digestive tract. Causes burns.	
Over-exposure signs/sym	itoms	
Eye contact	: Adverse symptoms may include the following: pain watering redness	
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing reduced fetal weight increase in fetal deaths skeletal malformations	
Skin contact	: Adverse symptoms may include the following: pain or irritation redness dryness cracking blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations	
Ingestion	: Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations	
Indication of immediate me	lical attention and special treatment needed, if necessary	
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.	
Specific treatments	: No specific treatment.	
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.	

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides Formaldehyde.
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protec	tiv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	<u>nt</u>	ainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas.

upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Product name AMERLOCK SEALER HRD

Section 6. Accidental release measures

	breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Special precautions	Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Vapors are heavier than air and may spread along floors. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
furfuryl alcohol	CA Alberta Provincial (Canada, 6/2018).
	Absorbed through skin.
	15 min OEL: 60 mg/m ³ 15 minutes.
	15 min OEL: 15 ppm 15 minutes.
	8 hrs OEL: 40 mg/m ³ 8 hours.
	8 hrs OEL: 10 ppm 8 hours.
	CA British Columbia Provincial (Canada,
	6/2022). Absorbed through skin.
	STEL: 10 ppm 15 minutes.
	TWA: 5 ppm 8 hours.
	CA Ontario Provincial (Canada, 6/2019).
	Absorbed through skin.
	TWA: 0.2 ppm 8 hours.
	CA Quebec Provincial (Canada, 6/2022).
	Absorbed through skin.
	STEV: 60 mg/m ³ 15 minutes.
	STEV: 15 ppm 15 minutes.
	TWAEV: 40 mg/m ³ 8 hours.
	TWAEV: 10 ppm 8 hours.
	CA Saskatchewan Provincial (Canada,
	7/2013). Absorbed through skin.
	STEL: 15 ppm 15 minutes.
	TWA: 10 ppm 8 hours.
Poly[oxy(methyl-1,2-ethanediyl)], α -(2-aminomethylethyl)- ω -	None.
	Canada Page: 8/1

Product name AMERLOCK SEALER HRD

Section 8. Exposure controls/personal protection

(2-aminomethylethoxy)-	
Polyaminoamide	None.
Formaldehyde, polymer with 1,3-dimethylbenzene	None.
benzyl alcohol	IPEL (-).
	TWA: 5 ppm
	STEL: 10 ppm
Formaldehyde, polymer with benzenamine, hydrogenated	None.
2,4,6-tris(dimethylaminomethyl)phenol	None.
4-nonylphenol, branched	None.
3,6-diazaoctanethylenediamin	CA Ontario Provincial (Canada, 6/2019).
	Absorbed through skin.
	TWA: 3 mg/m ³ 8 hours.
	TWA: 0.5 ppm 8 hours.
salicylic acid	None.
4,4'-methylenebis(cyclohexylamine)	None.
Phenol, 2-nonyl-, branched	None.

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures	:	Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	:	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures	
Hygiene measures :	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection :	Chemical splash goggles and face shield.
Skin protection	
Hand protection :	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
	nitrile neoprene Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Canada

Page: 10/17

Product name AMERLOCK SEALER HRD

Section 8. Exposure controls/personal protection

Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

	<u>Appearance</u>			
Odor:Characteristic.Odor threshold:Not available.pH:Not available.Boiling point:>37.78°C (>100°F)Flash point:>37.78°C (>100°C)Flash point:>37.78°C (>100°C)Flash point:Closed cup: 100°C (212°F)Auto-ignition temperature:Not available.Decomposition temperature:Not available.Ibamability:Not available.Lower and upper explosive:Not available.(flammable) limits:Not available.Evaporation rate:Not available.Vapor pressure:Not available.Vapor density:Not available.Relative density:1.02Density (lbs / gal):8.51Solubility(ies):MediaPartition coefficient: n- octanol/water:Viscosity:Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)Volatility:28% (v/v), 30.26% (w/w)	Physical state	1	Liquid.	
Odor threshold:Not available.pH:Not applicable.Melting point:Not available.Boiling point:>37.78°C (>100°F)Flash point::Flash point::Closed cup: 100°C (212°F)Auto-ignition temperature:Not available.Decomposition temperature:Not available.Flammability:Not available.Lower and upper explosive:Not available.(flammable) limits:Not available.Evaporation rate:Not available.Vapor pressure:Not available.Vapor density:Not available.Relative density:1.02Density (lbs / gal):8.51Solubility(ies)::Partition coefficient: n- octanol/water:Not applicable.Viscosity::Not applicable.Viscosity::Not applicable.Volatility::21 mm²/s (>21 cSt)Volatility::28% (v/v), 30.26% (w/w)	Color	4	Not available.	
pH: Not applicable.Melting point: Not available.Boiling point: >37.78°C (>100°F)Flash point: Closed cup: 100°C (212°F)Auto-ignition temperature: Not available.Decomposition temperature: Not available.Ileamability: Not available.Lower and upper explosive (flammable) limits: Not available.Evaporation rate: Not available.Vapor pressure: Not available.Vapor density: Not available.Relative density: 1.02Density (lbs / gal): 8.51Solubility(ies): MediaPartition coefficient: n- octanol/water: Not applicable.Viscosity: Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)Volatility: 28% (v/v), 30.26% (w/w)	Odor	1	Characteristic.	
Melting point:Not available.Boiling point:>37.78°C (>100°F)Flash point:Closed cup: 100°C (212°F)Auto-ignition temperature:Not available.Decomposition temperature:Not available.Flammability:Not available.Lower and upper explosive (flammable) limits:Not available.Evaporation rate:Not available.Vapor pressure:Not available.Vapor density:Not available.Relative density:1.02Density (lbs / gal):8.51Solubility(ies):Not applicable.Partition coefficient: n- octanol/water:Not applicable.Viscosity:Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)Volatility:28% (v/v), 30.26% (w/w)		1	Not available.	
Boiling point: >37.78°C (>100°F)Flash point: Closed cup: 100°C (212°F)Auto-ignition temperature: Not available.Decomposition temperature: Not available.Flammability: Not available.Lower and upper explosive: Not available.(flammable) limits:Evaporation rate: Not available.Vapor pressure: Not available.Vapor density: Not available.Relative density: 1.02Density (lbs / gal): 8.51Solubility(ies): MediaPartition coefficient: n- octanol/water: Not applicable.Viscosity: Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)Volatility: 28% (v/v), 30.26% (w/w)	рН	÷	Not applicable.	
Flash point:Closed cup: 100°C (212°F)Auto-ignition temperature:Not available.Decomposition temperature:Not available.Flammability:Not available.Cower and upper explosive (flammable) limits:Not available.Evaporation rate:Not available.Vapor pressure:Not available.Vapor density:Not available.Relative density:1.02Density (Ibs / gal):8.51Solubility(ies):MediaPartition coefficient: n- octanol/water:Viscosity:Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)Volatility:28% (v/v), 30.26% (w/w)	Melting point	4		
Auto-ignition temperature : Not available. Decomposition temperature : Not available. Flammability : Not available. Lower and upper explosive (flammable) limits : Not available. Evaporation rate : Not available. Vapor pressure : Not available. Vapor density : Not available. Relative density : 1.02 Density (Ibs / gal) : 8.51 Solubility(ies) : Media Partition coefficient: n- octanol/water : Not applicable. Viscosity : Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt) Volatility : 28% (v/v), 30.26% (w/w)	Boiling point	4	>37.78°C (>100°F)	
Decomposition temperature : Not available. Flammability : Not available. Lower and upper explosive : Not available. (flammable) limits : Not available. Evaporation rate : Not available. Vapor pressure : Not available. Vapor density : Not available. Relative density : 1.02 Density (lbs / gal) : 8.51 Solubility(ies) : Media Partition coefficient: n-octanol/water : Not applicable. Viscosity : Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt) Volatility : 28% (v/v), 30.26% (w/w)	Flash point	4	Closed cup: 100°C (212°F)	
Flammability : Not available. Lower and upper explosive : Not available. (flammable) limits : Not available. Evaporation rate : Not available. Vapor pressure : Not available. Vapor density : Not available. Relative density : 1.02 Density (lbs / gal) : 8.51 Solubility(ies) : Media Result cold water vot soluble Not applicable. Partition coefficient: n-octanol/water : Not applicable. Viscosity : Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt) Volatility : 28% (v/v), 30.26% (w/w)	Auto-ignition temperature	1	Not available.	
Lower and upper explosive (flammable) limits: Not available.Evaporation rate: Not available.Vapor pressure: Not available.Vapor density: Not available.Relative density: 1.02Density (lbs / gal): 8.51Solubility(ies): MediaResult cold waterNot solublePartition coefficient: n- octanol/water: Not applicable.Viscosity: Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)Volatility: 28% (v/v), 30.26% (w/w)	Decomposition temperature	1	Not available.	
(flammable) limits Evaporation rate : Not available. Vapor pressure : Not available. Vapor density : Not available. Relative density : 1.02 Density (lbs / gal) : 8.51 Solubility(ies) : Media Result cold water Not soluble Partition coefficient: n- octanol/water : Not applicable. Viscosity : Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt) Volatility : 28% (v/v), 30.26% (w/w)	Flammability	1	Not available.	
Vapor pressure : Not available. Vapor density : Not available. Relative density : 1.02 Density (lbs / gal) : 8.51 Solubility(ies) : Media Result cold water Not soluble Partition coefficient: n- octanol/water : Not applicable. Viscosity : Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt) Volatility : 28% (v/v), 30.26% (w/w)		1	Not available.	
Vapor density : Not available. Relative density : 1.02 Density (lbs / gal) : 8.51 Solubility(ies) : Media Result cold water Not soluble Partition coefficient: n-octanol/water Viscosity : Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt) Volatility : 28% (v/v), 30.26% (w/w)	Evaporation rate	1	Not available.	
Relative density : 1.02 Density (lbs / gal) : 8.51 Solubility(ies) : Media Result cold water Not soluble Partition coefficient: n- octanol/water : Not applicable. Viscosity : Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt) Volatility : 28% (v/v), 30.26% (w/w)	Vapor pressure	1	Not available.	
Density (lbs / gal) : 8.51 Solubility(ies) : Media Result cold water Not soluble Partition coefficient: n-octanol/water : Not applicable. Viscosity : Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt) Volatility : 28% (v/v), 30.26% (w/w)	Vapor density	1	Not available.	
Solubility(ies) Media Result Cold water Not soluble Partition coefficient: n- octanol/water : Not applicable. Viscosity : Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt) Volatility : 28% (v/v), 30.26% (w/w)	Relative density	1	1.02	
Solubility(ies) : cold water Not soluble Partition coefficient: n- octanol/water : Not applicable. Viscosity : Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt) Volatility : 28% (v/v), 30.26% (w/w)	Density(lbs / gal)	1	8.51	
Cold water Not soluble Partition coefficient: n- octanol/water : Not applicable. Viscosity : Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt) Volatility : 28% (v/v), 30.26% (w/w)	Solubility(ies)		Media	Result
octanol/water Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt) Volatility : 28% (v/v), 30.26% (w/w)	oorubiiity(ics)	Ċ	cold water	Not soluble
Volatility : 28% (v/v), 30.26% (w/w)		:	Not applicable.	
	Viscosity	1	Kinematic (40°C (104°F)): >	>21 mm²/s (>21 cSt)
% Solid. (w/w) : 69.74	Volatility	:	28% (v/v), 30.26% (w/w)	
	% Solid. (w/w)	:	69.74	

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.

Product name AMERLOCK SEALER HRD

Section 10. Stability and reactivity

Conditions to avoid	:	When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Incompatible materials	:	Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	:	Depending on conditions, decomposition products may include the following materials carbon oxides nitrogen oxides Formaldehyde.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
furfuryl alcohol	LC50 Inhalation Vapor	Rat	934 mg/m³	4 hours
-	LC50 Inhalation Vapor	Rat	233 ppm	4 hours
	LD50 Dermal	Rabbit	400 mg/kg	-
	LD50 Dermal	Rat	3825 mg/kg	-
	LD50 Oral	Rat	0.132 g/kg	-
Poly[oxy(methyl-	LD50 Dermal	Rat	2980 mg/kg	-
1,2-ethanediyl)], α-				
(2-aminomethylethyl)-ω-				
(2-aminomethylethoxy)-				
	LD50 Oral	Rat	2885 mg/kg	-
benzyl alcohol	LC50 Inhalation Dusts and mists	Rat	>4178 mg/m ³	4 hours
	LD50 Dermal	Rabbit	2000 mg/kg	-
	LD50 Oral	Rat	1.23 g/kg	-
2,4,6-tris	LD50 Dermal	Rabbit	1.28 g/kg	-
(dimethylaminomethyl)				
phenol				
	LD50 Dermal	Rat	1280 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-
4-nonylphenol, branched	LD50 Dermal	Rabbit	2.14 g/kg	-
	LD50 Oral	Rat	1300 mg/kg	-
3,6-diazaoctanethylenediamin	LD50 Dermal	Rabbit	1465 mg/kg	-
	LD50 Oral	Rat	1716 mg/kg	-
salicylic acid	LD50 Oral	Rat	0.891 g/kg	-
4,4'-methylenebis	LD50 Dermal	Rabbit	2.11 g/kg	-
(cyclohexylamine)				
	LD50 Oral	Rat	0.625 g/kg	-

Conclusion/Summary

: There are no data available on the mixture itself.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2,4,6-tris (dimethylaminomethyl)phenol	Skin - Visible necrosis	Rabbit	-	4 hours	7 days
	Skin - Erythema/Eschar	Rabbit	4	-	-

Conclusion/Summary	
Skin	: There are no data available on the mixture itself.
Eyes	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
Sensitization	

Canada Page: 11/17

Product name AMERLOCK SEALER HRD

Section 11. Toxicological information

Product/ingredient name	Route of exposure		Species	i	Result		
Formaldehyde, polymer with benzenamine, hydrogenated	skin		Guinea	Guinea pig		Sensitizing	
3,6-diazaoctanethylenediamin	skin		Guinea	Guinea pig			
Skin	: The	re are no	data availa	ble on the mixture	e itself.		
Respiratory	: The	re are no	data availa	ble on the mixture	e itself.		
<u>Mutagenicity</u>							
Conclusion/Summary	: The	re are no	data availa	ble on the mixture	e itself.		
Carcinogenicity							
Conclusion/Summary	: The	re are no	data availa	ble on the mixture	e itself.		
<u>Classification</u>							
Product/ingredient name		OSHA	IARC	NTP			
furfuryl alcohol		-	2B	-			
IARC: 1, 2A, 2B, 3, 4 NTP: Known to be OSHA: + Not listed/not regul	a human	carcinogen	; Reasonabl	y anticipated to be a	human carcinogen		
Reproductive toxicity							
Conclusion/Summary	: The	re are no	data availa	ble on the mixture	e itself.		
<u>Teratogenicity</u>							
Conclusion/Summary				ble on the mixture	e itself.		
Specific target organ toxicit	<u>y (sing</u> l	<u>e exposu</u>	<u>ire)</u>				
Name				Category	Route of exposure	Target organs	
furfuryl alcohol				Category 3	-	Respiratory tract irritation	
Formaldehyde, polymer with	1,3-dime	ethylbenze	ene	Category 3	-	Respiratory tract irritation	
Specific target organ toxicit	<u>y (repea</u>	ated expo	osure)				
Name				Category	Route of exposure	Target organs	

Name		exposure	l arget organs
furfuryl alcohol	Category 2	-	-
Formaldehyde, polymer with benzenamine, hydrogenated	Category 2	oral	kidneys
4,4'-methylenebis(cyclohexylamine)	Category 2	oral	-

Target organs

: Contains material which causes damage to the following organs: blood, liver, heart, brain, skin, central nervous system (CNS). Contains material which may cause damage to the following organs: kidneys, the

reproductive system, gastrointestinal tract, upper respiratory tract, eye, lens or cornea, muscle tissue, nose/sinuses.

Aspiration hazard

Not available.

Section 11. Toxicological information

Information on the likely routes of exposure

Eye contact	: Causes serious eye damage.
Inhalation	: Fatal if inhaled. May cause respiratory irritation.
Skin contact	: Causes severe burns. Harmful in contact with skin. Defatting to the skin. May cause an allergic skin reaction.
Ingestion	: Harmful if swallowed. Corrosive to the digestive tract. Causes burns.
Over-exposure signs/	/symptoms
Eye contact	: Adverse symptoms may include the following: pain

	pain watering redness
Inhalation	Adverse symptoms may include the following: respiratory tract irritation coughing reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact :	Adverse symptoms may include the following: pain or irritation redness dryness cracking blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion :	Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Conclusion/Summary	: There are no data available on the mixture itself. This product either contains formaldehyde or is capable of releasing formaldehyde above 0.5 ppm under certain conditions. Formaldehyde is a known cancer hazard, a skin sensitizer and a respiratory sensitizer. Can form nitrosamines in the presence of certain organic materials and if heated. Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. There is some evidence that repeated exposure to organic solvent vapors in combination with constant loud noise can cause greater hearing loss than expected from exposure to noise alone. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Product name AMERLOCK SEALER HRD

Section 11. Toxicological information

Short term exposure		
Potential immediate effects	There are no data available on the mixture itself.	
Potential delayed effects	There are no data available on the mixture itself.	
<u>Long term exposure</u>		
Potential immediate effects	There are no data available on the mixture itself.	
Potential delayed effects	There are no data available on the mixture itself.	
Potential chronic health eff	<u>s</u>	
General	May cause damage to organs through prolonged or repeated exposure. Prolong or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.	ged
Carcinogenicity	Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.	
Mutagenicity	No known significant effects or critical hazards.	
Reproductive toxicity	Suspected of damaging fertility or the unborn child.	
Numerical measures of toxic		

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
MERLOCK SEALER HRD	933.0	1954.3	N/A	1.3	0.63
furfuryl alcohol	500	1100	N/A	0.934	0.5
Poly[oxy(methyl-1,2-ethanediyl)], α-	2885	2980	N/A	N/A	N/A
(2-aminomethylethyl)-ω-(2-aminomethylethoxy)-					
benzyl alcohol	1230	2000	N/A	N/A	1.5
Formaldehyde, polymer with benzenamine,	500	N/A	N/A	N/A	N/A
hydrogenated					
2,4,6-tris(dimethylaminomethyl)phenol	1200	1280	N/A	N/A	N/A
4-nonylphenol, branched	1300	2140	N/A	N/A	N/A
3,6-diazaoctanethylenediamin	1716	1465	N/A	N/A	N/A
salicylic acid	891	N/A	N/A	N/A	N/A
4,4'-methylenebis(cyclohexylamine)	625	2110	N/A	N/A	N/A
Phenol, 2-nonyl-, branched	500	N/A	N/A	N/A	N/A

Section 12. Ecological information

Toxicity

Section 12. Ecological information

Product/ingredient name	Result	Species	Exposure
Poly[oxy(methyl-	EC50 15 mg/l	Algae	72 hours
1,2-ethanediyl)], α-			
(2-aminomethylethyl)-ω-			
(2-aminomethylethoxy)-			
Formaldehyde, polymer with	Acute EC50 63 mg/l	Fish	96 hours
benzenamine, hydrogenated			
2,4,6-tris	Acute LC50 175 mg/l	Fish	96 hours
(dimethylaminomethyl)phenol	-		
4-nonylphenol, branched	Acute EC50 0.044 mg/l	Crustaceans - Moina macrocopa	48 hours
	Acute LC50 0.221 mg/l	Fish	96 hours
salicylic acid	Acute EC50 1147.57 mg/l Fresh water	Daphnia - Daphnia longispina -	48 hours
		Neonate	
	Chronic NOEC 5.6 mg/l Fresh water	Daphnia - <i>Daphnia magna</i> -	21 days
		Neonate	-
Phenol, 2-nonyl-, branched	Acute LC50 0.017 mg/l	Fish - Pleuronectes americanus	96 hours

Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Poly[oxy(methyl- 1,2-ethanediyl)], α- (2-aminomethylethyl)-ω- (2-aminomethylethoxy)-	-	-	Not readily
benzyl alcohol	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential	
furfuryl alcohol	0.3	-	Low	
benzyl alcohol	0.87	-	Low	
Formaldehyde, polymer with	-	209 to 219	Low	
benzenamine, hydrogenated				
2,4,6-tris	0.219	-	Low	
(dimethylaminomethyl)phenol				
4-nonylphenol, branched	5.4	251.19	Low	
3,6-diazaoctanethylenediamin	-1.66 to -1.4	-	Low	
salicylic acid	2.21 to 2.26	-	Low	
4,4'-methylenebis	2.03	-	Low	
(cyclohexylamine)				

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Product name AMERLOCK SEALER HRD

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

Section 14. Transport information

	TDG	IMDG	ΙΑΤΑ
UN number	UN3066	UN3066	UN3066
UN proper shipping name	PAINT	PAINT	PAINT
Transport hazard class (es)	8	8	8
Packing group	III	III	Ш
Environmental hazards	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	(4-nonylphenol, branched, 4,4'-methylenebis (cyclohexylamine))	(4-nonylphenol, branched, 4,4'- methylenebis (cyclohexylamine))	Not applicable.

Additional information

			Canada Page	: 16/17
Proof of classificat statement	ion	:	Product classified as per the following sections of the Transportation of Dange Goods Regulations: 2.40-2.42 (Class 8), 2.7 (Marine pollutant mark).	rous
Transport in bulk a to IMO instruments		:	Not applicable.	
Special precaution	s for user	:	Transport within user's premises: always transport in closed containers that upright and secure. Ensure that persons transporting the product know what to the event of an accident or spillage.	
IATA :	The envi regulatio		mentally hazardous substance mark may appear if required by other transporta	tion
			pollutant mark is not required when transported in sizes of \leq 5 L or \leq 5 kg.	
TDG :	The mari	ne	pollutant mark is not required when transported by road or rail.	
Additional informa				

Product name AMERLOCK SEALER HRD

Section 15. Regulatory information

National Inventory List

Canada inventory (DSL)

: All components are listed or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health : 3 * Flammability : 1 Physical hazards : 1

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.) Health : 3 Flammability : 1 Instability : 1	
Date of issue/Date of revision	31 August 2023
Organization that prepared the SDS	: EHS
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.