

# SAFETY DATA SHEET



The information in this Safety Data Sheet is required pursuant to Hazardous Product Regulations 2015.

Date of issue/Date of revision 3 September 2023

Version 6.02

## Section 1. Identification

**Product name** : PSX 700SG WHITE F/S 17925 RESIN

**Product code** : 00425947

**Other means of identification** : Not available.

**Product type** : Liquid.

### Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Professional applications, Used by spraying.

**Use of the substance/mixture** : Coating.

**Uses advised against** : Not applicable.

**Supplier** : PPG Architectural Coatings Canada, Inc.  
1550, rue Ampère, bureau 500  
Boucherville (Québec) J4B 7L4  
Canada  
+1 450-655-3121

PPG Industries, Inc.  
One PPG Place  
Pittsburgh, PA 15272

**Emergency telephone number** : (412) 434-4515 (U.S.)  
(514) 645-1320 (Canada)  
SETIQ Interior de la República: 800-00-214-00 (México)  
SETIQ Ciudad de México: (55) 5559-1588 (México)

**Technical Phone Number** : 888-977-4762

## Section 2. Hazard identification

**Classification of the substance or mixture** : FLAMMABLE LIQUIDS - Category 4  
SKIN SENSITIZATION - Category 1B  
CARCINOGENICITY - Category 2  
TOXIC TO REPRODUCTION - Category 2  
Health Hazards Not Otherwise Classified - Category 1  
This product contains TiO<sub>2</sub> which has been classified as a GHS Carcinogen Category 2 based on its IARC 2B classification. For many products, TiO<sub>2</sub> is utilized as a raw material in a liquid coating formulation. In this case, the TiO<sub>2</sub> particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of TiO<sub>2</sub> when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/or engineering controls (see Section 8).

## Section 2. Hazard identification

### GHS label elements

#### Hazard pictograms



#### Signal word

: Danger

#### Hazard statements

: Combustible liquid.  
 May cause an allergic skin reaction.  
 Suspected of causing cancer.  
 Suspected of damaging fertility or the unborn child.  
 Prolonged or repeated contact may dry skin and cause irritation.

### Precautionary statements

#### Prevention

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing vapor. Contaminated work clothing should not be allowed out of the workplace.

#### Response

: IF exposed or concerned: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention.

#### Storage

: Store locked up.

#### Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

#### Supplemental label elements

: Sanding and grinding dusts may be harmful if inhaled. Trimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness. Avoid contact with skin and clothing. Wash thoroughly after handling. Emits toxic fumes when heated.

Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity:  
 55.8% (oral), 57.3% (dermal), 62.1% (inhalation)

## Section 3. Composition/information on ingredients

#### Substance/mixture

: Mixture

#### Product name

: PSX 700SG WHITE F/S 17925 RESIN

#### Other means of identification

: Not available.

### CAS number/other identifiers

Ingredient name	Synonyms	% (w/w)	CAS number
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Cyclohexanol, 4,4'-(1-methylethylidene) bis-, polymer with 2-(chloromethyl)oxirane; Cyclohexanol, 4,4'-(1-methylethylidene) bis-, polymer with (chloromethyl)oxirane; 2,2-Bis(4-hydroxycyclohexyl)propane, epichlorohydrin polymer; 4,4'-(1-Methylethylidene)biscyclohexanol, polymer with (chloromethyl)oxirane; 4,4'-(1-Methylethylidene)biscyclohexanol polymer with (chloromethyl)oxirane; POLYMER, CYCLOHEXANOL, 4,4'-(1-METHYLETHYLIDENE) BIS WITH	10 - 30*	30583-72-3

## Section 3. Composition/information on ingredients

titanium dioxide	(CHLOROMETHYL)OXIRANE; Cyclohexanol, 4,4'-(1-methylethylidene) bis-, polymer with 2-(chloromethyl)oxirane  Titanium oxide; Titanium oxide (TiO <sub>2</sub> ); CI 77891; Titanium peroxide; Rutile; C.I. Pigment White 6; titanium dioxide coated with isopropoxytitanium triisostearate, containing by weight 1,5 % or more but not more than 2,5 % of isopropoxytitanium triisostearate; glass flakes (CAS RN 65997-17-3): — of a thickness of 0,3 µm or more but not more than 10 µm, and — coated with titanium dioxide (CAS RN 13463-67-7) or iron oxide (CAS RN 18282- 10-5); titanium dioxide, other than those of heading 3206 11 00; C.I. 77891; E 171; titanium(IV) oxide, other than those of heading 3206 11 00	10 - 30*	13463-67-7
barium sulfate	Sulfuric acid, barium salt (1:1); CI 77120; Barytes; Barium salt of sulfuric acid; Barite; Artificial barite; barium sulphate; C. I. Pigment White 21; barium sulfate, natural; blanc fixe; C.I. 77120	1 - 5*	7727-43-7
Silica, amorphous, precipitated and gel	Silica gel, precipitated, crystalline-free; Silica gel, precipitated, crystalline free; Amorphous synthetic silica gel; Synthetic amorphous silica, precipitated; Synthetic, crystalline free, silica gel; Silica, amorphous, precipitated and gel.; Silica - Amorphous, gel; Silica, Amorphous - Precipitated and gel; Precipitated Silica; Silica gel; silica-amorphous: precipitated silica	1 - 5*	112926-00-8
n-butyl acetate	Acetic acid, butyl ester; Butyl Acetate; n-Butyl-acetate; Butyl ethanoate; n-Butyl ester of acetic acid; product composed of hydrocarbons (predominantly paraffinic and naphthenic) and n-butyl acetate; 1-butyl acetate; 1-Acetoxybutane; Butyl ester, Acetic acid; normal butyl acetate; Acetic acid, n-butyl ester	1 - 5*	123-86-4
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	Decanedioic acid, 1,10-bis (1,2,2,6,6-pentamethyl-4-piperidiny) ester; Decanedioic acid, bis (1,2,2,6,6-pentamethyl-4-piperidiny) ester; bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate; Bis(1,2,2,6,6-pentamethyl-4-piperidiny) decanedioate; Bis (1,2,2,6,6-pentamethyl-4-piperidyl) decanedioate; Decanedioic acid bis (1,2,2,6,6-pentamethyl-4-piperidiny) ester;	1 - 5*	41556-26-7

## Section 3. Composition/information on ingredients

	DECANEDIOATE, BIS (1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL) (PICCS); Bis(N-methyl-2,2,6,6-tetramethyl-4-piperidinyl) sebacate; Bis(1,2,2,6,6-pentamethyl-4-piperidyl) 1,8-octanedicarboxylate; Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate; DECANEDIOATE, BIS (1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL)		
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Decanedioic acid, 1-methyl 10-(1,2,2,6,6-pentamethyl-4-piperidinyl) ester; Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester; methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate; methyl 1,2,2,6,6-pentamethylpiperidin-4-yl sebacate; Decanedioic acid methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester; Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate; Methyl 1,2,2,6,6-pentamethyl-4-piperidinyl sebacate; DECANEDIOATE, METHYL, 1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL; Methyl 1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	0.1 - 1*	82919-37-7
propylidynetrimethanol	1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-; 1,1,1-Trimethylolpropane; Propane, 1,1,1-tris(hydroxymethyl)-; trimethylolpropane; 2-ethyl-2-hydroxymethylpropane-1,3-diol; 2-Ethyl-2-hydroxymethyl-1,3-propanediol; 1,1,1-TRIS(HYDROXYMETHYL)PROPANE; Hexaglycerine; Hexaglycerol; 2-Ethyl-2-(hydroxymethyl)-1,3-propanediol; Tris(hydroxymethyl)propane	0.1 - 1*	77-99-6

\*Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

SUB codes represent substances without registered CAS Numbers.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.**

**Occupational exposure limits, if available, are listed in Section 8.**

## Section 4. First-aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

### Description of necessary first aid measures

- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Defatting to the skin. May cause skin dryness and irritation. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : Adverse symptoms may include the following:  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

**Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

**Unsuitable extinguishing media** : Do not use water jet.

**Specific hazards arising from the chemical** : Combustible liquid. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon oxides  
nitrogen oxides  
sulfur oxides  
halogenated compounds  
metal oxide/oxides

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

## Section 6. Accidental release measures

- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Special precautions** : Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Vapors are heavier than air and may spread along floors. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits
<p>4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane titanium dioxide</p>	<p>None.</p> <p><b>CA British Columbia Provincial (Canada, 6/2022). [Titanium dioxide]</b> TWA: 10 mg/m<sup>3</sup> 8 hours. Form: Total dust TWA: 3 mg/m<sup>3</sup> 8 hours. Form: respirable fraction</p> <p><b>CA Quebec Provincial (Canada, 6/2022).</b> TWAEV: 10 mg/m<sup>3</sup> 8 hours. Form: Total dust.</p> <p><b>CA Alberta Provincial (Canada, 6/2018). Skin sensitizer.</b> 8 hrs OEL: 10 mg/m<sup>3</sup> 8 hours.</p> <p><b>CA Ontario Provincial (Canada, 6/2019).</b> TWA: 10 mg/m<sup>3</sup> 8 hours. Form: total dust</p> <p><b>CA Saskatchewan Provincial (Canada, 7/2013).</b> STEL: 20 mg/m<sup>3</sup> 15 minutes. TWA: 10 mg/m<sup>3</sup> 8 hours.</p>
barium sulfate	<p><b>CA British Columbia Provincial (Canada, 6/2022).</b> TWA: 5 mg/m<sup>3</sup> 8 hours. Form: Inhalable</p> <p><b>CA Ontario Provincial (Canada, 6/2019).</b> TWA: 5 mg/m<sup>3</sup> 8 hours. Form: Inhalable particulate matter.</p> <p><b>CA Alberta Provincial (Canada, 6/2018).</b> 8 hrs OEL: 10 mg/m<sup>3</sup> 8 hours.</p> <p><b>CA Quebec Provincial (Canada, 6/2022).</b> TWAEV: 5 mg/m<sup>3</sup> 8 hours. Form: inhalable dust</p> <p><b>CA Saskatchewan Provincial (Canada, 7/2013).</b> STEL: 20 mg/m<sup>3</sup> 15 minutes. TWA: 10 mg/m<sup>3</sup> 8 hours.</p>
Silica, amorphous, precipitated and gel	<p><b>CA British Columbia Provincial (Canada, 6/2022).</b> TWA: 1.5 mg/m<sup>3</sup> 8 hours. Form: Respirable</p> <p><b>CA Quebec Provincial (Canada, 6/2022).</b> TWAEV: 6 mg/m<sup>3</sup> 8 hours. Form: Respirable dust.</p> <p><b>CA Saskatchewan Provincial (Canada, 7/2013).</b> STEL: 20 mg/m<sup>3</sup> 15 minutes. TWA: 10 mg/m<sup>3</sup> 8 hours.</p>
n-butyl acetate	<p><b>CA Alberta Provincial (Canada, 6/2018). Skin sensitizer.</b> 15 min OEL: 950 mg/m<sup>3</sup> 15 minutes. 15 min OEL: 200 ppm 15 minutes. 8 hrs OEL: 713 mg/m<sup>3</sup> 8 hours. 8 hrs OEL: 150 ppm 8 hours.</p>



## Section 8. Exposure controls/personal protection

**CA Saskatchewan Provincial (Canada, 7/2013).**

STEL: 200 ppm 15 minutes.

TWA: 150 ppm 8 hours.

**CA Ontario Provincial (Canada, 6/2019).**

**[butyl acetates, all isomers]**

STEL: 150 ppm 15 minutes.

TWA: 50 ppm 8 hours.

**CA British Columbia Provincial (Canada, 6/2022). [butyl acetate, all isomers]**

STEL: 150 ppm 15 minutes.

TWA: 50 ppm 8 hours.

**CA Quebec Provincial (Canada, 6/2022).**

**[butyl acetates (all isomers)]**

STEV: 150 ppm 15 minutes.

TWAEV: 50 ppm 8 hours.

bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate  
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate  
propylidynetrimethanol

None.

None.

None.

### Consult local authorities for acceptable exposure limits.

**Recommended monitoring procedures** : Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety glasses with side shields.

#### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Gloves** : butyl rubber

## Section 8. Exposure controls/personal protection

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

## Section 9. Physical and chemical properties

### Appearance

- Physical state** : Liquid.
- Color** : White.
- Odor** : Characteristic.
- Odor threshold** : Not available.
- pH** : Not applicable.
- Melting point** : Not available.
- Boiling point** : >37.78°C (>100°F)
- Flash point** : Closed cup: 82°C (179.6°F)
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : Not available.
- Flammability** : Not available.
- Lower and upper explosive (flammable) limits** : Not available.
- Evaporation rate** : Not available.
- Vapor pressure** : Not available.
- Vapor density** : Not available.
- Relative density** : 1.49
- Density ( lbs / gal )** : 12.43

	Media	Result
<b>Solubility(ies)</b> :	cold water	Not soluble

- Partition coefficient: n-octanol/water** : Not applicable.
- Viscosity** : Kinematic (40°C (104°F)): >21 mm<sup>2</sup>/s (>21 cSt)
- Volatility** : 3% (v/v), 1.998% (w/w)
- % Solid. (w/w)** : 98.002

## Section 10. Stability and reactivity

- Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- Chemical stability** : The product is stable.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.  
Refer to protective measures listed in sections 7 and 8.
- Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
- Hazardous decomposition products** : Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides sulfur oxides halogenated compounds metal oxide/oxides

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
titanium dioxide	LC50 Inhalation Dusts and mists	Rat	>6.82 mg/l	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
barium sulfate	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Silica, amorphous, precipitated and gel	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
n-butyl acetate	LC50 Inhalation Vapor	Rat	>21.1 mg/l	4 hours
	LC50 Inhalation Vapor	Rat	2000 ppm	4 hours
	LD50 Dermal	Rabbit	>17600 mg/kg	-
	LD50 Oral	Rat	10.768 g/kg	-
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate methyl	LD50 Oral	Rat	3.125 g/kg	-
	LD50 Oral	Rat	3.125 g/kg	-
1,2,2,6,6-pentamethyl-4-piperidyl sebacate	LD50 Dermal	Rabbit	10 g/kg	-
	LD50 Oral	Rat	14000 mg/kg	-
propylidynetrimethanol	LD50 Oral	Rat	14000 mg/kg	-

**Conclusion/Summary** : There are no data available on the mixture itself.

#### Irritation/Corrosion

##### Conclusion/Summary

- Skin** : There are no data available on the mixture itself.
- Eyes** : There are no data available on the mixture itself.
- Respiratory** : There are no data available on the mixture itself.

#### Sensitization

- Skin** : There are no data available on the mixture itself.

## Section 11. Toxicological information

**Respiratory** : There are no data available on the mixture itself.

### Mutagenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Carcinogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Classification

Product/ingredient name	OSHA	IARC	NTP
Titanium dioxide	-	2B	-
Silica, amorphous, precipitated and gel	-	3	-

Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4

NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen

OSHA: +

Not listed/not regulated: -

### Reproductive toxicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Teratogenicity

**Conclusion/Summary** : There are no data available on the mixture itself.

### Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
n-butyl acetate	Category 3	-	Narcotic effects

### Specific target organ toxicity (repeated exposure)

Not available.

### Target organs

: Contains material which causes damage to the following organs: brain, upper respiratory tract, skin.  
Contains material which may cause damage to the following organs: kidneys, lungs, immune system, central nervous system (CNS), eye, lens or cornea.

### Aspiration hazard

Not available.

## Information on the likely routes of exposure

### Potential acute health effects

**Eye contact** : No known significant effects or critical hazards.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact** : Defatting to the skin. May cause skin dryness and irritation. May cause an allergic skin reaction.

**Ingestion** : No known significant effects or critical hazards.

### Over-exposure signs/symptoms

**Eye contact** : No specific data.

## Section 11. Toxicological information

- Inhalation** : Adverse symptoms may include the following:  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

### Delayed and immediate effects and also chronic effects from short and long term exposure

- Conclusion/Summary** : There are no data available on the mixture itself. Trimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness. This product contains TiO<sub>2</sub> which has been classified as a GHS Carcinogen Category 2 based on its IARC 2B classification. For many products, TiO<sub>2</sub> is utilized as a raw material in a liquid coating formulation. In this case, the TiO<sub>2</sub> particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of TiO<sub>2</sub> when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/or engineering controls (see Section 8). If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

### Short term exposure

- Potential immediate effects** : There are no data available on the mixture itself.
- Potential delayed effects** : There are no data available on the mixture itself.

### Long term exposure

- Potential immediate effects** : There are no data available on the mixture itself.
- Potential delayed effects** : There are no data available on the mixture itself.

### Potential chronic health effects

- General** : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : Suspected of damaging fertility or the unborn child.

### Numerical measures of toxicity

## Section 11. Toxicological information

### Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
PSX 700SG WHITE F/S 17925 RESIN	89842.7	22545.0	N/A	N/A	N/A
barium sulfate	N/A	2500	N/A	N/A	N/A
n-butyl acetate	10768	N/A	N/A	N/A	N/A
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	3125	N/A	N/A	N/A	N/A
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	3125	N/A	N/A	N/A	N/A
propylidynetrimethanol	14000	10000	N/A	N/A	N/A

## Section 12. Ecological information

### Toxicity

Product/ingredient name	Result	Species	Exposure
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	LC50 11.5 mg/l	Fish	96 hours
titanium dioxide	Acute LC50 >100 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
Silica, amorphous, precipitated and gel	NOEC >1000 ppm	Daphnia - <i>Daphnia magna</i>	24 hours
	Acute NOEC >10000 ppm Fresh water	Fish	96 hours Static
	Acute NOEC >10000 ppm	Fish - <i>Brachydanio rerio</i>	4 days Static
n-butyl acetate	Acute LC50 18 mg/l	Fish	96 hours
propylidynetrimethanol	Acute LC50 >1000 mg/l	Fish	96 hours

### Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
n-butyl acetate	TEPA and OECD 301D	83 % - Readily - 28 days	-	-

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Silica, amorphous, precipitated and gel	-	-	Not readily
n-butyl acetate	-	-	Readily

### Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Silica, amorphous, precipitated and gel	-	0	Low
n-butyl acetate	2.3	-	Low
propylidynetrimethanol	-0.47	-	Low

### Mobility in soil

## Section 12. Ecological information

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

## Section 14. Transport information

	TDG	IMDG	IATA
<b>UN number</b>	Not regulated.	Not regulated.	Not regulated.
<b>UN proper shipping name</b>	-	-	-
<b>Transport hazard class (es)</b>	-	-	-
<b>Packing group</b>	-	-	-
<b>Environmental hazards</b>	No.	No.	No.
<b>Marine pollutant substances</b>	Not applicable.	Not applicable.	Not applicable.

### Additional information

**TDG** : None identified.

**IMDG** : None identified.

**IATA** : None identified.

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

## Section 14. Transport information

Transport in bulk according to IMO instruments : Not applicable.

## Section 15. Regulatory information

### [National Inventory List](#)

Canada inventory ( DSL ) : All components are listed or exempted.

## Section 16. Other information

### [Hazardous Material Information System \(U.S.A.\)](#)

Health : 2 \* Flammability : 2 Physical hazards : 1  
(\* ) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

### [National Fire Protection Association \(U.S.A.\)](#)

Health : 2 Flammability : 2 Instability : 1

Date of issue/Date of revision : 3 September 2023

Organization that prepared the SDS : EHS

### [Key to abbreviations](#)

: ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
N/A = Not available  
SGG = Segregation Group  
UN = United Nations

▣ Indicates information that has changed from previously issued version.

### [Disclaimer](#)

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.