SAFETY DATA SHEET



The information in this Safety Data Sheet is required pursuant to Hazardous Product Regulations 2015.

Date of issue/Date of revision 4 September 2023 Version 3.01

Section 1. Identification				
Product name	: PITT-TECH PLUS EP DTM ACRYLIC SEMI-GLOSS MIDTONE BASE			
Product code	: 00445814			
Other means of identification	: Not available.			
Product type	: Liquid.			
Relevant identified uses of the substance or mixture and uses advised against				
Product use	: Professional applications, Used by spraying.			
Use of the substance/ mixture	: Coating.			
Uses advised against	: Not applicable.			
Supplier	 PPG Architectural Coatings Canada, Inc. 1550, rue Ampère, bureau 500 Boucherville (Québec) J4B 7L4 Canada +1 450-655-3121 			
	PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272			
Emergency telephone number	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)			
Technical Phone Number	: 888-977-4762			

Section 2. Hazard identification

Classification of the substance or mixture	: CARCINOGENICITY - Category 2
	This product contains TiO2 which has been classified as a GHS Carcinogen Category 2 based on its IARC 2B classification. For many products, TiO2 is utilized as a raw material in a liquid coating formulation. In this case, the TiO2 particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of TiO2 when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/or engineering controls (see Section 8).
GHS label elements	

Product name PITT-TECH PLUS EP DTM ACRYLIC SEMI-GLOSS MIDTONE BASE

Section 2. Hazard identification

ŝ,

Hazard pictograms



Signal word Hazard statements	/arning uspected of causing cancer.	
Precautionary statements		
Prevention	btain special instructions before use. Do not handle until all safety precat ave been read and understood. Wear protective gloves, protective clothir ye or face protection.	
Response	exposed or concerned: Get medical advice or attention. hotosensitive agents : In case of accidental eye contact, avoid direct expo le sun or other sources of UV light as severe irritation including burns may hese reactions can be delayed – get medical attention if pain, irritation or ccurs after contact. In case of accidental skin contact, avoid direct exposu- un or other sources of UV light as severe irritation including burns may re- hese reactions can be delayed – get medical attention if pain, irritation, ra istering occurs after contact.	y result. blistering ure to the sult.
Storage	tore locked up.	
Disposal	ispose of contents and container in accordance with all local, regional, na nd international regulations.	tional
Supplemental label elements	ontains isothiazolinones. May cause allergic reaction. Sanding and grind ay be harmful if inhaled. Emits toxic fumes when heated.	ing dusts
	ercentage of the mixture consisting of ingredient(s) of unknown acute tox 7.8% (oral), 27.8% (dermal), 33% (inhalation)	icity:

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Product name	: PITT-TECH PLUS EP DTM ACRYLIC SEMI-GLOSS MIDTONE BASE
Other means of identification	: Not available.

CAS number/other identifiers

Ingredient name	Synonyms	% (w/w)	CAS n	umber
Manium dioxide	Titanium oxide; Titanium oxide (TiO2); Cl 77891; Titanium peroxide; Rutile; C.I. Pigment White 6; titanium dioxide coated with isopropoxytitanium triisostearate, containing by weight 1,5 % or more but not more than 2,5 % of isopropoxytitanium triisostearate; glass flakes (CAS RN 65997-17-3): — of a thickness of 0,3 μ m or more but not more than 10 μ m, and — coated with titanium dioxide (CAS RN 13463-67-7) or iron oxide (CAS RN 18282- 10-5); titanium dioxide, other than those of heading 3206 11 00; C.I. 77891; E 171; titanium(IV) oxide, other than those of heading 3206 11 00	7 - 13*	13463-	67-7
		C	anada	Page: 2/13

Section 3. Composition/information on ingredients

Nepheline syenite	potassium, sodium, oxido-oxo- oxoalumanyloxysilane	1 - 5*	37244-96-5
barium sulfate	Sulfuric acid, barium salt (1:1); CI 77120; Barytes; Barium salt of sulfuric acid; Barite; Artificial barite; barium sulphate; C. I. Pigment White 21; barium sulfate, natural; blanc fixe; C.I. 77120	1 - 5*	7727-43-7
Propane-1,2-diol, propoxylated (MW<2000)	Poly[oxy(methyl-1,2-ethanediyl)], .alpha hydroomegahydroxy-; Poly[oxy(methyl- 1,2-ethanediyl)], α -hydro- ω -hydroxy-; Polypropylene glycol; α -hydro- ω - hydroxypoly(oxypropylene); PPO; polymethyloxirane; polyoxypropylene; polypropylene glycol; poly[oxy(methane- 1,2-ethanediyl)]; propylene glycol polyol; poly(1,2-epoxypropane); polypropylene oxide polyols; PO polyols; poly(propylene oxyde); poly(propene oxide); poly (oxypropylene); α -hydro- ω -hydroxypoly [oxy(methane-1,2-ethanediyl)]; Laprol 702; Polypropylene glycol 150	1 - 5*	25322-69-4
2-(2-butoxyethoxy)ethanol	diethylene glycol monobutyl ether; Ethanol, 2-(2-butoxyethoxy)-; DIETHYLENE GLYCOL BUTYL ETHER; Butyldiglycol; Diethylene glycol, monobutyl ether; Butyl carbitol; butyldigol; DEGBE; DIETHYLENE GLYCOL MONO- N-BUTYL ETHER; BUTOXYDIGLYCOL; DEGBE; Diglycol monobutyl ether	0.5 - 1.5*	112-34-5
benzophenone	Methanone, diphenyl-; Phenyl ketone; alpha-Oxodiphenylmethane; DIPHENYLMETHANONE; Diphenyl ketone; Benzoylbenzene; Benzophenon krist; Benzene, benzoyl-; alpha-Oxoditane; benzofenon	0.1 - 1*	119-61-9

*Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

SUB codes represent substances without registered CAS Numbers.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Description of necessary first aid measures

contact lenses, irrigate copiously with clean, fresh water, holding the apart for at least 10 minutes and seek immediate medical advice. of accidental eye contact, avoid direct exposure to the sun or other sources ht as severe irritation including burns may result. These reactions can be – get medical attention if pain, irritation or blistering occurs after contact.
to fresh air. Keep person warm and at rest. If not breathing, if breathing is or if respiratory arrest occurs, provide artificial respiration or oxygen by personnel.
contaminated clothing and shoes. Wash skin thoroughly with soap and use recognized skin cleanser. Do NOT use solvents or thinners. of accidental skin contact, avoid direct exposure to the sun or other sources ht as severe irritation including burns may result. These reactions can be – get medical attention if pain, irritation, rash or blistering occurs after
wed, seek medical advice immediately and show this container or label. rson warm and at rest. Do NOT induce vomiting.
and delayed

Potential acute health effects : No known significant effects or critical hazards. Eye contact : No known significant effects or critical hazards. Inhalation **Skin contact** : No known significant effects or critical hazards. : No known significant effects or critical hazards. Ingestion **Over-exposure signs/symptoms** Eye contact : No specific data. Inhalation : No specific data. **Skin contact** : No specific data.

: No specific data.

3	
Indication of immediate med	lical attention and special treatment needed, if necessary
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Indestion

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides sulfur oxides metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protec	tiv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	<u>ont</u>	ainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and

collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Product name PITT-TECH PLUS EP DTM ACRYLIC SEMI-GLOSS MIDTONE BASE

Section 6. Accidental release measures

		Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Special precautions	:	If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits			
Manium dioxide	CA British Columbia Provincial (Canada, 6/2022). [Titanium dioxide] TWA: 10 mg/m ³ 8 hours. Form: Total dust TWA: 3 mg/m ³ 8 hours. Form: Total dust fraction CA Quebec Provincial (Canada, 6/2022). TWAEV: 10 mg/m ³ 8 hours. Form: Total dust. CA Alberta Provincial (Canada, 6/2018). Skin sensitizer. 8 hrs OEL: 10 mg/m ³ 8 hours. CA Ontario Provincial (Canada, 6/2019). TWA: 10 mg/m ³ 8 hours. Form: total dust CA Saskatchewan Provincial (Canada, 7/2013). STEL: 20 mg/m ³ 15 minutes. TWA: 10 mg/m ³ 8 hours.			
Nepheline syenite barium sulfate	CA Ontario Provincial (Canada, 6/2019). TWA: 10 mg/m ³ 8 hours. Form: Total dust CA British Columbia Provincial (Canada, 6/2022). TWA: 5 mg/m ³ 8 hours. Form: Inhalable CA Ontario Provincial (Canada, 6/2019). TWA: 5 mg/m ³ 8 hours. Form: Inhalable particulate matter.			
	Canada, 6/2018). CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 10 mg/m ³ 8 hours. CA Quebec Provincial (Canada, 6/2022). Canada Page: 6/13			

Product name PITT-TECH PLUS EP DTM ACRYLIC SEMI-GLOSS MIDTONE BASE

Section 8. Exposure controls/personal protection

		TWAEV: 5 mg/m ³ 8 hours. Form: inhalable
		dust CA Saskatchewan Provincial (Canada, 7/2013). STEL: 20 mg/m³ 15 minutes. TWA: 10 mg/m³ 8 hours.
Propane-1,2-diol, propoxylate 2-(2-butoxyethoxy)ethanol	d (MW<2000)	None. CA Ontario Provincial (Canada, 6/2019). TWA: 10 ppm 8 hours. Form: Inhalable fraction and vapour.
benzophenone		None.
Consult local authorities for	acceptable exposure limits.	
Recommended monitoring procedures		to appropriate monitoring standards. Reference to ts for methods for the determination of hazardous uired.
Appropriate engineering controls	local exhaust ventilation or	e dust, fumes, gas, vapor or mist, use process enclosures other engineering controls to keep worker exposure to ow any recommended or statutory limits.
Environmental exposure controls	they comply with the require cases, fume scrubbers, filte	or work process equipment should be checked to ensure ements of environmental protection legislation. In some ers or engineering modifications to the process ry to reduce emissions to acceptable levels.
Individual protection measu	' <u>es</u>	
Hygiene measures	eating, smoking and using Appropriate techniques sho	d face thoroughly after handling chemical products, before the lavatory and at the end of the working period. buld be used to remove potentially contaminated clothing. ng before reusing. Ensure that eyewash stations and the workstation location.
Eye/face protection	: Safety glasses with side sh	
Skin protection		
Hand protection	be worn at all times when h this is necessary. Conside check during use that the g should be noted that the tin different for different glove	ious gloves complying with an approved standard should nandling chemical products if a risk assessment indicates ring the parameters specified by the glove manufacturer, gloves are still retaining their protective properties. It ne to breakthrough for any glove material may be manufacturers. In the case of mixtures, consisting of otection time of the gloves cannot be accurately
Gloves	: polyethylene	
Body protection		nent for the body should be selected based on the task sks involved and should be approved by a specialist ct.
Other skin protection		any additional skin protection measures should be being performed and the risks involved and should be ofore handling this product.

Section 8. Exposure controls/personal protection

Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
------------------------	--

Section 9. Physical and chemical properties

<u>Appearance</u>			
Physical state		Liquid.	
Color	÷	White.	
Odor	4	Characteristic.	
Odor threshold	1	Not available.	
рН	÷	Not available.	
Melting point		Not available.	
Boiling point		>37.78°C (>100°F)	
Flash point	1	Closed cup: 95°C (203°F)	
Auto-ignition temperature	1	Not available.	
Decomposition temperature	1	Not available.	
Flammability	1	Not available.	
Lower and upper explosive (flammable) limits	:	Not available.	
Evaporation rate	:	Not available.	
Vapor pressure	:	Not available.	
Vapor density	:	Not available.	
Relative density	:	1.15	
Density(lbs / gal)	:	9.6	
Solubility(ies)		Media	Result
Solubility(les)	1	cold water	Partially soluble
Partition coefficient: n- octanol/water	:	Not applicable.	
Viscosity	:	Kinematic (40°C (104°F)): 3	>21 mm²/s (>21 cSt)
Volatility	:	61% (v/v), 52.331% (w/w)	
% Solid. (w/w)	:	47.669	

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
	Canada Page: 8/13

Product name PITT-TECH PLUS EP DTM ACRYLIC SEMI-GLOSS MIDTONE BASE

Section 10. Stability and reactivity

Refer to protective measures listed in sections 7 and 8.

Incompatible materials	:	Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	:	Depending on conditions, decomposition products may include the following materials carbon oxides sulfur oxides metal oxide/oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
titanium dioxide	LC50 Inhalation Dusts and mists	Rat	>6.82 mg/l	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Nepheline syenite	LC50 Inhalation Dusts and mists	Rat	>5.07 mg/l	4 hours
	LD50 Dermal	Rat	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
barium sulfate	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Propane-1,2-diol,	LD50 Dermal	Rabbit	>10000 mg/kg	-
propoxylated (MW<2000)				
	LD50 Oral	Rat	1000 mg/kg	-
2-(2-butoxyethoxy)ethanol	LD50 Dermal	Rabbit	2700 mg/kg	-
	LD50 Oral	Rat	4500 mg/kg	-
benzophenone	LD50 Dermal	Rabbit	3.535 g/kg	-
	LD50 Oral	Rat	>10 g/kg	-
Conclusion/Summary	: There are no data available on	the mixture it	self	•

Conclusion/Summary	: There are no data available on the mixture itself.			able on the mixture itself.
Irritation/Corrosion				
Conclusion/Summary				
Skin	: 1	There are no	data avail	able on the mixture itself.
Eyes	11	There are no	data avail	able on the mixture itself.
Respiratory	1	There are no	data avail	able on the mixture itself.
Sensitization				
Skin	: 1	There are no	data avail	able on the mixture itself.
Respiratory	: 1	There are no data available on the mixture itself.		
<u>Mutagenicity</u>				
Conclusion/Summary	: 1	There are no	data avail	able on the mixture itself.
Carcinogenicity				
Conclusion/Summary	: 1	There are no	data avail	able on the mixture itself.
Classification				
Product/ingredient name		OSHA	IARC	NTP
tifanium dioxide		-	2B	-

Product/ingredient nameOSHAIARCNTPIffanium dioxide
benzophenone-2B
--2B--

Carcinogen Classification code:

Product name PITT-TECH PLUS EP DTM ACRYLIC SEMI-GLOSS MIDTONE BASE

Section 11. Toxicological information

IARC: 1, 2A, 2B, 3	, 4
NTP: Known to b	e a human carcinogen; Reasonably anticipated to be a human carcinogen
OSHA: +	
Not listed/not reg	ulated: -
Reproductive toxicity	
Conclusion/Summary	: There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
benzophenone	Category 2	oral	kidneys, liver

Target organs

: Contains material which may cause damage to the following organs: blood, lungs, liver, upper respiratory tract, skin, eyes, central nervous system (CNS).

Aspiration hazard

Not available.

Information on the likely routes of exposure

Potential acute health effects

Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Conclu	sion/Summary	: There are no data available on the mixture itself. Contains isothiazolinones. May cause allergic reaction. This product contains TiO2 which has been classified as a GHS Carcinogen Category 2 based on its IARC 2B classification. For many products, TiO2 is utilized as a raw material in a liquid coating formulation. In this case, the TiO2 particles are bound in a matrix with no meaningful potential for human exposure to unbound particles of TiO2 when the product is applied with a brush or roller. Sanding the coating surface or mist from spray applications may be harmful depending on the duration and level of exposure and require the use of appropriate personal protective equipment and/or engineering controls (see Section 8). Acrylate components of the mixture have irritating properties. Prolonged or repeated contact with skin or mucous membrane may result in irritation symptoms, such as redness, blistering, dermatitis etc. May cause allergic skin reactions with
--------	--------------	--

Canada Page: 10/13

Product name PITT-TECH PLUS EP DTM ACRYLIC SEMI-GLOSS MIDTONE BASE

Section 11. Toxicological information

	peated exposure. The inhalation of airborne droplets or aerosols mitation of the respiratory tract. Ingestion may cause nausea, weaknertral nervous system effects. If splashed in the eyes, the liquid maintation and reversible damage. This takes into account, where knowed immediate effects and also chronic effects of components from sing-term exposure by oral, inhalation and dermal routes of exposure ontact.	ess and y cause wn, delayed short-term and		
Short term exposure				
Potential immediate effects	here are no data available on the mixture itself.			
Potential delayed effects	here are no data available on the mixture itself.			
Long term exposure				
Potential immediate effects	here are no data available on the mixture itself.			
Potential delayed effects	here are no data available on the mixture itself.			
Potential chronic health effects				
General	o known significant effects or critical hazards.			
Carcinogenicity	uspected of causing cancer. Risk of cancer depends on duration an posure.	nd level of		
Mutagenicity	o known significant effects or critical hazards.			
Reproductive toxicity	o known significant effects or critical hazards.			

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
TT-TECH PLUS EP DTM ACRYLIC SEMI- GLOSS MIDTONE BASE	35921.6	54165.5	N/A	N/A	N/A
barium sulfate	N/A	2500	N/A	N/A	N/A
Propane-1,2-diol, propoxylated (MW<2000)	1000	N/A	N/A	N/A	N/A
2-(2-butoxyethoxy)ethanol	4500	2700	N/A	N/A	N/A
benzophenone	N/A	3535	N/A	N/A	N/A

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
	Acute LC50 >100 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 >100 mg/l	Fish	96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Date of issue 4 September 2023 Version 3.01

Product name PITT-TECH PLUS EP DTM ACRYLIC SEMI-GLOSS MIDTONE BASE

Section 12. Ecological information

Product/ingredient name	LogPow	BCF	Potential
Propane-1,2-diol, propoxylated (MW<2000)	-0.68 to 0.01	-	Low
2-(2-butoxyethoxy)ethanol benzophenone	1 3.18	- 12.02	Low Low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Section 13. Disposal considerations

```
Disposal methods
```

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

Section 14. Transport information

	TDG	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class (es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

Additional information

IMDG

- **TDG** : None identified.
 - : None identified.
- IATA : None identified.

Product name PITT-TECH PLUS EP DTM ACRYLIC SEMI-GLOSS MIDTONE BASE

Section 14. Transport information

Special precautions for user :	Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
Transport in bulk according : to IMO instruments	Not applicable.

Section 15. Regulatory information

National Inventory List

Canada inventory (DSL) : All components are listed or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health : 2 * Flammability : 1 Physical hazards : 0 (*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)

Health : 2 Flammabi Date of issue/Date of revision	ility : 1 Instability : 0 4 September 2023
Organization that prepared the SDS	: EHS
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.