SAFETY DATA SHEET



The information in this Safety Data Sheet is required pursuant to Hazardous Product Regulations 2015.

Date of issue/Date of revision 10 September 2023

Version 5.01

Section 1. Identification

Product name : PSX 700 CURE US
Product code : PX700-B-04.04
Other means of : Not available.

identification

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications.

Use of the substance/

mixture

: Coating.

Uses advised against : Not applicable.

Supplier : PPG Architectural Coatings Canada, Inc.

1550, rue Ampère, bureau 500 Boucherville (Québec) J4B 7L4

Canada

+1 450-655-3121

PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272 : (412) 434-4515 (U.S.)

Emergency telephone

<u>number</u>

(514) 645-1320 (Canada)

SETIQ Interior de la República: 800-00-214-00 (México) SETIQ Ciudad de México: (55) 5559-1588 (México)

Technical Phone Number: 888-977-4762

Section 2. Hazard identification

Classification of the substance or mixture

: ACUTE TOXICITY (oral) - Category 4 SKIN CORROSION - Category 1B SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1B GERM CELL MUTAGENICITY - Category 2 TOXIC TO REPRODUCTION - Category 1

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

Health Hazards Not Otherwise Classified - Category 1

GHS label elements

Canada Page: 1/14

Section 2. Hazard identification

Hazard pictograms







Signal word

Hazard statements

: Danger

: Harmful if swallowed.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.
Suspected of causing genetic defects.
May damage fertility or the unborn child.

Causes damage to organs.

Causes damage to organs through prolonged or repeated exposure. (immune system)

Causes digestive tract burns.

Prolonged or repeated contact may dry skin and cause irritation.

Precautionary statements

Prevention

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

Response

: IF exposed or concerned: Call a POISON CENTER or doctor. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

Storage Disposal

: Store locked up.

Supplemental label elements

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

: Do not taste or swallow. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapor/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. This product either contains formaldehyde or is capable of releasing formaldehyde above 0.5 ppm under certain conditions. Formaldehyde is a known cancer hazard, a skin sensitizer and a respiratory sensitizer. Avoid contact with skin and clothing. Wash thoroughly after handling. Emits toxic fumes when heated

Percentage of the mixture consisting of ingredient(s) of unknown acute inhalation toxicity: 7%

Canada Page: 2/14

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Product name : PSX 700 CURE US

Other means of : Not available.
identification

CAS number/other identifiers

Ingredient name	Synonyms	% (w/w)	CAS number
3-aminopropyltriethoxysilane	1-Propanamine, 3-(triethoxysilyl)-; aminopropyltriethoxysilane; 3- (Triethoxysilyl) propylamine; gamma-Aminopropyltriethoxysilane; 1-Propanamine, 3-triethoxysilyl-; γ-Aminopropyltriethoxysilane; Aminoalkylalkoxysilane [alkyl (C1-3), alkoxy (C1-2)]; 1-Propylamine, 3- (triethoxysilyl)-; 3-(Triethoxysilyl)-1-propanamine; UC-A 1100; NUCA 1100	80 - 100*	919-30-2
dibutylbis(pentane-2,4-dionato-O,O')tin	dibutylbis(pentane-2,4-dionato-O,O')tin; Tin, dibutylbis(2,4-pentanedionatokappa. O2,.kappa.O4)-, (OC-6-11)-; Tin, dibutylbis(2,4-pentanedionato-O,O')-, (OC-6-11)-; Tin, dibutylbis(2,4-pentanedionatokappa.O,.kappa.O')-, (OC-6-11)-; dibutyl{bis[4-(hydroxy-κO)pent-3-en-2-onato-κO]}tin; Dibutyltin bis (acetylacetonate); Dibutylbis (2,4-pentanedionato)tin(IV); Tin, dibutylbis (2,4-pentanedionato-κO2,κO4)-, (OC-6-11)-	3 - 7*	22673-19-4
ethanol	ethyl alcohol; ALCOHOL; Ethyl alcohol (Ethanol); EtOH; Grain alcohol; Cologne spirit; undenatured ethyl alcohol, of an alcoholic strength by volume of 80 % or more and containing up to 20 % activated carbon; mixture, consisting of ethyl alcohol, isopropanol, n-propanol and small quantities of other organic products; Denatured Alcohol; METHYLCARBINOL; 1-HYDROXYETHANE	0.5 - 1.5*	64-17-5

^{*}Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

SUB codes represent substances without registered CAS Numbers.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Canada Page: 3/14

Product code PX700-B-04.04
Product name PSX 700 CURE US

Section 4. First-aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Description of necessary first aid measures

Eye contact: Check for and remove any contact lenses. Immediately flush eyes with running

water for at least 15 minutes, keeping eyelids open. Seek immediate medical

attention.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

Skin contact: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognized skin cleanser. Do NOT use solvents or thinners.

Ingestion: If swallowed, seek medical advice immediately and show this container or label.

Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : No known significant effects or critical hazards.

Skin contact: Causes severe burns. Causes damage to organs following a single exposure in

contact with skin. Defatting to the skin. May cause an allergic skin reaction.

Ingestion : Harmful if swallowed. Corrosive to the digestive tract. Causes burns. Causes

damage to organs following a single exposure if swallowed.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

pain watering redness

Inhalation : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact: Adverse symptoms may include the following:

pain or irritation

redness dryness cracking

blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion : Adverse symptoms may include the following:

stomach pains reduced fetal weight increase in fetal deaths skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : No specific treatment.

Canada Page: 4/14

Product code PX700-B-04.04 **Product name PSX 700 CURE US**

Section 4. First-aid measures

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media

: None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products : Decomposition products may include the following materials:

carbon oxides nitrogen oxides metal oxide/oxides Formaldehyde.

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without

suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is

inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the

information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

> Page: 5/14 Canada

Section 6. Accidental release measures

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Special precautions

: Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Vapors are heavier than air and may spread along floors. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

including any incompatibilities

Conditions for safe storage, : Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters Occupational exposure limits

> Canada Page: 6/14

Section 8. Exposure controls/personal protection

Ingredient name	Exposure limits
3-aminopropyltriethoxysilane dibutylbis(pentane-2,4-dionato-O,O')tin	None. CA Alberta Provincial (Canada, 6/2018). [Tin Organic compounds as Sn] Absorbed through skin. 15 min OEL: 0.2 mg/m³, (as Sn) 15 minutes. 8 hrs OEL: 0.1 mg/m³, (as Sn) 8 hours. CA British Columbia Provincial (Canada, 6/2022). [Tin - Organic compounds as Sn] Absorbed through skin. TWA: 0.1 mg/m³, (as Sn) 8 hours. STEL: 0.2 mg/m³, (as Sn) 15 minutes. CA Quebec Provincial (Canada, 6/2022). [Tin Organic compounds] Absorbed through skin. TWAEV: 0.1 mg/m³, (as Sn) 8 hours. STEV: 0.2 mg/m³, (as Sn) 15 minutes. CA Ontario Provincial (Canada, 6/2019). [Tin (Organic compounds) as Sn] Absorbed through skin. TWA: 0.1 mg/m³, (as Sn) 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). [Tin organic compounds as Sn] Absorbed through skin. STEL: 0.2 mg/m³, (measured as Sn) 15 minutes. TWA: 0.1 mg/m³, (measured as Sn) 8 hours.
ethanol	CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 1000 ppm 8 hours. 8 hrs OEL: 1880 mg/m³ 8 hours. CA British Columbia Provincial (Canada, 6/2022). STEL: 1000 ppm 15 minutes. CA Ontario Provincial (Canada, 6/2019). STEL: 1000 ppm 15 minutes. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 1250 ppm 15 minutes. TWA: 1000 ppm 8 hours. CA Quebec Provincial (Canada, 6/2022). STEV: 1000 ppm 15 minutes.

Consult local authorities for acceptable exposure limits.

procedures

Recommended monitoring : Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

> Canada Page: 7/14

Section 8. Exposure controls/personal protection

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection
Skin protection
Hand protection

: Chemical splash goggles and face shield.

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately

estimated.

Gloves
Body protection

nitrile neoprenePersonal protective equipment for the body should be selected based on the task

being performed and the risks involved and should be approved by a specialist

before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Respiratory protection

: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid.

Color : Not available.

Odor : Characteristic.

Odor threshold : Not available.

pH : Not applicable.

Melting point : Not available.

Boiling point : >37.78°C (>100°F)

Flash point : Closed cup: 96.11°C (205°F)

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Flammability : Not available.

Canada Page: 8/14

Product name PSX 700 CURE US

Section 9. Physical and chemical properties

Lower and upper explosive

(flammable) limits

: Not available.

Evaporation rate: Not available.Vapor pressure: Not available.Vapor density: Not available.

Relative density : 0.96 Density (lbs / gal) : 8.01

Solubility(ies) : Media Result

cold water Not soluble

Partition coefficient: n-

octanol/water

: Not applicable.

Viscosity : Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)

Volatility : 2% (v/v), 1.86% (w/w)

% Solid. (w/w) : 98.14

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid

: When exposed to high temperatures may produce hazardous decomposition products.

Refer to protective measures listed in sections 7 and 8.

Incompatible materials

: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

Hazardous decomposition products

: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides Formaldehyde. metal oxide/oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
3-aminopropyltriethoxysilane	LC50 Inhalation Dusts and mists	Rat	>7.35 mg/l	4 hours
	LD50 Dermal	Rabbit	4 g/kg	-
	LD50 Oral	Rat	1.57 g/kg	-
dibutylbis(pentane-	LD50 Dermal	Rat	>2000 mg/kg	-
2,4-dionato-O,O')tin				
,	LD50 Oral	Rat	1864 mg/kg	-
ethanol	LC50 Inhalation Vapor	Rat	124700 mg/m ³	4 hours
	LD50 Dermal	Rat	17100 mg/kg	-
	LD50 Oral	Rat	7 g/kg	-

Canada Page: 9/14

Section 11. Toxicological information

Conclusion/Summary

: There are no data available on the mixture itself.

Irritation/Corrosion
Conclusion/Summary

Skin: There are no data available on the mixture itself.Eyes: There are no data available on the mixture itself.Respiratory: There are no data available on the mixture itself.

Sensitization

3	Route of exposure	Species	Result
3-aminopropyltriethoxysilane	skin	Guinea pig	Sensitizing

Skin : There are no data available on the mixture itself.Respiratory : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary: There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary: There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary: There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Name	3.3	Route of exposure	Target organs
dibutylbis(pentane-2,4-dionato-O,O')tin	Category 1	-	-

Specific target organ toxicity (repeated exposure)

Name	3.3	Route of exposure	Target organs
dibutylbis(pentane-2,4-dionato-O,O')tin	Category 1	-	immune system

Target organs

: Contains material which causes damage to the following organs: brain.

Contains material which may cause damage to the following organs: blood, kidneys, the reproductive system, liver, bladder, gastrointestinal tract, upper respiratory tract, immune system, skin, central nervous system (CNS), eye, lens or cornea.

Aspiration hazard

Not available.

Information on the likely routes of exposure

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : No known significant effects or critical hazards.

Skin contact : Causes severe burns. Causes damage to organs following a single exposure in contact with skin. Defatting to the skin. May cause an allergic skin reaction.

Canada Page: 10/14

Product name PSX 700 CURE US

Section 11. Toxicological information

Ingestion

: Harmful if swallowed. Corrosive to the digestive tract. Causes burns. Causes damage to organs following a single exposure if swallowed.

Over-exposure signs/symptoms

Eye contact: Adverse symptoms may include the following:

pain watering redness

Inhalation : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact: Adverse symptoms may include the following:

pain or irritation redness dryness

cracking blistering may occur reduced fetal weight increase in fetal deaths

Ingestion : Adverse symptoms may include the following:

stomach pains reduced fetal weight increase in fetal deaths skeletal malformations

skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Conclusion/Summary

: There are no data available on the mixture itself. This product either contains formaldehyde or is capable of releasing formaldehyde above 0.5 ppm under certain conditions. Formaldehyde is a known cancer hazard, a skin sensitizer and a respiratory sensitizer. Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. There is some evidence that repeated exposure to organic solvent vapors in combination with constant loud noise can cause greater hearing loss than expected from exposure to noise alone. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and longterm exposure by oral, inhalation and dermal routes of exposure and eye contact.

Short term exposure

Potential immediate

effects

effects

: There are no data available on the mixture itself.

Potential delayed effects

Long term exposure

: There are no data available on the mixture itself.

Potential immediate

ı.e

There are no data available on the mixture itself.

Potential delayed effects

: There are no data available on the mixture itself.

Canada Page: 11/14

Section 11. Toxicological information

Potential chronic health effects

General : Causes damage to organs through prolonged or repeated exposure. Prolonged or

repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : Suspected of causing genetic defects.Reproductive toxicity : May damage fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
PSX 700 CURE US	1618.0	3908.8	N/A	N/A	N/A
3-aminopropyltriethoxysilane	1570	4000	N/A	N/A	N/A
dibutylbis(pentane-2,4-dionato-O,O')tin	1864	2500	N/A	N/A	N/A
ethanol	7000	17100	N/A	124.7	N/A

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
3-aminopropyltriethoxysilane ethanol	<u> </u>	Fish Daphnia - <i>Daphnia magna</i>	96 hours 48 hours

Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
ethanol	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
3-aminopropyltriethoxysilane	1.7	3.4	Low
ethanol	-0.35	-	Low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Canada Page: 12/14

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release

Section 14. Transport information

	TDG	IMDG	IATA
UN number	UN3066	UN3066	UN3066
UN proper shipping name	PAINT	PAINT	PAINT
Transport hazard class (es)	8	8	8
Packing group	III	III	III
Environmental hazards	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	(dibutylbis(pentane- 2,4-dionato-O,O')tin)	(dibutylbis(pentane- 2,4-dionato-O,O')tin)	Not applicable.

Additional information

TDG : The marine pollutant mark is not required when transported by road or rail.

IMDG : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.

: The environmentally hazardous substance mark may appear if required by other transportation IATA

regulations.

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according: Not applicable. to IMO instruments

Proof of classification

statement

: Product classified as per the following sections of the Transportation of Dangerous

Goods Regulations: 2.40-2.42 (Class 8), 2.7 (Marine pollutant mark).

Canada Page: 13/14

Date of issue 10 September 2023 Version 5.01

Product code PX700-B-04.04

Product name PSX 700 CURE US

Section 15. Regulatory information

National Inventory List

Canada inventory (DSL) : All components are listed or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health: 3 * Flammability: 1 Physical hazards: 1

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)

Health: 3 Flammability: 1 Instability: 1

Date of issue/Date of 10 September 2023

revision

Organization that prepared : EHS

the SDS

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available SGG = Segregation Group UN = United Nations

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

Canada Page: 14/14