SAFETY DATA SHEET

Date of issue/Date of revision

: 25 October 2023



Version : 7 SECTION 1: Identification of the substance/mixture and of the company/ undertaking **1.1 Product identifier** : PITT-CHAR XP PF HARDENER BLACK **Product name Product code** : 00281340 Other means of identification Not available. 1.2 Relevant identified uses of the substance or mixture and uses advised against : Professional applications, Used by spraying. **Product use** Use of the substance/ : Coating. mixture : Product is not intended, labelled or packaged for consumer use. Uses advised against 1.3 Details of the supplier of the safety data sheet Sigma Coatings PTY 9 Arnold Street, Alrode, Alberton, Gauteng South Africa Tel: 0027 11 389 4800 e-mail address of person : PS.ACEMEA@ppg.com responsible for this SDS **1.4 Emergency telephone** : +27 51 444 2134 number **SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture **Product definition** : Mixture Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2, H351 Repr. 2, H361f STOT RE 2, H373 Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Code : 00281340	Date of issue/Date of revision : 25 October 2023
PITT-CHAR XP PF HARDENE	RBLACK
SECTION 2: Hazards	identification
Hazard pictograms	
Signal word	: Danger
Hazard statements	 Causes severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of causing cancer. Suspected of damaging fertility. May cause damage to organs through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.
Precautionary statements	
Prevention	: Wear protective gloves, protective clothing and eye or face protection. Avoid release to the environment. Do not breathe vapour.
Response	: Collect spillage. IF INHALED: Immediately call a POISON CENTER or doctor.
Storage	: Not applicable.
Disposal	 Dispose of contents and container in accordance with all local, regional, national and international regulations. P280, P273, P260, P391, P304 + P310, P501
Hazardous ingredients	 Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines 1,3,5-triazine-2,4,6-triamine 2,4,6-tris(dimethylaminomethyl)phenol 3,6-diazaoctanethylenediamin N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide)
Supplemental label elements	: Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Special packaging requirem	<u>ients</u>
Containers to be fitted with child-resistant fastenings	: Not applicable.
Tactile warning of danger	: Not applicable.
2.3 Other hazards	
Product meets the criteria for PBT or vPvB	: ₱his mixture does not contain any substances that are assessed to be a PBT or a vPvE
Other hazards which do	: Causes digestive tract burns.

Other hazards which do not result in classification

: Zauses digestive tract burns.

Code : 00281340

Date of issue/Date of revision

: 25 October 2023

PITT-CHAR XP PF HARDENER BLACK

SECTION 3: Composition/information on ingredients

3.2 Mixtures

: Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines	CAS: 68410-23-1	≥50 - ≤75	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Chronic 2, H411	-	[1]
1,3,5-triazine-2,4,6-triamine	REACH #: 01-2119485947-16 EC: 203-615-4 CAS: 108-78-1 Index: 613-345-00-2	≥10 - ≤25	Carc. 2, H351 Repr. 2, H361f STOT RE 2, H373 (urinary system)	-	[1] [3]
4,4'-Isopropylidenediphenol, ethoxylated	EC: polymer CAS: 32492-61-8 (EO> 4.5 moles)	≥5.0 - ≤10	Aquatic Chronic 3, H412	-	[1]
2,4,6-tris (dimethylaminomethyl) phenol	REACH #: 01-2119560597-27 EC: 202-013-9 CAS: 90-72-2 Index: 603-069-00-0	≥5.0 - ≤10	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1C, H314 Eye Dam. 1, H318	ATE [Oral] = 1200 mg/ kg ATE [Dermal] = 1280 mg/kg	[1]
3,6-diazaoctanethylenediamin	EC: 203-950-6 CAS: 112-24-3 Index: 612-059-00-5	≥1.0 - <5.0	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412	ATE [Oral] = 1716 mg/ kg ATE [Dermal] = 1465 mg/kg	[1] [2]
N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan- 1-amide)	REACH #: 01-2119978265-26 EC: 204-613-6 CAS: 123-26-2	≤0.30	Skin Sens. 1B, H317 Aquatic Chronic 3, H412	-	[1] [2]
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. <u>Type</u>

Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Code: 00281340Date of issue/Date of revision: 25 October 2023PITT-CHAR XP PF HARDENER BLACK

SECTION 4: First aid measures

4.1 Description of first aid m	easures
Eye contact	: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Inhalation	 Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

4.2 Wost important sy	iptonis and enects, both acute and delayed
Potential acute health	effects
Eye contact	: Causes serious eye damage.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes severe burns. May cause an allergic skin reaction.
Ingestion	: 🖉 orrosive to the digestive tract. Causes burns.
Over-exposure signs/	symptoms
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: Adverse symptoms may include the following: reduced foetal weight increase in foetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced foetal weight increase in foetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: stomach pains reduced foetal weight increase in foetal deaths skeletal malformations
4.3 Indication of any in	mediate medical attention and special treatment needed
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.

Code	: 00281340	Date of issue/Date of revision	: 25 October 2023
PITT-CHAR X	(P PF HARDENER BLACK		

SECTION 5: Firefighting measures

•		
5.1 Extinguishing media Suitable extinguishing media	:	Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	:	None known.
5.2 Special hazards arising fi	rom	the substance or mixture
Hazards from the substance or mixture	:	In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	:	Decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides
5.3 Advice for firefighters		
Special precautions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

		English (GB)	South Africa	5/15
Large spill	:	Stop leak if without risk. Move contained upwind. Prevent entry into sewers, wate spillages into an effluent treatment plant spillage with non-combustible, absorben diatomaceous earth and place in contain Dispose of via a licensed waste disposa may pose the same hazard as the spilt p	er courses, basements or confine or proceed as follows. Contain it material e.g. sand, earth, vermi ner for disposal according to loca I contractor. Contaminated abso	ed areas. Wash and collect iculite or I regulations.
Small spill	:	Stop leak if without risk. Move contained if water-soluble. Alternatively, or if water place in an appropriate waste disposal c disposal contractor.	r-insoluble, absorb with an inert c	lry material and
6.3 Methods and material for				
6.2 Environmental precautions	:	Avoid dispersal of spilt material and rund sewers. Inform the relevant authorities i pollution (sewers, waterways, soil or air) the environment if released in large quar	if the product has caused enviror . Water polluting material. May	mental
For emergency responders	:	If specialised clothing is required to deal Section 8 on suitable and unsuitable ma emergency personnel".		
For non-emergency personnel	:	No action shall be taken involving any per- Evacuate surrounding areas. Keep unner entering. Do not touch or walk through s Provide adequate ventilation. Wear app inadequate. Put on appropriate personal	ecessary and unprotected person spilt material. Do not breathe vap propriate respirator when ventilation	nnel from pour or mist.
6.1 Personal precautions, pro	ote	ctive equipment and emergency proce	dures	

: 00281340 Code

PITT-CHAR XP PF HARDENER BLACK

Date of issue/Date of revision

2

: 25 October 2023

SECTION 6: Accidental release measures

6.4 Reference to other sections

See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Fut on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
7.2 Conditions for safe storage, including any incompatibilities	: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
gfass, oxide, chemicals	DOL OEL (South Africa, 3/2021). [synthetic vitreous fibres [SVF]: continuous filament glass fibres] TWA: 2 f/ml 8 hours. Form: Respirable fibres: length> 5 µm; aspect ratio ≥ 3:1 as determined by the membrane filter method at 400-450X magnification (4mm objective), using phase-contrast illumination. TWA: 10 mg/m ³ 8 hours.

Code : 00281340	Date of issue/Date of revision : 25 October 2023
PITT-CHAR XP PF HARDEN	ER BLACK
Recommended monitoring procedures	: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
8.2 Exposure controls	
Appropriate engineering controls	: If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Individual protection measu	<u>ires</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection Skin protection	: Chemical splash goggles and face shield.
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Gloves	: nitrile neoprene
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Date of issue/Date of revision

: 25 October 2023

- Code : 00281340
- PITT-CHAR XP PF HARDENER BLACK

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

<u>Appearance</u>								
Physical state	:	Liquid.						
Colour	:	Black.						
Ddour	:	Aromatic.						
Ddour threshold	:	Not available.	lot available.					
Melting point/freezing point	:	May start to solidify at the following temperature: 12°C (53.6°F) This is based on data for the following ingredient: 3,6-diazaoctanethylenediamin. Weighted average: -59.91°C (-75.8°F)						
nitial boiling point and poiling range	:	>37.78°C						
Flammability	:	Not available.						
Jpper/lower flammability or explosive limits	:	Lower: 1.4% Upper:	: 1%					
Flash point	:	Closed cup: Not app	licable.					
Auto-ignition temperature		Ingredient name		°C	°F		Method	
		3,6-diazaoctanethylened	liamin	337.78	640			
Decomposition temperature	:	Stable under recomm	mended st	orage ar	nd handling c	ondition	s (see Sec	tion 7).
H	1	Not applicable. insol	uble in wa	ter.				
/iscosity	:	Kinematic (40°C): >2	21 mm²/s					
Solubility(ies)	1							
Media		Result						
cold water		Not soluble						
Partition coefficient: n-octanol/ vater	:	Not applicable.						
Vapour pressure	:		Vapour Pressu		ure at 20°C	Va	Vapour pressure at 50°	
		Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
		2,4,6-tris	0.056	0.0075	EU A.4			
		(dimethylaminomethyl) phenol						
vaporation rate	:	(dimethylaminomethyl)						
-	: :	(dimethylaminomethyl) phenol						
Relative density		(dimethylaminomethyl) phenol Not available.	e: 5.04 (A	r = 1) (3	3,6-diazaocta	nethyler	nediamin).	
Evaporation rate Relative density Vapour density Explosive properties	:	(dimethylaminomethyl) phenol Not available. 1.14	not explos	ive, but		-	,	nixture of

Oxidising properties Particle characteristics Median particle size

: Not applicable.

9.2 Other information

No additional information.

: Product does not present an oxidizing hazard.

Code	: 00281340	Date of issue/Date of revision	: 25 October 2023
PITT-CHAR >	(P PF HARDENER BLACK		

SECTION	10 :	Stability	and	reactivity
---------	-------------	-----------	-----	------------

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
10.6 Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
melamine	LC50 Inhalation Dusts and	Rat	>5190 mg/m ³	4 hours
	mists			
	LD50 Oral	Rat	3161 mg/kg	-
2,4,6-tris(dimethylaminomethyl)phenol	LD50 Dermal	Rabbit	1.28 g/kg	-
	LD50 Dermal	Rat	1280 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-
3,6-diazaoctanethylenediamin	LD50 Dermal	Rabbit	1465 mg/kg	-
•	LD50 Oral	Rat	1716 mg/kg	-
N,N'-ethane-1,2-diylbis	LC50 Inhalation Dusts and	Rat	>5.11 mg/l	4 hours
(12-hydroxyoctadecan-1-amide)	mists			
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-

Conclusion/Summary : There are no data available on the mixture itself.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2,4,6-tris(dimethylaminomethyl)phenol	Skin - Visible necrosis	Rabbit	-	4 hours	7 days

<u>Sensitisation</u>	
Respiratory	: There are no data available on the mixture itself.
Eyes	: There are no data available on the mixture itself.
Skin	: There are no data available on the mixture itself.
Conclusion/Summary	

|--|

Product/ingredient name	Route of exposure	Species	Result
Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines	skin	Mouse	Sensitising
3,6-diazaoctanethylenediamin	skin	Guinea pig	Sensitising

Conclusion/Summary

Skin

: There are no data available on the mixture itself.

English (GB)

Code : 00281340	Date of issue/Date of revision	: 25 October 2023
PITT-CHAR XP PF HARDENER BLACK		

SECTION 11: Toxicological information

Respiratory	: There are no data available on the mixture itself.
Mutagenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Carcinogenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Reproductive toxicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Teratogenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Specific target organ tox	<u>icity (single exposure)</u>
Not available.	

Specific target organ toxicity (repeated exposure)

Product/ingredient name		Category	Route of exposure	Target organs
7,3,5-triazine-2,4,6-triamine		Category 2	-	urinary system
Aspiration hazard Not available.		· · ·		
Information on likely routes of exposure	: Not available.			

Potential acute health effects

	English (GB) South Africa
Short term exposure Potential immediate effects	: Not available.
Delayed and immediate effect	cts as well as chronic effects from short and long-term exposure
Eye contact	: Adverse symptoms may include the following: pain watering redness
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced foetal weight increase in foetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: stomach pains reduced foetal weight increase in foetal deaths skeletal malformations
Inhalation	: Adverse symptoms may include the following: reduced foetal weight increase in foetal deaths skeletal malformations
•	/sical, chemical and toxicological characteristics
Eye contact	: Causes severe burns. May cause an allergic skin reaction. : Causes serious eye damage.
Ingestion Skin contact	 Corrosive to the digestive tract. Causes burns. Causes severe burns. May cause an allergic skin reaction.
Inhalation	: No known significant effects or critical hazards.
<u>i otentiai acute nealtri enecta</u>	-

- Code : 00281340
- PITT-CHAR XP PF HARDENER BLACK
- Date of issue/Date of revision

: 25 October 2023

SECTION 11: Toxicological information

		_
Potential delayed effects	:	Not available.
<u>Long term exposure</u>		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Potential chronic health effe	ect	<u>5</u>
Not available.		
Conclusion/Summary	:	Not available.
General	:	May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	1	Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	1	No known significant effects or critical hazards.
Reproductive toxicity	:	Suspected of damaging fertility.
Other information	:	Not available.
	~	

Zauses digestive tract burns. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines	EC50 4.11 mg/l Fresh water	Algae	72 hours
melamine	Acute EC50 200 mg/l	Daphnia	48 hours
2,4,6-tris(dimethylaminomethyl)phenol	Acute LC50 175 mg/l	Fish	96 hours
N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-	Acute EC50 29 to 43 mg/l	Algae -	72 hours
1-amide)		Pseudokirchneriella subcapitata	
	Acute EC50 94 mg/l	Daphnia - Daphnia magna	48 hours

Conclusion/Summary

: There are no data available on the mixture itself.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
Atty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan- 1-amide)	-	15 % - 28 days 63 % - 28 days	-	-

Conclusion/Summary : There are no data available on the mixture itself.

South Africa	11/15
	South Africa

Code : 00281340 PITT-CHAR XP PF HARDENER BLACK	Date of issue	/Date of revision	: 25 October 2023
SECTION 12: Ecological information			
Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines N.N'-ethane-1.2-divlbis(12-hvdroxvoctadecan-	-	-	Not readily Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
 <i>I</i>,3,5-triazine-2,4,6-triamine 2,4,6-tris(dimethylaminomethyl)phenol 3,6-diazaoctanethylenediamin N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan- 1-amide) 	-1.22 0.219 -1.66 to -1.4 >6	3.8 - - -	Low Low Low High

12.4 Mobility in soil

1-amide)

Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

ProductMethods of disposal: The generation of waste should be avoided or minimised wherever possible. Disposal
of this product, solutions and any by-products should at all times comply with the
requirements of environmental protection and waste disposal legislation and any
regional local authority requirements. Dispose of surplus and non-recyclable products
via a licensed waste disposal contractor. Waste should not be disposed of untreated to
the sewer unless fully compliant with the requirements of all authorities with jurisdiction.Hazardous waste: Yes.

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Code : 00281340 Date of issue/Date of revision : 25 October 2023 PITT-CHAR XP PF HARDENER BLACK

SECTION 13: Disposal considerations

Type of packaging		European waste catalogue (EWC)
Container	15 01 06	mixed packaging
Special precautions	taken when l Empty conta	I and its container must be disposed of in a safe way. Care should be handling emptied containers that have not been cleaned or rinsed out. iners or liners may retain some product residues. Avoid dispersal of spilt runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

Additional information

ADR/RID : None identified. IMDG : None identified. ΙΑΤΑ : None identified.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk : Not applicable. according to IMO instruments

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

Code: 00281340Date of issue/Date of revision: 25 October 2023PITT-CHAR XP PF HARDENER BLACK

SECTION 15: Regulatory information

Intrinsic property	Ingredient name	Status	Reference number	Date of revision
Substance of equivalent concern for human health	melamine	Candidate	D(2022) 9120-DC	1/17/2023
Substance of equivalent concern for environment	melamine	Candidate	D(2022) 9120-DC	1/17/2023

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles

Other national and international regulations.

Ozone depleting substances (1005/2009/EU)

Not listed.

- 15.2 Chemical safety
- : No Chemical Safety Assessment has been carried out.
- assessment

SECTION 16: Other information

Indicates information that	has changed from previ	ously issued version		
Abbreviations and acronyms	1272/2008] DNEL = Derived N EUH statement = 0	n, Labelling and Pac o Effect Level CLP-specific Hazard No Effect Concentra		EC) No.
Full text of abbreviated H statements	H312 Harmful i H314 Causes s H315 Causes s H317 May cause H318 Causes s H351 Suspecte H361f Suspecte H373 May cause H411 Toxic to a	f swallowed. In contact with skin. Severe skin burns an skin irritation. Se an allergic skin re serious eye damage. Ed of causing cancer ad of damaging fertili se damage to organs aquatic life with long to aquatic life with long	action. ty. s through prolonged or repeated lasting effects.	exposure.
Full text of classifications [CLP/GHS]	: Acute Tox. 4 Aquatic Chronic 2 Aquatic Chronic 3 Carc. 2 Eye Dam. 1 Repr. 2 Skin Corr. 1B Skin Corr. 1C Skin Irrit. 2 Skin Sens. 1 Skin Sens. 1A Skin Sens. 1B STOT RE 2	ACUTE TO LONG-TER LONG-TER CARCINOC SERIOUS B REPRODU SKIN CORI SKIN CORI SKIN SENS SKIN SENS SKIN SENS SKIN SENS	XICITY - Category 4 M (CHRONIC) AQUATIC HAZA M (CHRONIC) AQUATIC HAZA ENICITY - Category 2 EYE DAMAGE/EYE IRRITATION CTIVE TOXICITY - Category 2 ROSION/IRRITATION - Categor ROSION/IRRITATION - Categor ROSION/IRRITATION - Categor SITISATION - Category 1 SITISATION - Category 1 CARGET ORGAN TOXICITY - F E - Category 2	NRD - Category 3 N - Category 1 y 1B y 1C y 2
		English (GB)	South Africa	14/15

Code : 00281340	Date of issue/Date of revision	: 25 October 2023
PITT-CHAR XP PF HARDENER BLACK		

SECTION 16: Other information

: 25 October 2023
: 15 May 2018
: EHS
: 7

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.