SAFETY DATA SHEET

United Arab Emirates

Date of issue/Date of revision

: 25 October 2023

Version

: 7.01

SECTION 1: Identific undertaking	ation of the substance/mixture and of the company/
1.1 Product identifier	
Product name	: PITT-CHAR XP PF HARDENER BLACK
Product code	: 00281340
Other means of identificati	on
Not available.	
1.2 Relevant identified uses	of the substance or mixture and uses advised against
Product use	: Professional applications, Used by spraying.
Use of the substance/ mixture	: Coating.
Uses advised against	: Product is not intended, labelled or packaged for consumer use.
1.3 Details of the supplier of	the safety data sheet
Sigma Paint Saudi Arabia Lto PO Box 7509 Dammam 31472 Saudi Arabia	l.
Tel: 00966 138 47 31 00 Fax: 00966 138 47 17 34	
e-mail address of person responsible for this SDS	: ndpic@sfda.gov.sa
1.4 Emergency telephone number	: 00966 138473100 extn 1001

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Product definition : Mixture <u>Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]</u> Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2, H351 Repr. 2, H361f STOT RE 2, H373 Aquatic Chronic 2, H411 The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Code : 00281340	Date of issue/Date of revision: 25 October 2023							
PITT-CHAR XP PF HARDENE	R BLACK							
SECTION 2: Hazards identification								
Hazard pictograms								
Signal word	: Danger							
Hazard statements	 Causes severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of causing cancer. Suspected of damaging fertility. May cause damage to organs through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects. 							
Precautionary statements								
Prevention	: Wear protective gloves, protective clothing and eye or face protection. Avoid release to the environment. Do not breathe vapour.							
Response	: Collect spillage. IF INHALED: Immediately call a POISON CENTER or doctor.							
Storage	: Not applicable.							
Disposal	 Dispose of contents and container in accordance with all local, regional, national and international regulations. P280, P273, P260, P391, P304 + P310, P501 							
Hazardous ingredients	 Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines 1,3,5-triazine-2,4,6-triamine 2,4,6-tris(dimethylaminomethyl)phenol 3,6-diazaoctanethylenediamin N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide) 							
Supplemental label elements	: Not applicable.							
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.							
Special packaging requirem	ents							
Containers to be fitted with child-resistant fastenings	: Not applicable.							
Tactile warning of danger	: Not applicable.							
2.3 Other hazards								
Product meets the criteria for PBT or vPvB	: This mixture does not contain any substances that are assessed to be a PBT or a vPvI							
Other hazards which do not result in classification	: Causes digestive tract burns.							

Code : 00281340

Date of issue/Date of revision

: 25 October 2023

PITT-CHAR XP PF HARDENER BLACK

SECTION 3: Composition/information on ingredients

3.2 Mixtures

: Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines	CAS: 68410-23-1	≥50 - ≤75	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Chronic 2, H411	-	[1]
1,3,5-triazine-2,4,6-triamine	REACH #: 01-2119485947-16 EC: 203-615-4 CAS: 108-78-1 Index: 613-345-00-2	≥10 - ≤25 Carc. 2, H351 Repr. 2, H361f STOT RE 2, H373 (urinary system)		-	[1] [3]
4,4'-Isopropylidenediphenol, ethoxylated	EC: polymer CAS: 32492-61-8 (EO> 4.5 moles)	≥5.0 - ≤10	Aquatic Chronic 3, H412	-	[1]
2,4,6-tris (dimethylaminomethyl) phenol	REACH #: 01-2119560597-27 EC: 202-013-9 CAS: 90-72-2 Index: 603-069-00-0	≥5.0 - ≤10	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1C, H314 Eye Dam. 1, H318	ATE [Oral] = 1200 mg/ kg ATE [Dermal] = 1280 mg/kg	[1]
3,6-diazaoctanethylenediamin	EC: 203-950-6 CAS: 112-24-3 Index: 612-059-00-5	≥1.0 - <5.0	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412	ATE [Oral] = 1716 mg/ kg ATE [Dermal] = 1465 mg/kg	[1] [2]
N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan- 1-amide)	REACH #: 01-2119978265-26 EC: 204-613-6 CAS: 123-26-2	≤0.30	Skin Sens. 1B, H317 Aquatic Chronic 3, H412	-	[1] [2]
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. <u>Type</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Code: 00281340Date of issue/Date of revision: 25 October 2023PITT-CHAR XP PF HARDENER BLACK

SECTION 4: First aid measures

4.1 Description of first aid m	neasures
Eye contact	: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health e	ffects
Eye contact	: Causes serious eye damage.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes severe burns. May cause an allergic skin reaction.
Ingestion	: Corrosive to the digestive tract. Causes burns.
Over-exposure signs/sy	mptoms
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: Adverse symptoms may include the following: reduced foetal weight increase in foetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced foetal weight increase in foetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: stomach pains reduced foetal weight increase in foetal deaths skeletal malformations
4.3 Indication of any imm	ediate medical attention and special treatment needed
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.

Code	: 00281340	Date of issue/Date of revision	: 25 October 2023
PITT-CHAR >	(P PF HARDENER BLACK		

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising fr	om the substance or mixture
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides
5.3 Advice for firefighters	
Special precautions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	ote	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
6.3 Methods and material for	со	ntainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.
		English (GB) United Arab Emirates 5/15

- Code : 00281340
- PITT-CHAR XP PF HARDENER BLACK

Date of issue/Date of revision : 25 Oc

: 25 October 2023

SECTION 6: Accidental release measures

2

6.4 Reference to other sections

See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
7.2 Conditions for safe storage, including any incompatibilities	: Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values						
glass, oxide, chemicals	 ACGIH TLV (United States). TWA: 1 f/cc Form: Continuous filament glass fibres TWA: 5 mg/m³, (Inhalable) Form: Continuous filament glass fibres TWA: 3 mg/m³ Form: Respirable TWA: 10 mg/m³ Form: Total dust ACGIH TLV (United States, 1/2022). [Continuous filament glass fibers Inhalable fraction / Respirable fibers] TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction TWA: 1 f/cc 8 hours. Form: Respirable fibers: length greater than 5 uM; aspect ratio equal to or greater than 3:1 as determined by the 						
	English (GB) United Arab Emirates 6/15						

Code : 00281340		Date of issue/Date of revision : 25 October 2023					
PITT-CHAR XP PF HARDENE	R BLA	CK					
		membrane filter method at 400-450X magnification (4-mm objective) phase contrast illumination.					
Recommended monitoring procedures	Sta by stra apj bio rec age	Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.					
8.2 Exposure controls							
Appropriate engineering controls	loc	ser operations generate dust, fumes, gas, vapour or mist, use process enclosures, al exhaust ventilation or other engineering controls to keep worker exposure to porne contaminants below any recommended or statutory limits.					
Individual protection measu	res						
Hygiene measures	eat Ap Co coi	ash hands, forearms and face thoroughly after handling chemical products, before ing, smoking and using the lavatory and at the end of the working period. propriate techniques should be used to remove potentially contaminated clothing. Intaminated work clothing should not be allowed out of the workplace. Wash intaminated clothing before reusing. Ensure that eyewash stations and safety owers are close to the workstation location.					
Eye/face protection Skin protection	: Ch	emical splash goggles and face shield.					
Hand protection	wo dui not glo pro fre (br (br Th pro as	emical-resistant, impervious gloves complying with an approved standard should be in at all times when handling chemical products if a risk assessment indicates this is bessary. Considering the parameters specified by the glove manufacturer, check ing use that the gloves are still retaining their protective properties. It should be ed that the time to breakthrough for any glove material may be different for different ve manufacturers. In the case of mixtures, consisting of several substances, the tection time of the gloves cannot be accurately estimated. When prolonged or quently repeated contact may occur, a glove with a protection class of 6 eakthrough time greater than 480 minutes according to EN 374) is recommended. then only brief contact is expected, a glove with a protection class of 2 or higher eakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this duct is the most appropriate and takes into account the particular conditions of use, included in the user's risk assessment.					
Gloves		ile neoprene					
Body protection	pei	rsonal protective equipment for the body should be selected based on the task being formed and the risks involved and should be approved by a specialist before adding this product.					
Other skin protection	bas	propriate footwear and any additional skin protection measures should be selected sed on the task being performed and the risks involved and should be approved by a secialist before handling this product.					
Respiratory protection	:						
Environmental exposure controls	the cas	issions from ventilation or work process equipment should be checked to ensure y comply with the requirements of environmental protection legislation. In some ses, fume scrubbers, filters or engineering modifications to the process equipment be necessary to reduce emissions to acceptable levels.					

Date of issue/Date of revision

: 25 October 2023

- Code : 00281340
- PITT-CHAR XP PF HARDENER BLACK

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

<u>Appearance</u>									
Physical state	:	Liquid.							
Colour	:	Black.							
Odour	:	Aromatic.	romatic.						
Odour threshold	:	Not available.							
Melting point/freezing point	:	May start to solidify at the following temperature: 12°C (53.6°F) This is based on data for the following ingredient: 3,6-diazaoctanethylenediamin. Weighted average: -59.91°C (-75.8°F)							
Initial boiling point and boiling range	:	>37.78°C							
Flammability	:	Not available.	Not available.						
Upper/lower flammability or explosive limits	:	Lower: 1.4% Upper:	_ower: 1.4% Upper: 1%						
Flash point	:	Closed cup: Not applicable.							
Auto-ignition temperature	:	Ingredient name		°C	°F		Method		
		3,6-diazaoctanethylened	iamin	337.78	6	40			
Decomposition temperature	1	Stable under recomr	mended st	orade al	nd handli	na condit	ions (see Sec	tion 7)
pH		Not applicable. insol		•				(
Viscosity	:	Kinematic (40°C): >2							
Solubility(ies)	:	(, , , , , , , , , , , , , , , , , , ,							
Media		Result							
cold water		Not soluble							
Partition coefficient: n-octano water	I/ :	Not applicable.							
Vapour pressure	:		Vapour Press		sure at 20	°C	Vapour pressure at 5		sure at 50°C
		Ingredient name	mm Hg	kPa	Metho	d m He		kPa	Method
		2,4,6-tris (dimethylaminomethyl) phenol	0.056	0.0075	EU A.4				
Evaporation rate	:	Not available.			•				
Relative density	1	1.14							
-									

Vapour density Explosive properties

- : Highest known value: 5.04 (Air = 1) (3,6-diazaoctanethylenediamin).
- : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.
 - : Product does not present an oxidizing hazard.

: Not applicable.

Oxidising properties Particle characteristics Median particle size

9.2 Other information

No additional information.

Code	: 00281340	Date of issue/Date of revision	: 25 October 2023
PITT-CHAR >	(P PF HARDENER BLACK		

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.	
10.2 Chemical stability	: The product is stable.	
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.	
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.	
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.	
10.6 Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides	

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
melamine	LC50 Inhalation Dusts and	Rat	>5190 mg/m ³	4 hours
	mists			
	LD50 Oral	Rat	3161 mg/kg	-
2,4,6-tris(dimethylaminomethyl)phenol	LD50 Dermal	Rabbit	1.28 g/kg	-
	LD50 Dermal	Rat	1280 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-
3,6-diazaoctanethylenediamin	LD50 Dermal	Rabbit	1465 mg/kg	-
·	LD50 Oral	Rat	1716 mg/kg	-
N,N'-ethane-1,2-diylbis	LC50 Inhalation Dusts and	Rat	>5.11 mg/l	4 hours
(12-hydroxyoctadecan-1-amide)	mists			
· · · · /	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-

Conclusion/Summary : There are no data available on the mixture itself.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2,4,6-tris(dimethylaminomethyl)phenol	Skin - Visible necrosis	Rabbit	-	4 hours	7 days

Sensitisation	
Respiratory	: There are no data available on the mixture itself.
Eyes	: There are no data available on the mixture itself.
Skin	: There are no data available on the mixture itself.
Conclusion/Summary	

Product/ingredient name	Route of exposure	Species	Result
Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines	skin	Mouse	Sensitising
3,6-diazaoctanethylenediamin	skin	Guinea pig	Sensitising

Conclusion/Summary

Skin

: There are no data available on the mixture itself.

English (GB) United Arab Emirates

Code : 00281340 Date of issue/Date of revision : 25 October 2023 PITT-CHAR XP PF HARDENER BLACK

SECTION 11: Toxicological information

Respiratory	: There are no data available on the mixture itself.	
Mutagenicity		
Conclusion/Summary	: There are no data available on the mixture itself.	
Carcinogenicity		
Conclusion/Summary	: There are no data available on the mixture itself.	
Reproductive toxicity		
Conclusion/Summary	: There are no data available on the mixture itself.	
Teratogenicity		
Conclusion/Summary	: There are no data available on the mixture itself.	
Specific target organ tox	<u>icity (single exposure)</u>	
Not available.		

Specific target organ toxicity (repeated exposure)

Product/ir	igredient name	Category	Route of exposure	Target organs
1,3,5-triazine-2,4,6-triamin	9	Category 2	-	urinary system
Aspiration hazard Not available.		L	1	
Information on likely routes of exposure	: Not available.			
Potential acute health eff	ects			
Inhalation	: No known significant effe	ects or critical ha	zards.	
Ingestion	: Corrosive to the digestiv	e tract. Causes l	ourns.	
Skin contact	: Causes severe burns. N	/lay cause an alle	ergic skin reaction.	
Eye contact	: Causes serious eye dan	nage.		
Symptoms related to the	physical, chemical and toxic	ological charact	eristics	
Inhalation	: Adverse symptoms may reduced foetal weight increase in foetal deaths skeletal malformations		wing:	
Ingestion	: Adverse symptoms may stomach pains reduced foetal weight increase in foetal deaths skeletal malformations		wing:	
Skin contact	: Adverse symptoms may pain or irritation redness blistering may occur reduced foetal weight increase in foetal deaths skeletal malformations		ving:	
Eye contact	: Adverse symptoms may pain watering redness	include the follow	ving:	
Delayed and immediate e	ffects as well as chronic effe	cts from short a	nd long-term exp	<u>oosure</u>
Short term exposure			-	
Potential immediate effects	: Not available.			
	Eng	ılish (GB) U	Inited Arab Emira	ates 10/15

- Code : 00281340
- PITT-CHAR XP PF HARDENER BLACK
- Date of issue/Date of revision

: 25 October 2023

SECTION 11: Toxicological information

Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health effe	e <u>cts</u>
Not available.	
Conclusion/Summary	: Not available.
General	: May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: Suspected of damaging fertility.
Other information	: Not available.
• • • • • • •	

Causes digestive tract burns. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines	EC50 4.11 mg/l Fresh water	Algae	72 hours
melamine	Acute EC50 200 mg/l	Daphnia	48 hours
2,4,6-tris(dimethylaminomethyl)phenol	Acute LC50 175 mg/l	Fish	96 hours
N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-	Acute EC50 29 to 43 mg/l	Algae -	72 hours
1-amide)		Pseudokirchneriella subcapitata	
	Acute EC50 94 mg/l	Daphnia - <i>Daphnia</i> <i>magna</i>	48 hours

Conclusion/Summary

: There are no data available on the mixture itself.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan- 1-amide)	-	15 % - 28 days 63 % - 28 days	-	-

Conclusion/Summary : There are no data available on the mixture itself.

English (GB)	United Arab Emirates	11/15

Code : 00281340	Date of issue/Date of revision	: 25 October 2023
PITT-CHAR XP PF HARDENER BLACK		
SECTION 12: Ecological information		

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan- 1-amide)	-	-	Not readily Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
1,3,5-triazine-2,4,6-triamine 2,4,6-tris(dimethylaminomethyl)phenol 3,6-diazaoctanethylenediamin N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan- 1-amide)	-1.22 0.219 -1.66 to -1.4 >6	3.8 - - -	Low Low Low High

12.4 Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

ProductMethods of disposal: The generation of waste should be avoided or minimised wherever possible. Disposal
of this product, solutions and any by-products should at all times comply with the
requirements of environmental protection and waste disposal legislation and any
regional local authority requirements. Dispose of surplus and non-recyclable products
via a licensed waste disposal contractor. Waste should not be disposed of untreated to
the sewer unless fully compliant with the requirements of all authorities with jurisdiction.Hazardous waste: Yes.

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Conforms to Regulation (E 2020/878	C) No. 1907/2006 (F	REACH), Annex II, as amended by Commissio	n Regulation (EU)
Code : 00281340		Date of issue/Date of revision	: 25 October 2023
PITT-CHAR XP PF HARDE	NER BLACK		
SECTION 13: Disp	osal considera	ations	
Type of packaging		European waste catalogue (EWC)	
Container	15 01 06	mixed packaging	

This material and its container must be disposed of in a safe way. Care should be ÷. taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	ΙΑΤΑ
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

Additional information

Special precautions

ADR/RID : None identified. IMDG : None identified. ΙΑΤΑ : None identified.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk : Not applicable. according to IMO instruments

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

Code : 00281340 PITT-CHAR XP PF HARDENER BLACK Date of issue/Date of revision

: 25 October 2023

SECTION 15: Regulatory information

•	3			
Intrinsic property	Ingredient name	Status	Reference number	Date of revision
Substance of equivalent concern for human health	melamine	Candidate	D(2022) 9120-DC	1/17/2023
Substance of equivalent concern for environment	melamine	Candidate	D(2022) 9120-DC	1/17/2023

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles

Other national and international regulations.

Ozone depleting substances (1005/2009/EU)

Not listed.

- 15.2 Chemical safety
- : No Chemical Safety Assessment has been carried out.
- assessment

SECTION 16: Other information

Indicates information that h	າas changed from previoເ	isly issued versio	n.	
Abbreviations and acronyms	: ATE = Acute Toxicity CLP = Classification, 1272/2008] DNEL = Derived No EUH statement = CL PNEC = Predicted N RRN = REACH Regi	Labelling and Pa Effect Level P-specific Hazard o Effect Concenti		(EC) No.
Full text of abbreviated H statements	H314Causes seH315Causes skiH317May causeH318Causes seH351SuspectedH361fSuspectedH373May causeH411Toxic to aq	contact with skin vere skin burns a in irritation. an allergic skin r rious eye damage of causing cance of damaging fert damage to organ uatic life with long	nd eye damage. eaction. e. er. ility. ns through prolonged or repeated	ł exposure.
Full text of classifications [CLP/GHS]	: Acute Tox. 4 Aquatic Chronic 2 Aquatic Chronic 3 Carc. 2 Eye Dam. 1 Repr. 2 Skin Corr. 1B Skin Corr. 1C Skin Irrit. 2 Skin Sens. 1 Skin Sens. 1A Skin Sens. 1B STOT RE 2	LONG-TE LONG-TE CARCINO SERIOUS REPRODI SKIN COF SKIN COF SKIN SEN SKIN SEN SKIN SEN SKIN SEN SKIN SEN	DXICITY - Category 4 RM (CHRONIC) AQUATIC HAZA RM (CHRONIC) AQUATIC HAZA GENICITY - Category 2 EYE DAMAGE/EYE IRRITATION JCTIVE TOXICITY - Category 2 RROSION/IRRITATION - Categor ROSION/IRRITATION - Categor ROSION/IRRITATION - Categor SITISATION - Category 1 ISITISATION - Category 1 SITISATION - Category 18 TARGET ORGAN TOXICITY - F RE - Category 2	ARD - Category 3 N - Category 1 ry 1B ry 1C ry 2
		English (GB)	United Arab Emirates	14/15

Code : 00281340	Date of issue/Date of revision	: 25 October 2023
PITT-CHAR XP PF HARDENER BLACK		

SECTION 16: Other information

: 25 October 2023
: 25 October 2023
: EHS
: 7.01

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.