SAFETY DATA SHEET



Date of issue 26 October 2023

Version 6

Section 1. Product and company identification

Product name
Product code
Other means of identification
Product type

- : PITT-CHAR XP HARDENER BLACK SINGLE FEED
- : 00375571
- : Not available.
 - : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Coating. Paints. Painting-related materials.

Uses advised against	Reason		
Not applicable.			

Supplier's details:	
Supplier	 PPG Industries Colombia Ltda Calle 51 # 40-13 Municipio de Itagüí Antioquia, Colombia (57) (4) 3787400 (Porteria)
Email address:	: HazComLatam@ppg.com
Emergency telephone number	: Colombia: 01 8000 916012 (CISPROQUIM) + 571 288 6012 (CISPROQUIM) Ecuador: 1800-59-3005 (CISPROQUIM) Peru: 080-050-847 (CISPROQUIM)

Section 2. Hazards identification

Classification of the	: 🗚 CUTE TOXICITY (oral) - Category 5
substance or mixture	ACUTE TOXICITY (dermal) - Category 4
	SKIN CORROSION - Category 1C
	SERIOUS EYE DAMAGE - Category 1
	SKIN SENSITIZATION - Category 1
	CARCINOGENICITY - Category 1A
	TOXIC TO REPRODUCTION - Category 2
	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
Target organs	: Contains material which may cause damage to the following organs: kidneys, liver, bladder, brain, upper respiratory tract, skin, eyes.

Code00375571Product namePITT-CHAR	Date of issue 26 October 2023 Version 6 XP HARDENER BLACK SINGLE FEED 6
Section 2. Hazards	identification
	 Percentage of the mixture consisting of ingredient(s) of unknown acute oral toxicity: 68.8% Percentage of the mixture consisting of ingredient(s) of unknown acute dermal toxicity: 88.9% Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 61%
GHS label elements	
Hazard pictograms	
Signal word	: Danger
Hazard statements	 May be harmful if swallowed. Harmful in contact with skin. Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. (urinary system)
Precautionary statements	
Prevention	: Øbtain special instructions before use. Wear protective gloves, protective clothing and eye or face protection. Do not breathe vapor.
Response	: IF exposed or concerned: Get medical advice or attention. IF INHALED: Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with wate Immediately call a POISON CENTER or doctor. Wash contaminated clothing before reuse. IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Storage	: Not applicable.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Other hazards which do not result in classification	: Causes digestive tract burns.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Not available.
identification	

CAS number/other identifiers

CAS number	: Not applicable.
------------	-------------------

6

Section 3. Composition/information on ingredients

Ingredient name	%	CAS number	
Polyaminoamide	30 - <60	68082-29-1	
melamine	20 - <30	108-78-1	
4,4'-Isopropylidenediphenol, ethoxylated	7 - <10	32492-61-8 (EO>	
		4.5 moles)	
2,4,6-tris(dimethylaminomethyl)phenol	5 - <7	90-72-2	
3,6-diazaoctanethylenediamin	2 - <3	112-24-3	
glass, oxide, chemicals	1 - <2	65997-17-3	
crystalline silica, respirable powder (>10 microns)	0.5 - <1	14808-60-7	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Section 4. First aid measures

Description of necessary fir	<u>st a</u>	id measures
Eye contact	:	Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Inhalation	:	Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	:	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	:	If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
Indication of immediate medical attention and special treatment needed, if necessary		
Notes to physician Specific treatments	:	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. No specific treatment.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
Potential acute health effects		
Eye contact	1	Causes serious eye damage.
Inhalation	1	No known significant effects or critical hazards.
Skin contact	:	Causes severe burns. Harmful in contact with skin. May cause an allergic skin reaction.
Ingestion	- :	May be harmful if swallowed. Corrosive to the digestive tract. Causes burns.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	 Decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides
Special protective actions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

ctive equipment and emergency procedures
: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
ontainment and cleaning up
: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

English (US)

Colombia

Section 7. Handling and storage

Precautions for safe handling	:	Fut on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Conditions for safe storage, including any incompatibilities	:	Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
glass, oxide, chemicals	ACGIH TLV (United States). TWA: 1 f/cc Form: Continuous filament glass fibers TWA: 5 mg/m³, (Inhalable) Form: Continuous filament glass fibers TWA: 3 mg/m³ Form: Respirable TWA: 10 mg/m³ Form: Total dust ACGIH TLV (United States, 1/2022). [Continuous filament glass fibers Inhalable fraction / Respirable fibers] TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction TWA: 1 f/cc 8 hours. Form: Respirable fibers: length greater than 5 uM; aspect ratio equal to or greater than 3:1 as determined by the membrane filter method at 400-450X magnification (4-mm objective) phase contrast illumination.
Recommended monitoring procedures	: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

English (US)

Colombia

5/13

Section 8. Exposu	controls/personal protection
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensu they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measu	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period Appropriate techniques should be used to remove potentially contaminated clothin Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye protection	Chemical splash goggles and face shield.
Skin protection	
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard shou be worn at all times when handling chemical products if a risk assessment indicate this is necessary. Considering the parameters specified by the glove manufacture check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	nitrile neoprene
Body protection	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this necessary.

Section 9. Physical and chemical properties

Appearance	
Physical state	: Liquid.
Color	: Black.
Odor	: Characteristic.
рН	: Not applicable.
Melting point	: Not available.
Boiling point	: >37.78°C (>100°F)
Flash point	: Closed cup: 93.33°C (200°F)
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Not available.

Section 9. Physical and chemical properties

Vapor pressure	4	Not available.
Vapor density	:	Not available.
Relative density	:	1.14
Solubility(ies)		Media Result
Solubility(les)	1	cold water Not soluble
Water Solubility at room temperature	:	13.7 g/l
Partition coefficient: n- octanol/water	:	Not applicable.
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
Viscosity	:	Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides metal oxide/oxides

Section 11. Toxicological information

Information on toxicological effects

Product/ingredient name	Result	Species	Dose	Exposure
melamine	LC50 Inhalation Dusts and mists	Rat	>5190 mg/m ³	4 hours
	LD50 Oral	Rat	3161 mg/kg	-
2,4,6-tris	LD50 Dermal	Rabbit	1.28 g/kg	-
(dimethylaminomethyl)				
	LD50 Dermal	Rat	1280 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-
3,6-diazaoctanethylenediamin	LD50 Dermal	Rabbit	1465 mg/kg	-
-	LD50 Oral	Rat	1716 mg/kg	-

Conclusion/Summary

: There are no data available on the mixture itself.

Irritation/Corrosion

Code 00375571 Product name PITT-CHAR	XP HARDENER I	Date of BLACK SINGLE		26 Octol	ber 2023 Ve	rsion 6
Section 11. Toxico	logical i	nforma	tion			
Product/ingredient name	Result		Species	Score	Exposure	Observation
2,4,6-tris (dimethylaminomethyl) phenol	Skin - Visible	necrosis	Rabbit	-	4 hours	7 days
<u>Conclusion/Summary</u> Skin Eyes Respiratory <u>Sensitization</u>	: There are r	no data avail	lable on the mi lable on the mi lable on the mi	xture itself	f.	
Product/ingredient name	Route of	Specie	:S		Result	
₿,6-diazaoctanethylenediamin	exposure skin	Guinea	a pig		Sensitizing	
Conclusion/Summary Skin Respiratory Mutagenicity Not available. Conclusion/Summary Carcinogenicity Not available.	: There are r	no data avail	lable on the mi lable on the mi lable on the mi	xture itself	f.	
Conclusion/Summary <u>Classification</u>	: There are r	no data avail	lable on the mi	xture itself	f.	
Product/ingredient name	OSHA I	ARC NT	Р			
melamine glass, oxide, chemicals crystalline silica, respirable powder (>10 microns)	- 2 - 3 - 1		own to be a hu	man carci	inogen.	
Carcinogen Classification of IARC: 1, 2A, 2B, 3, 4 NTP: Known to be a OSHA: + Not listed/not regula	l a human carcino	gen; Reasonat	oly anticipated to	be a human	carcinogen	
Not available.						
Conclusion/Summary Teratogenicity Not available.	: There are r	no data avail	lable on the mi	xture itself	f.	
Conclusion/Summary Specific target organ toxicity Not available.			lable on the mi	xture itself	F.	
	v (repeated a)					
Specific target organ toxicity	<u>y (repeateu e</u>)	<u>xposurej</u>				
Specific target organ toxicity		<u>xposure</u>)	E	nglish (US)	Colombia	8/13

Code 00375571 Product name PITT-CH	Da AR XP HARDENER BLACK S		6 October 2023	Version 6		
Section 11. Toxic	cological infor	mation				
Name		Category	Route of exposure	Target organs		
melamine		Category 2	-	urinary system		
<u>Target organs</u>		which may cause dama per respiratory tract, skir		ı organs: kidneys, live		
Aspiration hazard Not available.						
nformation on the likely outes of exposure	: Not available.					
Potential acute health effect						
Eye contact	 Causes serious eye damage. No known significant effects or critical hazards. 					
Inhalation	•					
Skin contact	: Causes severe bu reaction.	rns. Harmful in contact	with skin. May ca	iuse an allergic skin		
Ingestion	: May be harmful if s	swallowed. Corrosive to	o the digestive trac	t. Causes burns.		
Symptoms related to the pl	hysical, chemical and t	oxicological character	<u>ristics</u>			
Eye contact	: Adverse symptoms pain watering redness	s may include the follow	<i>v</i> ing:			
Inhalation	: Adverse symptoms reduced fetal weig increase in fetal de skeletal malformat	eaths	<i>v</i> ing:			
Skin contact	: Adverse symptoms pain or irritation redness blistering may occu reduced fetal weig increase in fetal de skeletal malformat	ht eaths	ving:			
Ingestion	: Adverse symptoms stomach pains reduced fetal weig increase in fetal de skeletal malformat	eaths	<i>r</i> ing:			

Delayed and immediate effects and also chronic effects from short and long term exposure

Code00375571Product namePIT	T-CHAR X	Date of issue P HARDENER BLACK SINGLE FEED	26 October 2023	Version	6
Section 11. To	oxico	logical information			
Conclusion/Summa	ry :	There are no data available on the silica which can cause lung canced duration and level of exposure to applications. Exposure to compositated occupational exposure limit mucous membrane and respirato kidneys, liver and central nervous dizziness, fatigue, muscular weak consciousness. Solvents may cathrough the skin. There is some ovapors in combination with constate expected from exposure to noise cause irritation and reversible dar vomiting. This takes into account and also chronic effects of composional, inhalation and dermal routes	er or silicosis. The risk of o dust from sanding surface nent solvent vapor concen- it may result in adverse he- ry system irritation and ad- system. Symptoms and s cness, drowsiness and, in e use some of the above eff evidence that repeated exp ant loud noise can cause g alone. If splashed in the e mage. Ingestion may caus t, where known, delayed an onents from short-term and	cancer depend s or mist from trations in exc alth effects sur- verse effects or signs include h extreme cases ects by absorp posure to orga reater hearing eyes, the liquid is nausea, diar nd immediate of l long-term exp	is on the spray ess of the ch as on the leadache, a, loss of otion nic solvent loss than may rrhea and effects
Short term exposure					
Potential immediate effects	:	: There are no data available on th	e mixture itself.		
Potential delayed ef Long term exposure	fects	: There are no data available on th	e mixture itself.		
Potential immediate effects	:	: There are no data available on th	e mixture itself.		
Potential delayed ef	fects :	: There are no data available on the	e mixture itself.		
Potential chronic hea	<u>lth effec</u>	<u>ets</u>			
Not available.					
General	:	: May cause damage to organs three sensitized, a severe allergic react low levels.			
Carcinogenicity		: May cause cancer. Risk of cance	er depends on duration and	d level of expo	sure.

- Mutagenicity
- **Reproductive toxicity** : Suspected of damaging fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
TT-CHAR XP HARDENER BLACK SINGLE FEED	2496.1	1816.4	N/A	N/A	N/A
melamine	3161	N/A	N/A	N/A	N/A
2,4,6-tris(dimethylaminomethyl)phenol	1200	1280	N/A	N/A	N/A
3,6-diazaoctanethylenediamin	1716	1465	N/A	N/A	N/A

: No known significant effects or critical hazards.

Other information

: Not available.

English (US) Co

Section 12. Ecological information

Ecotoxicity

Product/ingredient name	Result	Species	Exposure
	Acute EC50 200 mg/l	Daphnia	48 hours
	Acute LC50 175 mg/l	Fish	96 hours

Persistence/degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
melamine	-1.22	3.8	Low
2,4,6-tris	0.219	-	Low
(dimethylaminomethyl)phenol			
3,6-diazaoctanethylenediamin	-1.66 to -1.4	-	Low

Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	Brazil (ANTT)	IMDG	ΙΑΤΑ
UN number	UN3066	UN3066	UN3066	UN3066
UN proper shipping name	PAINT	PAINT	PAINT	PAINT
Transport hazard class(es)	8	8	8	8
Packing group	III	III		
English (US) Colombia 11/				11/13

Code 00375571		Date of issue	26 October 2023	Version 6	
Product name	PITT-CHAR XP HARDENER	BLACK SINGLE FEED			
Section 14.	Transport info	rmation			
Environmental hazards	No.	No.	No.	No.	
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.	
Additional information	tion				
UN	: None identified.				
Brazil	: None identified.				
Risk number	: 80				
IMDG	: None identified.				
ΙΑΤΑ	: None identified.				
Special precaution	10	t within user's premise d secure. Ensure that pe of an accident or spillage	rsons transporting the p		
Transport in bulk a to IMO instruments		able.			
Section 15.	Regulatory info	ormation			
		specific national and/or i its ingredients).	regional regulations appl	icable to this product	

Section 16. Other information

motory	<u>History</u>	
--------	----------------	--

Date of previous issue	: 8/6/2020
Version	: 6
	EHS
Key to abbreviations	 ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail UN = United Nations
References	: ABNT NBR 14725-4: 2014 ANTT - National Land Transportation Agency

Indicates information that has changed from previously issued version.

Code	00375571	Date of issue	26 October 2023	Version	6
Product nam	e	PITT-CHAR XP HARDENER BLACK SINGLE FEED			

Section 16. Other information

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.