# **SAFETY DATA SHEET**

Date of issue/Date of revision : 26 October 2023 Version : 1.02



# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : PITT-CHAR XP HARDENER BLACK SINGLE FEED

Product code : 00375571

Product description

Product type : Liquid.

Other means of : Not available.

identification

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.

Use of the substance/

mixture

: Coating.

**Uses advised against**: Product is not intended, labelled or packaged for consumer use.

### 1.3 Details of the supplier of the safety data sheet

PPG Coatings Belgium BV/SRL Tweemontstraat 104 B-2100 Deurne Belgium Telephone +32-33606311 Fax +32-33606435

: Product.Stewardship.EMEA@ppg.com

e-mail address of person responsible for this SDS

1.4 Emergency telephone number

**Supplier** 

+31 20 4075210

### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

Product definition : Mixture
Classification according to UK CLP/GHS

Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2, H351 Repr. 2, H361f STOT RE 2, H373

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms







Signal word : Danger

English (GB) United Kingdom (UK) 1/14

PITT-CHAR XP HARDENER BLACK SINGLE FEED

# **SECTION 2: Hazards identification**

**Hazard statements** : Causes severe skin burns and eye damage.

> May cause an allergic skin reaction. Suspected of causing cancer. Suspected of damaging fertility.

May cause damage to organs through prolonged or repeated exposure.

**Precautionary statements** 

**Prevention** : Wear protective gloves, protective clothing and eye or face protection. Do not

breathe vapour.

: IF INHALED: Immediately call a POISON CENTER or doctor. IF SWALLOWED: Response

Immediately call a POISON CENTER or doctor. IF ON SKIN (or hair): Take off

immediately all contaminated clothing. Rinse skin with water.

**Storage** : Not applicable.

Disposal : Dispose of contents and container in accordance with all local, regional, national

and international regulations.

P280, P260, P304 + P310, P301 + P310, P303 + P361 + P353, P501

Supplemental label

elements

: Not applicable.

: Not applicable.

**Annex XVII - Restrictions** on the manufacture, placing on the market and use of certain dangerous substances, mixtures and

articles

Special packaging requirements

**Containers to be fitted** 

with child-resistant fastenings

: Not applicable.

**Tactile warning of danger** : Not applicable.

2.3 Other hazards

**Product meets the criteria** for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

: This mixture does not contain any substances that are assessed to be a PBT or a

vPvB.

Other hazards which do not result in classification

: Causes digestive tract burns.

# **SECTION 3: Composition/information on ingredients**

Mixture

#### 3.2 Mixtures

Product/ingredient name	Identifiers	%	Classification	Type
Polyaminoamide	EC: Polymer CAS: 68082-29-1	≥50 - ≤75	Eye Dam. 1, H318	[1]
1,3,5-triazine-2,4,6-triamine	REACH #: 01-2119485947-16 EC: 203-615-4 CAS: 108-78-1 Index: 613-345-00-2	≥10 - ≤25	Carc. 2, H351 Repr. 2, H361f STOT RE 2, H373 (urinary system)	[1]
4,4'-Isopropylidenediphenol, ethoxylated	EC: polymer CAS: 32492-61-8 (EO> 4.5 moles)	≥5.0 - ≤10	Aquatic Chronic 3, H412	[1]
2,4,6-tris(dimethylaminomethyl) phenol	REACH #: 01-2119560597-27 EC: 202-013-9 CAS: 90-72-2 Index: 603-069-00-0	≥5.0 - ≤10	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1C, H314 Eye Dam. 1, H318	[1]
3,6-diazaoctanethylenediamin	EC: 203-950-6	≥1.0 - <5.0	Acute Tox. 4, H302	[1]

2/14 **United Kingdom (UK)** English (GB)

PITT-CHAR XP HARDENER BLACK SINGLE FEED

# **SECTION 3: Composition/information on ingredients**

	CAS: 112-24-3 Index: 612-059-00-5		Acute Tox. 4, H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412	
N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan-1-amide)	REACH #: 01-2119978265-26 EC: 204-613-6 CAS: 123-26-2	<1.0	Skin Sens. 1B, H317 Aquatic Chronic 3, H412	[1]
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

[1] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

**Eye contact**: Check for and remove any contact lenses. Immediately flush eyes with running water for

at least 15 minutes, keeping eyelids open. Seek immediate medical attention.

Inhalation: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing.

: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained

personnel.

Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water

or use recognised skin cleanser. Do NOT use solvents or thinners.

Ingestion : If swallowed, seek medical advice immediately and show the container or label. Keep

person warm and at rest. Do NOT induce vomiting.

**Protection of first-aiders**: No action shall be taken involving any personal risk or without suitable training. If it

is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing

thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

### Potential acute health effects

**Eye contact** : Causes serious eye damage.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact**: Causes severe burns. May cause an allergic skin reaction.

**Ingestion**: Corrosive to the digestive tract. Causes burns.

### Over-exposure signs/symptoms

**Eye contact**: Adverse symptoms may include the following:

pain watering redness

**Inhalation** : Adverse symptoms may include the following:

reduced foetal weight increase in foetal deaths skeletal malformations

English (GB) United Kingdom (UK) 3/14

PITT-CHAR XP HARDENER BLACK SINGLE FEED

### **SECTION 4: First aid measures**

Skin contact : Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur reduced foetal weight increase in foetal deaths skeletal malformations

Ingestion : Adverse symptoms may include the following:

> stomach pains reduced foetal weight increase in foetal deaths skeletal malformations

### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

: No specific treatment. Specific treatments

# SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing** 

media

: None known.

#### 5.2 Special hazards arising from the substance or mixture

**Hazards from the** substance or mixture

: In a fire or if heated, a pressure increase will occur and the container may burst.

**Hazardous combustion** 

products

: Decomposition products may include the following materials:

carbon oxides nitrogen oxides metal oxide/oxides

### 5.3 Advice for firefighters

**Special protective actions** 

for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without

suitable training.

**Special protective** equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is

inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any

information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

4/14 English (GB) United Kingdom (UK)

Code : 00375571 Date of issue/Date of revision

# PITT-CHAR XP HARDENER BLACK SINGLE FEED

# **SECTION 6: Accidental release measures**

### 6.3 Methods and material for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

: 26 October 2023

Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

6.4 Reference to other sections

: See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

# **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

**Protective measures** 

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

See Section 1.2 for Identified uses.

English (GB) United Kingdom (UK) 5/14

PITT-CHAR XP HARDENER BLACK SINGLE FEED

# SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### **Occupational exposure limits**

No exposure limit value known.

procedures

Recommended monitoring: Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### **DNELs/DMELs**

Product/ingredient name	Туре	Exposure	Value	Population	Effects
1,3,5-triazine-2,4,6-triamine	DNEL	Long term Oral	0.42 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	1.5 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Dermal	4.2 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	8.3 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	11.8 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	117 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	82.3 mg/m <sup>3</sup>	Workers	Systemic
2,4,6-tris	DNEL	Long term Oral	0.075 mg/kg bw/day	General population	Systemic
(dimethylaminomethyl)phenol					
	DNEL	Short term Dermal	0.075 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.075 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	0.13 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	0.13 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Dermal	0.15 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	0.53 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Dermal	0.6 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	2.1 mg/m³	Workers	Systemic

### **PNECs**

No PNECs available

### 8.2 Exposure controls

**Appropriate engineering** controls

: If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection **Skin protection** 

**Hand protection** 

Chemical splash goggles and face shield.

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use,

English (GB) United Kingdom (UK)

PITT-CHAR XP HARDENER BLACK SINGLE FEED

# SECTION 8: Exposure controls/personal protection

as included in the user's risk assessment.

nitrile neoprene

**Body protection** : Personal protective equipment for the body should be selected based on the task being

performed and the risks involved and should be approved by a specialist before

handling this product.

: Appropriate footwear and any additional skin protection measures should be selected Other skin protection

based on the task being performed and the risks involved and should be approved by a

specialist before handling this product.

Respirator selection must be based on known or anticipated exposure levels, the **Respiratory protection** 

> hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate

filter P3

**Environmental exposure** 

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment

will be necessary to reduce emissions to acceptable levels.

# **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

**Appearance** 

**Physical state** : Liquid. Colour Black.

Odour : Characteristic. : Not available. **Odour threshold** 

Melting point/freezing point : May start to solidify at the following temperature: 12°C (53.6°F) This is based on

data for the following ingredient: 3,6-diazaoctanethylenediamin. Weighted average:

-11.02°C (12.2°F)

Initial boiling point and

boiling range

: >37.78°C (>100°F)

Flammability (solid, gas)

**Upper/lower flammability or** 

! liquid

explosive limits

Greatest known range: Lower: 1.1% Upper: 6.4% (3,6-diazaoctanethylenediamin)

Flash point Closed cup: 93.33°C (200°F)

**Auto-ignition temperature** 

Ingredient name	°C	°F	Method
3,6-diazaoctanethylenediamin	337.78	640	

**Decomposition temperature** 

pH : Not applicable.

Not applicable. insoluble in water.

**Viscosity** : Kinematic (40°C): >21 mm<sup>2</sup>/s

Solubility(ies)

Media	Result
cold water	Not soluble

Solubility in water 13.7 g/l Miscible with water No.

Partition coefficient: n-octanol/ : Not applicable.

water

PITT-CHAR XP HARDENER BLACK SINGLE FEED

# **SECTION 9: Physical and chemical properties**

Vapour pressure

	Vapour Pressure at 20°C			Var	re at 50°C	
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
2,4,6-tris(dimethylaminomethyl) phenol	0.056	0.0075	EU A.4			

Relative density : 1.14

**Vapour density** : Highest known value: 5.04 (Air = 1) (3,6-diazaoctanethylenediamin).

**Explosive properties** : The product itself is not explosive, but the formation of an explosible mixture of

vapour or dust with air is possible.

Oxidising properties

: Product does not present an oxidizing hazard.

**Particle characteristics** 

**Median particle size** : Not applicable.

# **SECTION 10: Stability and reactivity**

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid

: When exposed to high temperatures may produce hazardous decomposition products.

Refer to protective measures listed in sections 7 and 8.

10.5 Incompatible materials

: Keep away from the following materials to prevent strong exothermic reactions:

oxidising agents, strong alkalis, strong acids.

10.6 Hazardous decomposition products

: Depending on conditions, decomposition products may include the following

materials: carbon oxides nitrogen oxides metal oxide/oxides

# **SECTION 11: Toxicological information**

# 11.1 Information on toxicological effects

### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
1,3,5-triazine-2,4,6-triamine	LC50 Inhalation Dusts and	Rat	>5190 mg/m <sup>3</sup>	4 hours
	mists			
	LD50 Oral	Rat	3161 mg/kg	-
2,4,6-tris	LD50 Dermal	Rabbit	1.28 g/kg	-
(dimethylaminomethyl)				
phenol				
	LD50 Dermal	Rat	1280 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-
3,6-diazaoctanethylenediamin	LD50 Dermal	Rabbit	1465 mg/kg	-
-	LD50 Oral	Rat	1716 mg/kg	-
N,N'-ethane-1,2-diylbis	LC50 Inhalation Dusts and	Rat	>5.11 mg/l	4 hours
(12-hydroxyoctadecan-	mists			
1-amide)				
,	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-

Conclusion/Summary
Acute toxicity estimates

: There are no data available on the mixture itself.

English (GB) United Kingdom (UK) 8/14

PITT-CHAR XP HARDENER BLACK SINGLE FEED

# **SECTION 11: Toxicological information**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
PITT-CHAR XP HARDENER BLACK SINGLE FEED	16275.6	16330.4	N/A	N/A	N/A
1,3,5-triazine-2,4,6-triamine	3161	N/A	N/A	N/A	N/A
2,4,6-tris(dimethylaminomethyl)phenol	1200	1280	N/A	N/A	N/A
3,6-diazaoctanethylenediamin	1716	1465	N/A	N/A	N/A

### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
2,4,6-tris (dimethylaminomethyl)phenol	Skin - Visible necrosis	Rabbit	-	4 hours	7 days

Conclusion/Summary : Not available.

Skin : There are no data available on the mixture itself.
 Eyes : There are no data available on the mixture itself.
 Respiratory : There are no data available on the mixture itself.

**Sensitisation** 

Product/ingredient name	Route of exposure	Species	Result
3,6-diazaoctanethylenediamin	skin	Guinea pig	Sensitising

**Conclusion/Summary** 

**Skin** : There are no data available on the mixture itself. **Respiratory** : There are no data available on the mixture itself.

**Mutagenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Carcinogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

Reproductive toxicity

**Conclusion/Summary**: There are no data available on the mixture itself.

**Teratogenicity** 

Conclusion/Summary :

There are no data available on the mixture itself.

### Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
1,3,5-triazine-2,4,6-triamine	Category 2	-	urinary system

### **Aspiration hazard**

Not available.

Information on likely routes : Not available.

of exposure

Potential acute health effects

**Eye contact** : Causes serious eye damage.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact**: Causes severe burns. May cause an allergic skin reaction.

English (GB) United Kingdom (UK) 9/14

PITT-CHAR XP HARDENER BLACK SINGLE FEED

# **SECTION 11: Toxicological information**

**Ingestion** : Corrosive to the digestive tract. Causes burns.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact**: Adverse symptoms may include the following:

pain watering redness

**Inhalation** : Adverse symptoms may include the following:

reduced foetal weight increase in foetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

pain or irritation redness

blistering may occur reduced foetal weight increase in foetal deaths skeletal malformations

**Ingestion** : Adverse symptoms may include the following:

stomach pains reduced foetal weight increase in foetal deaths skeletal malformations

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Short term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects: Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

**Conclusion/Summary**: Not available.

General : May cause damage to organs through prolonged or repeated exposure. Once

sensitized, a severe allergic reaction may occur when subsequently exposed to very

low levels.

**Carcinogenicity** : Suspected of causing cancer. Risk of cancer depends on duration and level of

exposure.

**Mutagenicity**: No known significant effects or critical hazards.

**Reproductive toxicity**: Suspected of damaging fertility.

Other information : Not available.

# **SECTION 12: Ecological information**

12.1 Toxicity

English (GB) United Kingdom (UK) 10/14

PITT-CHAR XP HARDENER BLACK SINGLE FEED

# **SECTION 12: Ecological information**

Product/ingredient name	Result	Species	Exposure
1,3,5-triazine-2,4,6-triamine 2,4,6-tris (dimethylaminomethyl) phenol	Acute EC50 200 mg/l Acute LC50 175 mg/l		48 hours 96 hours
N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan- 1-amide)	Acute EC50 29 to 43 mg/l	subcapitata	72 hours
	Acute EC50 94 mg/l	Daphnia - <i>Daphnia magna</i>	48 hours

**Conclusion/Summary**: Not available.

### 12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan- 1-amide)	-	63 % - 28 days	-	-

**Conclusion/Summary**: Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan- 1-amide)	-	-	Readily

### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
1,3,5-triazine-2,4,6-triamine 2,4,6-tris	-1.22 0.219	3.8	Low Low
(dimethylaminomethyl) phenol 3,6-diazaoctanethylenediamin N,N'-ethane-1,2-diylbis (12-hydroxyoctadecan-	-1.66 to -1.4 >6	- -	Low High
1-amide)			

### 12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Mobility : Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6 Other adverse effects**: No known significant effects or critical hazards.

# **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 13.1 Waste treatment methods

**Product** 

English (GB) United Kingdom (UK) 11/14

Code : 00375571 Date of issue/Date of revision

PITT-CHAR XP HARDENER BLACK SINGLE FEED

# **SECTION 13: Disposal considerations**

**Methods of disposal** 

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

: 26 October 2023

**Hazardous waste** 

: Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.

#### Waste catalogue

Waste code	Waste designation	
08 01 99	wastes not otherwise specified	

### **Packaging**

**Methods of disposal** 

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** 

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

# **SECTION 14: Transport information**

	•			
	ADR/RID	ADN	IMDG	IATA
14.1 UN number	UN3066	UN3066	UN3066	UN3066
14.2 UN proper shipping name	PAINT	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	8	8	8	8
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	No.	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.

#### **Additional information**

ADR/RID : None identified.

**Tunnel code** : (E)

ADN : None identified. : None identified. **IMDG** IATA : None identified.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments

: Not available.

12/14 English (GB) United Kingdom (UK)

Code : 00375571 Date of issue/Date of revision

# SECTION 15: Regulatory information

PITT-CHAR XP HARDENER BLACK SINGLE FEED

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

### **UK (GB)/REACH**

**Annex XIV - List of substances subject to authorisation** 

**Annex XIV** 

None of the components are listed.

Substances of very high concern

None of the components are listed.

### Ozone depleting substances

Not listed.

**Annex XVII - Restrictions**: Not applicable. on the manufacture, placing on the market and use of certain dangerous substances,

#### **Seveso Directive**

mixtures and articles

This product is not controlled under the Seveso Directive.

### SECTION 16: Other information

Indicates information that has changed from previously issued version.

**Abbreviations and** acronyms

: ATE = Acute Toxicity Estimate

GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and

Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019

: 26 October 2023

No. 720 and amendments

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = GB CLP-specific Hazard statement

N/A = Not available

PBT = Persistent. Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification

Classification	Justification	
Skin Corr. 1C, H314	Calculation method	
Eye Dam. 1, H318	Calculation method	
Skin Sens. 1, H317	Calculation method	
Carc. 2, H351	Calculation method	
Repr. 2, H361f	Calculation method	
STOT RE 2, H373	Calculation method	

### **Full text of abbreviated H statements**

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H351	Suspected of causing cancer.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

### **Full text of classifications**

13/14 **United Kingdom (UK)** English (GB)

PITT-CHAR XP HARDENER BLACK SINGLE FEED

### **SECTION 16: Other information**

Acute Tox. 4 ACUTE TOXICITY - Category 4

Aquatic Chronic 3 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3

Carc. 2 CARCINOGENICITY - Category 2

Eye Dam. 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1

Repr. 2 REPRODUCTIVE TOXICITY - Category 2
Skin Corr. 1B SKIN CORROSION/IRRITATION - Category 1B
Skin Corr. 1C SKIN CORROSION/IRRITATION - Category 1C

Skin Sens. 1 SKIN SENSITISATION - Category 1
Skin Sens. 1B SKIN SENSITISATION - Category 1B

STOT RE 2 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2

#### **History**

Date of issue/ Date of : 26 October 2023

revision

Date of previous issue : 25 October 2023

Prepared by : EHS Version : 1.02

### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

English (GB) United Kingdom (UK) 14/14